

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : TURMOFLUID ED 13 LOSE
Revision date : 16.12.2024
Print date : 16.12.2024

Version (Revision) : 3.1.0 (3.0.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

TURMOFLUID ED 13 LOSE

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Product Categories [PC]

PC24 - Lubricants, greases, release products

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Lubricant Consult GmbH

Street : Gutenbergstraße 13

Postal code/city : 63477 MAINTAL (GERMANY)

Telephone : +49 6109/7650-0

Telefax : +49 6109/7650-51

E-mail : msds-request@lubcon.com

Information contact : Environment, Health & Safety: Dr. Jens Matthes

US Distributor
Fuchs Lubricants Co.
17050 Lathrop Avenue
Harvey, IL 60426
(708) 333-8900
(800) 255-3924 24 hrs
Emergency

1.4 Emergency telephone number

+49 6109/7650-0

Monday to Friday 8:00 AM to 4:00 PM (CET)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Chronic 3 ; Harmful to aquatic life with long lasting effects.

STOT RE 2 ; H373 - STOT-repeated exposure : Category 2 ; May cause damage to organs through prolonged or repeated exposure.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard components for labelling

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : 64742-82-1

Hazard statements

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P314 Get medical advice/attention if you feel unwell.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : TURMOFLUID ED 13 LOSE
Revision date : 16.12.2024
Print date : 16.12.2024

Version (Revision) : 3.1.0 (3.0.0)

3.2 Mixtures

Hazardous ingredients

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; REACH registration No. : 01-2119473977-17-xxxx ; EC No. : 919-164-8; CAS No. : 64742-82-1

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Asp. Tox. 1 ; H304 STOT RE 1 ; H372 Aquatic Chronic 3 ; H412

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; REACH registration No. : 01-2119488991-20-xxxx ; EC No. : 203-749-3; CAS No. : 110-25-8

Weight fraction : $\geq 0,5 - < 1 \%$

Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 Aquatic Acute 1 ; H400 Aquatic Chronic 3 ; H412

2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol ; REACH registration No. : 01-2119777867-13-xxxx ; EC No. : 202-414-9; CAS No. : 95-38-5

Weight fraction : $\geq 0,5 - < 1 \%$

Classification 1272/2008 [CLP] : STOT RE 2 ; H373 Skin Corr. 1C ; H314 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410

2-Ethylhexyl zinc dithiophosphate ; REACH registration No. : 01-2119493635-27-xxxx ; EC No. : 224-235-5; CAS No. : 4259-15-8

Weight fraction : $\geq 0,5 - < 1 \%$

Classification 1272/2008 [CLP] : Lact. ; H362 STOT SE 2 ; H371 STOT RE 2 ; H373 Eye Dam. 1 ; H318 Aquatic Chronic 2 ; H411

Further ingredients

SHC (Synthetic hydrocarbon)

Additives not to declare

Additional information

2-Ethylhexyl zinc dithiophosphate (CAS No. 4259-15-8) is classified according to Korean law (KOSHA, Korea Occupational Safety & Health Agency). Under REACH legislation H362, H371 and H373 are not required.

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

In case of skin contact

Remove contaminated, saturated clothing immediately. Wash immediately with: Water and soap In case of skin irritation, consult a physician.

After eye contact

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Let water be drunken in little sips (dilution effect). Get medical advice/attention if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : TURMOFLUID ED 13 LOSE
Revision date : 16.12.2024
Print date : 16.12.2024

Version (Revision) : 3.1.0 (3.0.0)

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Dry extinguishing powder. Carbon dioxide (CO₂). ABC-powder. BC-powder. Foam. Dry sand.

Unsuitable extinguishing media

Water. Strong water jet. High power water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products: Carbon monoxide (CO). Carbon dioxide (CO₂). Burning produces heavy smoke.

5.3 Advice for firefighters

Use suitable breathing apparatus.

5.4 Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

Special danger of slipping by leaking/spilling product.

6.1 Personal precautions, protective equipment and emergency procedures

None

6.2 Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Ensure waste is collected and contained. Make sure spills can be contained, e.g. in sump pallets or kerbed areas.

6.3 Methods and material for containment and cleaning up

Take up mechanically, placing in appropriate containers for disposal. Soak up inert absorbent and dispose as waste requiring special attention. Suitable material for taking up: Universal binder. Kieselguhr.

6.4 Reference to other sections

None

SECTION 7: Handling and storage



7.1 Precautions for safe handling

Protective measures

It is recommended to design all work processes always so that the following is excluded: Generation/formation of mist. Avoid: Inhalation of vapours or spray/mists. Skin contact, Eye contact. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

7.2 Conditions for safe storage, including any incompatibilities

Hints on joint storage

Storage class : 10

Storage class (TRGS 510) : 10

Keep away from

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : TURMOFLUID ED 13 LOSE
Revision date : 16.12.2024
Print date : 16.12.2024

Version (Revision) : 3.1.0 (3.0.0)

Food and feedingstuffs

Further information on storage conditions

Keep/Store only in original container. Keep container tightly closed. Protect against UV-radiation/sunlight. Humidity.
Contact with air/oxygen. Dust deposits.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

Keep away from food, drink and animal feeding stuffs. Wash hands before breaks and after work. Take the precautions customary when handling chemicals. Change contaminated, saturated clothing. Keep away from sources of ignition - No smoking.

8.1 Control parameters

Occupational exposure limit values

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : 64742-82-1

Limit value type (country of origin) : TLV/TWA (EC)

Limit value : 100 ppm / 375 mg/m³

Version :

DNEL/DMEL and PNEC values

DNEL/DMEL

Limit value type : DNEL Consumer (systemic) (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : 64742-82-1)

Exposure route : Dermal

Exposure frequency : Long-term (repeated)

Limit value : = 125 mg/kg/d

Limit value type : DNEL Consumer (systemic) (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : 64742-82-1)

Exposure route : Inhalation

Exposure frequency : Long-term (repeated)

Limit value : = 185 mg/m³

Safety factor : 24 h

Limit value type : DNEL Consumer (systemic) (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : 64742-82-1)

Exposure route : Oral

Exposure frequency : Long-term (repeated)

Limit value : = 125 mg/kg/d

Limit value type : DNEL/DMEL (Industrial) (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : 64742-82-1)

Exposure route : Dermal

Exposure frequency : Long-term (repeated)

Limit value : = 208 mg/kg/d

Limit value type : DNEL/DMEL (Industrial) (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : 64742-82-1)

Exposure route : Inhalation

Exposure frequency : Short-term (acute)

Limit value : = 871 mg/kg

Safety factor : 8 h

Limit value type : DNEL worker (systemic) (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : 64742-82-1)

Exposure route : Dermal

Exposure frequency : Long-term (repeated)

Limit value : = 208 mg/kg/d

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : TURMOFLUID ED 13 LOSE
Revision date : 16.12.2024
Print date : 16.12.2024

Version (Revision) : 3.1.0 (3.0.0)

Limit value type :	DNEL worker (systemic) (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : 64742-82-1)
Exposure route :	Inhalation
Exposure frequency :	Short-term (acute)
Limit value :	= 871 mg/m ³
Safety factor :	8 h
Limit value type :	DNEL Consumer (local) ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Exposure route :	Inhalation
Exposure frequency :	Short-term (acute)
Limit value :	= 9 mg/m ³
Limit value type :	DNEL Consumer (local) ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Exposure route :	Inhalation
Exposure frequency :	Long-term (repeated)
Limit value :	= 0,005 mg/m ³
Limit value type :	DNEL Consumer (systemic) ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Exposure route :	Oral
Exposure frequency :	Short-term (acute)
Limit value :	= 92 mg/kg
Limit value type :	DNEL Consumer (systemic) ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Exposure route :	Oral
Exposure frequency :	Long-term (repeated)
Limit value :	= 5 mg/kg
Limit value type :	DNEL Consumer (systemic) ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Exposure route :	Dermal
Exposure frequency :	Long-term (repeated)
Limit value :	= 5 mg/kg
Limit value type :	DNEL Consumer (systemic) ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Exposure route :	Dermal
Exposure frequency :	Short-term (acute)
Limit value :	= 50 mg/kg
Limit value type :	DNEL Consumer (systemic) ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Exposure route :	Inhalation
Exposure frequency :	Long-term (repeated)
Limit value :	= 0,1 mg/m ³
Limit value type :	DNEL worker (local) ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Exposure route :	Inhalation
Exposure frequency :	Short-term (acute)
Limit value :	= 18 mg/m ³
Limit value type :	DNEL worker (local) ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Exposure route :	Inhalation
Exposure frequency :	Long-term (repeated)
Limit value :	= 0,01 mg/m ³
Limit value type :	DNEL worker (systemic) ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Exposure route :	Dermal
Exposure frequency :	Short-term (acute)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : TURMOFLUID ED 13 LOSE
Revision date : 16.12.2024
Print date : 16.12.2024

Version (Revision) : 3.1.0 (3.0.0)

Limit value : = 100 mg/kg
Limit value type : DNEL worker (systemic) (2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol ; CAS No. : 95-38-5)
Exposure route : Dermal
Exposure frequency : Short-term (acute)
Limit value : = 2 mg/kg
Limit value type : DNEL worker (systemic) (2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol ; CAS No. : 95-38-5)
Exposure route : Inhalation
Exposure frequency : Short-term (acute)
Limit value : = 14 mg/m³
Limit value type : DNEL worker (systemic) ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Exposure route : Dermal
Exposure frequency : Long-term (repeated)
Limit value : = 10 mg/kg
Limit value type : DNEL worker (systemic) ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : = 0,2 mg/m³
Limit value type : DNEL worker (systemic) (2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol ; CAS No. : 95-38-5)
Exposure route : Dermal
Exposure frequency : Long-term (repeated)
Limit value : = 0,6 mg/kg
Limit value type : DNEL worker (systemic) (2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol ; CAS No. : 95-38-5)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : = 0,46 mg/m³
Limit value type : DNEL Consumer (systemic) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Exposure route : Oral
Exposure frequency : Long-term (repeated)
Limit value : = 0,19 mg/kg/d
Limit value type : DNEL Consumer (systemic) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : = 1,67 mg/m³
Limit value type : DNEL Consumer (systemic) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Exposure route : Dermal
Exposure frequency : Long-term (repeated)
Limit value : = 4,8 mg/kg
Limit value type : DNEL worker (local) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Exposure route : Dermal
Exposure frequency : Short-term (acute)
Limit value : = 0,09 mg/cm²
Limit value type : DNEL worker (local) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Exposure route : Inhalation
Exposure frequency : Short-term (acute)
Limit value : = 0,42 ppm
Limit value type : DNEL worker (local) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Exposure route : Dermal
Exposure frequency : Long-term

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : TURMOFLUID ED 13 LOSE
Revision date : 16.12.2024
Print date : 16.12.2024

Version (Revision) : 3.1.0 (3.0.0)

Limit value :	= 0,09 mg/cm ² /d
Limit value type :	DNEL worker (local) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Exposure route :	Inhalation
Exposure frequency :	Long-term (repeated)
Limit value :	= 0,07 ppm
Limit value type :	DNEL worker (systemic) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Exposure route :	Dermal
Exposure frequency :	Short-term (acute)
Limit value :	= 0,14 mg/kg/d
Limit value type :	DNEL worker (systemic) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Exposure route :	Inhalation
Exposure frequency :	Short-term (acute)
Limit value :	= 0,42 ppm
Limit value type :	DNEL worker (systemic) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	= 9,59 mg/kg
Limit value type :	DNEL worker (systemic) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Exposure route :	Inhalation
Exposure frequency :	Long-term (repeated)
Limit value :	= 0,21 ppm
Limit value type :	DNEL worker (systemic) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Exposure route :	Inhalation
Exposure frequency :	Long-term (repeated)
Limit value :	= 6,6 mg/m ³
Limit value type :	DNEL worker (systemic) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Exposure route :	Dermal
Exposure frequency :	Long-term (repeated)
Limit value :	= 9,6 mg/kg/d

PNEC

Limit value type :	PNEC (Aquatic, freshwater) (2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol ; CAS No. : 95-38-5)
Limit value :	= 0,0003 mg/l
Limit value type :	PNEC (Aquatic, freshwater) ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Limit value :	= 0,00043 mg/l
Limit value type :	PNEC (Aquatic, intermittent release) ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Limit value :	= 0,0043 mg/l
Limit value type :	PNEC (Aquatic, marine water) ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Limit value :	= 0,00004 mg/l
Limit value type :	PNEC (Aquatic, marine water) (2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol ; CAS No. : 95-38-5)
Limit value :	< 0,00001 mg/l
Limit value type :	PNEC (Sediment, freshwater) (2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol ; CAS No. : 95-38-5)
Limit value :	= 0,376 mg/kg
Limit value type :	PNEC (Sediment, marine water) (2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol ; CAS No. : 95-38-5)
Limit value :	= 0,0376 mg/kg
Limit value type :	PNEC Soil (2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol ; CAS No. : 95-38-5)
Limit value :	= 0,075 mg/kg
Limit value type :	PNEC (Sewage treatment plant) (2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol ; CAS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : TURMOFLUID ED 13 LOSE
Revision date : 16.12.2024
Print date : 16.12.2024

Version (Revision) : 3.1.0 (3.0.0)

	No. : 95-38-5)
Limit value :	= 0,27 mg/l
Limit value type :	PNEC (Air) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Limit value :	= 7,1 mg/m ³
Limit value type :	PNEC (Aquatic, freshwater) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Limit value :	= 0,004 mg/l
Limit value type :	PNEC (Aquatic, marine water) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Limit value :	= 0,0046 mg/l
Limit value type :	PNEC (Sediment, freshwater) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Limit value :	= 0,0701 mg/kg
Limit value type :	PNEC (Sediment, marine water) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Limit value :	= 0,00701 mg/kg
Limit value type :	PNEC Soil (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Limit value :	= 0,0548 mg/kg
Limit value type :	PNEC (Secondary poisoning) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Limit value :	= 8,3 mg/kg
Limit value type :	PNEC (Sewage treatment plant) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Limit value :	= 3,8 mg/l

8.2 Exposure controls

Personal protection equipment

Eye/face protection

Eye protection: not required. Avoid: Eye contact.

Recommended eye protection articles

DIN EN 166

Skin protection

Hand protection

Has degreasing effect on the skin. Wear suitable gloves.

By long-term hand contact : Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Suitable material : PE (Polyethylene). NR (natural rubber, natural latex). NBR (Nitrile rubber). CR (polychloroprene, chloroprene rubber).

Breakthrough time (maximum wearing time) : PE < 30 min. ; NR < 10 min.; NBR > 480 min.

Thickness of the glove material : min. 0,38 mm

Recommended glove articles : EN ISO 374; DIN EN 420 Uvex. KCL, MAPA. Or comparable articles from other companies.

Respiratory protection

No special measures are necessary. Avoid: Inhalation of vapours or spray/mists

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Colour : light yellow

Safety relevant basis data

Physical state :

Solidifying point :	(1013 hPa)	approx.	liquid	-50 °C
Initial boiling point and boiling range :	(1013 hPa)	>		345 °C

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : TURMOFLUID ED 13 LOSE
Revision date : 16.12.2024
Print date : 16.12.2024

Version (Revision) : 3.1.0 (3.0.0)

Decomposition temperature :	(1013 hPa)	>	345	°C
Flash point :	(1013 hPa)	>	140	°C
Vapour pressure :	(50 °C)	approx.	0,02	hPa
Density :	(20 °C)	=	0,88	g/cm ³
Viscosity :	(40 °C)	=	22	mm ² /s
Viscosity :	(100 °C)	=	4,1	mm ² /s

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

The product is stable.

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

Oxidising agent, strong.

10.6 Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Gases/vapours, harmful.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute effects

By analogy:

Acute oral toxicity

Parameter :	LD50
Exposure route :	Oral
Species :	Rat
Effective dose :	> 5000 mg/kg

Acute dermal toxicity

Parameter :	LD50
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	> 2000 mg/kg

Acute inhalation toxicity

Parameter :	LD50 (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : 64742-82-1)
Exposure route :	Inhalation (vapour)
Species :	Rat
Effective dose :	= 13,1 mg/m ³
Exposure time :	4 h
Method :	OECD 403
Parameter :	LC50 ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Exposure route :	Inhalation
Species :	Rat

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : TURMOFLUID ED 13 LOSE
Revision date : 16.12.2024
Print date : 16.12.2024

Version (Revision) : 3.1.0 (3.0.0)

Effective dose : = 1,37 mg/l
Exposure time : 4 h

Irritant and corrosive effects

Primary irritation to the skin

Parameter : Primary irritation to the skin ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Species : Rabbit
Result : Irritant
Method : OECD 404
Parameter : Primary irritation to the skin (2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol ; CAS No. : 95-38-5)
Species : Rabbit
Result : Causes burns
Method : OECD 404
Parameter : Primary irritation to the skin (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Species : Rabbit
Result : Not an irritant

Irritation to eyes

Parameter : Irritation to eyes ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Species : Rabbit
Result : Irreversible.
Parameter : Irritation to eyes (2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol ; CAS No. : 95-38-5)
Species : Rabbit
Result : Causes serious eye damage
Method : OECD 405
Parameter : Irritation to eyes (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Species : Rabbit
Result : Risk of serious damage to eyes
Method : OECD 405

Sensitisation

In case of skin contact

Parameter : Skin sensitisation ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Species : Guinea pig
Result : Not sensitising.
Method : OECD 406
Parameter : Skin sensitisation ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Species : Mouse
Result : Not sensitising.
Method : OECD 429
Parameter : Skin sensitisation (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Species : Guinea pig
Result : Not sensitising.
Method : OECD 406

In case of inhalation

Parameter : Sensitisation to the respiratory tract (2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol ; CAS No. : 95-38-5)
Species : Guinea pig
Result : Not sensitising.
Method : OECD 406

Repeated dose toxicity (subacute, subchronic, chronic)

Subacute oral toxicity

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : TURMOFLUID ED 13 LOSE
Revision date : 16.12.2024
Print date : 16.12.2024

Version (Revision) : 3.1.0 (3.0.0)

Parameter : NOAEL(C) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Exposure route : Oral
Species : Rat
Effective dose : = 125 mg/kg

Subacute dermal toxicity

Parameter : NOAEL(C) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Exposure route : Dermal
Effective dose : = 1250 mg/kg
Exposure time : 1 d

Subacute inhalation toxicity

Parameter : NOAEC (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Exposure route : Inhalation
Effective dose : = 214 mg/m³
Exposure time : 1 d

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

Parameter : Carcinogenicity (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Test result : Negative.
Parameter : NOAEL(C) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Exposure route : Oral
Species : Rat
Effective dose : = 30 mg/kg

Germ cell mutagenicity

In vitro mutagenicity

Parameter : Gene-mutations microorganisms ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Test result : Negative.
Parameter : Gene-mutations mammalian cells (2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol ; CAS No. : 95-38-5)
Test result : Negative.
Parameter : Gene-mutations mammalian cells ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Test result : Negative.
Parameter : In vitro mutagenicity (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Test result : Ames test negative.

In vivo mutagenicity

Parameter : In vivo mutagenicity (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Test result : Negative.

Reproductive toxicity

Adverse effects on developmental toxicity

Parameter : Adverse effects on developmental toxicity ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Species : Mammalian cells (with metabolic activation)
Test result : Negative.
Method : OECD 421

Developmental toxicity/teratogenicity

One generation reproduction toxicity test

Parameter : One generation reproduction toxicity test (2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol ; CAS No. : 95-38-5)
Test result : Negative.
Method : OECD 422
Parameter : One generation reproduction toxicity test (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : TURMOFLUID ED 13 LOSE
Revision date : 16.12.2024
Print date : 16.12.2024

Version (Revision) : 3.1.0 (3.0.0)

Exposure route : Oral
Species : Rat
Effective dose : = 30 mg/kg
Method : OECD 421
Parameter : NOAEL(C) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Exposure route : Oral
Species : Rat
Effective dose : = 30 mg/kg
Test result : Questionable.

STOT-single exposure

STOT SE 1 and 2

Parameter : NOAEL(C) (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Exposure route : Oral
Species : Rat
Effective dose : = 30 mg/kg

11.2 Information on other hazards

No information available.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter : LC50 (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : 64742-82-1)
Species : Oncorhynchus mykiss (Rainbow trout)
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : = 10 - 100 mg/l
Exposure time : 96 h
Parameter : LC50 ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Species : Leuciscus idus (golden orfe)
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : 3,2 - 4,6 mg/l
Exposure time : 96 h
Evaluation : Very toxic to fish.
Method : DIN 38412 / part 15
Parameter : LC50 (2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol ; CAS No. : 95-38-5)
Species : Brachydanio rerio (Zebra-fish)
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : = 0,3 mg/l
Exposure time : 96 h
Method : OECD 203
Parameter : LC50 (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Species : Oncorhynchus mykiss (Rainbow trout)
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : = 4,4 mg/l
Exposure time : 96 h
Method : OECD 203

Acute (short-term) daphnia toxicity

Parameter : EC50 (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : 64742-82-1)
Species : Daphnia magna (Big water flea)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : TURMOFLUID ED 13 LOSE
Revision date : 16.12.2024
Print date : 16.12.2024

Version (Revision) : 3.1.0 (3.0.0)

Evaluation parameter :	Acute (short-term) daphnia toxicity
Effective dose :	= 10 - 22 mg/l
Exposure time :	48 h
Parameter :	EC50 ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Species :	Daphnia magna (Big water flea)
Evaluation parameter :	Acute (short-term) daphnia toxicity
Effective dose :	= 0,53 mg/l
Exposure time :	48 h
Evaluation :	Very toxic to daphnia.
Parameter :	EC50 (2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol ; CAS No. : 95-38-5)
Species :	Daphnia magna (Big water flea)
Evaluation parameter :	Acute (short-term) daphnia toxicity
Effective dose :	= 0,136 mg/l
Exposure time :	48 h
Method :	OECD 202
Parameter :	EC50 (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Species :	Daphnia magna (Big water flea)
Evaluation parameter :	Acute (short-term) daphnia toxicity
Effective dose :	= 75 mg
Exposure time :	48 h
Method :	OECD 202
Chronic (long-term) daphnia toxicity	
Parameter :	NOEC (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Species :	Daphnia magna (Big water flea)
Evaluation parameter :	Chronic (long-term) daphnia toxicity
Effective dose :	= 0,4 mg/l
Exposure time :	21 d
Acute (short-term) algae toxicity	
Parameter :	EC50 (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : 64742-82-1)
Species :	Pseudokirchneriella subcapitata
Evaluation parameter :	Acute (short-term) algae toxicity
Effective dose :	= 50 - 100 mg/l
Exposure time :	72 h
Parameter :	EC50 ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Species :	Scenedesmus subspicatus
Evaluation parameter :	Acute (short-term) algae toxicity
Effective dose :	= 5,1 mg/l
Exposure time :	72 h
Evaluation :	Very toxic to algae.
Parameter :	EC50 (2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol ; CAS No. : 95-38-5)
Species :	Desmodesmus subspicatus
Evaluation parameter :	Acute (short-term) algae toxicity
Effective dose :	= 0,03 mg/l
Exposure time :	72 h
Method :	OECD 201
Parameter :	EC50 (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Species :	Scenedesmus subspicatus
Evaluation parameter :	Acute (short-term) algae toxicity
Effective dose :	> 240 mg/l
Exposure time :	72 h
Bacteria toxicity	
Parameter :	EC50 (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : TURMOFLUID ED 13 LOSE
Revision date : 16.12.2024
Print date : 16.12.2024

Version (Revision) : 3.1.0 (3.0.0)

Species : Pseudomonas putida
Evaluation parameter : Bacteria toxicity
Effective dose : = 380 mg/l
Exposure time : 16 h
Method : OECD 209

12.2 Persistence and degradability

Biodegradation

Parameter : Biodegradation (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : 64742-82-1)
Effective dose : = 74,7 %
Exposure time : 28 d
Evaluation : Readily biodegradable (according to OECD criteria).
Parameter : Biodegradation ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Evaluation : Readily biodegradable (according to OECD criteria).
Parameter : Biodegradation (2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol ; CAS No. : 95-38-5)
Evaluation parameter : Aerobic
Effective dose : approx. 1 %
Exposure time : 28 d
Evaluation : Poorly biodegradable.
Method : OECD 301B
Parameter : CO2 formation (% of the theoretical value) ((Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine ; CAS No. : 110-25-8)
Effective dose : = 85 %
Exposure time : 28 d
Method : OECD 301B
Parameter : Biodegradation (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Inoculum : Degree of elimination
Effective dose : < 5 %
Exposure time : 5 d
Evaluation : Poorly biodegradable.
Method : OECD 301D

Overall evaluation on the mixture: Not readily biodegradable (according to OECD criteria).

12.3 Bioaccumulative potential

Parameter : Bioconcentration factor (BCF) (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : 64742-82-1)
Concentration : = 4,2 - 7,2
Parameter : Partition coefficient: n-octanol/water (2-Ethylhexyl zinc dithiophosphate ; CAS No. : 4259-15-8)
Concentration : = 3,59

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

Endocrine disrupting potential: None known.

12.7 Other adverse effects

This product does not contain nanoparticles.

12.8 Overall evaluation

If product enters soil, it will be mobile and may contaminate groundwater. In accordance with the required stability the product is poorly biodegradable.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : TURMOFLUID ED 13 LOSE
Revision date : 16.12.2024
Print date : 16.12.2024

Version (Revision) : 3.1.0 (3.0.0)

SECTION 13: Disposal considerations

Dispose according to legislation. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

13.1 Waste treatment methods

Send to a hazardous waste incinerator facility under observation of official regulations. Collect the waste separately. Evidence for disposal must be provided.

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

13 02 05 - Mineral-based non-chlorinated engine, gear and lubricating oils

Waste code packaging

15 01 10 - Packaging containing residues of or contaminated by hazardous substances. - Dispose of completely emptied containers as combustible waste or metal waste depending on the material.

SECTION 14: Transport information

14.1 UN number or ID number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Restrictions of occupation

Not relevant

Störfallverordnung

Not subject to StörfallVO.

Emission control act (TA-Luft)

Weight fraction (Number 5.2.5. I) : <= 5 %

Water hazard class (WGK)

Class : 2 (Significant hazardous to water) Classification according to AwSV

Other regulations, restrictions and prohibition regulations

General Water Assessment Methodology (ABM) of the Netherlands: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Part of substances from the ZZS category (Zeer Zorgwekkende)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : TURMOFLUID ED 13 LOSE
Revision date : 16.12.2024
Print date : 16.12.2024

Version (Revision) : 3.1.0 (3.0.0)

Stoffen = Substances of very high concern): None.

Switzerland

VOCV-Regulation

Volatile organic compounds (VOC) content in percent by weight : 5 %

Additional information

TSCA (Toxic Substances Control Act) - USA, United States of America

All chemical substances in this mixture are included on or are exempted from listing on the TSCA Inventory for Chemical Substances.

California Proposition 65 - State of California

Based on available information this product does not contain any components or chemicals currently known to the State of California to cause cancer, birth defects or reproductive harm at levels which would be subject to Proposition 65.

15.2 Chemical safety assessment

No information available.

SECTION 16: Other information

16.1 Indication of changes

02. Classification of the substance or mixture · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] - Hazard components for labelling · 03. Hazardous ingredients · 15. National regulations

16.2 Abbreviations and acronyms

None

16.3 Key literature references and sources for data

Includes supplements in accordance with Regulation (EU) 2020/878 of June 18, 2020

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The statement is derived from the properties of the single components.

16.5 Relevant H- and EUH-phrases (Number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H362	May cause harm to breast-fed children.
H371	May cause damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : TURMOFLUID ED 13 LOSE
Revision date : 16.12.2024
Print date : 16.12.2024

Version (Revision) : 3.1.0 (3.0.0)

sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
