Safety Data Sheet

Revised On 01/22/2016

Page 1/5

Printing date 01/26/2016	Revised On 01/22/2016
1 Identification of the substance a	nd manufacturer
Trade name:	HI TECH VISTA GREEN
Product code:	0000160131
Product category Manufacturer/Supplier:	PC9a Paints and coatings. Seymour of Sycamore
	917 Crosby Avenue Sycamore, IL 60178
	Phone: 815-895-9101 www.seymourpaint.com
Emergency telephone number:	CHEMTEL 1-800-255-3924, or 813-248-0585.
2 Hazard(s) identification	
Classification of the substance or m	
Flam. Aerosol 1 H222 Extremely flam Press. Gas H280 Contains das u	mable aerosol. nder pressure; may explode if heated.
Skin Irrit. 2 H315 Causes skin irr	
Eye Irrit. 2A H319 Causes serious	
Repr. 2 H361 Suspected of d STOT SE 3 H336 May cause dro	amaging fertility or the unborn child. wsiness or dizziness.
STOT RE 2 H373 May cause dan	nage to organs through prolonged or repeated exposure.
GHS Hazard pictograms	$\langle \bullet \rangle \langle \bullet \rangle \langle \bullet \rangle \langle \bullet \rangle \langle \bullet \rangle$
	GHS02 GHS04 GHS07 GHS08
Signal word	Danger
Hazard statements	Extremely flammable aerosol. Contains gas under pressure; may explode if heated.
	Causes skin irritation. Causes serious eye irritation.
	Suspected of damaging fertility or the unborn child.
	May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking.
	Do not spray on an open flame or other ignition source.
	Do not pierce or burn, even after use. Wash hands thoroughly after handling.
	Use only outdoors of in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.
	Do not handle until all safety precautions have been read and understood.
	Wear protective gloves. Do not breathe dust/fume/gas/mist/vapors/spray.
	IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
	Call a PÓISON CENTER/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention.
	IF ON SKIN: Wash with plenty of water. If eye irritation persists: Get medical advice/attention.
	lake off contaminated clothing and wash it before reuse.
	Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
	Protect from sunlight. Store in a well-ventilated place. Store in a well-ventilated place. Keep container tightly closed.
	Dispose of contents/container in accordance with local/regional/national/international regulations.
3 Composition/information on ingr	
Chemical characterization: Mixtures Chemical Description:	This product is a mixture of the substances listed below with nonhazardous additions.
Dangerous components: 67-64-1 Acetone	37.91%
74-98-6 propane	15.7%
108-88-3 Toluene	11.9%
106-97-8 n-butane 13463-67-7 titanium dioxide	9.22% 2.55%
108-10-1 methyl isobutyl ketone	2.24%
107-87-9 Methyl Propyl Ketone	1.92%
2807-30-9 Glycol Ether EP	1.55%
4 First-aid measures	
After inhalation:	Supply fresh air; consult doctor in case of complaints.
After skin contact: After eye contact:	Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. If symptoms persist, consult a
-	doctor.
After swallowing:	Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.
	(Contd. on page 2)

Safety Data Sheet

Page 2/5

Printing date 01/26/2016		Revised On 01/22/2016
Trade name: HI TECH VISTA GREEN		
Most important symptoms and		(Contd. of page 1)
effects:	Dizziness	
Indication of any immediate medica attention needed:	No further relevant information available.	
5 Fire-fighting measures		
Extinguishing agents:	CO2, extinguishing powder or water spray. Fight larger fires with water spray.	
Special hazards: Protective equipment for	Can form explosive gas-air mixtures.	
firefighters:	A respiratory protective device may be necessary.	
6 Accidental release measures		
Personal precautions, protective		
equipment and emergency procedures:	Wear protective equipment. Keep unprotected persons away.	
•	Use respiratory protective device against the effects of fumes/dust/aerosol.	
Methods and material for containment and cleaning up:	Ensure adequate ventilation.	
J	Dispose contaminated material as waste according to section 13.	
7 Handling and storage		
Precautions for safe handling Storage requirements:	Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehou	ise in subfreezing
	conditions. Store locked up.	
8 Exposure controls/personal prot		
Components with limit values that r	equire monitoring at the workplace:	
67-64-1 Acetone PEL (USA) Long-term value: 2400 mg	1/m³ 1000 ppm	
REL (USA) Long-term value: 590 mg/		
TLV (USA) Short-term value: 1187 m	g/m ³ , 500 ppm	
Long-term value: 594 mg/	m³, 250 ppm	
74-98-6 propane		
PEL (USA) Long-term value: 1800 mg		
REL (USA) Long-term value: 1800 mg TLV (USA) refer to Appendix F inTLV		
108-88-3 Toluene		
PEL (USA) Long-term value: 200 ppn	1	
Ceiling limit value: 300; 50 *10-min peak per 8-hr shi)0* ppm	
REL (USA) Short-term value: 560 mg	[/] m ³ , 150 ppm	
Long-term value: 375 mg/		
TLV (USA) Long-term value: 75 mg/n BEI	1º, 20 ppm	
106-97-8 n-butane		
REL (USA) Long-term value: 1900 mg		
TLV (USA) Short-term value: 2370 m 108-10-1 methyl isobutyl ketone	g/m°, TUUU ppm	
PEL (USA) Long-term value: 410 mg/	m ³ . 100 ppm	
REL (USA) Short-term value: 300 mg	/m ³ , 75 ppm	
Long-term value: 205 mg/		
TLV (USA) Short-term value: 307 mg. Long-term value: 82 mg/n	¹³ , 20 ppm	
BEI		
107-87-9 Methyl Propyl Ketone PEL (USA) Long-term value: 700 mg/	m ³ . 200 ppm	
REL (USA) Long-term value: 530 mg/	m ³ , 150 ppm	
TLV (USA) Short-term value: 529 mg	/m³, 150 ppm	
Ingredients with biological limit value	Jes:	
67-64-1 Acetone BEI (USA) 50 mg/L		
Medium: urine		
Time: end of shift Parameter: Acetone (nons	necific)	
	peomoj	(Contd. on page 3)

F

Revised On 01/22/2016

Page 3/5

Trade name: HI TECH VISTA GREEN

	(Contd. of page 2)
108-88-3 Toluene	
BEI (USA) 0.02 mg/L Medium: blood Time: prior to last shift of w Parameter: Toluene 0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene 0.3 mg/g creatinine	vorkweek
Medium: urine	
Time: end of shift	
Parameter: o-Cresol with h	ydrolysis (background)
108-10-1 methyl isobutyl ketone	
BEI (USA) 1 mg/L Medium: urine Time: end of shift Parameter: MIBK	
Hygienic protection: Breathing equipment:	Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working. A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical
Hand protection:	hygeine. Nitrile gloves.
Hand protection:	Protective gloves. The glove material must be impermeable and resistant to the substance.
Eye protection:	Tightly sealed goggles
9 Physical and chemical propertie	s
Appearance:	Aerosol.
Appearance: Odor:	Aerosol. Aromatic
Odor threshold:	Not determined

Appearance:	Aerosol.
Odor:	Aromatic
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range	Undetermined.
Boiling point:	-110 °C (-166 °F)
Flash point:	-19 °C (-2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.7 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapour density	Not determined.
Evaporation rate	Not applicable.
Partition coefficient: n-octonal/water:	Not determined.
Solubility:	Not determined.
Viscosity:	Not determined.
VOC content:	537.4 g/l / 4.48 lb/gl
VOC content (less exempt solvents):	45.0 %
MIR Value:	1.09
Solids content:	17.0 %

Reactivity:	
	Stable at normal temperatures. Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing
t Chemical stability: Possibility of hazardous reactions: Incompatible materials:	temperatures. Not fully evaluated. No dangerous reactions known. No further relevant information available. No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:	
106-97-8 n-butane	
Inhalative LC50/4 h 658 mg/l (rat)	
(Contd. or	page 4)

Revised On 01/22/2016

Page 4/5

Trade name: HI TECH VISTA GREEN	
	(Contd. of page 3)
13463-67-7 titanium dioxide	
Oral LD50 >20000 mg/kg (ra	
Dermal LD50 >10000 mg/kg (rb	t)
Inhalative LC50/4 h >6.82 mg/l (rat)	
108-10-1 methyl isobutyl ketone	
Oral LD50 2100 mg/kg (rat)	
Dermal LD50 16000 mg/kg (rab	
Inhalative LC50/4 h 8.3-16.6 mg/l (rat)	
Information on toxicological effects:	
Skin effects:	No irritant effect.
Eye effects: Sensitization:	Irritating effect. No sensitizing effects known.
Carcinogenic categories	
IARC (International Agency for Rese	
108-88-3 Toluene	3
13463-67-7 titanium dioxide	2B
108-10-1 methyl isobutyl ketone	2B
NTP (National Toxicology Program)	
None of the ingredients is listed.	
12 Ecological information	
12 Ecological information	
Aquatic toxicity:	Hazardous for water, do not empty into drains.
Persistence and degradability: Bioaccumulative potential:	The product is degradable after prolonged exposure to natural weathering processes. No further relevant information available.
Mobility in soil:	No further relevant information available.
Other adverse effects:	No further relevant information available.
13 Disposal considerations	
	ete and federal regulations. De net superior incinerate as compact. Destinity compares
be disposed of responsibly. Do not be	ate, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must t or cut empty containers with electric or gas torches.
Recommendation:	Completely empty cans should be recycled.
4.4 Tropper out information	
14 Transport information	10/4050
UN-Number	UN1950
DOT	N/A UN1950
DOT	Consumer Commodity ORM-D
	Aerosols, flammable
ADR	1950 Aerosols
Transport hazard class(es):	
Class	2.1
Marine pollutant:	No Werring: Coord
Special precautions for user: EMS Number:	Warning: Gases
Packaging Group:	F-D,S-U
UN "Model Regulation":	UN1950, Aerosols, 2.1
15 Degulatory information	
15 Regulatory information	
SARA Section 355 (extremely hazard	
None of the ingredients in this product	are listed.
SARA Section 313 (Specific toxic ch	emical listings):
108-88-3 Toluene	
108-10-1 methyl isobutyl ketone	
CPSC:	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.
California Proposition 65 chemicals	
13463-67-7 titanium dioxide	
108-10-1 methyl isobutyl ketone	
100-41-4 ethyl benzene	
1333-86-4 Carbon black	
California Proposition 65 chemicals known to cause developmental	
toxicity:	108-88-3 Toluene
CANADIAN ENVIRONMENTAL	
PROTECTION ACT:	All hazardous ingredients for this product appear on the Canadian Domestice Substance List.
WHMIS Symbols for Canada:	A - Compressed gas
•	D2 <u>A</u> - Ver <u>v t</u> oxic material causing other toxic effects
	「「人後人!」
	(Contd. on page 5)

Printing date 01/26/2016

1

Page 5/5 Revised On 01/22/2016

ade name: HI TECH VISTA GREEN		
		(Contd. of pag
EPA:		
67-64-1 Acetone		
108-88-3 Toluene		
108-10-1 methyl isobutyl ketone		
6 Other information		
Contact: Date of preparation / last revision	Regulatory Affairs 01/26/2016 / -	