



Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 08-1276-8
Issue Date: 06/28/16

Version Number: 10.00
Supersedes Date: 12/17/14

SECTION 1: Identification

1.1. Product identifier

16-501 3M Zinc Spray

Product Identification Numbers

80-6109-2798-2, 80-6116-1654-3

1.2. Recommended use and restrictions on use

Recommended use

PROTECTIVE COATING, protective coating

Restrictions on use

INDUSTRIAL USE ONLY

1.3. Supplier's details

MANUFACTURER: 3M
DIVISION: Electrical Markets Division
ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Flammable Aerosol: Category 1.

Gas Under Pressure: Liquefied gas.

Serious Eye Damage/Irritation: Category 2A.

Reproductive Toxicity: Category 1B.

Simple Asphyxiant.

Specific Target Organ Toxicity (single exposure): Category 1.

Specific Target Organ Toxicity (single exposure): Category 3.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Gas cylinder | Exclamation mark | Health Hazard |

Pictograms



Hazard Statements

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

May cause drowsiness or dizziness.

May damage fertility or the unborn child.

May displace oxygen and cause rapid suffocation.

Causes damage to organs:
cardiovascular system |

Causes damage to organs through prolonged or repeated exposure:
nervous system |
sensory organs |

Precautionary Statements

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear eye/face protection.

Wear protective gloves.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see Notes to Physician on this label).

Storage:

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Notes to Physician:

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

2.3. Hazards not otherwise classified

Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.

3% of the mixture consists of ingredients of unknown acute oral toxicity.

3% of the mixture consists of ingredients of unknown acute dermal toxicity.

52% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
ZINC	7440-66-6	45 - 53 Trade Secret *
BUTANE	106-97-8	10 - 15 Trade Secret *
PROPANE	74-98-6	10 - 15 Trade Secret *
METHYL ETHYL KETONE (MEK)	78-93-3	8 - 13 Trade Secret *
TOLUENE	108-88-3	2 - 5 Trade Secret *
HEPTANE	142-82-5	2 - 5 Trade Secret *
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	2 - 5 Trade Secret *
Resin Epoxy Ester	66070-75-5	1 - 5 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. Get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Oxides of Lead	During Combustion
Oxides of Zinc	During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
BUTANE	106-97-8	ACGIH	STEL:1000 ppm	
TOLUENE	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin
TOLUENE	108-88-3	CMRG	STEL:75 ppm	SKIN
TOLUENE	108-88-3	OSHA	TWA:200 ppm;CEIL:300 ppm	
HEPTANE	142-82-5	ACGIH	TWA:400 ppm;STEL:500 ppm	
HEPTANE	142-82-5	OSHA	TWA:2000 mg/m3(500 ppm)	
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	CMRG	TWA:300 ppm	
PROPANE	74-98-6	ACGIH	Limit value not established:	
PROPANE	74-98-6	OSHA	TWA:1800 mg/m3(1000 ppm)	
METHYL ETHYL KETONE (MEK)	78-93-3	ACGIH	TWA:200 ppm;STEL:300 ppm	
METHYL ETHYL KETONE (MEK)	78-93-3	OSHA	TWA:590 mg/m3(200 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls**8.2.1. Engineering controls**

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates
 Half facepiece or full facepiece supplied-air respirator
 Organic vapor respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:	Liquid
Specific Physical Form:	Compressed Gas
Odor, Color, Grade:	HYDROCARBON ODOR, GRAY, HEAVY METAL DISPERSION
Odor threshold	<i>No Data Available</i>
Boiling Point	-44 - 325 °F
Flash Point	-78 °F [<i>Test Method:</i> Closed Cup] [<i>Details:</i> Based on butane]
Evaporation rate	>=1 [<i>Ref Std:</i> ETHER=1]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	0.9 %
Flammable Limits(UEL)	Approximately 10 %
Vapor Pressure	<i>No Data Available</i>
Vapor Density	<i>No Data Available</i>
Density	1144 kg/l
Specific Gravity	1.15 [<i>Ref Std:</i> WATER=1] [<i>Details:</i> Reference standard: Water = 1]
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Volatile Organic Compounds	Approximately 52 % weight <i>No Data Available</i>
Percent volatile	Approximately 88 % volume
VOC Less H2O & Exempt Solvents	<i>No Data Available</i>

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat
 Sparks and/or flames

10.5. Incompatible materials

Strong acids
 Strong bases
 Strong oxidizing agents

10.6. Hazardous decomposition products

Substance	Condition
Hydrocarbons	Normal Use
Ketones	Normal Use
Toxic Vapor, Gas, Particulate	Normal Use

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled. Intentional concentration and inhalation may be harmful or fatal.

Simple Asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Prolonged or repeated exposure may cause target organ effects:

Ocular Effects: Signs/symptoms may include blurred or significantly impaired vision.

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Olfactory Effects: Signs/symptoms may include decreased ability to detect odors and/or complete loss of smell.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE 5 - 12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
ZINC	Dermal	Rabbit	LD50 > 5,000 mg/kg
ZINC	Inhalation-Dust/Mist	Rat	LC50 > 5.4 mg/l
ZINC	Ingestion	Rat	LD50 > 2,000 mg/kg
PROPANE	Inhalation-Gas (4 hours)	Rat	LC50 > 200,000 ppm
METHYL ETHYL KETONE (MEK)	Dermal	Rabbit	LD50 > 8,050 mg/kg
METHYL ETHYL KETONE (MEK)	Inhalation-Vapor (4 hours)	Rat	LC50 34.5 mg/l
METHYL ETHYL KETONE (MEK)	Ingestion	Rat	LD50 2,737 mg/kg
BUTANE	Inhalation-Gas (4 hours)	Rat	LC50 277,000 ppm
TOLUENE	Dermal	Rat	LD50 12,000 mg/kg
TOLUENE	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
TOLUENE	Ingestion	Rat	LD50 5,550 mg/kg
HEPTANE	Dermal	Rabbit	LD50 3,000 mg/kg
HEPTANE	Inhalation-Vapor (4 hours)	Rat	LC50 103 mg/l
HEPTANE	Ingestion	Rat	LD50 > 15,000 mg/kg
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	Dermal	Rabbit	LD50 3,000 mg/kg
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	Inhalation-Vapor (4 hours)	Rat	LC50 > 5.2 mg/l
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
PROPANE	Rabbit	Minimal irritation
METHYL ETHYL KETONE (MEK)	Rabbit	Minimal irritation
BUTANE	Professional judgement	No significant irritation

	nt	
TOLUENE	Rabbit	Irritant
HEPTANE	Human	Mild irritant
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
PROPANE	Rabbit	Mild irritant
METHYL ETHYL KETONE (MEK)	Rabbit	Severe irritant
BUTANE	Rabbit	No significant irritation
TOLUENE	Rabbit	Moderate irritant
HEPTANE	Professional judgement	Moderate irritant
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
TOLUENE	Guinea pig	Not sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
PROPANE	In Vitro	Not mutagenic
METHYL ETHYL KETONE (MEK)	In Vitro	Not mutagenic
BUTANE	In Vitro	Not mutagenic
TOLUENE	In Vitro	Not mutagenic
TOLUENE	In vivo	Not mutagenic
HEPTANE	In Vitro	Not mutagenic
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
METHYL ETHYL KETONE (MEK)	Inhalation	Human	Not carcinogenic
TOLUENE	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
TOLUENE	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
TOLUENE	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
METHYL ETHYL KETONE (MEK)	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	LOAEL 8.8 mg/l	during gestation
TOLUENE	Inhalation	Some positive female reproductive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
TOLUENE	Inhalation	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 2.3 mg/l	1 generation

TOLUENE	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
TOLUENE	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
PROPANE	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
PROPANE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
PROPANE	Inhalation	respiratory irritation	All data are negative	Human	NOAEL Not available	
METHYL ETHYL KETONE (MEK)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	official classification	NOAEL Not available	
METHYL ETHYL KETONE (MEK)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
METHYL ETHYL KETONE (MEK)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
METHYL ETHYL KETONE (MEK)	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	not applicable
METHYL ETHYL KETONE (MEK)	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1,080 mg/kg	not applicable
BUTANE	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
BUTANE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
BUTANE	Inhalation	heart	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 5,000 ppm	25 minutes
BUTANE	Inhalation	respiratory irritation	All data are negative	Rabbit	NOAEL Not available	
TOLUENE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
TOLUENE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
TOLUENE	Inhalation	immune system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 0.004 mg/l	3 hours
TOLUENE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
HEPTANE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
HEPTANE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
HEPTANE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
SOLVENT NAPHTHA (PETROLEUM), LIGHT	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional	NOAEL Not available	

ALIPHATIC				judgement		
-----------	--	--	--	-----------	--	--

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
METHYL ETHYL KETONE (MEK)	Dermal	nervous system	All data are negative	Guinea pig	NOAEL Not available	31 weeks
METHYL ETHYL KETONE (MEK)	Inhalation	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 14.7 mg/l	90 days
METHYL ETHYL KETONE (MEK)	Inhalation	heart endocrine system bone, teeth, nails, and/or hair hematopoietic system immune system muscles	All data are negative	Rat	NOAEL 14.7 mg/l	90 days
METHYL ETHYL KETONE (MEK)	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	7 days
METHYL ETHYL KETONE (MEK)	Ingestion	nervous system	All data are negative	Rat	NOAEL 173 mg/kg/day	90 days
BUTANE	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 4,489 ppm	90 days
BUTANE	Inhalation	blood	All data are negative	Rat	NOAEL 4,489 ppm	90 days
TOLUENE	Inhalation	auditory system nervous system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
TOLUENE	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
TOLUENE	Inhalation	heart liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 11.3 mg/l	15 weeks
TOLUENE	Inhalation	endocrine system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	4 weeks
TOLUENE	Inhalation	immune system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL Not available	20 days
TOLUENE	Inhalation	bone, teeth, nails, and/or hair	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	8 weeks
TOLUENE	Inhalation	hematopoietic system vascular system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
TOLUENE	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
TOLUENE	Ingestion	heart	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2,500 mg/kg/day	13 weeks
TOLUENE	Ingestion	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
TOLUENE	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 600 mg/kg/day	14 days
TOLUENE	Ingestion	endocrine system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 105 mg/kg/day	28 days
TOLUENE	Ingestion	immune system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 105 mg/kg/day	4 weeks

HEPTANE	Inhalation	liver nervous system kidney and/or bladder	All data are negative	Rat	NOAEL 12 mg/l	26 weeks
---------	------------	--	-----------------------	-----	---------------	----------

Aspiration Hazard

Name	Value
TOLUENE	Aspiration hazard
HEPTANE	Aspiration hazard
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable), D035 (Methyl ethyl ketone)

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
TOLUENE	108-88-3	Trade Secret 2 - 5
ZINC	7440-66-6	Trade Secret 45 - 53

ZINC (Zinc)

7440-66-6

45 - 53

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information**NFPA Hazard Classification**

Health: 2 Flammability: 4 Instability: 1 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: *2 Flammability: 4 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document Group: 08-1276-8
Issue Date: 06/28/16

Version Number: 10.00
Supersedes Date: 12/17/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com