MATERIAL SAFETY 3M DATA SHEET 3M Center St. Paul, Minnesota 55144-1000 1-800-364-3577 or (651) 737-6501 (24 hours) Copyright, 2001, Minnesota Mining and Manufacturing Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: 1) the information is copied in full with no changes unless prior agreement is obtained from 3M, and 2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. DIVISION: ELECTRICAL PRODUCTS DIVISION TRADE NAME: QUICK-TERM II SILICONE RUBBER HI-K TERMINATION KIT 5635K ID NUMBER/U.P.C.: 80-6101-2335-0 00-54007-12257-9 80-6108-3633-2 00-54007-41979-2 80-6112-1591-6 --ISSUED: March 12, 2001 SUPERSEDES: August 23, 1996 DOCUMENT: 10-5708-2 This product is a kit or a multipart product which consists of multiple, independently packaged components. An MSDS for each of these components is included. Please do not separate the component MSDSs from this cover page. The document numbers of the MSDSs for components of this product are: 10-2656-6 11-4627-3 _____ Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately _____ The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining

whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.



Material Safety Data Sheet

Copyright, 2005, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SILICONE LUBRICANT **MANUFACTURER:** 3M

DIVISION: Electrical Markets Division

ADDRESS: 3M Center St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 12/23/2005 **Supercedes Date:** 11/01/2005

Document Group: 10-2656-6

Product Use:

Specific Use:

SILICONE LUBRICANT GREASE FOR ELECTRICAL SPLICES

SECTION 2: INGREDIENTS

Ingredient	<u>C.A.S. No.</u>	<u>% by Wt</u>
SILICONE GREASE	63148-62-9	85 - 95
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	112945-52-5	5 - 15

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: MITS data: GREASE Odor, Color, Grade: Light colored grease, no odor General Physical Form: Solid grease Immediate health, physical, and environmental hazards:

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Mild Eye Irritation: Signs/symptoms may include redness, pain, and tearing.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Inhalation:

No health effects are expected.

Ingestion:

No health effects are expected.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

Inhalation: No need for first aid is anticipated.

If Swallowed: No need for first aid is anticipated.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature Flash Point Flammable Limits - LEL Flammable Limits - UEL No Data Available Not Applicable No Data Available No Data Available

5.2 EXTINGUISHING MEDIA

Ordinary combustible material. Use fire extinguishers with class A extinguishing agents (e.g., water, foam).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Not applicable. No unusual fire or explosion hazards are anticipated. Non-flammable: ordinary combustible material.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Collect as much of the spilled material as possible. Clean up residue with an appropriate organic solvent. Read and follow safety precautions on the solvent label and MSDS. Place in a closed container approved for transportation by appropriate authorities.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Avoid eye contact with vapors, mists, or spray. For industrial use only. Not intended for use as a medical device or drug. Avoid contact with oxidizing agents. Do not mix with oxidizers to avoid risk of explosion.

7.2 STORAGE

Store away from acids. Store away from oxidizing agents.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Not applicable. Provide appropriate local exhaust when product is heated.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray. The following eye protection(s) are recommended: Safety Glasses with side shields.

8.2.2 Skin Protection

Gloves are not required.

8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

8.2.4 Prevention of Swallowing

Not applicable.

8.3 EXPOSURE GUIDELINES

None Established

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form: Odor, Color, Grade: General Physical Form: MITS data: GREASE Light colored grease, no odor Solid grease Autoignition temperature Flash Point Flammable Limits - LEL Flammable Limits - UEL Boiling point

Vapor Density

Vapor Pressure

Specific Gravity

pH Melting point

Evaporation rate Volatile Organic Compounds VOC Less H2O & Exempt Solvents No Data Available Not Applicable No Data Available No Data Available Not Applicable Not Applicable 1.02 Units not avail. or not appl. - 1.6 Units not avail. or not appl. [Ref Std: WATER=1] Not Applicable No Data Available

Not Applicable No Data Available No Data Available

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid: Strong oxidizing agents; Strong acids; Strong bases; Reducing agents

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

Substance Formaldehyde Carbon monoxide Carbon dioxide <u>Condition</u> Oxidative Degradation During Combustion During Combustion

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of completely absorbed waste product in a sanitary landfill. As a disposal alternative, Incinerate in an industrial or commercial facility in the presence of a combustible material.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14:TRANSPORT INFORMATION

ID Number 78-8007-1728-8 80-6109-3893-0 UPC 00-51138-58612-6 **ID Number** 80-6108-3463-4

UPC 00-54007-41814-6

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

STATE REGULATIONS

Contact 3M for more information.

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS.

The components of this product are listed on the Canadian Domestic Substances List.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 1 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 1 Flammability: 1 Reactivity: 0 Protection: A

Hazardous Material Identification System (HMIS(r)) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS(r) ratings are to be used with a fully implemented HMIS(r) program. HMIS(r) is a registered mark of the National Paint and Coatings Association (NPCA).

Reason for Reissue: The MSDS has been revised because 3M has adopted the 16-section ANSI/ISO format. The potential hazards of the product have not changed. We encourage you to reread the MSDS and review the information.

Revision Changes:

- Section 3: Potential effects from eye contact was modified.
- Section 3: Potential effects from skin contact information was modified.
- Section 3: Potential effects from inhalation information was modified.
- Section 3: Potential effects from ingestion information was modified.
- Section 7: Handling information was modified.
- Section 8: Engineering controls information was modified.
- Section 8: Eye/face protection phrase was modified.
- Section 8: Skin protection phrase was modified.
- Section 15: Inventories information was modified.
- Section 4: First aid for ingestion (swallowing) none was added.
- Section 4: First aid for inhalation none was added.
- Section 4: First aid for inhalation termination of exposure was deleted.
- Section 4: First aid for inhalation medical assistance was deleted.
- Section 4: First aid for ingestion (swallowing) decontamination was deleted.
- Section 4: First aid for ingestion (swallowing) intervention was deleted.
- Section 4: First aid for ingestion (swallowing) medical assistance was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M

MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com



Material Safety Data Sheet

Copyright, 2006, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:CC-2 PREP KIT (CABLE CLEANER)**MANUFACTURER:**3M**DIVISION:**Electrical Markets Division

ADDRESS: 3M Center St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 03/27/2006 Supercedes Date: 10/26/2003

Document Group: 11-4627-3

Product Use:

Specific Use:

SOLVENT SOAKED RAGS FOR CABLE CLEANING

SECTION 2: INGREDIENTS

Ingredient

PETROLEUM DISTILLATES D-LIMONENE <u>C.A.S. No.</u> 64771-72-8 5989-27-5 <u>% by Wt</u> 80 - 95 5 - 20

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Odor, Color, Grade: clear, citrus-like odor General Physical Form: Liquid Immediate health, physical, and environmental hazards: Flammable liquid and vapor. Combustible liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back. May cause allergic skin reaction. May cause target organ effects.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin Contact:

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Inhalation:

Upper Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May be absorbed following inhalation and cause target organ effects.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, nausea, diarrhea and vomiting. Chemical (Aspiration) Pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish colored skin (cyanosis), and may be fatal.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

3.3 POTENTIAL ENVIRONMENTAL EFFECTS

VOC Data: 740 grams/liter maximum VOC (less water and exempt compounds). U.S. EPA Waste Number: None. 5 Day Biological Oxygen Demand (BOD-5) = 77,000 mg/L. Chemical Oxygen Demand (COD) = 290,000 mg/L.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

Do not induce vomiting. Give victim two glasses of water. Never give anything by mouth to an unconscious If Swallowed: person. Get immediate medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature Flash Point Flash Point Flash Point Flammable Limits - LEL **Flammable Limits - UEL OSHA Flammability Classification:**

No Data Available >=144 °F [*Test Method:* Closed Cup] 144 °F [Test Method: Closed Cup] [Details: MITS data] >=165 °F [*Test Method:* Open Cup] No Data Available No Data Available Class IIIA Combustible Liquid

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Flammable liquid and vapor. Combustible liquid and vapor. Not applicable. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Contain spill. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Place in a metal container approved for transportation by appropriate authorities.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. No smoking while handling this material. Avoid breathing of vapors, mists or spray. Avoid eye contact with vapors, mists, or spray. Avoid contact with oxidizing agents.

7.2 STORAGE

Store away from acids. Store away from heat. Store out of direct sunlight. Keep container in well-ventilated area. Store away from oxidizing agents.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Provide appropriate local exhaust ventilation on open containers. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use respiratory protection equipment.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact. Avoid eye contact with vapors, mists, or spray. The following eye protection(s) are recommended: Indirect Vented Goggles.

8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials. Gloves made from the following material(s) are recommended: Fluoroelastomer (Viton), Nitrile Rubber, Polyethylene.

8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

Ingredient	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	Additional Information
PETROLEUM DISTILLATES	CMRG	TWA	300 ppm	

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Odor, Color, Grade:	clear, citrus-like odor
General Physical Form:	Liquid
Autoignition temperature	No Data Available
Flash Point	>=144 °F [Test Method: Closed Cup]
Flash Point	144 °F [Test Method: Closed Cup] [Details: MITS data]
Flash Point	>=165 °F [Test Method: Open Cup]
Flammable Limits - LEL	No Data Available
Flammable Limits - UEL	No Data Available
Boiling point	380.00 - 480.00 °F
Boiling point	>=95 °F [Details: MITS data]
Density	0.76 g/ml
Vapor Density	>=1.00 [Ref Std: AIR=1]
Vapor Pressure	<=1.0000 mmHg [<i>Details:</i> CONDITIONS: Less than 1 mmHg at 25 C]
Specific Gravity	0.76 [<i>Details:</i> MITS data]
pH	7.0
Melting point	No Data Available

Evaporation rate Volatile Organic Compounds VOC Less H2O & Exempt Solvents Viscosity Not Applicable Approximately 740 g/l No Data Available No Data Available

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid: Strong oxidizing agents

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

Substance Carbon monoxide Carbon dioxide Condition Not Specified Not Specified

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in an industrial or commercial facility. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14:TRANSPORT INFORMATION

ID Number(s):

78-8061-7605-9, 80-6105-9299-2, 80-6112-0013-2, 80-6114-2769-3

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

STATE REGULATIONS

Contact 3M for more information.

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS.

Contact 3M for more information.

The components of this product are listed on the Canadian Domestic Substances List.

Additional Information: All components are on the TSCA; EINECS; and CDSL Inventories.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

WHMIS: Hazardous

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 2 Flammability: 2 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification Health: 2 Flammability: 2 Reactivity: 0 Protection: B

Hazardous Material Identification System (HMIS®) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint and Coatings Association (NPCA).

Revision Changes: Section 16: NFPA hazard classification heading was modified. Section 16: HMIS hazard classification heading was modified. Section 3: Potential environmental effects heading was modified. Section 3: Other potential health effects heading was modified. Section 1: Division name was modified. Copyright was modified. Section 8: Exposure guidelines data source legend was modified. Section 3: Immediate physical hazard(s) was modified. Section 3: Potential effects from eye contact was modified. Section 3: Potential effects from inhalation information was modified. Section 3: Potential effects from ingestion information was modified. Section 5: Fire fighting procedures information was modified. Section 5: Unusual fire and explosion hazard information was modified. Section 6: Release measures information was modified. Section 7: Handling information was modified. Section 7: Storage information was modified. Section 8: Eve/face protection phrase was modified. Section 15: 311/312 hazard categories heading was modified. Section 15: International regulations information was modified. Section 15: State regulations information was modified. Section 15: US federal regulations information was modified. Section 10: Hazardous polymerization heading was modified. Section 3: Other health effects information was modified. Section 14: ID Number(s) was modified. Section 16: HMIS explanation was modified. Section 16: NFPA explanation was modified. Section 15: 311/312 Delayed Hazard score was modified. Section 15: Inventories information was modified. Section 12: Ecotoxicological information heading was modified. Section 12: Chemical fate information heading was modified. Section 16: NFPA hazard classification for special hazards was modified. Section 15: Inventories comment was modified. Section 12: Ecotoxicological phrase was modified. Section 12: Chemical Fate phrase was modified. Section 15: WHMIS regulations heading was added.

Section 15: WHMIS regulations information was added.

Section 2: Ingredient phrase was added.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com

3M MATERIAL SAFETY DATA SHEET CC-2 PREP KIT (CABLE CLEANER) 03/27/2006