

MATERIAL SAFETY 3M
DATA SHEET 3M Center
 St. Paul, Minnesota
 55144-1000
 1-800-364-3577 or (651) 737-6501 (24 hours)

Copyright, 1996, Minnesota Mining and Manufacturing Company.
All rights reserved. Copying and/or downloading of this
information for the purpose of properly utilizing 3M products
is allowed provided that:

- 1) the information is copied in full with no changes unless
prior agreement is obtained from 3M, and
- 2) neither the copy nor the original is resold or otherwise
distributed with the intention of earning a profit thereon.

DIVISION: ELECTRICAL PRODUCTS DIVISION

TRADE NAME:

THREE CONDUCTOR INLINE SPLICING KIT 5762

ID NUMBER/U.P.C.:

80-6101-5437-1 00-54007-12262-3

ISSUED: August 23, 1996

SUPERSEDES: February 23, 1995

DOCUMENT: 10-5793-4

This product is a kit or a multipart product which consists of multiple,
independently packaged components. An MSDS for each of these components is
included. Please do not separate the component MSDSs from this cover page.
The document numbers of the MSDSs for components of this product are:

10-2613-7

11-4627-3

Abbreviations: N/D - Not Determined N/A - Not Applicable

The information in this Material Safety Data Sheet (MSDS) is believed to
be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR
IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF
MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF
PERFORMANCE OR USAGE OF TRADE. User is responsible for determining
whether the 3M product is fit for a particular purpose and suitable for
user's method of use or application. Given the variety of factors that
can affect the use and application of a 3M product, some of which are
uniquely within the user's knowledge and control, it is essential that
the user evaluate the 3M product to determine whether it is fit for a
particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers.
Due to the remote possibility that electronic transfer may have resulted
in errors, omissions or alterations in this information, 3M makes no
representations as to its completeness or accuracy. In addition,
information obtained from a database may not be as current as the
information in the MSDS available directly from 3M.

MATERIAL SAFETY 3M
 DATA SHEET 3M Center
 St. Paul, Minnesota
 55144-1000
 1-800-364-3577 or (651) 737-6501 (24 hours)

Copyright, 2001, Minnesota Mining and Manufacturing Company.
 All rights reserved. Copying and/or downloading of this
 information for the purpose of properly utilizing 3M products
 is allowed provided that:

- 1) the information is copied in full with no changes unless
 prior agreement is obtained from 3M, and
- 2) neither the copy nor the original is resold or otherwise
 distributed with the intention of earning a profit thereon.

DIVISION: ELECTRICAL PRODUCTS DIVISION

TRADE NAME:

SCOTCHCAST BRAND FLAME RETARDANT COMPOUND 2130

ID NUMBER/U.P.C.:

78-8025-2873-3	-	-	-	78-8025-2874-1	-	-	-
78-8046-9214-9	-	-	-	78-8046-9215-6	-	-	-
80-6100-7694-7	00-54007-31401-1	80-6100-7695-4	00-54007-31402-8				
80-6101-3292-2	00-54007-34359-2	80-6101-3293-0	00-54007-09143-1				
80-6107-3082-4	-	-	-	80-6107-3083-2	-	-	-
80-6107-3084-0	-	-	-	80-6112-0128-8	-	-	-
80-6112-0147-8	-	-	-	80-6112-0148-6	00-54007-43548-8		
80-6112-0149-4	-	-	-	80-6112-0150-2	00-54007-43550-1		
80-6112-0151-0	00-54007-43551-8	80-6112-0152-8	-	-	-	-	
80-6112-0171-8	-	-	-				

ISSUED: May 02, 2001

SUPERSEDES: April 16, 2001

DOCUMENT: 10-2613-7

1. INGREDIENT	C.A.S. NO.	PERCENT
Part A.....	Unknown	N/A
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)....	26447-40-5	10 - 20
MDI-PPO-Hydrogenated polyButadiene polymer.....	154517-54-1	10 - 20
1,2-BENZENEDICARBOXYLIC ACID, DIUNDECYL ESTER, BRANCHED AND LINEAR.....	85507-79-5	1 - 8
BENZENE, 1,1'-METHYLENEBIS[ISOCYANATO-, HOMOPOLYMER.....	39310-05-9	2 - 8
Part B.....	Unknown	N/A
1,3-BUTADIENE, HOMOPOLYMER, HYDROXY- TERMINATED.....	69102-90-5	15 - 25
DECABROMODIPHENYL ETHER.....	1163-19-5	10 - 20
1,2-BENZENEDICARBOXYLIC ACID, DIUNDECYL ESTER, BRANCHED AND LINEAR.....	85507-79-5	5 - 10
GLYCOLS, POLYPROPYLENE.....	25322-69-4	2 - 10
ANTIMONY TRIOXIDE.....	1309-64-4	3 - 10
N,N-DI(2-HYDROXYPROPYL)ANILINE.....	3077-13-2	2 - 6
DIPROPYLENE GLYCOL.....	25265-71-8	1 - 10
ALUMINUM POTASSIUM SODIUM SILICATE.....	12736-96-8	1 - 6
CASTOR OIL.....	8001-79-4	1 - 6

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

1. INGREDIENT	C.A.S. NO.	PERCENT
CARBON BLACK.....	1333-86-4	0.5 - 2
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica.....	68909-20-6	0.1 - 2
HYDROCINNAMIC ACID, 3,5-DI-TERT-BUTYL-4-HYDROXY-, OCTADECYL ESTER.....	2082-79-3	0.1 - 0.5
TRIETHYLENEDIAMINE.....	280-57-9	0.05 - 0.1
ARSENIC.....	7440-38-2	.02144

The components of this product are in compliance with the chemical notification requirements of TSCA. All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS.

This product contains the following toxic chemical or chemicals subject to the reporting requirements of Section 313 of Title III of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR Part 372:

DECABROMODIPHENYL ETHER
ANTIMONY TRIOXIDE
ARSENIC

2. PHYSICAL DATA

BOILING POINT:..... N/A
VAPOR PRESSURE:..... N/A
VAPOR DENSITY:..... N/A
EVAPORATION RATE:..... N/A
SOLUBILITY IN WATER:..... Reacts
SPECIFIC GRAVITY:..... PRE.:1.09 POL.:1.29
PERCENT VOLATILE:..... 0
pH:..... N/A
VISCOSITY:..... PRE.:8p POL.:30p
MELTING POINT:..... N/D

APPEARANCE AND ODOR:

PREPOLYMER:Hazy, amber liquid POLYOL:Black viscous liquid

3. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:..... Both >290F Closed Cup
FLAMMABLE LIMITS - LEL:..... N/D
FLAMMABLE LIMITS - UEL:..... N/D
AUTOIGNITION TEMPERATURE:..... N/D

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

3. FIRE AND EXPLOSION HAZARD DATA (continued)

EXTINGUISHING MEDIA:

Carbon dioxide, Dry chemical, Foam

SPECIAL FIRE FIGHTING PROCEDURES:

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

See Hazardous Decomposition section for products of combustion.

4. REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY - MATERIALS/CONDITIONS TO AVOID:

Amines, Alcohols, Water. Reaction with water, alcohols and amines is not hazardous if container can vent to the atmosphere to prevent pressure buildup.

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide and Carbon Dioxide, Oxides of Nitrogen, Hydrogen Cyanide, Isocyanates.

5. ENVIRONMENTAL INFORMATION

SPILL RESPONSE:

Observe precautions from other sections. Ventilate area. Contain spill. Evacuate unprotected personnel from hazard area. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Alternatively, pour water on spill and allow to react for more than 30 minutes. Cover with absorbent. Place in an approved drum, but do not seal the drum for 48 hours to avoid possible pressure buildup. Neutralize spill residue with decontaminant solution.

RECOMMENDED DISPOSAL:

Do not release to waterways or sewer. Incinerate in an industrial or commercial facility in the presence of a combustible material.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

5. ENVIRONMENTAL INFORMATION (continued)

ENVIRONMENTAL DATA:
Not determined.

REGULATORY INFORMATION:
Volatile Organic Compounds: N/D.
VOC Less H2O & Exempt Solvents: N/D.

Since regulations vary, consult applicable regulations or authorities before disposal. In the event of an uncontrolled release of this material, the user should determine if the release qualifies as a reportable quantity. U.S. EPA Hazardous Waste Number = D004 (Arsenic)

EPCRA HAZARD CLASS:
FIRE HAZARD: No PRESSURE: No REACTIVITY: Yes ACUTE: Yes CHRONIC: Yes

6. SUGGESTED FIRST AID

EYE CONTACT:
Immediately flush eyes with large amounts of water. Get immediate medical attention.

SKIN CONTACT:
Flush skin with large amounts of water. If irritation persists, get medical attention.

INHALATION:
Remove person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, get immediate medical attention.

IF SWALLOWED:
Do not induce vomiting. Drink two glasses of water. Call a physician.

7. PRECAUTIONARY INFORMATION

EYE PROTECTION:
Avoid eye contact. Wear safety glasses with side shields.

SKIN PROTECTION:
Avoid prolonged or repeated skin contact. Wear appropriate gloves when handling this material. A pair of gloves made from the following material(s) are recommended: butyl rubber, nitrile rubber, polyvinyl alcohol, polyvinyl chloride.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

7. PRECAUTIONARY INFORMATION (continued)

RECOMMENDED VENTILATION:

Provide sufficient ventilation to maintain emissions below recommended exposure limits. If exhaust ventilation is not adequate, use appropriate respiratory protection.

RESPIRATORY PROTECTION:

Avoid breathing of vapors. Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: half-mask organic vapor respirator.

PREVENTION OF ACCIDENTAL INGESTION:

Do not ingest.

RECOMMENDED STORAGE:

Store in a cool place. Store away from heat. Keep container in well-ventilated area. Keep out of the reach of children.

FIRE AND EXPLOSION AVOIDANCE:

Keep container tightly closed. Keep away from heat, sparks, open flame, and other sources of ignition. No smoking while handling this material. Do not heat under confinement.

HMIS HAZARD RATINGS: HEALTH: 3 FLAMMABILITY: 1 REACTIVITY: 1
PERSONAL PROTECTION: X (See precautions, section 7.)

EXPOSURE LIMITS

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
-----	-----	-----	-----	-----	-----
Part A.....	NONE	NONE	NONE	NONE	
1,1'-					
METHYLENEBIS(ISOCYANATOBENZENE)....	0.005	PPM	TWA	ACGIH	
1,1'-					
METHYLENEBIS(ISOCYANATOBENZENE)....	0.02	PPM	CEIL	OSHA	
MDI-PPO-Hydrogenated polyButadiene					
polymer.....	NONE	NONE	NONE	NONE	
1,2-BENZENEDICARBOXYLIC ACID,					
DIUNDECYL ESTER, BRANCHED AND					
LINEAR.....	NONE	NONE	NONE	NONE	
BENZENE, 1,1'-					
METHYLENEBIS[ISOCYANATO-,					
HOMOPOLYMER.....	NONE	NONE	NONE	NONE	
Part B.....	NONE	NONE	NONE	NONE	
1,3-BUTADIENE, HOMOPOLYMER,					
HYDROXY-TERMINATED.....	NONE	NONE	NONE	NONE	
DECABROMODIPHENYL ETHER.....	5	MG/M3	TWA	CMRG	
DECABROMODIPHENYL ETHER.....	5	MG/M3	TWA	AIHA	
1,2-BENZENEDICARBOXYLIC ACID,					
DIUNDECYL ESTER, BRANCHED AND					
-----	-----	-----	-----	-----	-----

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

EXPOSURE LIMITS (continued)					
INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
LINEAR.....	NONE	NONE	NONE	NONE	
GLYCOLS, POLYPROPYLENE.....	10	MG/M3	TWA	AIHA	
	AS PARTICULATE				
ANTIMONY TRIOXIDE.....	0.5	MG/M3	TWA	ACGIH	
	as Sb				
N,N-DI(2-HYDROXYPROPYL)ANILINE.....	NONE	NONE	NONE	NONE	
DIPROPYLENE GLYCOL.....	NONE	NONE	NONE	NONE	
ALUMINUM POTASSIUM SODIUM SILICATE...	NONE	NONE	NONE	NONE	
CASTOR OIL.....	10	MG/M3	TWA	OSHA	
	AS MIST				
CARBON BLACK.....	3.5	MG/M3	TWA	ACGIH	
CARBON BLACK.....	3.5	MG/M3	TWA	OSHA	
CARBON BLACK.....	0.5	MG/M3	TWA	CMRG	
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica.....	NONE	NONE	NONE	NONE	
HYDROCINNAMIC ACID, 3,5-DI-TERT-BUTYL-4-HYDROXY-, OCTADECYL ESTER..	NONE	NONE	NONE	NONE	
TRIETHYLENEDIAMINE.....	NONE	NONE	NONE	NONE	
ARSENIC.....	0.01	MG/M3	TWA	OSHA	
ARSENIC.....	0.01	MG/M3	TWA	ACGIH	
ARSENIC.....	0.005	MG/M3	TWA	OSHA	
OSHA ACTION LEVEL					

* SKIN NOTATION: Listed substances indicated with 'Y' under SKIN refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

SOURCE OF EXPOSURE LIMIT DATA:

- ACGIH: American Conference of Governmental Industrial Hygienists
- AIHA: American Industrial Hygiene Assoc. Workplace Environmental Exposure Level Guideline
- CMRG: Chemical Manufacturer Recommended Exposure Guidelines
- OSHA: Occupational Safety and Health Administration
- NONE: None Established

8. HEALTH HAZARD DATA

EYE CONTACT:

Mild Eye Irritation: signs/symptoms can include redness, swelling, pain, and tearing.

SKIN CONTACT:

Allergic Skin Reaction: signs/symptoms can include redness, swelling, blistering, and itching.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

8. HEALTH HAZARD DATA (continued)

Mild Skin Irritation: signs/symptoms can include redness, swelling, and itching.

INHALATION:

Allergic Respiratory Reaction: signs/symptoms can include difficulty breathing, wheezing, tightness of chest, and respiratory failure.

Irritation (upper respiratory): signs/symptoms can include soreness of the nose and throat, coughing and sneezing.

Vapors of the uncured product may cause irritation of the respiratory system.

IF SWALLOWED:

Irritation of Gastrointestinal Tissues: signs/symptoms can include pain, vomiting, abdominal tenderness, nausea, blood in vomitus, and blood in feces.

CANCER:

WARNING: Contains a chemical which can cause cancer. (1309-64-4)
(ACGIH suspected human carcinogen A2, IARC possible human carcinogen 2B, Calif. Proposition 65)

WARNING: Contains a chemical which can cause cancer. (1333-86-4)
(IARC possible human carcinogen 2B)

WARNING: Contains a chemical which can cause cancer. (7440-38-2) (NTP human carcinogen-Arsenic inorganic compounds, IARC human carcinogen 1, OSHA listed carcino gen, Calif. Proposition 65 - Inorganic Arsenic Compounds)

SECTION CHANGE DATES

HEADING	SECTION CHANGED SINCE April 16, 2001	ISSUE
---------	--------------------------------------	-------

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.



Material Safety Data Sheet

Copyright, 2006, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: CC-2 PREP KIT (CABLE CLEANER)

MANUFACTURER: 3M

DIVISION: Electrical Markets Division

ADDRESS: 3M Center
St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 03/27/2006

Supersedes Date: 10/26/2003

Document Group: 11-4627-3

Product Use:

Specific Use: SOLVENT SOAKED RAGS FOR CABLE CLEANING

SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
PETROLEUM DISTILLATES	64771-72-8	80 - 95
D-LIMONENE	5989-27-5	5 - 20

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Odor, Color, Grade: clear, citrus-like odor

General Physical Form: Liquid

Immediate health, physical, and environmental hazards: Flammable liquid and vapor. Combustible liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back. May cause allergic skin reaction. May cause target organ effects.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin Contact:

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Inhalation:

Upper Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May be absorbed following inhalation and cause target organ effects.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, nausea, diarrhea and vomiting.

Chemical (Aspiration) Pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish colored skin (cyanosis), and may be fatal.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

3.3 POTENTIAL ENVIRONMENTAL EFFECTS

VOC Data: 740 grams/liter maximum VOC (less water and exempt compounds). U.S. EPA Waste Number: None. 5 Day Biological Oxygen Demand (BOD-5) = 77,000 mg/L. Chemical Oxygen Demand (COD) = 290,000 mg/L.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: Do not induce vomiting. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get immediate medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature

No Data Available

Flash Point

≥ 144 °F [*Test Method:* Closed Cup]

Flash Point

144 °F [*Test Method:* Closed Cup] [*Details:* MITS data]

Flash Point

≥ 165 °F [*Test Method:* Open Cup]

Flammable Limits - LEL

No Data Available

Flammable Limits - UEL

No Data Available

OSHA Flammability Classification:

Class IIIA Combustible Liquid

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Flammable liquid and vapor. Combustible liquid and vapor. Not applicable. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Contain spill. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Place in a metal container approved for transportation by appropriate authorities. Seal the container.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. No smoking while handling this material. Avoid breathing of vapors, mists or spray. Avoid eye contact with vapors, mists, or spray. Avoid contact with oxidizing agents.

7.2 STORAGE

Store away from acids. Store away from heat. Store out of direct sunlight. Keep container in well-ventilated area. Store away from oxidizing agents.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Provide appropriate local exhaust ventilation on open containers. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use respiratory protection equipment.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact. Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Indirect Vented Goggles.

8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Fluoroelastomer (Viton), Nitrile Rubber, Polyethylene.

8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
PETROLEUM DISTILLATES	CMRG	TWA	300 ppm	

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Odor, Color, Grade:	clear, citrus-like odor
General Physical Form:	Liquid
Autoignition temperature	No Data Available
Flash Point	>=144 °F [Test Method: Closed Cup]
Flash Point	144 °F [Test Method: Closed Cup] [Details: MITS data]
Flash Point	>=165 °F [Test Method: Open Cup]
Flammable Limits - LEL	No Data Available
Flammable Limits - UEL	No Data Available
Boiling point	380.00 - 480.00 °F
Boiling point	>=95 °F [Details: MITS data]
Density	0.76 g/ml
Vapor Density	>=1.00 [Ref Std: AIR=1]
Vapor Pressure	<=1.0000 mmHg [Details: CONDITIONS: Less than 1 mmHg at 25 C]
Specific Gravity	0.76 [Details: MITS data]
pH	7.0
Melting point	No Data Available

Evaporation rate	Not Applicable
Volatile Organic Compounds	Approximately 740 g/l
VOC Less H2O & Exempt Solvents	No Data Available
Viscosity	No Data Available

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid: Strong oxidizing agents

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in an industrial or commercial facility. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14: TRANSPORT INFORMATION

ID Number(s):

78-8061-7605-9, 80-6105-9299-2, 80-6112-0013-2, 80-6114-2769-3

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

STATE REGULATIONS

Contact 3M for more information.

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS.

Contact 3M for more information.

The components of this product are listed on the Canadian Domestic Substances List.

Additional Information: All components are on the TSCA; EINECS; and CDSL Inventories.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

WHMIS: Hazardous

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 2 **Flammability:** 2 **Reactivity:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 2 **Flammability:** 2 **Reactivity:** 0 **Protection:** B

Hazardous Material Identification System (HMIS®) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint and Coatings Association (NPCA).

Revision Changes:

Section 16: NFPA hazard classification heading was modified.
Section 16: HMIS hazard classification heading was modified.
Section 3: Potential environmental effects heading was modified.
Section 3: Other potential health effects heading was modified.
Section 1: Division name was modified.
Copyright was modified.
Section 8: Exposure guidelines data source legend was modified.
Section 3: Immediate physical hazard(s) was modified.
Section 3: Potential effects from eye contact was modified.
Section 3: Potential effects from inhalation information was modified.
Section 3: Potential effects from ingestion information was modified.
Section 5: Fire fighting procedures information was modified.
Section 5: Unusual fire and explosion hazard information was modified.
Section 6: Release measures information was modified.
Section 7: Handling information was modified.
Section 7: Storage information was modified.
Section 8: Eye/face protection phrase was modified.
Section 15: 311/312 hazard categories heading was modified.
Section 15: International regulations information was modified.
Section 15: State regulations information was modified.
Section 15: US federal regulations information was modified.
Section 10: Hazardous polymerization heading was modified.
Section 3: Other health effects information was modified.
Section 14: ID Number(s) was modified.
Section 16: HMIS explanation was modified.
Section 16: NFPA explanation was modified.
Section 15: 311/312 Delayed Hazard score was modified.
Section 15: Inventories information was modified.
Section 12: Ecotoxicological information heading was modified.
Section 12: Chemical fate information heading was modified.
Section 16: NFPA hazard classification for special hazards was modified.
Section 15: Inventories comment was modified.
Section 12: Ecotoxicological phrase was modified.
Section 12: Chemical Fate phrase was modified.
Section 15: WHMIS regulations heading was added.
Section 15: WHMIS regulations information was added.
Section 2: Ingredient phrase was added.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com

