Material Safety Data Sheet

The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know.

The following material safety data sheet covers the hazardous ingredients associated with more than one color bulk product. As per 29 CFR 1900, 1200 paragraph (g); whenever the hazards associated with similar mixtures are the same, then one MSDS may be prepared to cover several products.

This MSDS covers the following Aervoe bulk products.

PRODUCT NAME: Direct To Metal Rust Proofing Paint (solvent-based)

300 Safety Purple	308 Brite Red	318 Light Blue	348 Meter Green
301 Safety Red	309 Aluminum	319 Royal Blue	349 Meter Gray (ANSI-49)
302 Safety Yellow	311 Gold	320 Forest Green	361 Light Gray (ANSI-61)
303 Safety Blue	312 Flat Black	321 Equipment Orange	365 Blue-Gray (ANSI-70)
304 Safety Green	313 Flat White	333 Dark Gray (ANSI-33)	380 Mica
305 Safety Orange	314 Brown	342 Semi Flat Black	395 Dove Gray
306 Safety Black	317 Tan	344 Satin Black	396 Marine Gray
307 Safety White			•
306 Safety Black			,

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Aervoe Industries Inc.

INFORMATION PHONE: 775-782-0100

DATE REVISED: February 23, 2006

ADDRESS: 1198 Mark Circle, Gardnerville, NV 89410

EMERGENCY PHONE: 1-800-424-9300

REASON REVISED: Updated

SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION **OCCUPATIONAL EXPOSURE LIMITS**

HAZARDOUS WEIGH COMPONENTS PERCE		ACGIH TLV	ACGIH STEL	LD50 SPECIES & ROUTE	LC50 SPECIES & ROUTE
Aliphatic Hydrocarbon (CAS 64742-47-8) 10 - 30	500 ppm	100 ppm		N / AV	N / AV
Aliphatic Hydrocarbon (CAS 64741-41-9) 7 - 13	500 ppm 3	100 ppm		N / AV	N / AV
Aliphatic Hydrocarbon (CAS 8052-41-3) 5 - 10	500 ppm 0	100 ppm		N / AV	N / AV
Aliphatic Petroleum Distillates (CAS 64742-88-7) 1 - 5	100 ppm	100 ppm		N / AV	N / AV
Aliphatic Petroleum Distillates (CAS 64742-89-8) 1 - 3	N / AV	300 ppm		N / AV	N / AV
*Xylene (CAS 1330-20-7) 1 - 3	100 ppm	100 ppm		4300 mg / kg (Rat-Oral)	6700 ppm / 4 hr (Rat-Inha)

^{*}Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

NOTE: N / AP = Not Applicable N / AV = Not Available

Direct To Metal Rust Proof Paint (solvent based - bulk) February 23, 2006

11B2

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT: 340° F (171° C) **SPECIFIC GRAVITY (H20 = 1):** 1.0 to 1.3 PHYSICAL STATE: Liquid

VAPOR DENSITY: Heavier than air **SOLUBILITY IN WATER:** Very slight

EVAPORATION RATE: Slower than n-Butyl Acetate APPEARANCE AND ODOR: Opaque liquid with hydrocarbon odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 110° F (43° C) METHOD USED: Estimated FLAMMABLE LIMITS: LEL: 0.7% UEL: 7.0%

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, water spray

SPECIAL FIRE FIGHTING PROCEDURES: Use water spray to cool containers exposed to heat or fire to prevent pressure build up.

Self-contained breathing apparatus should be used if product is involved in fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may rupture due to pressure build up from extreme temperature.

FLAMMABILITY: Combustible liquid under conditions of sparks, flame or hot surfaces.

SENSITIVITY TO IMPACT: Product will leak if container is punctured. SENSITIVITY TO STATIC DISCHARGE: Primarily vapors

SECTION V - REACTIVITY DATA

STABILITY: Stable CONDITIONS TO AVOID: Open flames, sparks, electrical arcs.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon monoxide, carbon dioxide

HAZARDOUS POLYMERIZATION: Will not occur

SECTION VI - HEALTH HAZARD DATA

INHALATION: Respiratory tract irritant. May cause dizziness, light-headedness and / or headaches.

SKIN CONTACT: Prolonged or repeated contact may cause irritation and dermatitis.

EYE CONTACT: Painful with slight to moderate irritation.

SKIN ABSORPTION: Not likely to be absorbed in toxic amounts under normal use. INGESTION: Not likely in normal use but swallowing large amounts may be harmful.

CARCINOGENICITY: The ingredients are not listed as a human carcinogen by IARC, ACGIH, NTP, or OSHA.

TERATOGENICITY: Not established **MUTAGENICITY**: Not established MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE: Not established

EMERGENCY AND FIRST AID PROCEDURES: INHALATION - Remove from exposure, seek medical attention if signs/symptoms persist.

SKIN - Wash affected area with soap and water, remove contaminated clothing, seek medical attention if irritation persists.

EYES - Flush immediately with water for 15 minutes, seek medical attention if irritation persists.

INGESTION - Do NOT induce vomiting, drink plenty of water, seek medical attention.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Ventilate area. Prevent from entering a watercourse. Use an inert absorbent material and non-sparking type tools.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120° F (49° C).

Do not store or use near heat, sparks or flame.

OTHER PRECAUTIONS: Do not smoke while using this product. Dust from sanding the dry paint film should be treated as a nuisance dust with an OSHA PEL (TWA) of 15 mg/cubic meter.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: In areas with poor ventilation, use a NIOSH approved Organic Vapor Cartridge Respirator.

For concentrations above the TLV (as defined in Section II), use a positive air supplied respirator.

VENTILATION: General ventilation to maintain exposure limits below TLV's as defined in Section II.

PROTECTIVE GLOVES: Chemical resistant gloves such as Neoprene or Nitrile rubber.

EYE PROTECTION: Safety glasses or goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Not established.

WORK / HYGIENIC PRACTICES: Avoid prolonged or repeated contact. Do not breathe vapors. Wash contaminated clothing prior to reuse.

SECTION IX - DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.