

# MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

## IDENTITY AND MANUFACTURER'S INFORMATION

NFPA Rating: Health-2; Flammability-2; Reactivity-0; Special-0		HMIS Rating: Health-2; Flammability-2; Reactivity-0; Personal Protection-8	
Manufacturer's Name: AMREP, INC.		DOT Hazard Classification: ORM-D	
Address: 990 Industrial Park Drive Marietta, GA 30062		Identity (trade name as used on label): MISTY FURNITURE POLISH	
Date Prepared: 3/1/93	Prepared By: ES/KD	MSDS Number: 134	Revision: 9
Information Calls: (770)422-2071		NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA	
EMERGENCY RESPONSE NUMBER: 1(800)255-3924			

## SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION

COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
PETROLEUM SOLVENT	64742-48-9	No	300	300	d
PETROLEUM DISTILLATES	68551-15-5	No	N/E	N/E	d
ISOBUTANE / PROPANE BLEND	75-28-5	No	800	800	d
	74-98-6	No	1000	1000	d

## SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: NA	Specific Gravity (H <sub>2</sub> O=1): Concentrate Only = 0.956
Vapor Pressure: PSIG @ 70°F (Aerosols): Max.60	Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A
Vapor Density (Air = 1): N/E	Evaporation Rate ( = 1): N/E
Solubility in Water: Slight	Water Reactive: No
Appearance and Odor: Creamy white spray with lemon fragrance.	

## SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) <b>NON-FLAMMABLE</b>	Auto Ignition Temperature N/E	Flammability Limits in Air by % in Volume: % LEL: N/E      % UEL: N/E
FLASH POINT AND METHOD USED (non-aerosols): N/A	EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide.	
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.		
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.		

## SECTION 4 - REACTIVITY HAZARD DATA

STABILITY [ X ] STABLE [ ] UNSTABLE	HAZARDOUS POLYMERIZATION [ ] WILL [ X ] WILL NOT OCCUR
Incompatibility (Mat. to avoid): Strong oxidizers and alkalies.	Conditions to Avoid: Open flame, welding arcs, heat, sparks.
Hazardous Decomposition Products: CO <sub>2</sub> , CO, hydrogen chloride.	

## SECTION 5 - HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: [ X ] INHALATION [ ] INGESTION [ X ] SKIN ABSORPTION [ ] EYE [ ] NOT HAZARDOUS	
ACUTE EFFECTS:	
Inhalation: Excessive inhalation of vapors can be harmful and may cause headaches, dizziness, asphyxia, anesthetic effects and possible unconsciousness.	
Eye Contact: Mild irritant.	Skin Contact: Mild irritant.
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.	
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause cardiac abnormality, liver abnormalities, kidney and/or lung damage.	
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, upper respiratory conditions, liver disease & heart irregularities.	

## EMERGENCY FIRST AID PROCEDURES

Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.
Skin Contact: Wash with soap and water. If irritated, seek medical attention.
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.

## SECTION 6 - CONTROL AND PROTECTIVE MEASURES

Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor.	Eye Protection: Safety glasses recommended.
Protective Gloves: Latex if skin is easily irritated.	
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.	
Other Protective Clothing & Equipment: None	
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.	

## SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or Federal regulations. DO NOT FLUSH TO SEWER.
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

\*\* Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only