



MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Product name	9732 Silicone Sealant Series
Product name(s) covered	See Section 16 for Product Names Covered.
MSDS name	9732 Silicone Sealants - Various Colors
CAS number	Mixture
Generic description	Silicone Sealant
Manufacturer	Bostik, Inc. 211 Boston Street Middleton, MA 01949 USA
24 hour emergency assistance	Telephone: 1-800-227-0332
General assistance	Telephone: 1-978-777-0100
MSDS assistance	Telephone: 1-414-607-1347

2. COMPOSITION / INFORMATION ON INGREDIENTS

The manufacturer lists no ingredients as hazardous according to OSHA 29 CFR 1910.1200.

3. HAZARDS IDENTIFICATION

Emergency overview	Extended contact with this material may cause irritation to the skin, eyes, and mucous membranes.
Potential health effects	
Skin	Skin contact may cause irritation.
Eyes	This product may cause irritation to the eyes.
Inhalation	This product may cause irritation to the respiratory system.
Ingestion	This product can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.
Target organs	None known for product as a whole.

4. FIRST AID MEASURES

First aid	
Skin	For skin contact, wash immediately with soap and water. Seek medical attention if irritation, rash, or other symptoms develop.
Eye	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention or advice.
Inhalation	Remove to fresh air. Call a physician if symptoms develop or persist.
Ingestion	If ingested, get immediate medical attention. Do not induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to a victim who is unconscious or is having convulsions.
Notes to physician	Treat symptomatically and supportively. Contact Bostik to determine whether any additional information is available.

5. FIRE FIGHTING MEASURES

Hazardous combustion products	Fumes from complete or incomplete combustion may include carbon dioxide, carbon monoxide, water vapor, acetic acid, formaldehyde, oxides of nitrogen and silicon, and a wide variety of innocuous or toxic fumes.
Extinguishing media	Use dry chemical, carbon dioxide, or foam. Water spray (fog).
Dust explosion hazard	None Known
Sensitivity to mechanical impact	None Known
Sensitivity to static discharge	None Known
Fire fighting equipment/instructions	Firefighters should wear full protective clothing including self contained breathing apparatus.

Flash point > 200 °F (> 93.3 °C)

6. ACCIDENTAL RELEASE MEASURES

Emergency action Appropriate safety measures and protective equipment should be used. See Section 8. Do not discharge to lakes, streams, ponds, or sewers. Dispose of in compliance with local, state, and federal regulations.

Spill or leak procedure Scrape up paste and place in steel drums that are in good condition. Thoroughly clean area where spill occurred.

Reporting See Federal reporting requirements listed in Section 15. We recommend you contact local authorities to determine if there may be other local reporting requirements.

7. HANDLING & STORAGE

Handling Wash hands thoroughly after handling, especially before eating, drinking, smoking, and using restroom facilities. Wash contaminated goggles, face shields, and gloves. Professionally launder contaminated clothing before re-use.

Storage Store in a cool, dry, well-ventilated area away from heat, ignition sources and direct sunlight. Water contamination should be avoided. Cool location should be 60-80 degrees F or 15-30 degrees C.

Empty container precaution Attention! Follow label warnings even after container is emptied since empty containers may retain product residues. Do not reuse empty container without professional cleaning for food, clothing, or products for human or animal consumption, or where skin contact can occur.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls Use local exhaust ventilation when vapors, mists, or dusts are being generated. Suitable respiratory equipment should be used when insufficient ventilation or operational procedures demand it.

Eye protection Wear goggles or safety glasses with side shields.

Skin and body protection Wear appropriate clothing to minimize skin contact with this product.

Respiratory protection If ventilation is not sufficient to effectively prevent buildup of vapors, appropriate NIOSH/MSHA respiratory protection must be provided

9. PHYSICAL & CHEMICAL PROPERTIES

Density 1.035 g/cc

Color Various

Physical state Paste

Freeze protect No

10. STABILITY & REACTIVITY

Hazardous reactions/decomposition products Unknown due to the complex nature of this material. Fumes from complete or incomplete combustion may include carbon dioxide, carbon monoxide, water vapor, acetic acid, formaldehyde, oxides of nitrogen and silicon, and a wide variety of innocuous or toxic fumes.

Hazardous polymerization Will not occur.

Conditions to avoid Avoid contact with Strong Oxidizers and Strong Acids.

Stability This is a stable material.

11. TOXICOLOGICAL INFORMATION

Toxicological data If any toxicological data is available, it will be listed below:

12. ECOLOGICAL INFORMATION

Ecotoxicological information No data available for this product.

13. DISPOSAL CONSIDERATIONS

It is the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable local, state and federal regulations.

Waste disposal

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations. When intending to dispose of this material, the user is advised that this product would not be classified as a Hazardous Waste under U.S. Federal Regulations in effect at the time this MSDS was created.

14. TRANSPORT INFORMATION**Department of Transportation (DOT) Requirements**

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. REGULATORY INFORMATION

This MSDS is prepared and distributed pursuant to the Federal Hazard Communication Standard, 29 CFR 1910.1200.

Federal regulations

All components are on the U.S. EPA TSCA Inventory List.

State regulations

If this product contains any ingredients listed under California Proposition 65, they will be noted below:

International regulations

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and contains all the information required by the Controlled Products Regulations.

HMIS Ratings

Health: 1
Flammability: 1
Physical hazard: 0
Personal protection: X

SARA 311/312 HAZARD CATEGORIES

Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

WHMIS status

Non-controlled

16. OTHER INFORMATION**Product name(s) covered**

K130205 - BOSTIK SIL 9732 CLEAR 4.5GL PL
K130237 - 9732 CLEAR 24/10.1/300 ML
K130238 - 9732 CLEAR 12/3 OZ
K130305 - SILICONE 9732 WHITE 4.5GL PL
K130337 - 9732 WHITE 24/10.1/300 ML
K130338 - 9732 WHITE 12/3 OZ
K130405 - SILICONE 9732 BLACK 4.5GL PL
K130437 - 9732 BLACK 24/10.1/300 ML
K130438 - 9732 BLACK 12/3 OZ
K130637 - 9732 ALUM 24/10.1/300 ML
K210903 - 9732 RED HI 12/3 OZ
K210905 - SILICONE 9732 RED 4.5GA PL
K719010 - 9732 RED 24/10.1/300 ML

Disclaimer

The data in this MSDS has been compiled from publicly available sources. This data relates only to the designated product and not to the use of said product in combination with other materials. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Responsibility for proper precautions and safe use of the product lies with the user. All data in this MSDS is typical of the product as a whole, and does not represent any individual lot or batch, therefore, Bostik, Inc. makes no warranty about the accuracy of the data herein and assumes no liability for the use of such data. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.

Issue date

11-JAN-08

Prepared by

Pam Larsen

Supercedes

15-NOV-06