

MATERIAL SAFETY DATA SHEET

DATE: 4/11/86

96

| SECTION 1                                                                                    |                                                    |
|----------------------------------------------------------------------------------------------|----------------------------------------------------|
| MANUFACTURER'S NAME<br>Burton Rubber Processing, Inc.                                        | EMERGENCY TELEPHONE NO.<br>216-834-4644            |
| ADDRESS (Number, Street, City, State and ZIP Code)<br>14330 Kinsman Road, Burton, Ohio 44021 |                                                    |
| CHEMICAL NAME AND SYNONYMS<br>Polychloroprene MB                                             | TRADE NAME AND SYNONYMS<br>6020 MB                 |
| CHEMICAL FAMILY<br>Polymeric                                                                 | FORMULA<br>Proprietary-generated by AGI Rubber Co. |

| SECTION II - HAZARDOUS INGREDIENTS                    |      |             |                                        |      |             |             |
|-------------------------------------------------------|------|-------------|----------------------------------------|------|-------------|-------------|
| PAINTS, PRESERVATIVES & SOLVENTS                      | %    | TLV (Units) | ALLOYS AND METALLIC COATINGS           | %    | TLV (Units) |             |
| PIGMENTS                                              | None |             | BASE METAL                             | None |             |             |
| CATALYST                                              | None |             | ALLOYS                                 | None |             |             |
| VEHICLE                                               | None |             | METALLIC COATINGS                      | None |             |             |
| SOLVENTS                                              | None |             | FILLER METAL PLUS COATING OR CORE FLUX | None |             |             |
| ADDITIVES                                             | None |             | OTHERS                                 |      |             |             |
| OTHERS                                                |      |             |                                        |      |             |             |
| HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES |      |             |                                        |      | %           | TLV (Units) |
| Octylated diphenylamine, irritant, CAS 101-67-7       |      |             |                                        |      |             | 5mg/m       |
| Soybean oil epoxide, irritant                         |      |             |                                        |      |             | None        |
|                                                       |      |             |                                        |      |             |             |
|                                                       |      |             |                                        |      |             |             |
|                                                       |      |             |                                        |      |             |             |
|                                                       |      |             |                                        |      |             |             |
|                                                       |      |             |                                        |      |             |             |
|                                                       |      |             |                                        |      |             |             |
|                                                       |      |             |                                        |      |             |             |
|                                                       |      |             |                                        |      |             |             |

| SECTION III - PHYSICAL DATA |                                           |                                       |      |
|-----------------------------|-------------------------------------------|---------------------------------------|------|
| BOILING POINT (°F.)         | NA                                        | SPECIFIC GRAVITY (H <sub>2</sub> O=1) | 1.43 |
| VAPOR PRESSURE (mm Hg.)     | NA                                        | PERCENT VOLATILE BY VOLUME (%)        | NA   |
| VAPOR DENSITY (AIR=1)       | NA                                        | EVAPORATION RATE (_____ = 1)          | NA   |
| SOLUBILITY IN WATER         | Nil                                       |                                       |      |
| APPEARANCE AND ODOR         | Black, Rubbery solid; characteristic odor |                                       |      |

| SECTION IV - FIRE AND EXPLOSION HAZARD DATA |                                                       |                  |    |
|---------------------------------------------|-------------------------------------------------------|------------------|----|
| FLASH POINT (Method Used)                   | NA                                                    | FLAMMABLE LIMITS | NA |
| EXTINGUISHING MEDIA                         | Water spray, protein-type air foam, ABC dry chemical. |                  |    |
| SPECIAL FIRE FIGHTING PROCEDURES            | Wear self-contained breathing apparatus.              |                  |    |
| UNUSUAL FIRE AND EXPLOSION HAZARDS          | Combustion releases HCl fumes (TLV-5ppm).             |                  |    |

96

| SECTION V - HEALTH HAZARD DATA     |                                                                                                                   |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------|
| THRESHOLD LIMIT VALUE              | NA                                                                                                                |
| EFFECTS OF OVEREXPOSURE            | Contains irritant vapors at processing temperatures.                                                              |
|                                    |                                                                                                                   |
| EMERGENCY AND FIRST AID PROCEDURES | Flush eyes/skin with plenty of water-consult physician if irritation persists.<br>If inhaled-remove to fresh air. |
|                                    |                                                                                                                   |

| SECTION VI - REACTIVITY DATA         |                |   |                     |
|--------------------------------------|----------------|---|---------------------|
| STABILITY                            | UNSTABLE       |   | CONDITIONS TO AVOID |
|                                      | STABLE         | X | NONE                |
| INCOMPATIBILITY (Materials to avoid) |                |   |                     |
| Strong oxidizing agents              |                |   |                     |
| HAZARDOUS DECOMPOSITION PRODUCTS     |                |   |                     |
| CO, CO <sub>2</sub> and HCN          |                |   |                     |
| HAZARDOUS POLYMERIZATION             | MAY OCCUR      |   | CONDITIONS TO AVOID |
|                                      | WILL NOT OCCUR | X | NONE                |

| SECTION VII - SPILL OR LEAK PROCEDURES                              |  |
|---------------------------------------------------------------------|--|
| STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED           |  |
| Collect: return to container                                        |  |
|                                                                     |  |
| WASTE DISPOSAL METHOD                                               |  |
| Dispose of in accordance with local, state and federal regulations. |  |

| SECTION VIII - SPECIAL PROTECTION INFORMATION                         |                      |                |
|-----------------------------------------------------------------------|----------------------|----------------|
| RESPIRATORY PROTECTION (Specify type)                                 |                      |                |
| Organic vapor respirator is recommended if ventilation is inadequate. |                      |                |
| VENTILATION                                                           | LOCAL EXHAUST        | SPECIAL        |
|                                                                       | MECHANICAL (General) | OTHER          |
| PROTECTIVE GLOVES                                                     |                      | EYE PROTECTION |
| Recommended                                                           |                      | Recommended    |
| OTHER PROTECTIVE EQUIPMENT                                            |                      |                |

| SECTION IX - SPECIAL PRECAUTIONS                                 |  |
|------------------------------------------------------------------|--|
| PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING                  |  |
| Store below 120°F away from direct sources of heat and sunlight. |  |
|                                                                  |  |
| OTHER PRECAUTIONS                                                |  |
| Wash thoroughly after handling.                                  |  |

DATE 9/14/85

SIGNATURE Dorcas L. Decker

TITLE Chemist