Section 1: Product & Company Identification

Product Name: Carb & Choke Cleaner (aerosol)

Product Number (s): 03077

Product Use: Carburetor Cleaner

Manufacturer / Supplier Contact Information:

In United States: In Canada: CRC Industries, Inc. CRC Canada Co.

2-1246 Lorimar Drive 885 Louis Drive Warminster, PA 18974 Mississauga, Ontario L5S 1R2

www.crcindustries.com www.crc-canada.ca 1-905-670-2291

1-215-674-4300 (General) (800) 521-3168 (Technical)

(800) 272-4620 (Customer Service)

In Mexico:

CRC Industries Mexico Av. Benito Juárez 4055 G

Colonia Orquídea

San Luís Potosí, SLP CP 78394

www.crc-mexico.com 52-444-824-1666

24-Hr Emergency - CHEMTREC: (800) 424-9300 or (703) 527-3887

Section 2: Hazards Identification

Emergency Overview

DANGER: Extremely Flammable. Vapors May Cause Flash Fires. Harmful if swallowed.

Eve and Skin Irritant. Contents Under Pressure.

Appearance & Odor: Clear colorless liquid, solvent odor

Potential Health Effects:

ACUTE EFFECTS:

EYE: Eye irritant. Contact may cause moderate to severe eye irritation including stinging, watering and

redness.

Skin irritant. Contact may cause redness, itching, burning, and skin damage. Prolonged or repeated SKIN:

contact can worsen irritation by causing drying and cracking of the skin, leading to dermatitis

(inflammation).

Low to moderate degree of toxicity by inhalation. Effects of overexposure may include irritation to the INHALATION:

respiratory tract and signs of nervous system depression (headache, drowsiness, dizziness, loss of

coordination, disorientation and fatigue).

INGESTION: Main hazard is aspiration. This material can enter lungs during swallowing or vomiting and cause lung

inflammation and damage. Swallowing this material may also cause nausea and diarrhea. Acetone

poisoning may result in liver and kidney damage.

CHRONIC EFFECTS: Exposure to high concentrations of this material may increase the sensitivity of the heart to

certain drugs. Reports have associated repeated and prolonged overexposure to solvents with

permanent brain and nervous system damage.

TARGET ORGANS: Liver, kidney, central nervous system

Medical Conditions Aggravated by Exposure: Skin disorders, respiratory (asthma-like) disorders

Product Number (s): 03077

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.
Heptane isomers	142-82-5 / 64742-49-0	5 - 15
Acetone	67-64-1	80 - 90
Carbon dioxide	124-38-9	8 - 13

Section 4: First Aid Measures

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician if

irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If

breathing is difficult give oxygen. Call a physician.

Ingestion: Do NOT induce vomiting or give anything by mouth because material can enter the lungs and cause

severe lung damage. Seek medical attention immediately.

Note to Physicians: Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed

to high concentrations of hydrocarbon solvents. The use of other drugs with less arrhythmogenic

potential should be considered.

Section 5: Fire-Fighting Measures

Flammable Properties: This product is extremely flammable in accordance with aerosol flammability definitions.

(See 16 CFR 1500.3(c)(6)).

Flash Point: < 0°F / -18°C (TCC) Upper Explosive Limit: 12.8 Autoignition Temperature: 869°F / 465°C Lower Explosive Limit: 2.5

Fire and Explosion Data:

Suitable Extinguishing Media: Dry chemical, carbon dioxide or foam is recommended.

Products of Combustion: Oxides of carbon

Explosion Hazards: Aerosol containers, when exposed to heat from fire, may build pressure and explode. Vapors

may accumulate in a confined space and create a flammable atmosphere.

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for

protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition. Avoid spreading

burning liquid with water used for cooling purposes.

Section 6: Accidental Release Measures

Product Number (s): 03077

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into

sewers or storm drains.

Methods for Containment & Clean-up: Eliminate all potential sources of ignition. Dike area to contain spill. Ventilate the

area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used

absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Do not use on or around any potential sources of ignition or live equipment. Wash thoroughly

after use and before handling food. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. For product use instructions, please see the product

label.

Storage Procedures: Aerosol cans must be maintained below 120°F / 49°C to prevent cans from rupturing. Use and

store this material in cool, dry, well-ventilated areas away from heat, direct sunlight, hot metal

surfaces, and all sources of ignition. Keep away from incompatible material.

Aerosol Storage Level: III

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

	OSHA		ACGIH		OTHER		
COMPONENT	TWA	STEL	TWA	STEL	TWA	SOURCE	UNIT
Heptane isomers	500	NE	400	500	NE		ppm
Acetone	750 (v)	1000 (v)	500	750	NE		ppm
Carbon dioxide	5000	30000(v)	5000	30000	NE		ppm
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

Controls and Protection:

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally

preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA

regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls

are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and

for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid

contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile, PVA or Viton®. Also, use full protective clothing if there is

prolonged or repeated contact of liquid with skin.

Product Number (s): 03077

Section 9: Physical and Chemical Properties

Physical State: liquid Color: clear, colorless

Odor: solvent

Odor Threshold: ND
Specific Gravity: 0.780
Initial Boiling Point: 132°F / 56°C
Freezing Point: <-100°F / -73°C

Vapor Pressure: ND

Vapor Density: 2 (air = 1)

Evaporation Rate: fast

Solubility: slightly soluble in water Coefficient of water/oil distribution: ND

pH: NA

Volatile Organic Compounds: wt %: 9.0 g/L: 70.2 lbs./gal: 0.59

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Sources of ignition, temperature extremes

Incompatible Materials: Avoid contact with acids and oxidizers such as chlorine and other halogens, chromates,

perchlorates, peroxides and oxygen.

Hazardous Decomposition Products: Oxides of carbon

Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

Acute Toxicity:

<u>Component</u>	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 (rat)
Heptane isomers	> 15000 mg/kg	> 2000 mg/kg	103 g/m ³ /4H
Acetone	5800 mg/kg	> 15,800 mg/kg	30,000 ppm/4H
Carbon dioxide	No data	No data	470,000 ppm/30M

Chronic Toxicity:

	OSHA	IARC	NTP		
<u>Component</u>	Carcinogen	Carcinogen	Carcinogen	<u>Irritant</u>	Sensitizer
Heptane isomers	No	No	No	Skin	No
Acetone	No	No	No	Eye	No
Carbon dioxide	No	No	No	No	No

Product Number (s): 03077

Reproductive Toxicity: No information available No information available

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: n-heptane - 24 Hr EC50 Daphnia magna: >10 mg/L

acetone - 48 Hr EC50 Daphnia magna: 12600 mg/L

Persistence / Degradability:
Bioaccumulation / Accumulation:
Mobility in Environment:

No information available
No information available

Section 13: Disposal Considerations

Waste Classification: The dispensed liquid product is a RCRA hazardous waste for the characteristic of ignitability with

the following potential waste codes: D001, F003. (See 40 CFR Part 261.20 – 261.33) Empty aerosol containers may be recycled. Any liquid product should be managed as a

hazardous waste.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

Section 14: Transport Information

US DOT (ground): UN1950, Aerosols, flammable, 2.1, Limited Quantity**

ICAO/IATA (air): UN1950, Aerosols, flammable, 2.1, Limited Quantity

IMO/IMDG (water): UN1950, Aerosols, 2.1, Limited Quantity

Special Provisions: **This product can be classified and labeled as 'Consumer Commodity, ORM-D' for domestic

ground shipping until January 1, 2014.

If shipping as limited quantity by ground, note that shipping papers are not required.

Section 15: Regulatory Information

U.S. Federal Regulations:

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: Acetone (5000 lbs)

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Product Number (s): 03077

Section 311/312 Hazard Categories: Fire Hazard Yes

Reactive Hazard No Release of Pressure Yes Acute Health Hazard Yes Chronic Health Hazard No

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements

of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of

1986 and 40 CFR Part 372:

None

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

Occupational Safety and Health Administration (OSHA):

This product is regulated under the Hazard Communication Standard.

U.S. State Regulations:

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of

California to cause cancer, birth defects or other reproductive harm: toluene (< 0.005%)

Consumer Products VOC Regulations: In states with Consumer Products VOC regulations, this product is compliant as

a carburetor cleaner.

State Right to Know:

New Jersey: 142-82-5, 67-64-1, 124-38-9 Pennsylvania: 142-82-5, 67-64-1, 124-38-9 Massachusetts: 142-82-5, 67-64-1, 124-38-9 Rhode Island: 142-82-5, 67-64-1, 124-38-9

Canadian Regulations:

Controlled Products Regulations:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the

MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: A, B5, D2B

<u>Canadian DSL Inventory</u>: All ingredients are either listed on the DSL Inventory or are exempt.

European Union Regulations:

RoHS Compliance: This product is compliant with Directive 2002/95/EC of the European Parliament and of the

Council of 27 January 2003. This product does not contain any of the restricted substances as

listed in Article 4(1) of the RoHS Directive.


Additional Regulatory Information: None

Product Number (s): 03077

Section 16: Other Information

HMIS® (II)		
Health:	2	
Flammability:	3	
Reactivity:	0	
PPE:	В	

Ratings range from 0 (no hazard) to 4 (severe hazard)



Prepared By: Michelle Rudnick

CRC #: 920B Revision Date: 04/19/2012

Changes since last revision: Section 2: Emergency Overview

Section 14: Transport Information

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstract Service
CFR: Code of Federal Regulations
DOT: Department of Transportation
DSL: Domestic Substance List

g/L: grams per Liter

HMIS: Hazardous Materials Identification System
 IARC: International Agency for Research on Cancer
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organization
 IMDG: International Maritime Dangerous Goods
 IMO: International Maritime Organization

IMO: International Maritime lbs./gal: pounds per gallon

LC: Lethal Concentration

LD: Lethal Dose

NA: Not Applicable ND: Not Determined

NIOSH: National Institute of Occupational Safety & Health

NFPA: National Fire Protection Association NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PMCC: Pensky-Martens Closed Cup PPE: Personal Protection Equipment

ppm: Parts per Million

RoHS: Restriction of Hazardous Substances

STEL: Short Term Exposure Limit

TCC: Tag Closed Cup
TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Information

System