

# **Material Safety Data Sheet**

# **Section 1: Product & Company Identification**

Product Name: Contact Cleaner & Protectant (Aerosol)

Product Number (s): 03140

Manufactured By:

CRC Industries, Inc.

885 Louis Drive

Warminster, PA 18974

www.crcindustries.com

General Information
Technical Assistance
(800) 521-3168
Customer Service
(800) 272-4620
24-Hr Emergency (CHEMTREC)
(800) 424-9300

# **Section 2: Hazards Identification**

### **Emergency Overview**

Appearance & Odor: Clear, water-white liquid with mild solvent odor

#### **DANGER**

Extremely flammable. Harmful or fatal if swallowed. Contents under pressure.

As defined by OSHA's Hazard Communication Standard, this product is hazardous.

#### **Potential Health Effects:**

EYE: May cause mild irritation including stinging and redness, but does not injure eye.

SKIN: Single, brief exposures may cause mild irritation. Frequent or prolonged contact

may cause more severe irritation, defatting of the skin, and dermatitis.

INHALATION: High vapor concentrations are irritating to the respiratory tract and may cause

headaches, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects, including death. May cause peripheral nervous system

disorder and/or damage.

INGESTION: Low order of toxicity by ingestion. Main hazard is aspiration into the lungs during

swallowing or vomiting. Small amounts aspirated into the respiratory system may cause bronchopneumonia or pulmonary adema, possible progressing to death.

CHRONIC EFFECTS: Overexposure to n-hexane may cause progressive and potentially irreversible

damage to the peripheral nervous system, particularly in the arms and legs.

TARGET ORGANS: central nervous system, peripheral nervous system, respiratory system

Medical Conditions Aggravated by Exposure: skin and respiratory conditions

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Product Number (s): 03140

# Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.
Hexane isomers	various	65 - 75
n-Hexane	110-54-3	2.2
Polydimethylsiloxane	63148-62-9	2 - 5
1,1-Difluoroethane (HFC-152a)	75-37-6	20 - 30

### **Section 4: First Aid Measures**

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician

if irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If

breathing is difficult give oxygen. Call a physician.

Ingestion: DO NOT induce vomiting. Contact a physician immediately.

Note to Physicians: Treat symptomatically. Gastric lavage using a cuffed endotracheal tube may be performed at

your discretion.

# **Section 5: Fire-Fighting Measures**

<u>Flammable Properties</u>: This product is extremely flammable in accordance with aerosol flammability

definitions (16 CFR 1500.3(c)(6)).

Flash Point: < 0 F (TCC) Upper Explosive Limit: 9.0 Autoignition Temperature: 489 F Lower Explosive Limit: 1.7

Suitable Extinguishing Media: Class B fire extinguishers, dry chemical, foam or CO2

Products of Combustion: fumes, smoke and carbon monoxide

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for

protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water fog or spray to keep fire-exposed

containers cool and to knock down vapors which may result from product

decomposition. Do not spray water directly on fire; product will float and could be

reignited on surface of water.

### Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush

into sewers or storm drains.

Product Number (s): 03140

Methods for Containment & Clean-up: Dike area to contain spill. Remove all sources of ignition. Ventilate the area

with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used

absorbents into proper waste containers.

# Section 7: Handling and Storage

Handling Procedures: Use proper grounding and bonding procedures for transferring materials. Do not use product

near any source of ignition. Do not touch container to electrical sources as container will

conduct electricity. Avoid contact with eyes and skin. Avoid breathing vapors.

Storage Procedures: Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120 F

to prevent cans from rupturing.

Aerosol Storage Level: III

### Section 8: Exposure Controls/Personal Protection

### **Exposure Guidelines:**

	OSHA		ACGIH		OTHER		
COMPONENT	TWA	STEL	TWA	STEL	TWA	SOURCE	UNIT
Hexane isomers	500(v)	1000(v)	500	1000	NE		ppm
n-Hexane	500	NE	50(s)	NE	NE		ppm
Polydimethylsiloxane	NE	NE	NE	NE	NE		
1,1-Difluoroethane (HFC-152a)	NE	NE	NE	NE	1000	AIHA	ppm
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

Engineering Controls: Area should have ventilation to provide fresh air. Use local exhaust to prevent accumulation

of vapors. Use mechanical means if necessary to maintain vapor levels below the exposure

guidelines. If working in a confined space, follow applicable OSHA regulations

Respiratory Protection: None required for normal work where adequate ventilation is provided. Use a NIOSH-

approved cartridge respirator with an organic vapor cartridge if vapors exceed exposure limits. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid

contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile, PVC or Viton. Also, use full protective clothing if there

is prolonged or repeated contact of liquid with skin.

### Section 9: Physical and Chemical Properties

Physical State: liquid
Color: clear, water-white
Odor: mild solvent
Specific Gravity: 0.667

Product Number (s): 03140

Initial Boiling Point: 140 F Freezing Point: < -76 F

Vapor Pressure: 160 mmHg @ 68 F Vapor Density: > 1 (air = 1)

Evaporation Rate: > 1 (Butyl acetate = 1)

Solubility: negligible in water

pH: NA

Volatile Organic Compounds: wt %: 71.85 g/L: 479.2 lbs./qal: 3.99

### Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: sources of ignition, temperature extremes

Incompatible Materials: strong oxidizers

Hazardous Decomposition Products: oxides of carbon

Possibility of Hazardous Reactions: No

# **Section 11: Toxicological Information**

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

#### **ACUTE EFFECTS**

Component	<u>Test</u>	<u>Result</u>	Route	<u>Species</u>
n-hexane	LD50	28710 mg/kg	Oral	Rat
n-hexane	LD50	3000 mg/kg	Dermal	Rabbit
n-hexane	LC50	48000 ppm/4H	Inhalation	Rat

### **CHRONIC EFFECTS**

Carcinogenicity:

Component Result

OSHA: None listed IARC: None listed NTP: None listed

Mutagenicity: No information available

# **Section 12: Ecological Information**

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: n-hexane - 48 Hr EC50 water flea: 3.87 mg/L

96 Hr LC50 Lepomis macrochirus: 4.12 mg/L

Persistence / Degradability: No information available Bioaccumulation / Accumulation: No information available

Product Number (s): 03140

Mobility in Environment: No information available

### **Section 13: Disposal Considerations**

Disposal: The dispensed liquid product is a RCRA hazardous waste for the characteristic of ignitability with a waste

code of D001 (See 40 CFR Part 261.20 - 261.33).

Aerosol containers should be emptied and depressurized before disposal. Empty containers may be

recycled. Any liquid product should be managed as a hazardous waste.

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

# **Section 14: Transport Information**

Proper shipping description:

US DOT (ground): Consumer Commodity, ORM-D

Special Provisions: None

# **Section 15: Regulatory Information**

#### U.S. Federal

# Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

### Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: n-hexane (5000 lbs)

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

### Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories: Fire Hazard Yes

Reactive Hazard No Release of Pressure Yes Acute Health Hazard Yes Chronic Health Hazard Yes

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting

requirements of Section 313 of Title III of the Superfund Amendments and

Reauthorization Act of 1986 and 40 CFR Part 372:

n-hexane (2.2%)

# Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): n-hexane

Page 5 of 6

Product Number (s): 03140

### **State Regulations**

# California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm:

NONE

# State Right to Know:

New Jersey: 75-83-2, 110-54-3, 79-29-8, 75-37-6

Pennsylvania: 107-83-5, 75-83-2, 110-54-3, 79-29-8, 75-37-6 Massachusetts: 107-83-5, 75-83-2, 110-54-3, 79-29-8, 75-37-6

Rhode Island: 110-54-3, 75-37-6

Additional Regulatory Information: This product complies with Consumer Products VOC regulations as an

Electronic Cleaner.

### **Section 16: Other Information**

NFPA: Health: 2 Flammability: 3 Reactivity: 0

HMIS: Health: 2 Flammability: 3 Reactivity: 0 PPE: B

Prepared By: Michelle Rudnick

CRC #: 460A

Revision Date: 01/06/2009

Changes since last revision: Section 15: Additional Regulatory Information revised

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS: **Chemical Abstract Service** NA: Not Applicable ppm: Parts per Million ND: Not Determined Tag Closed Cup Not Established TCC: NE: Pensky-Martens Closed Cup PMCC: g/L: grams per Liter Personal Protection Equipment pounds per gallon PPE: lbs./gal:

TWA: Time Weighted Average STEL: Short Term Exposure Limit

OSHA: Occupational Safety and Health Administration

ACGIH American Conference of Governmental Industrial Hygienists

NIOSH National Institute of Occupational Safety & Health