

Common Name: CUTTING OIL THREAD CUTTING LUBRICANT 14050

Manufacturer: CRC

SDS Revision Date: 5/21/2015

SDS Format: GHS-US

Item Number(s): 2F146

Manufacturer Model Number(s):

SDS Table of Contents

Click the desired link below to jump directly to that section in the SDS.

- [1. IDENTIFICATION](#)
- [2. HAZARD\(S\) IDENTIFICATION](#)
- [3. COMPOSITION/INFORMATION ON INGREDIENTS](#)
- [4. FIRST-AID MEASURES](#)
- [5. FIRE-FIGHTING MEASURES](#)
- [6. ACCIDENTAL RELEASE MEASURES](#)
- [7. HANDLING AND STORAGE](#)
- [8. EXPOSURE CONTROLS/PERSONAL PROTECTION](#)
- [9. PHYSICAL AND CHEMICAL PROPERTIES](#)
- [10. STABILITY AND REACTIVITY](#)
- [11. TOXICOLOGICAL INFORMATION](#)
- [12. ECOLOGICAL INFORMATION](#)
- [13. DISPOSAL CONSIDERATIONS](#)
- [14. TRANSPORT INFORMATION](#)
- [15. REGULATORY INFORMATION](#)
- [16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION](#)

CRC (R*)

SAFETY DATA SHEET

1. IDENTIFICATION



PRODUCT IDENTIFIER: CUTTING OIL THREAD CUTTING LUBRICANT

OTHER MEANS OF IDENTIFICATION:

PRODUCT CODE: 14050

RECOMMENDED USE: CUTTING OIL

RECOMMENDED RESTRICTIONS: NONE KNOWN.

MANUFACTURER/IMPORTER/SUPPLIER/DISTRIBUTOR INFORMATION:

MANUFACTURED OR SOLD BY:

COMPANY NAME: CRC INDUSTRIES, INC.

ADDRESS:
885 LOUIS DR.
WARMINSTER, PA 18974
US

TELEPHONE:
GENERAL INFORMATION: 215-674-4300
TECHNICAL ASSISTANCE: 800-521-3168

CUSTOMER SERVICE: 800-272-4620

24-HOUR EMERGENCY (CHEMTREC):
800-424-9300 (US)
703-527-3887 (INTERNATIONAL)

WEBSITE: WWW.CRCINDUSTRIES.COM

2. HAZARD(S) IDENTIFICATION



PHYSICAL HAZARDS:
FLAMMABLE AEROSOLS: CATEGORY 1
GASES UNDER PRESSURE: LIQUEFIED GAS

HEALTH HAZARDS: NOT CLASSIFIED.

ENVIRONMENTAL HAZARDS: NOT CLASSIFIED.

OSHA DEFINED HAZARDS: NOT CLASSIFIED.

LABEL ELEMENTS:
FLAME
GAS CYLINDER

SIGNAL WORD: DANGER

HAZARD STATEMENT:
EXTREMELY FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

PRECAUTIONARY STATEMENT:

PREVENTION:
KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES. - NO SMOKING. DO NOT SPRAY ON AN OPEN FLAME OR OTHER IGNITION SOURCE. DO NOT APPLY WHILE EQUIPMENT IS ENERGIZED.

PRESSURIZED CONTAINER:
DO NOT PIERCE OR BURN, EVEN AFTER USE. EXTINGUISH ALL FLAMES, PILOT LIGHTS AND HEATERS. VAPORS WILL ACCUMULATE READILY AND MAY IGNITE. USE ONLY WITH ADEQUATE VENTILATION; MAINTAIN VENTILATION DURING USE AND UNTIL ALL VAPORS ARE GONE. OPEN DOORS AND WINDOWS OR USE OTHER MEANS TO ENSURE A FRESH AIR SUPPLY DURING USE AND WHILE PRODUCT IS DRYING. IF YOU EXPERIENCE ANY SYMPTOMS LISTED ON THIS LABEL, INCREASE VENTILATION OR LEAVE THE AREA.

RESPONSE: WASH HANDS AFTER HANDLING.

STORAGE:
STORE IN A WELL-VENTILATED PLACE. PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50 DEG. C/122 DEG. F. EXPOSURE TO HIGH TEMPERATURE MAY CAUSE CAN TO BURST.

DISPOSAL:

DISPOSE OF CONTENTS/CONTAINER IN ACCORDANCE WITH LOCAL/REGIONAL/NATIONAL REGULATIONS.

HAZARD(S) NOT OTHERWISE CLASSIFIED (HNOC): NONE KNOWN.

3. COMPOSITION/INFORMATION ON INGREDIENTS



MIXTURES:

CHEMICAL NAME	COMMON NAME AND SYNONYMS	CAS NUMBER	%
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC		64742-52-5	70 - 80
LIQUEFIED PETROLEUM GAS		68476-86-8	20 - 30

SPECIFIC CHEMICAL IDENTITY AND/OR PERCENTAGE OF COMPOSITION HAS BEEN WITHHELD AS A TRADE SECRET.

4. FIRST-AID MEASURES



INHALATION:

MOVE TO FRESH AIR. CALL A PHYSICIAN IF SYMPTOMS DEVELOP OR PERSIST.

SKIN CONTACT:

RINSE SKIN WITH WATER/SHOWER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS AND PERSISTS.

EYE CONTACT:

RINSE WITH WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS AND PERSISTS.

INGESTION:

IF SWALLOWED, OBSERVE FOR SIGNS OF STOMACH DISCOMFORT OR NAUSEA. IF SYMPTOMS PERSIST, SEEK MEDICAL HELP. DO NOT INDUCE VOMITING. IF THERE IS ANY SUSPICION OF ASPIRATION INTO LUNGS, OBTAIN IMMEDIATE MEDICAL ATTENTION.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

DIRECT CONTACT WITH EYES MAY CAUSE TEMPORARY IRRITATION.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

PROVIDE GENERAL SUPPORTIVE MEASURES AND TREAT SYMPTOMATICALLY.

GENERAL INFORMATION:

ENSURE THAT MEDICAL PERSONNEL ARE AWARE OF THE MATERIAL(S) INVOLVED, AND TAKE PRECAUTIONS TO PROTECT THEMSELVES.

5. FIRE-FIGHTING MEASURES



SUITABLE EXTINGUISHING MEDIA:

WATER FOG. FOAM. DRY CHEMICAL POWDER. CARBON DIOXIDE (CO2).

UNSUITABLE EXTINGUISHING MEDIA:

DO NOT USE WATER JET AS AN EXTINGUISHER, AS THIS WILL SPREAD THE FIRE.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

CONTENTS UNDER PRESSURE. PRESSURIZED CONTAINER MAY RUPTURE WHEN EXPOSED TO HEAT OR FLAME. DURING FIRE, GASES HAZARDOUS TO HEALTH MAY BE FORMED.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIREFIGHTERS:

FIREFIGHTERS MUST USE STANDARD PROTECTIVE EQUIPMENT INCLUDING FLAME RETARDANT COAT, HELMET WITH FACE SHIELD, GLOVES, RUBBER BOOTS, AND IN ENCLOSED SPACES, SCBA.

FIRE-FIGHTING EQUIPMENT/INSTRUCTIONS:

IN CASE OF FIRE:

STOP LEAK IF SAFE TO DO SO. MOVE CONTAINERS FROM FIRE AREA IF YOU CAN DO SO WITHOUT RISK. CONTAINERS SHOULD BE COOLED WITH WATER TO PREVENT VAPOR PRESSURE BUILD UP.

GENERAL FIRE HAZARDS:

EXTREMELY FLAMMABLE AEROSOL. CONTENTS UNDER PRESSURE. PRESSURIZED CONTAINER MAY RUPTURE WHEN EXPOSED TO HEAT OR FLAME.

6. ACCIDENTAL RELEASE MEASURES



PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

KEEP UNNECESSARY PERSONNEL AWAY. KEEP PEOPLE AWAY FROM AND UPWIND OF SPILL/LEAK. KEEP OUT OF LOW AREAS. MANY VAPORS ARE HEAVIER THAN AIR AND WILL SPREAD ALONG GROUND AND COLLECT IN LOW OR CONFINED AREAS (SEWERS, BASEMENTS, TANKS). WEAR APPROPRIATE PROTECTIVE EQUIPMENT AND CLOTHING DURING CLEAN-UP. EMERGENCY PERSONNEL NEED SELF-CONTAINED BREATHING EQUIPMENT. DO NOT TOUCH DAMAGED CONTAINERS OR SPILLED MATERIAL UNLESS WEARING APPROPRIATE PROTECTIVE CLOTHING. VENTILATE CLOSED SPACES BEFORE ENTERING THEM. LOCAL AUTHORITIES SHOULD BE ADVISED IF SIGNIFICANT SPILLAGES CANNOT BE CONTAINED. FOR PERSONAL PROTECTION, SEE SECTION 8 OF THE SDS.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

ELIMINATE ALL IGNITION SOURCES (NO SMOKING, FLARES, SPARKS, OR FLAMES IN IMMEDIATE AREA). KEEP COMBUSTIBLES (WOOD, PAPER, OIL, ETC.) AWAY FROM SPILLED MATERIAL. STOP THE FLOW OF MATERIAL, IF THIS IS WITHOUT RISK. WIPE UP WITH ABSORBENT MATERIAL (E.G. CLOTH, FLEECE). CLEAN SURFACE THOROUGHLY TO REMOVE RESIDUAL CONTAMINATION. FOR WASTE DISPOSAL, SEE SECTION 13 OF THE SDS.

ENVIRONMENTAL PRECAUTIONS:

AVOID DISCHARGE INTO DRAINS, WATER COURSES OR ONTO THE GROUND.

7. HANDLING AND STORAGE



PRECAUTIONS FOR SAFE HANDLING:

PRESSURIZED CONTAINER:

DO NOT PIERCE OR BURN, EVEN AFTER USE. DO NOT USE IF SPRAY BUTTON IS MISSING OR DEFECTIVE. DO NOT SPRAY ON A NAKED FLAME OR ANY OTHER INCANDESCENT MATERIAL. DO NOT SMOKE WHILE USING OR UNTIL SPRAYED SURFACE IS THOROUGHLY DRY. DO NOT CUT, WELD, SOLDER, DRILL, GRIND, OR EXPOSE CONTAINERS TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION. USE CAUTION AROUND ENERGIZED EQUIPMENT. THE METAL CONTAINER WILL CONDUCT ELECTRICITY IF IT CONTACTS A LIVE SOURCE. THIS MAY RESULT IN INJURY TO THE USER FROM ELECTRICAL SHOCK AND/OR FLASH FIRE. USE ONLY IN WELL-VENTILATED AREAS. WEAR APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT.

OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES. FOR PRODUCT USAGE INSTRUCTIONS, PLEASE SEE THE PRODUCT LABEL.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:
LEVEL 3 AEROSOL.

PRESSURIZED CONTAINER. PROTECT FROM SUNLIGHT AND DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50 DEG. C/122 DEG. F. DO NOT PUNCTURE, INCINERATE OR CRUSH. DO NOT HANDLE OR STORE NEAR AN OPEN FLAME, HEAT OR OTHER SOURCES OF IGNITION. THIS MATERIAL CAN ACCUMULATE STATIC CHARGE WHICH MAY CAUSE SPARK AND BECOME AN IGNITION SOURCE. STORE IN A WELL-VENTILATED PLACE. STORE AWAY FROM INCOMPATIBLE MATERIALS (SEE SECTION 10 OF THE SDS).

8. EXPOSURE CONTROLS/PERSONAL PROTECTION



OCCUPATIONAL EXPOSURE LIMITS:

US. OSHA TABLE Z-1 LIMITS FOR AIR CONTAMINANTS (29 CFR 1910.1000):

COMPONENTS	TYPE	VALUE	FORM
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)	PEL	5 MG/M3 2000 MG/M3 500 PPM	MIST.

US. ACGIH THRESHOLD LIMIT VALUES:

COMPONENTS	TYPE	VALUE	FORM
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)	TWA	5 MG/M3	INHALABLE FRACTION.

US. NIOSH: POCKET GUIDE TO CHEMICAL HAZARDS

COMPONENTS	TYPE	VALUE	FORM
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)	CEILING	1800 MG/M3	
	STEL	10 MG/M3	MIST.

BIOLOGICAL LIMIT VALUES:

NO BIOLOGICAL EXPOSURE LIMITS NOTED FOR THE INGREDIENT(S).

APPROPRIATE ENGINEERING CONTROLS:

GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES PER HOUR) SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS. IF APPLICABLE, USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING CONTROLS TO MAINTAIN AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS. IF EXPOSURE LIMITS HAVE NOT BEEN ESTABLISHED, MAINTAIN AIRBORNE LEVELS TO AN ACCEPTABLE LEVEL.

INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:
EYE/FACE PROTECTION: WEAR SAFETY GLASSES WITH SIDE SHIELDS (OR GOGGLES).

SKIN PROTECTION:

HAND PROTECTION:

WEAR PROTECTIVE GLOVES SUCH AS: NITRILE. NEOPRENE.

OTHER: WEAR SUITABLE PROTECTIVE CLOTHING.

RESPIRATORY PROTECTION:

IF ENGINEERING CONTROLS ARE NOT FEASIBLE OR IF EXPOSURE EXCEEDS THE APPLICABLE EXPOSURE LIMITS, USE A NIOSH-APPROVED CARTRIDGE RESPIRATOR WITH AN ORGANIC VAPOR CARTRIDGE. USE A SELF-CONTAINED BREATHING APPARATUS IN CONFINED SPACES AND FOR EMERGENCIES. AIR MONITORING IS NEEDED TO DETERMINE ACTUAL EMPLOYEE EXPOSURE LEVELS.

THERMAL HAZARDS:

WEAR APPROPRIATE THERMAL PROTECTIVE CLOTHING, WHEN NECESSARY.

GENERAL HYGIENE CONSIDERATIONS:

WHEN USING DO NOT SMOKE. ALWAYS OBSERVE GOOD PERSONAL HYGIENE MEASURES, SUCH AS WASHING AFTER HANDLING THE MATERIAL AND BEFORE EATING, DRINKING, AND/OR SMOKING. ROUTINELY WASH WORK CLOTHING AND PROTECTIVE EQUIPMENT TO REMOVE CONTAMINANTS.

9. PHYSICAL AND CHEMICAL PROPERTIES



APPEARANCE:

PHYSICAL STATE: LIQUID.

FORM: AEROSOL.

COLOR: BROWN.

ODOR: MILD PETROLEUM.

ODOR THRESHOLD: NOT AVAILABLE.

PH: NOT AVAILABLE.

MELTING POINT/FREEZING POINT: -40 DEG. F (-40 DEG. C) ESTIMATED

INITIAL BOILING POINT AND BOILING RANGE: 500 DEG. F (260 DEG. C) ESTIMATED

FLASH POINT: >300 DEG. F (>148.9 DEG. C) CLEVELAND OPEN CUP

EVAPORATION RATE: SLOW.

FLAMMABILITY (SOLID, GAS): NOT AVAILABLE.

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:

FLAMMABILITY LIMIT - LOWER (%): NOT AVAILABLE.

FLAMMABILITY LIMIT - UPPER (%): NOT AVAILABLE.

VAPOR PRESSURE: 965.3 HPA ESTIMATED

VAPOR DENSITY: >5 (AIR = 1)

RELATIVE DENSITY: 0.85

SOLUBILITY (WATER): NEGLIGIBLE.

PARTITION COEFFICIENT (N-OCTANOL/WATER): NOT AVAILABLE.

AUTO-IGNITION TEMPERATURE: 600 DEG. F (315.6 DEG. C) ESTIMATED

DECOMPOSITION TEMPERATURE: NOT AVAILABLE.

VISCOSITY (KINEMATIC): NOT AVAILABLE.

PERCENT VOLATILE: 94.4% ESTIMATED

10. STABILITY AND REACTIVITY



REACTIVITY:

THE PRODUCT IS STABLE AND NON-REACTIVE UNDER NORMAL CONDITIONS OF USE, STORAGE AND TRANSPORT.

CHEMICAL STABILITY: MATERIAL IS STABLE UNDER NORMAL CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS:

NO DANGEROUS REACTION KNOWN UNDER CONDITIONS OF NORMAL USE.

CONDITIONS TO AVOID:

HEAT, FLAMES AND SPARKS. CONTACT WITH INCOMPATIBLE MATERIALS.

INCOMPATIBLE MATERIALS: STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON OXIDES. SULFUR OXIDES. ALDEHYDES.

11. TOXICOLOGICAL INFORMATION



INFORMATION ON LIKELY ROUTES OF EXPOSURE:

INHALATION: PROLONGED INHALATION MAY BE HARMFUL.

SKIN CONTACT: PROLONGED SKIN CONTACT MAY CAUSE TEMPORARY IRRITATION.

EYE CONTACT: DIRECT CONTACT WITH EYES MAY CAUSE TEMPORARY IRRITATION.

INGESTION: EXPECTED TO BE A LOW INGESTION HAZARD.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL

CHARACTERISTICS: DIRECT CONTACT WITH EYES MAY CAUSE TEMPORARY IRRITATION.

INFORMATION ON TOXICOLOGICAL EFFECTS:

ACUTE TOXICITY: NOT AVAILABLE.

PRODUCT	SPECIES	TEST RESULTS
---------	---------	--------------

CUTTING OIL THREAD CUTTING LUBRICANT:

ACUTE:

DERMAL:

LD50	RABBIT	2841 MG/KG ESTIMATED
------	--------	----------------------

INHALATION:

LC50	RAT	30 MG/L, 4 HOURS ESTIMATED
------	-----	----------------------------

ORAL:

LD50	RAT	5924 MG/KG ESTIMATED
------	-----	----------------------

*ESTIMATES FOR PRODUCT MAY BE BASED ON ADDITIONAL COMPONENT DATA NOT SHOWN.

SKIN CORROSION/IRRITATION:

PROLONGED SKIN CONTACT MAY CAUSE TEMPORARY IRRITATION.

SERIOUS EYE DAMAGE/EYE IRRITATION:
DIRECT CONTACT WITH EYES MAY CAUSE TEMPORARY IRRITATION.

RESPIRATORY SENSITIZATION: NOT A RESPIRATORY SENSITIZER.

SKIN SENSITIZATION:
THIS PRODUCT IS NOT EXPECTED TO CAUSE SKIN SENSITIZATION.

GERM CELL MUTAGENICITY:
NO DATA AVAILABLE TO INDICATE PRODUCT OR ANY COMPONENTS PRESENT AT GREATER THAN 0.1% ARE MUTAGENIC OR GENOTOXIC.

CARCINOGENICITY:
THIS PRODUCT IS NOT CONSIDERED TO BE A CARCINOGEN BY IARC, ACGIH, NTP, OR OSHA.

REPRODUCTIVE TOXICITY:
THIS PRODUCT IS NOT EXPECTED TO CAUSE REPRODUCTIVE OR DEVELOPMENTAL EFFECTS.

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE: NOT CLASSIFIED.

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE: NOT CLASSIFIED.

ASPIRATION HAZARD: NOT EXPECTED TO BE AN ASPIRATION HAZARD.

12. ECOLOGICAL INFORMATION



ECOTOXICITY:
THE PRODUCT IS NOT CLASSIFIED AS ENVIRONMENTALLY HAZARDOUS. HOWEVER, THIS DOES NOT EXCLUDE THE POSSIBILITY THAT LARGE OR FREQUENT SPILLS CAN HAVE A HARMFUL OR DAMAGING EFFECT ON THE ENVIRONMENT.

PRODUCT	SPECIES	TEST RESULTS
---------	---------	--------------

CUTTING OIL THREAD CUTTING LUBRICANT:

AQUATIC:

ACUTE:

CRUSTACEA	EC50	DAPHNIA	25000 MG/L, 48 HOURS ESTIMATED
FISH	LC50	FISH	16094.4199 MG/L, 96 HOURS ESTIMATED

COMPONENTS	SPECIES	TEST RESULTS
------------	---------	--------------

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5):

AQUATIC:

ACUTE:

FISH	LC50	PIMEPHALES PROMELAS	>30000 MG/L, 96 HOURS
------	------	---------------------	-----------------------

*ESTIMATES FOR PRODUCT MAY BE BASED ON ADDITIONAL COMPONENT DATA NOT SHOWN.

PERSISTENCE AND DEGRADABILITY:
NO DATA IS AVAILABLE ON THE DEGRADABILITY OF THIS PRODUCT.

BIOACCUMULATIVE POTENTIAL: NO DATA AVAILABLE.

MOBILITY IN SOIL: NO DATA AVAILABLE.

OTHER ADVERSE EFFECTS:

NO OTHER ADVERSE ENVIRONMENTAL EFFECTS (E.G. OZONE DEPLETION, PHOTOCHEMICAL OZONE CREATION POTENTIAL, ENDOCRINE DISRUPTION, GLOBAL WARMING POTENTIAL) ARE EXPECTED FROM THIS COMPONENT.

13. DISPOSAL CONSIDERATIONS



DISPOSAL OF WASTE FROM RESIDUES / UNUSED PRODUCTS:

THE DISPENSED LIQUID PRODUCT IS NOT A RCRA HAZARDOUS WASTE (SEE 40 CFR PART 261.20 - 261.33). EMPTY CONTAINER CAN BE RECYCLED. COLLECT AND RECLAIM OR DISPOSE IN SEALED CONTAINERS AT LICENSED WASTE DISPOSAL SITE. DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.

HAZARDOUS WASTE CODE: NOT REGULATED.

CONTAMINATED PACKAGING:

SINCE EMPTIED CONTAINERS MAY RETAIN PRODUCT RESIDUE, FOLLOW LABEL WARNINGS EVEN AFTER CONTAINER IS EMPTIED. EMPTY CONTAINERS SHOULD BE TAKEN TO AN APPROVED WASTE HANDLING SITE FOR RECYCLING OR DISPOSAL.

14. TRANSPORT INFORMATION



DOT:

UN NUMBER: UN1950

UN PROPER SHIPPING NAME: AEROSOLS, FLAMMABLE, LIMITED QUANTITY

TRANSPORT HAZARD CLASS(ES):

CLASS: 2.1

SUBSIDIARY RISK:

LABEL(S): 2.1

PACKING GROUP: NOT APPLICABLE.

SPECIAL PRECAUTIONS FOR USER:

READ SAFETY INSTRUCTIONS, SDS AND EMERGENCY PROCEDURES BEFORE HANDLING.

SPECIAL PROVISIONS: N82

PACKAGING EXCEPTIONS: 306

PACKAGING NON BULK: NONE

PACKAGING BULK: NONE

IATA:

UN NUMBER: UN1950

UN PROPER SHIPPING NAME: AEROSOLS, FLAMMABLE, LIMITED QUANTITY

TRANSPORT HAZARD CLASS(ES):

CLASS: 2.1

SUBSIDIARY RISK:

PACKING GROUP: NOT APPLICABLE.

ENVIRONMENTAL HAZARDS: NO.

ERG CODE: 10L

SPECIAL PRECAUTIONS FOR USER:
READ SAFETY INSTRUCTIONS, SDS AND EMERGENCY PROCEDURES BEFORE HANDLING.

OTHER INFORMATION:
PASSENGER AND CARGO AIRCRAFT: ALLOWED.
CARGO AIRCRAFT ONLY: ALLOWED.

IMDG:
UN NUMBER: UN1950
UN PROPER SHIPPING NAME: AEROSOLS, LIMITED QUANTITY

TRANSPORT HAZARD CLASS(ES):
CLASS: 2
SUBSIDIARY RISK:

PACKING GROUP: NOT APPLICABLE.

ENVIRONMENTAL HAZARDS:
MARINE POLLUTANT: NO.

EMS: F-D, S-U

SPECIAL PRECAUTIONS FOR USER:
READ SAFETY INSTRUCTIONS, SDS AND EMERGENCY PROCEDURES BEFORE HANDLING.

15. REGULATORY INFORMATION



US FEDERAL REGULATIONS:
THIS PRODUCT IS A "HAZARDOUS CHEMICAL" AS DEFINED BY THE OSHA HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200.

TSCA SECTION 12(B) EXPORT NOTIFICATION (40 CFR 707, SUBPT. D):
NOT REGULATED.

US. OSHA SPECIFICALLY REGULATED SUBSTANCES (29 CFR 1910.1001-1050):
NOT LISTED.

SARA 304 EMERGENCY RELEASE NOTIFICATION: NOT REGULATED.

US EPCRA (SARA TITLE III) SECTION 313 - LISTED SUBSTANCE
TOXIC CHEMICAL

NOT LISTED.

CERCLA HAZARDOUS SUBSTANCE LIST (40 CFR 302.4): NOT LISTED.

CERCLA HAZARDOUS SUBSTANCES REPORTABLE QUANTITY

NOT LISTED.

SPILLS OR RELEASES RESULTING IN THE LOSS OF ANY INGREDIENT AT OR ABOVE ITS RQ REQUIRE IMMEDIATE NOTIFICATION TO THE NATIONAL RESPONSE CENTER (800-424-8802) AND TO YOUR LOCAL EMERGENCY PLANNING COMMITTEE.

CLEAN AIR ACT (CAA) SECTION 112 HAZARDOUS AIR POLLUTANTS (HAPS) LIST:
NOT REGULATED.

CLEAN AIR ACT (CAA) SECTION 112(R) ACCIDENTAL RELEASE PREVENTION (40 CFR 68.130): NOT REGULATED.

SAFE DRINKING WATER ACT (SDWA): NOT REGULATED.

FOOD AND DRUG ADMINISTRATION (FDA): NOT REGULATED.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA):

SECTION 311/312 HAZARD CATEGORIES:

IMMEDIATE HAZARD: NO

DELAYED HAZARD: NO

FIRE HAZARD: YES

PRESSURE HAZARD: YES

REACTIVITY HAZARD: NO

SARA 302 EXTREMELY HAZARDOUS SUBSTANCE: NO

US STATE REGULATIONS:

US. CALIFORNIA. CANDIDATE CHEMICALS LIST. SAFER CONSUMER PRODUCTS REGULATIONS (CAL. CODE REGS, TIT. 22, 69502.3, SUBD. (A)):

LIQUEFIED PETROLEUM GAS (CAS 68476-86-8)

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)

US. CALIFORNIA CONTROLLED SUBSTANCES. CA DEPARTMENT OF JUSTICE (CALIFORNIA HEALTH AND SAFETY CODE SECTION 11100): NOT LISTED.

US. NEW JERSEY WORKER AND COMMUNITY RIGHT-TO-KNOW ACT:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)

US. MASSACHUSETTS RTK - SUBSTANCE LIST:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)

US. PENNSYLVANIA WORKER AND COMMUNITY RIGHT-TO-KNOW LAW: NOT LISTED.

US. RHODE ISLAND RTK: NONE.

US. CALIFORNIA PROPOSITION 65:

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 (PROPOSITION 65):

THIS MATERIAL IS NOT KNOWN TO CONTAIN ANY CHEMICALS CURRENTLY LISTED AS CARCINOGENS OR REPRODUCTIVE TOXINS.

VOLATILE ORGANIC COMPOUNDS (VOC) REGULATIONS:

EPA:

VOC CONTENT (40 CFR 51.100(S)): 100%

CONSUMER PRODUCTS (40 CFR 59, SUBPT. C): NOT REGULATED

STATE:

CONSUMER PRODUCTS:

THIS PRODUCT IS REGULATED AS A CUTTING OR TAPPING OIL (AEROSOL). THIS PRODUCT IS COMPLIANT FOR USE IN ALL 50 STATES.

LOCAL RESTRICTION:

THIS PRODUCT CANNOT BE USED IN THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT OF CALIFORNIA.

VOC CONTENT (CA): 20%

VOC CONTENT (OTC): 20%

INTERNATIONAL INVENTORIES:

COUNTRY(S) OR REGION	INVENTORY NAME	ON INVENTORY (YES/NO) *
AUSTRALIA	AUSTRALIAN INVENTORY OF CHEMICAL SUBSTANCES (AICS)	YES
CANADA	DOMESTIC SUBSTANCES LIST (DSL)	YES
CANADA	NON-DOMESTIC SUBSTANCES LIST (NDSL)	NO
CHINA	INVENTORY OF EXISTING CHEMICAL SUBSTANCES IN CHINA (IECSC)	YES
EUROPE	EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES (EINECS)	NO
EUROPE	EUROPEAN LIST OF NOTIFIED CHEMICAL SUBSTANCES (ELINCS)	NO
JAPAN	INVENTORY OF EXISTING AND NEW CHEMICAL SUBSTANCES (ENCs)	NO
KOREA	EXISTING CHEMICALS LIST (ECL)	YES
NEW ZEALAND	NEW ZEALAND INVENTORY	YES
PHILIPPINES	PHILIPPINE INVENTORY OF CHEMICALS AND CHEMICAL SUBSTANCES (PICCS)	YES
UNITED STATES & PUERTO RICO	TOXIC SUBSTANCES CONTROL ACT (TSCA) INVENTORY	YES

*A "YES" INDICATES THAT ALL COMPONENTS OF THIS PRODUCT COMPLY WITH THE INVENTORY REQUIREMENTS ADMINISTERED BY THE GOVERNING COUNTRY(S)

A "NO" INDICATES THAT ONE OR MORE COMPONENTS OF THE PRODUCT ARE NOT LISTED OR EXEMPT FROM LISTING ON THE INVENTORY ADMINISTERED BY THE GOVERNING COUNTRY(S).

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION



OR LAST REVISION

ISSUE DATE: 04-28-2015

REVISION DATE: 05-21-2015

PREPARED BY: ALLISON CHO

VERSION #: 02

FURTHER INFORMATION: CRC # 574

HMIS(R*) RATINGS:

HEALTH	1
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

NFPA RATINGS:

HEALTH	1
--------	---

FLAMMABILITY 3
INSTABILITY 0

NFPA RATINGS:

1
3
0

DISCLAIMER:

THE INFORMATION CONTAINED IN THIS DOCUMENT APPLIES TO THIS SPECIFIC MATERIAL AS SUPPLIED. IT MAY NOT BE VALID FOR THIS MATERIAL IF IT IS USED IN COMBINATION WITH ANY OTHER MATERIALS. THIS INFORMATION IS ACCURATE TO THE BEST OF CRC INDUSTRIES' KNOWLEDGE OR OBTAINED FROM SOURCES BELIEVED BY CRC TO BE ACCURATE. BEFORE USING ANY PRODUCT, READ ALL WARNINGS AND DIRECTIONS ON THE LABEL. FOR FURTHER CLARIFICATION OF ANY INFORMATION CONTAINED ON THIS (M)SDS CONSULT YOUR SUPERVISOR, A HEALTH & SAFETY PROFESSIONAL, OR CRC INDUSTRIES.

MATERIAL NAME: CUTTING OIL THREAD CUTTING LUBRICANT

SDS: US