Section 1: Product & Company Identification

Product Name: Freeze-Off® Super Penetrant (aerosol)

Product Number (s): 05002

Product Use: Penetrant

Manufacturer / Supplier Contact Information:

<u>In United States</u>: <u>In Canada</u>: <u>In Mexico</u>:

CRC Industries, Inc.

CRC Canada Co.

CRC Industries Mexico

Av. Benito Juárez 4055 G

Warminster, PA 18974 Mississauga, Ontario L5S 1R2 Colonia Orquídea

<u>www.crcindustries.com</u> <u>www.crc-canada.ca</u> San Luís Potosí, SLP CP 78394 1-215-674-4300(General) 1-905-670-2291 <u>www.crc-mexico.com</u>

(800) 521-3168 (Technical)

(800) 272-4620 (Customer Service)

24-Hr Emergency - CHEMTREC: (800) 424-9300 or (703) 527-3887

Section 2: Hazards Identification

Emergency Overview

DANGER: Extremely Flammable. Harmful or Fatal if Swallowed. Eye Irritant. Contents Under Pressure.

Appearance & Odor: Reddish liquid, pine odor

Potential Health Effects:

ACUTE EFFECTS:

EYE: Liquid may cause mild irritation including stinging, tearing and redness.

SKIN: Liquid may cause mild to moderate skin irritation including redness, itching and burning. Repeated

contact may cause drying and cracking of skin. Product becomes colder the longer it is sprayed and

52-444-824-1666

may cause frostbite if sprayed on skin after extended use.

INHALATION: Breathing small amounts of vapor during normal handling is not likely to case harmful effects.

Breathing large amounts may cause irritation to the nose and throat as well as headache, drowsiness

or other nervous system effects.

INGESTION: Swallowing small amounts during normal handling is not likely to cause harmful effects. Swallowing

large amounts may be harmful. Main hazard is aspiration of this material into the lungs during

swallowing or vomiting. This can result in lung inflammation and other lung injury.

CHRONIC EFFECTS: Unknown

TARGET ORGANS: Inadequate data available for this material

Medical Conditions Aggravated by Exposure: skin or respiratory conditions

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.	
Aliphatic hydrocarbon	8052-41-3	10 - 15	
Hydrotreated petroleum distillates	64742-47-8 / 64742-46-7	15 - 20	
Turpentine oil	8006-64-2	3 - 6	
COzol™ 306	proprietary blend	3 - 6	
2-Butoxyethanol	111-76-2	2 - 3	
Diacetone alcohol	123-42-2	1 - 3	
1,1-Difluoroethane (HFC-152a)	75-37-6	45 - 55	

Section 4: First Aid Measures

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician if

irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If

breathing is difficult give oxygen. Call a physician.

Ingestion: Do NOT induce vomiting due to aspiration hazard. Seek medical attention.

Note to Physicians: This material is an aspiration hazard. Treat symptomatically.

Section 5: Fire-Fighting Measures

<u>Flammable Properties</u>: This product is extremely flammable in accordance with aerosol flammability definitions.

(See 16 CFR 1500.3(c)(6)).

Flash Point: 109°F / 43°C (TCC) Upper Explosive Limit: ND Autoignition Temperature: -58°F / -50°C (estimate) Lower Explosive Limit: ND

Fire and Explosion Data:

Suitable Extinguishing Media: Use extinguishing media appropriate for a Class B fire.

Products of Combustion: Oxides of carbon.

Explosion Hazards: Aerosol containers, when exposed to heat from fire, may build pressure and explode. Vapors

may accumulate in a confined space and create a flammable atmosphere.

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for

protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool

and to knock down vapors which may result from product decomposition.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Product Name: Freeze-Off® Super Penetrant

Product Number (s): 05002

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into

sewers or storm drains.

Methods for Containment & Clean-up: Eliminate all sources of ignition. Dike area to contain spill. Ventilate the area

with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used

absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Do not use near flames, sparks or other sources of ignition. Do not heat product. Us with

adequate ventilation in order to prevent vapor build-up and a flammable atmosphere. Avoid contact with skin and eyes. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical

shock and/or flash fire. For product use instructions, please see the product label.

Storage Procedures: Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120°F /

49°C to prevent cans from rupturing.

Aerosol Storage Level: III

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

	OS	SHA	AC	GIH	O	THER	
COMPONENT	TWA	STEL	TWA	STEL	TWA	SOURCE	UNIT
Aliphatic hydrocarbon	100 (v)	NE	100	NE	NE		ppm
Hydrotreated petroleum distillates	NE	NE	NE	NE	NE		
Turpentine oil	100	NE	20	NE	NE		ppm
COzol [™] 306	NE	NE	NE	NE	NE		
2-Butoxyethanol	50 (s)	NE	20	NE	NE		ppm
Diacetone alcohol	50	NE	50	NE	NE		ppm
1,1-Difluoroethane	NE	NE	NE	NE	1000	AIHA	ppm
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

Controls and Protection:

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally

preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA

regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls

are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and

for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid

contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile or other synthetic rubbers. Also, use full protective

clothing if there is prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: liquid Color: reddish Odor: pine

Odor Threshold: ND
Specific Gravity: 0.822
Initial Boiling Point: ND
Freezing Point: ND
Vapor Pressure: ND

Vapor Density: > 1 (air = 1)

Evaporation Rate: slow Solubility: negligible

Coefficient of water/oil distribution: ND

pH: NA

Volatile Organic Compounds: wt %: 36.55 g/L: 300.4 lbs./gal: 2.5

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Heat, sources of ignition

Incompatible Materials: Strong oxidizers

Hazardous Decomposition Products: Oxides of carbon

Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

Acute Toxicity:

Component	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 (rat)
Aliphatic hydrocarbon	> 5 mg/kg	> 3 mg/kg	> 1400 ppm/8H
Hydrotreated petroleum distillates	> 5 g/kg	> 2 g/kg	> 5 mg/L/4H
Turpentine oil	5760 mg/kg	No data	13,700 mg/m ³ /4H
COzol™ 306 (Ingredient #1)	3200 mg/kg	5 g/kg	No data
COzol™ 306 (Ingredient #2)	No data	No data	No data
COzol™ 306 (Ingredient #3)	25,000 mg/kg	No data	No data
2-Butoxyethanol	470 mg/kg	220 mg/kg	450 ppm/4H
Diacetone alcohol	2520 mg/kg	13,500 mg/kg	No data
1,1-Difluoroethane	No data	No data	25 ppm/30M

Chronic Toxicity:

	OSHA	IARC	NTP		
<u>Component</u>	Carcinogen	Carcinogen	<u>Carcinogen</u>	<u>Irritant</u>	<u>Sensitizer</u>
Aliphatic hydrocarbon	No	No	No	E (mild) /	Unknown
				S (mild)	
Hydrotreated petroleum distillates	No	No	No	E (mild) /	Unknown
				S (mild) /	
				R (mild)	
Turpentine oil	No	No	No	E (moderate) /	Unknown
				S (moderate)	
COzol™ 306 (Ingredient #1)	No	No	No	E (moderate) /	No
				S (moderate)	
COzol™ 306 (Ingredient #2)	No	No	No	E (moderate) /	Unknown
				S (moderate) /	
				R (mild)	
COzol™ 306 (Ingredient #3)	No	No	No	No	Unknown
2-Butoxyethanol	No	No	No	E (severe) /	No
				S (mild) /	
				R (mild)	
Diacetone alcohol	No	No	No	E (moderate) /	Unknown
				R (mild)	
1,1-Difluoroethane	No	No	No	No	Unknown

E – Eye	S – Skin	R - Respiratory
---------	----------	-----------------

Reproductive Toxicity: No information available No information available

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: 2-Butoxyethanol 96 Hr LC50, Bluegill sunfish: 1490 mg/L

24 Hr LC50, daphnia: 1720 mg/L

Persistence / Degradability:
Bioaccumulation / Accumulation:
Mobility in Environment:

No information available
No information available

Section 13: Disposal Considerations

<u>Waste Classification</u>: The dispensed liquid product is a RCRA hazardous waste for the characteristic of ignitability

with a waste code of D001. (See 40 CFR Part 261.20 - 261.33)

Empty aerosol containers may be recycled. Any liquids should be collected and properly

disposed as hazardous waste.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

Section 14: Transport Information

US DOT (ground): UN1950, Aerosols, flammable, 2.1, Limited Quantity**

ICAO/IATA (air): UN1950, Aerosols, flammable, 2.1, Limited Quantity

IMO/IMDG (water): UN1950, Aerosols, 2.1, Limited Quantity

Special Provisions: **This product can be classified and labeled as 'Consumer Commodity, ORM-D' for domestic

ground shipping until January 1, 2014.

If shipping as limited quantity by ground, note that shipping papers are not required.

Section 15: Regulatory Information

U.S. Federal Regulations:

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: None

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories: Fire Hazard Yes

Reactive Hazard No Release of Pressure Yes Acute Health Hazard Yes Chronic Health Hazard No

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements

of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of

1986 and 40 CFR Part 372:

2-Butoxyethanol (Glycol ethers category) (2.5%)

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

Occupational Safety and Health Administration (OSHA):

This product is regulated under the Hazard Communication Standard.

U.S. State Regulations:

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of

California to cause cancer, birth defects or other reproductive harm: cumene

Consumer Products VOC Regulations: In states with Consumer Products VOC regulations, this product is compliant as

a penetrant.

State Right to Know:

New Jersey: 8052-41-3, 111-76-2, 8002-09-3, 8006-64-2, 123-42-2, 75-37-6

Pennsylvania: 8052-41-3, 123-42-2, 111-76-2

Massachusetts: 8052-41-3, 8006-64-2, 123-42-2, 111-76-2, 75-37-6

Rhode Island: 8052-41-3, 111-76-2, 8006-64-2, 123-42-2,

Canadian Regulations:

Controlled Products Regulations:

Product Number (s): 05002

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: A, B5, D1A, D1B

Canadian DSL Inventory: All ingredients are either listed on the DSL Inventory or are exempt.

European Union Regulations:

RoHS Compliance: This product is compliant with Directive 2002/95/EC of the European Parliament and of the

Council of 27 January 2003. This product does not contain any of the restricted substances as


listed in Article 4(1) of the RoHS Directive.

Additional Regulatory Information: None

Section 16: Other Information

HMIS® (II)			
Health:	1		
Flammability:	4		
Reactivity:	0		
PPE:	В		

Ratings range from 0 (no hazard) to 4 (severe hazard)



Prepared By: Michelle Rudnick

CRC #: 447B Revision Date: 01/11/2013

Changes since last revision: Section 15: Prop 65

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstract Service
CFR: Code of Federal Regulations
DOT: Department of Transportation
DSL: Domestic Substance List

g/L: grams per Liter

HMIS: Hazardous Materials Identification System
IARC: International Agency for Research on Cancer
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization

IMDG: International Civil Aviation Organization
IMDG: International Maritime Dangerous Goods
IMO: International Maritime Organization

lbs./gal: pounds per gallon

LC: Lethal Concentration

LD: Lethal Dose

NA: Not Applicable ND: Not Determined

NIOSH: National Institute of Occupational Safety & Health

NFPA: National Fire Protection Association NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PMCC: Pensky-Martens Closed Cup PPE: Personal Protection Equipment

ppm: Parts per Million

RoHS: Restriction of Hazardous Substances

STEL: Short Term Exposure Limit

TCC: Tag Closed Cup
TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Information

System