

Section 1: Product & Company Identification

Product Name: Lectra Shield[™] Long Term Corrosion Inhibitor

Product Number (s): 02031

Product Use: corrosion inhibitor

Manufacturer / Supplier Contact Information:

In United States: CRC Industries, Inc. 885 Louis Drive Warminster, PA 18974 <u>www.crcindustries.com</u> 1-215-674-4300 (General) (800) 521-3168 (Technical) (800) 272-4620 (Customer Service) In Canada: CRC Canada Co. 2-1246 Lorimar Drive Mississauga, Ontario L5S 1R2 <u>www.crc-canada.ca</u> 1-905-670-2291 In Mexico: CRC Industries Mexico Av. Benito Juárez 4055 G Colonia Orquídea San Luís Potosí, SLP CP 78394 www.crc-mexico.com 52-444-824-1666

24-Hr Emergency - CHEMTREC: (800) 424-9300 or (703) 527-3887

Section 2: Hazards Identification

Emergency Overview

DANGER: Extremely Flammable. Harmful or Fatal if Swallowed. Contents Under Pressure. Appearance & Odor: Dark amber viscous liquid with petroleum odor

Potential Health Effects:

ACUTE EFFECTS:

- EYE: May cause mild to moderate irritation including stinging and redness.
- SKIN: Single, brief exposures may cause mild irritation. Frequent or prolonged contact may cause more severe irritation, defatting of the skin, and dermatitis.
- INHALATION: High vapor concentrations are irritating to the mucous membranes and upper respiratory tract and may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects, including death. May cause peripheral nervous system disorder and/or damage.
- INGESTION: Low order of toxicity by ingestion. May cause irritation of the gastrointestinal lining and nausea. Main hazard is aspiration into the lungs during swallowing or vomiting. Small amounts aspirated into the respiratory system may cause bronchopneumonia or pulmonary adema, possibly progressing to death.
- CHRONIC EFFECTS: Overexposure to n-hexane may cause progressive and potentially irreversible damage to the peripheral nervous system, particularly in the arms and legs. Repeated overexposure to aliphatic mineral spirits such as stoddard solvent can cause chronic nervous system disease.
- TARGET ORGANS: central nervous system, peripheral nervous system, respiratory system

Medical Conditions Aggravated by Exposure: skin and respiratory system

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.
Hexane isomers	64742-49-0 / 107-83-5	20 - 30
n-Hexane	110-54-3	0.8
Mineral spirits	8052-41-3	15 - 20
Additive blend	proprietary	22 - 27
Dipropylene glycol monomethyl ether	34590-94-8	1 - 5
Liquefied petroleum gas	68476-86-8	25 - 35

Section 4: First Aid Measures

Eye Contact:	Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.
Skin Contact:	Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.
Inhalation:	Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.
Ingestion:	Do NOT induce vomiting. Contact a physician immediately. If victim is conscious, give 2 glasses of water.
Note to Physicians	Treat symptomatically Gastric lavage using a cuffed endotracheal tube may be performed at your

Note to Physicians: Treat symptomatically. Gastric lavage using a cuffed endotracheal tube may be performed at your discretion.

Section 5: Fire-Fighting Measures

Flammable Properties: This product is extremely flammable in accordance with aerosol flammability definitions. (See 16 CFR 1500.3(c)(6)). Flash Point: $< 0^{\circ}F / -18^{\circ}C$ (TCC) Upper Explosive Limit: 9.0 Autoignition Temperature: 489°F / 254°C Lower Explosive Limit: 1.7 Fire and Explosion Data: Suitable Extinguishing Media: Class B fire extinguishers, dry chemical, foam or CO₂ Products of Combustion: Fumes, smoke and carbon monoxide **Explosion Hazards:** Aerosol containers, when exposed to heat from fire, may build pressure and explode. Vapors may accumulate in a confined space and create a flammable atmosphere. Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition. Do not spray water directly on fire; product will float and could be reignited on surface of water.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Product Name: Lectra Shield[™] Long Term Corrosion Inhibitor (aerosol) Product Number (s): 02031

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.
Methods for Containment & Clean-up: Dike area to contain spill. Remove all sources of ignition. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures:	Do not use product near any potential source of ignition. Avoid contact with eyes and skin. Avoid breathing vapors. Wash thoroughly after handling. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. For product use instructions, please see the product label.
Storage Procedures:	Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120°F / 49°C to prevent cans from rupturing. Do not store near potential sources of ignition.
Aerosol Storage Level:	III

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

	OS	SHA	AC	GIH	0	THER	
COMPONENT	TWA	STEL	TWA	STEL	TWA	SOURCE	UNIT
Hexane isomers	500(v)	1000(v)	500	1000	NE		ppm
n-Hexane	500	NE	50(s)	NE	NE		ppm
Stoddard solvent	500	NE	100	NE	NE		ppm
Additive blend	NE	NE	NE	NE	NE		
Dipropylene glycol monomethyl ether	100	150 (v)	100	150	NE		ppm
Liquefied petroleum gas	1000	NE	1000	NE	NE		ppm
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

Controls and Protection:

Engineering Controls:	Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.
Respiratory Protection:	None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and for emergencies.
Eye/face Protection:	For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.
Skin Protection:	Use protective gloves such as nitrile, PVC or Viton. Also, use full protective clothing if there is

prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: liquid Color: dark amber, viscous Odor: petroleum		
Odor Threshold: ND		
Specific Gravity: 0.787		
Initial Boiling Point: 140°F / 60°C		
Freezing Point: < -50°F / -45°C		
Vapor Pressure: ND		
Vapor Density: > 1 (air = 1)		
Evaporation Rate: fast		
Solubility: negligible in water		
Coefficient of water/oil distribution: ND		
pH: NA		
Volatile Organic Compounds: <u>wt %</u> : 79.2	<u>g/L</u> : 623.3	<u>lbs./gal</u> : 5.2

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid:	Sources of ig	Sources of ignition, temperature extremes			
Incompatible Materials:	Strong oxidizers				
Hazardous Decomposition	Products:	Oxides of carbon, aldehydes and other products of incomplete combustion			
Possibility of Hazardous R	eactions:	No			

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

Acute Toxicity:

<u>Component</u>	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 (rat)
Hexane isomers	No data	No data	No data
n-Hexane	28,710 mg/kg	3000 mg/kg	48,000 ppm/4H
Stoddard solvent	> 5 g/kg	> 2 g/kg	> 1400 ppm/8H
Additive blend	No data	No data	No data
Dipropylene glycol monomethyl ether	5.5 mL/kg	10 mL/kg	No data
Liquefied petroleum gas	No data	No data	No data

Product Name: Lectra Shield[™] Long Term Corrosion Inhibitor (aerosol) Product Number (s): 02031

Chronic Toxicity:

	OSHA	IARC	NTP		
Component	Carcinogen	Carcinogen	Carcinogen	Irritant	<u>Sensitizer</u>
Hexane isomers	No	No	No	E & S (mild)	Unknown
n-Hexane	No	No	No	E, S & R	Unknown
				(moderate)	
Stoddard solvent	No	No	No	E & S (mild)	Unknown
Additive blend	No	No	No	Unknown	Unknown
Dipropylene glycol monomethyl ether	No	No	No	E (moderate) / S (mild)	No
Liquefied petroleum gas	No	No	No	No	No
			E – Eye	S – Skin	R - Respiratory
Reproductive Toxicity: No informatic					it itespirate

<u>Reproductive Toxicity</u> :	No information available
Teratogenicity:	No information available
Mutagenicity:	No information available
Synergistic Effects:	No information available

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity:	n-hexane - 48 Hr EC50 water flea: 3.87 mg/L				
	96 I	Hr LC50 Lepomis macrochirus: 4.12 mg/L			
Persistence / De	gradability:	No information available			
Bioaccumulation	/ Accumulation:	No information available			
Mobility in Enviro	onment:	No information available			

Section 13: Disposal Considerations

<u>Waste Classification</u>: The dispensed liquid product is RCRA hazardous waste for the characteristic of ignitability with a waste code of D001. (See 40 CFR Part 261.20 – 261.33) Empty aerosol containers may be recycled. Any liquid product should be managed as a hazardous waste.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

Section 14: Transport Information

US DOT (ground): Consumer Commodity, ORM-D

ICAO/IATA (air): Consumer Commodity, ID8000, 9

IMO/IMDG (water): Aerosols, UN1950, 2.1, Limited Quantity

Special Provisions: None

Section 15: Regulatory Information

Product Name: Lectra Shield[™] Long Term Corrosion Inhibitor (aerosol) Product Number (s): 02031

U.S. Federal Regulations:

<u>Toxic Substances Control Act (TSCA)</u>: All ingredients are either listed on the TSCA inventory or are exempt.

<u>Comprehensive Environmental Response, Compensation and Liability Act (CERCLA)</u>: Reportable Quantities (RQ's) exist for the following ingredients: n-hexane (5000 lbs)

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III: Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories: Fire Hazard Yes Reactive Hazard No Release of Pressure Yes

Acute Health Hazard Yes

Chronic Health Hazard Yes

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: n-hexane (0.8%)

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): n-hexane

<u>Occupational Safety and Health Administration</u>: This product is regulated by the Hazard Communications Standard.

U.S. State Regulations:

<u>California Safe Drinking Water and Toxic Enforcement Act (Prop 65)</u>: This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm:

None

<u>Consumer Products VOC Regulations</u>: This product is not regulated under state or federal VOC regulations.

State Right to Know:

New Jersey:75-83-2, 110-54-3, 79-29-8, 68476-86-8, 8052-42-3, 34590-94-8Pennsylvania:107-83-5, 75-83-2, 110-54-3, 79-29-8, 68476-86-8, 8052-42-3, 34590-94-8Massachusetts:107-83-5, 75-83-2, 110-54-3, 79-29-8, 68476-86-8, 8052-42-3, 34590-94-8Rhode Island :110-54-3, 68476-86-8, 8052-42-3, 34590-94-8

Canadian Regulations:

Controlled Products Regulations:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: A, B5, D2B

Canadian DSL Inventory: All ingredients are either listed on the DSL Inventory or are exempt.


European Union Regulations:

<u>RoHS Compliance</u>: This product is compliant with Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003. This product does not contain any of the restricted substances as listed in Article 4(1) of the RoHS Directive.

Additional Regulatory Information: None

Section 16: Other Information

HMIS® (II)					
Health:	2				
Flammability:	3				
Reactivity:	0				
PPE:	В				



Ratings range from 0 (no hazard) to 4 (severe hazard)

Prepared By:	Michelle Rudnick
CRC #:	522G/H
Revision Date:	09/15/2011

Changes since last revision: Revision date

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

CAS: CFR: DOT: DSL: g/L: HMIS: IARC: IATA: ICAO: IMDG: IMO:	American Conference of Governmental Industrial Hygienists Chemical Abstract Service Code of Federal Regulations Department of Transportation Domestic Substance List grams per Liter Hazardous Materials Identification System International Agency for Research on Cancer International Air Transport Association International Civil Aviation Organization International Maritime Dangerous Goods International Maritime Organization	NFPA: NTP: OSHA: PMCC: PPE: ppm: RoHS: STEL: TCC:	Short Term Exposure Limit Tag Closed Cup
-		-	
lbs./gal:	pounds per gallon	TWA:	Time Weighted Average
LC:	Lethal Concentration	WHMIS:	Workplace Hazardous Materials Information
LD:	Lethal Dose		System