### **Section 1: Product & Company Identification**

Product Name: QD® Contact Cleaner (bulk)

Product Number (s): 02131, 02132, 02133

Product Use: Electronic contact cleaner

**Manufacturer / Supplier Contact Information:** 

<u>In United States</u>: <u>In Canada</u>: <u>In Mexico</u>:

CRC Industries, Inc.

CRC Canada Co.

CRC Industries Mexico

Av. Benito Juárez 4055 G

Warminster, PA 18974 Mississauga, Ontario L5S 1R2 Colonia Orquídea

<u>www.crcindustries.com</u> <u>www.crc-canada.ca</u> San Luís Potosí, SLP CP 78394 1-215-674-4300(General) 1-905-670-2291 <u>www.crc-mexico.com</u>

(800) 521-3168 (Technical)

(800) 272-4620 (Customer Service)

24-Hr Emergency - CHEMTREC: (800) 424-9300 or (703) 527-3887

### Section 2: Hazards Identification

#### **Emergency Overview**

52-444-824-1666

**DANGER:** Extremely Flammable. Harmful or Fatal if Swallowed. Appearance & Odor: Clear, colorless liquid with alcohol odor

#### **Potential Health Effects:**

**ACUTE EFFECTS:** 

EYE: May cause mild irritation including stinging and redness, but does not injure eye.

SKIN: Single, brief exposures may cause mild irritation. Frequent or prolonged contact may cause more

severe irritation, defatting of the skin, and dermatitis.

INHALATION: High vapor concentrations are irritating to the respiratory tract and may cause headaches, dizziness,

anesthesia, drowsiness, unconsciousness and other central nervous system effects, including death.

May cause peripheral nervous system disorder and/or damage.

INGESTION: Low order of toxicity by ingestion. Main hazard is aspiration into the lungs during swallowing or

vomiting. Small amounts aspirated into the respiratory system may cause bronchopneumonia or

pulmonary adema, possibly progressing to death.

CHRONIC EFFECTS: Overexposure to n-hexane may cause progressive and potentially irreversible damage to the

peripheral nervous system, particularly in the arms and legs.

TARGET ORGANS: central nervous system, peripheral nervous system, respiratory system

Medical Conditions Aggravated by Exposure: skin and respiratory conditions

See Section 11 for toxicology and carcinogenicity information on product ingredients.

### Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.	
Hexane isomers	64742-49-0 / 107-83-5	65 - 75	
Pentafluorobutane (HFC-365 mfc)	406-58-6	20 - 30	
n-Hexane	110-54-3	5.1	
Isoparaffinic hydrocarbon	64741-66-8	5 - 10	
Methanol	67-56-1	< 1	

#### **Section 4: First Aid Measures**

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician if

irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If

breathing is difficult give oxygen. Call a physician.

Ingestion: Do NOT induce vomiting. Contact a physician immediately.

Note to Physicians: Treat symptomatically. Gastric lavage using a cuffed endotracheal tube may be performed at your

discretion.

## Section 5: Fire-Fighting Measures

<u>Flammable Properties</u>: As defined by OSHA, this product is a Class 1B Flammable Liquid.

Flash Point: < 0°F / -17°C (TCC) Upper Explosive Limit: 9.0
Autoignition Temperature: 489°F / 254°C Lower Explosive Limit: 1.7

Fire and Explosion Data:

Suitable Extinguishing Media: Class B fire extinguishers, dry chemical, foam or carbon dioxide

Products of Combustion: Fumes, smoke, carbon monoxide, hydrogen fluoride and fluorophosgene

Explosion Hazards: Containers, when exposed to heat from fire, may build pressure and rupture. Vapors may

accumulate in a confined space and create a flammable atmosphere.

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for

protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition. Do not spray water directly on fire; product will float and could be reignited on surface of water.

#### Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into

sewers or storm drains.

Methods for Containment & Clean-up: Dike area to contain spill. Remove all sources of ignition. Ventilate the area with

fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used

absorbents into proper waste containers.

### Section 7: Handling and Storage

Handling Procedures: Use proper grounding and bonding procedures for transferring materials. Do not use product

near any source of ignition. Keep containers closed when not in use. Provide adequate ventilation. Avoid contact with eyes and skin. Avoid breathing vapors. For product use

instructions, please see the product label.

Storage Procedures: Store in a cool dry area out of direct sunlight and away from sources of ignition. Containers

should be tightly closed while in storage.

Aerosol Storage Level: NA

## **Section 8: Exposure Controls/Personal Protection**

#### **Exposure Guidelines:**

	OSHA		ACGIH		OTHER		
COMPONENT	TWA	STEL	TWA	STEL	TWA	SOURCE	UNIT
He are larger	500()	4000()	500	4000	NIE		
Hexane isomers	500(v)	1000(v)	500	1000	NE		ppm
Pentafluorobutane (HFC-365 mfc)	NE	NE	NE	NE	NE		
n-Hexane	500	NE	50(s)	NE	NE		ppm
Synthetic isoparaffinic hydrocarbon	NE	NE	NE	NE	NE		
Methanol	200	250 (v)	200	250	NE		ppm
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

#### **Controls and Protection:**

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally

preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA

regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls

are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and

for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid

contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile, PVC, or neoprene. Also, use full protective clothing if

there is prolonged or repeated contact of liquid with skin.

# Section 9: Physical and Chemical Properties

Physical State: liquid Color: clear, colorless

Odor: alcohol Odor Threshold:

ND 0.737

Specific Gravity: Initial Boiling Point: 104°F / 40°C Freezing Point: < -76°F / -60°C

Vapor Pressure: ND

Vapor Density: (air = 1)> 1

**Evaporation Rate:** very fast Solubility: negligible in water

Coefficient of water/oil distribution: ND

pH:

Volatile Organic Compounds:

wt %: 74.9

552 g/L:

4.6 lbs./gal:

Federal: CARB: wt %: 100

g/L: 737 lbs./gal: 6.14

# Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Sources of ignition, temperature extremes

Incompatible Materials: Alkali or alkaline earth metals such as powdered or freshly abraded aluminum, sodium,

magnesium, zinc, beryllium, etc; strong bases such as sodium hydroxide, potassium hydroxide,

etc; strong oxidizers

Hazardous Decomposition Products: Oxides of carbon, hydrogen fluoride and fluorophosgene

Possibility of Hazardous Reactions: No

# **Section 11: Toxicological Information**

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

#### **Acute Toxicity:**

<u>Component</u>	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 (rat)
Hexane isomers	> 15,000 mg/kg	> 2000 mg/kg	No data
Pentafluorobutane	> 2000 mg/kg	No data	No data
n-Hexane	28,710 mg/kg	3000 mg/kg	48,000 ppm/4H
Synthetic isoparaffinic hydrocarbon	No data	No data	No data
Methanol	5600 mg/kg	15,800 mg/kg	81,000 mg/m <sup>3</sup> /14H

#### **Chronic Toxicity:**

	OSHA	IARC	NTP		
<u>Component</u>	Carcinogen	Carcinogen	Carcinogen	<u>Irritant</u>	Sensitizer
Hexane isomers	No	No	No	None	Unknown
Pentafluorobutane	No	No	No	E (mild)	Unknown
n-Hexane	No	No	No	E, S & R (moderate)	Unknown
Synthetic isoparaffinic	No	No	No	S (mild)	Unknown
hydrocarbon					
Methanol	No	No	No	E & S (moderate)	Unknown

E – Eye S – Skin R - Respiratory

Reproductive Toxicity:
Teratogenicity:
Mutagenicity:
Synergistic Effects:
No information available
No information available
No information available

### **Section 12: Ecological Information**

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: n-hexane - 48 Hr EC50 water flea: 3.87 mg/L

96 Hr LC50 Lepomis macrochirus: 4.12 mg/L

Persistence / Degradability: This product is not readily biodegradable.

Bioaccumulation / Accumulation: No information available Mobility in Environment: No information available

### Section 13: Disposal Considerations

<u>Waste Classification</u>: This product is a RCRA hazardous waste for the characteristic of ignitability with a waste code

of D001. (See 40 CFR Part 261.20 – 261.33)

Empty containers may be recycled. Any liquid product should be managed as a hazardous

waste.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

# **Section 14: Transport Information**

US DOT (ground): 02131, 02132 UN1993, Flammable Liquids, n.o.s. (Isohexane, Pentafluorobutane), 3, PGII

02133 UN1993, Flammable Liquids, n.o.s. (Isohexane, Pentafluorobutane), 3, PGII,

Limited Quantity\*\*

ICAO/IATA (air): 02131, 02132 UN1993, Flammable Liquids, n.o.s. (Isohexane, Pentafluorobutane), 3, PGII

02133 UN1993, Flammable Liquids, n.o.s. (Isohexane, Pentafluorobutane), 3, PGII,

**Limited Quantity** 

IMO/IMDG (water): 02131, 02132 UN1993, Flammable Liquids, n.o.s. (Isohexane, Pentafluorobutane), 3, PGII

**02133** UN1993, Flammable Liquids, n.o.s. (Isohexane, Pentafluorobutane), 3, PGII,

**Limited Quantity** 

Special Provisions: \*\*This product can be classified and labeled as 'Consumer Commodity, ORM-D' for domestic

ground shipping.

# Section 15: Regulatory Information

#### **U.S. Federal Regulations:**

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: n-hexane (5000 lbs)

methanol (5000 lbs)

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories: Fire Hazard Yes

Reactive Hazard No Release of Pressure No Acute Health Hazard Yes Chronic Health Hazard No

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements

of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of

1986 and 40 CFR Part 372:

n-hexane (5.1%), methanol (0.6%)

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): n-hexane, methanol

Occupational Safety and Health Administration:

This product is regulated under the Hazard Communication Standard.

**U.S. State Regulations:** 

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of

California to cause cancer, birth defects or other reproductive harm: methanol

Consumer Products VOC Regulations: This product cannot be sold for use in California. In other states with Consumer

Products VOC regulations, this product is compliant as an Electronic Cleaner.

State Right to Know:

New Jersey: 75-83-2, 110-54-3, 79-29-8, 67-56-1

Pennsylvania: 107-83-5, 75-83-2, 110-54-3, 79-29-8, 67-56-1 Massachusetts: 107-83-5, 75-83-2, 110-54-3, 79-29-8, 67-56-1

Rhode Island: 110-54-3, 67-56-1

Canadian Regulations:

**Controlled Products Regulations:** 

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: B2, D2B

Canadian DSL Inventory: All ingredients are either listed on the DSL Inventory or are exempt.

**European Union Regulations:** 

RoHS Compliance: This product is compliant with Directive 2002/95/EC of the European Parliament and of the

Council of 27 January 2003. This product does not contain any of the restricted substances as


listed in Article 4(1) of the RoHS Directive.

Additional Regulatory Information: None

#### Section 16: Other Information

HMIS® (II)		
Health:	1	
Flammability:	3	
Reactivity:	0	
PPE:	В	

Ratings range from 0 (no hazard) to 4 (severe hazard)



Prepared By: Michelle Rudnick

CRC #: 844 Revision Date: 06/14/2013

Changes since last revision: Section 14: Transport Information

Section 15: Prop 65

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

ACGIH: American Conference of Governmental Industrial Hygienists

CARB: California Air Resources Board
CAS: Chemical Abstract Service
CFR: Code of Federal Regulations
DOT: Department of Transportation
DSL: Domestic Substance List

g/L: grams per Liter

HMIS: Hazardous Materials Identification System
IARC: International Agency for Research on Cancer
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization

IMDG: International Maritime Dangerous Goods IMO: International Maritime Organization

lbs./gal: pounds per gallon LC: Lethal Concentration LD: Lethal Dose
NA: Not Applicable
ND: Not Determined

NIOSH: National Institute of Occupational Safety & Health

NFPA: National Fire Protection Association NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PMCC: Pensky-Martens Closed Cup PPE: Personal Protection Equipment

ppm: Parts per Million

RoHS: Restriction of Hazardous Substances

STEL: Short Term Exposure Limit TCC: Tag Closed Cup

TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Information

System