



# Material Safety Data Sheet

## Section 1: Product & Company Identification

Product Name: True Tap™ Foamy

Product Number (s): 03410

**Manufactured By:**

CRC Industries, Inc.  
885 Louis Drive  
Warminster, PA 18974  
[www.crcindustries.com](http://www.crcindustries.com)

General Information	(215) 674-4300
Technical Assistance	(800) 521-3168
Customer Service	(800) 272-4620
24-Hr Emergency (CHEMTREC)	(800) 424-9300

## Section 2: Hazards Identification

### Emergency Overview

Appearance & Odor: Clear liquid, slight petroleum odor

### WARNING

Flammable. Vapor Harmful. Contents Under Pressure.

As defined by OSHA's Hazard Communication Standard, this product is hazardous.

### Potential Health Effects:

EYE:	May cause mild to moderate irritation.
SKIN:	May cause mild irritation with extended contact.
INHALATION:	Inhalation of oil mist is harmful and may cause damage if TLV is exceeded.
INGESTION:	May cause nausea.
CHRONIC EFFECTS:	Unknown
TARGET ORGANS:	Unknown

Medical Conditions Aggravated by Exposure:

pre-existing skin disorders

See Section 11 for toxicology and carcinogenicity information on product ingredients.

---

**Section 3: Composition/Information on Ingredients**

COMPONENT	CAS NUMBER	% by Wt.
Chlorinated paraffin	63449-39-8	20 - 30
Glycerol ester of fatty acids	proprietary	20 – 30
Hydrotreated light naphthenic distillate	64742-53-6	15 – 25
Liquefied petroleum gas	68476-86-8	20 - 30

---

**Section 4: First Aid Measures**

Eye Contact:	Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.
Skin Contact:	Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.
Inhalation:	Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.
Ingestion:	Do not induce vomiting unless directed by medical personnel. Never give anything by mouth to an unconscious person.
<i>Note to Physicians:</i>	Treat symptomatically.

---

**Section 5: Fire-Fighting Measures**

<u>Flammable Properties:</u>	This product is flammable in accordance with aerosol flammability definitions (16 CFR 1500.3(c)(6) ).		
Flash Point:	415 F (PMCC)	Upper Explosive Limit:	ND
Autoignition Temperature:	ND	Lower Explosive Limit:	ND
Suitable Extinguishing Media:	Foam or dry chemical		
Products of Combustion:	Oxides of carbon		
Protection of Fire-Fighters:	Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.		

---

**Section 6: Accidental Release Measures**

Personal Precautions:	Use personal protection recommended in Section 8.
Environmental Precautions:	Take precautions to prevent contamination of ground and surface waters. Do not flush

into sewers or storm drains.

Methods for Containment & Clean-up: Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

---

## Section 7: Handling and Storage

Handling Procedures: Use as directed. Normal safety precautions common to good manufacturing should be followed.

Storage Procedures: Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120 F to prevent cans from rupturing.

Aerosol Storage Level: III

---

## Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
Chlorinated paraffin	NE	NE	NE	NE	5	mfg	mg/m <sup>3</sup>
Glycerol ester of fatty acid	NE	NE	NE	NE	NE		
Hydrotreated light naphthenic distillate	5*	NE	5*	NE	NE		mg/m <sup>3</sup>
Liquefied petroleum gas	1000	NE	1000	NE	NE		ppm
N.E. – Not Established      (c) – ceiling      (s) – skin      (v) – vacated      * - oil mist							

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile or Viton. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

---

## Section 9: Physical and Chemical Properties

Physical State: liquid

Color: clear

Odor: petroleum

Specific Gravity: 1.04

Initial Boiling Point: 212 F

Freezing Point: ND

Vapor Pressure: ND

Vapor Density: &gt; 1 (air = 1)

Evaporation Rate: &lt; 1 (ether = 1)

Solubility: negligible in water

pH: NA

Volatile Organic Compounds: wt %: < 40 g/L: ND lbs./gal: ND

---

**Section 10: Stability and Reactivity**

Stability: Stable

Conditions to Avoid: Do not touch can to live electrical sources.

Incompatible Materials: Strong acids and bases.

Hazardous Decomposition Products: Oxides of carbon

Possibility of Hazardous Reactions: No

---

**Section 11: Toxicological Information**

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

**ACUTE EFFECTS**

<u>Component</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
Chlorinated paraffin	LD50	> 10 mL/kg	Dermal	Rabbit
Chlorinated paraffin	LD50	26100 mg/kg	Oral	Rat

**CHRONIC EFFECTS**

Carcinogenicity:

	<u>Component</u>	<u>Result</u>
OSHA:	Chlorinated paraffin	Hazard Communication Carcinogen
IARC:	Chlorinated paraffin	2B – Possibly carcinogenic to humans
NTP:	None listed	

Mutagenicity: No information available

Other: None

---

**Section 12: Ecological Information**

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity:	No information available
Persistence / Degradability:	No information available
Bioaccumulation / Accumulation:	No information available
Mobility in Environment:	No information available

---

### Section 13: Disposal Considerations

Disposal: The material, as packaged, is not a RCRA hazardous waste. (See 40 CFR Part 261.20 – 261.33)  
If this material is mixed with other materials, such as certain heavy metals, the resulting waste should be evaluated for waste classification.

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

---

### Section 14: Transport Information

Proper shipping description:

US DOT (ground): Consumer Commodity, ORM-D

Special Provisions: None

---

### Section 15: Regulatory Information

#### U.S. Federal

##### Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

##### Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: None

**Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.**

##### Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories:	Fire Hazard	No
	Reactive Hazard	No
	Release of Pressure	Yes
	Acute Health Hazard	Yes
	Chronic Health Hazard	Yes

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:  
polychlorinated alkanes (< 30%)

##### Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

**State Regulations**California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm: NONE

State Right to Know:

New Jersey: None  
Pennsylvania: None  
Massachusetts: None  
Rhode Island : None

**Additional Regulatory Information:** None

---

**Section 16: Other Information**

NFPA: Health: 1 Flammability: 1 Reactivity: 1  
HMIS: Health: 1 Flammability: 1 Reactivity: 1 PPE: B

Prepared By: Michelle Rudnick  
CRC #: 03410  
Revision Date: 03/07/2007

Changes since last revision: MSDS reformatted in accordance with ANSI Z400.1-2004

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS:	Chemical Abstract Service	NA:	Not Applicable
ppm:	Parts per Million	ND:	Not Determined
TCC:	Tag Closed Cup	NE:	Not Established
PMCC:	Pensky-Martens Closed Cup	g/L:	grams per Liter
PPE:	Personal Protection Equipment	lbs./gal:	pounds per gallon
TWA:	Time Weighted Average	STEL:	Short Term Exposure Limit
OSHA:	Occupational Safety and Health Administration		
ACGIH	American Conference of Governmental Industrial Hygienists		
NIOSH	National Institute of Occupational Safety & Health		