



SAFETY DATA SHEET

1. Identification

Product identifier Upside Down Marking Spray Paint - Safety Green - 1 lb 1 oz

Other means of identification

Product Code No. 18203 (Item# 1005222)

Recommended use Coating

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.
Warminster, PA 18974 US

Telephone

General Information 215-674-4300

Technical Assistance 800-521-3168

Customer Service 800-272-4620

**24-Hour Emergency
(CHEMTREC)** 800-424-9300 (US)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Liquefied gas
Health hazards	Carcinogenicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
OSHA defined hazards	Not classified.	

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Do not breathe mist/vapors. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear protective gloves/eye protection/face protection.

Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell. If exposed or concerned: Get medical advice/attention.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
water		7732-18-5	20 - 30
propane		74-98-6	15 - 25
solvent naphtha (petroleum), light aliph.		64742-89-8	15 - 25
calcium carbonate		1317-65-3	15 - 20
n-butane		106-97-8	10 - 15
distillates (petroleum), hydrotreated light		64742-47-8	1 - 5
titanium dioxide		13463-67-7	1 - 5
ethylbenzene		100-41-4	≤ 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

Skin contact

Wash off with soap and water. Take off contaminated clothing and wash before reuse. Get medical attention if irritation develops and persists.

Eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Aspiration may cause pulmonary edema and pneumonitis. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. Dizziness. Direct contact with eyes may cause temporary irritation. May cause respiratory irritation. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Carbon dioxide (CO2). Dry chemical powder. Water spray.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not breathe mist/vapors. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains. Observe good industrial hygiene practices. For product usage instructions, see the product label.
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
calcium carbonate (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
ethylbenzene (CAS 100-41-4)	PEL	435 mg/m3	
		100 ppm	

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm	
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	PEL	400 mg/m3	
titanium dioxide (CAS 13463-67-7)	PEL	100 ppm 15 mg/m3	Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value
ethylbenzene (CAS 100-41-4)	TWA	20 ppm
n-butane (CAS 106-97-8)	STEL	1000 ppm
titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
calcium carbonate (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	100 mg/m3	
ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3	
		125 ppm	
	TWA	435 mg/m3 100 ppm	
n-butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm	
propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm	
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	TWA	400 mg/m3 100 ppm	

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear protective gloves such as: Silver Shield®. Nitrile.
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Aerosol.
Color	Green.
Odor	Aromatic.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	95 °F (35 °C) estimated
Flash point	-2.2 °F (-19.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.7 %
Flammability limit - upper (%)	10.9 %
Vapor pressure	4025.9 hPa estimated
Vapor density	Not available.
Relative density	0.77 - 0.85
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	410 °F (210 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Percent volatile	93.2 % estimated
Other information	
VOC-State Aerosol Coatings (MIR)	0.52

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
-------------------	---

Material name: Upside Down Marking Spray Paint - Safety Green - 1 lb 1 oz

No. 18203 (Item# 1005222) Version #: 01 Issue date: 02-17-2021

SDS US

5 / 11

Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, flames and sparks. Contact with incompatible materials. Avoid freezing.
Incompatible materials	Acids. Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause irritation to the respiratory system. Prolonged inhalation may be harmful.
Skin contact	Prolonged skin contact may cause temporary irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May be fatal if swallowed and enters airways. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. Dizziness. Direct contact with eyes may cause temporary irritation. May cause respiratory irritation.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Product	Species	Test Results
---------	---------	--------------

Upside Down Marking Spray Paint - Safety Green - 1 lb 1 oz

Acute

Dermal

LD50	Rabbit	> 10000 mg/kg
------	--------	---------------

Inhalation

Dust and mist.

LC50	Rat	> 6.82 mg/l, 4 hours
------	-----	----------------------

Oral

LD50	Rat	> 20000 mg/kg
------	-----	---------------

Components	Species	Test Results
------------	---------	--------------

distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Acute

Dermal

LD50	Rabbit	> 2000 mg/kg
------	--------	--------------

Inhalation

LC50	Rat	> 5 mg/l, 4 hours
------	-----	-------------------

Oral

LD50	Rat	> 5000 mg/kg
------	-----	--------------

n-butane (CAS 106-97-8)

Acute

Inhalation

LC50	Rat	658 mg/l, 4 Hours
------	-----	-------------------

titanium dioxide (CAS 13463-67-7)

Acute

Dermal

LD50	Rabbit	> 10000 mg/kg
------	--------	---------------

Oral

LD50	Rat	> 10000 mg/kg
------	-----	---------------

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

ethylbenzene (CAS 100-41-4) 2B Possibly carcinogenic to humans.

titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure May cause respiratory irritation.

Specific target organ toxicity - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Product	Species		Test Results
Upside Down Marking Spray Paint - Safety Green - 1 lb 1 oz			
Aquatic			
Acute			
Crustacea	EC50	Daphnia	9130.4346 mg/l, 48 hours
Fish	LC50	Fish	15344.3115 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

ethylbenzene 3.15

n-butane 2.89

propane 2.36

Bioconcentration factor (BCF)

ethylbenzene 1

titanium dioxide 352

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions If discarded, this product is considered a RCRA ignitable waste, D001. Empty container can be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	304
Packaging bulk	None


IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.


IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	Yes, but exempt from the regulations.
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

DOT; IMDG



IATA



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

ethylbenzene (CAS 100-41-4)

CERCLA Hazardous Substances: Reportable quantity

ethylbenzene (CAS 100-41-4)

1000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ethylbenzene (CAS 100-41-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

n-butane (CAS 106-97-8)

propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA)

Contains component(s) regulated under the Safe Drinking Water Act.

Food and Drug Administration (FDA)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)

Gas under pressure

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

Yes

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
ethylbenzene	100-41-4	≤ 1

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

calcium carbonate (CAS 1317-65-3)

ethylbenzene (CAS 100-41-4)

n-butane (CAS 106-97-8)

propane (CAS 74-98-6)

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

titanium dioxide (CAS 13463-67-7)

US. Massachusetts RTK - Substance List

calcium carbonate (CAS 1317-65-3)

ethylbenzene (CAS 100-41-4)

n-butane (CAS 106-97-8)

propane (CAS 74-98-6)

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

calcium carbonate (CAS 1317-65-3)

distillates (petroleum), hydrotreated light (CAS 64742-47-8)

ethylbenzene (CAS 100-41-4)

n-butane (CAS 106-97-8)

propane (CAS 74-98-6)
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)
titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

calcium carbonate (CAS 1317-65-3)
distillates (petroleum), hydrotreated light (CAS 64742-47-8)
ethylbenzene (CAS 100-41-4)
n-butane (CAS 106-97-8)
propane (CAS 74-98-6)
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)
titanium dioxide (CAS 13463-67-7)

California Proposition 65



WARNING: This product can expose you to chemicals including ethylbenzene, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

ethylbenzene (CAS 100-41-4)	Listed: June 11, 2004
titanium dioxide (CAS 13463-67-7)	Listed: September 2, 2011

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

distillates (petroleum), hydrotreated light (CAS 64742-47-8)
ethylbenzene (CAS 100-41-4)
n-butane (CAS 106-97-8)
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)
titanium dioxide (CAS 13463-67-7)

Volatile organic compounds (VOC) regulations

EPA

Aerosol coatings (40 CFR 59, Subpt. E) Compliant

State

Aerosol coatings This product is regulated as a Ground Traffic and Marking Coating. This product is compliant for sale in all 50 states.

Maximum incremental reactivity (MIR) 0.52

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	02-17-2021
Prepared by	Danica Fulmer
Version #	01

Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc..

Revision information

This document has undergone significant changes and should be reviewed in its entirety.