Chemsico Division of United Industries Corp. P.O. Box 142642 St. Louis, MO 63114-0642

## Hazardous Material Identification System-(HMIS) REACTIVITY - 0 HEALTH - 0 FLAMMABILITY - 2 PERSONAL -

## Material Safety Data Sheet

| Complies with OSHA's Hazard Communica  | tion Standard, 29 CFR                      | 1910.1200   |   |   |
|--|--|---|---|---|
| I Trade Name: DG Guarantee [   | Dusting Spray                              |   |   |   |
| <b>Product Type:</b> Aerosol Furniture Dus   | fing Spray                                 |   |   |   |
| Product Item Number: 41010   | Formula Code Number: 21-0395               |   |   |   |
| EPA Registration Number  | Manufacture                                | r   | Emergency Telephone No.   |   |
| N/A  | Chemsico<br>8494 Chapin I<br>St. Louis, MO | ndustrial Dr.<br>63114  | For Chemical Emergency:<br>For information:<br>Prepared by:<br>Date Prepared:   | 1-800-633-2873<br>1-800-678-9258<br>C.A. Duckworth<br>Sept 26, 2001 |
| II Hazardous Ingredients/Identity Information  |  | III Physical and Chemical Characteristics   |   |   |
| Chemical % OSHA PEL ACGIH TLV Mineral Spirits 10.0 100 ppm 100 ppm Boll CAS #8054-41-3 Isobutane 7.5 NE NE Var CAS #75-28-5 Propane 2.5 1000 ppm NE Var CAS #74-98-6  IV Fire and Explosion Hazard Data  Flash Point: 156°F (TCC) Flame Extension: 0" (Lovel 1 Acrosol) Flammable Limits: N/A Autoignition Temp.: N/A Fire Extinguishing Media: Water Fog, Carbon Dioxide, Dry Hazard March Pell ACGIH TLV App Boll Hazard Data  V  State Point: 156°F (TCC) Point Point: 156°F (TCC) Flammable Limits: N/A Autoignition Temp.: N/A Fire Extinguishing Media: Water Fog, Carbon Dioxide, Dry Hazard Data |  |   | Appearance and Odor: Fine mist. Fragrance. No visible residue.  Bolling Point: NA Melting Point: NA Wapor Pressure: 90 psig @ 54°C/130°F Specific Gravity: 0.95 (H <sub>2</sub> 0=1) % Volotile (by vol.): 92% Solubility in Water: greater than 1 (Air=1) % Volotile (by vol.): 92% Solubility in Water: greater than 72% less than 1 (Butyl Acetate=1)  V Reactivity Data  Stability: Stable Polymerization: Will not occur Conditions to Avold: Temperatures over 130°F Incompatible Materials: N/A Hazardous Decomposition or Byproducts: Carbon dioxide, carbon monoxide |   |
| VI Health Hazard Data  |  | VII Precautions for Safe Handling and Use   |   |   |
| Ingestion (Swallowing): May be harmful if swallowed. First Aid: Consult a physician. Skin Contact: N/A First Aid: N/A Eye Contact: May cause eye irritation. First Aid: Flush eyes with plenty of water. Inhalation Toxicity: N/A First Ald: N/A Special Notes: None Health Conditions Aggravated by Exposure: None Known Ingredients listed by NTP, OSHA or IARC as Carcinogens or potential carcinogens: None  |  | Steps to be Taken In Case Material is Released or Spilled: Avoid breathing vapors. Remove ignition sources. Soak up liquid with absorbent material and discard.  Waste Disposal: Do not puncture or incinerate containers. Give empty, leaking or full containers to a facility qualified to dispose of pressurized containers.  Handling & Storage Precautions: Do not store where temperatures can exceed 54°C/130°F. |   |   |
| VIII Control Measures  |  | IX Transportation Data  |   |   |
| Read and follow label directions. They are your best guide to using this product effectively, and give necessary safety precautions to protect your health.  |  | DOT Shipping Name - Consumer Commodity DOT Hazard Class - ORM-D   |   |   |

The information and statements herein are believed to be reliable but are not to be construed as warranty or representation for which we assume legal responsibility. Users should undertake sufficient verification and testing to determine the sultability for their own particular purpose of any information or products referred to herein. NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE.