

MATERIAL SAFETY DATA SHEET

DATE OF PRINTING: 7/28/06

SECTION I

MANUFACTURER: GLYPTAL, INC.
305 EASTERN AVE
CHELSEA, MA 02150
TELEPHONE: 617-884-6918
PRODUCT CLASS: BUFF EPOXY PAINT
CODE IDENTIFICATION: 74004
TRADE NAME: GLYPTAL

HMIS 2 3 0

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT BY WEIGHT	ACGIH TLV PPM	mg/cu.m.	OSHA PEL PPM	mg/cu.m.
XYLENE	9.1	100		100	
CAS NUMBER 1330-20-7					
HMIS HEALTH=1 FLAMMABILITY=3 REACTIVITY=0					
XYLOL					
CELLOSOLVE	8.8	5		200	
CAS NUMBER 110-80-5					
HMIS HEALTH=2 FLAMMABILITY=2 REACTIVITY=0					
OXYGENATED HYDROCARBON					
METHYL ISOBUTYL KETONE	8.8	50		50	
CAS NUMBER 108-10-1					
HMIS HEALTH=2 FLAMMABILITY=3 REACTIVITY=0					
KETONE					
ZINC COMPOUND	1.2		15		
CAS NUMBER 7440-66-6					
HMIS HEALTH=1 FLAMMABILITY=0 REACTIVITY=0					
ZINC COMPOUND					
BLACK IRON OXIDE	0.3			15	
CAS NUMBER 1317-61-9					
HMIS HEALTH=0 FLAMMABILITY=1 REACTIVITY=1					
SYNTHETIC IRON OXIDE					
HYDRATED MAGNESIUM SILICATE	5.7	20			
CAS NUMBER 14807-96-6					
HMIS HEALTH=2 FLAMMABILITY=0 REACTIVITY=0					
TALC					
BARYTES	15.2		10	10	
CAS NUMBER 7727-43-7					
HMIS HEALTH= FLAMMABILITY= REACTIVITY=					
BARIUM SULFATE					

N/A MEANS NOT AVAILABLE N/EST MEANS NOT ESTABLISHED

NOT EST. means NOT ESTABLISHED

NOT EST. means NOT ESTABLISHED

N/A MEANS NOT AVAILABLE NOT EST MEANS NOT ESTABLISHED

SECTION III - PHYSICAL DATA

BOILING RANGE: 241.0 TO 284.0 F

VAPOR DENSITY: HEAVIER THAN AIR

EVAPORATION RATE: SLOWER THAN ETHER
PERCENT VOLATILE BY VOLUME: 42.8
WEIGHT PER GALLON: 11.36 POUNDS

VOC (less water): 3.08 LBS/GAL

1
V.O.C.Is determined per EPA Reference method 24 using ASTM procedures D2369
,D1475 and D 3960.

VAPOR PRESSURE: NA

MELTING POINT: NA

SOLUBILITY IN WATER: NEGLIGIBLE

APPEARANCE AND ODOR: BEIGE PAINT

=====

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

OSHA CATEGORY: FLAMMABLE LIQUID

FLASH POINT : 71 F CC-PM

LEL: 1.0

UEL: NA

EXTINGUISHING MEDIA:

Carbon dioxide, dry chemical or foam

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Pressure may build up in closed containers that are exposed to heat.

Solvent vapors are heavier than air and may travel a considerable
distance along the ground to an ignition source and "flash back".

SPECIAL FIRE FIGHTING PROCEDURES:

Water may be ineffective, however, water may be used to cool closed
containers that are exposed to heat. Firefighting personnel should
wear self-contained breathing apparatus.

=====

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: SEE SECTION II

PRIMARY ROUTE(S) OF ENTRY:

Inhalation and skin contact

EFFECTS OF OVEREXPOSURE:

Headache, nausea, dizziness, confusion, irritability.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Respiratory difficulties or preexisting skin sensitization.

CARCINOGENICITY:

None of the components of this product are reported carcinogens in A/C with
OSHA,NTP,IARC and NIOSH.

EMERGENCY FIRST AID PROCEDURES:

INHALATION: Remove to fresh air. Administer artificial respiration
or oxygen if breathing is difficult.

SKIN: Wash affected area with soap and water. Remove and launder
contaminated clothing. Consult a physician if irritation
persists.

EYES: Flush immediately with large amounts of water for at least 15
minutes. Take to a physician for medical treatment.

INGESTION: Call a physician immediately.

Pre-Existing liver and/or kidney disorders may be aggravated by exposure to
xylene.Reports have associated repeated and prolonged occupational overexpo
sure to xylene with permanent brain and nervous system damage.

In laboratory inhalation studies on cellosolve,birth defects,increased feta
l lethality,and delayed fetal development have been observed in offspring o
f female animals exposed during pregnancy,with a threshold response level i

n the range of 150 to 250 ppm concentration in the air.

=====

SECTION VI - REACTIVITY DATA

STABILITY: NORMALLY STABLE

CONDITIONS TO AVOID:

None known

INCOMPATIBILITY (Materials to avoid)

Strong acids and bases

HAZARDOUS DECOMPOSITION PRODUCTS:

BY FIRE: Normal products of incomplete combustion.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID:

None known

=====

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Provide adequate ventilation. Remove all possible ignition sources.

Absorb and dispose using non-sparking tools.

Eliminate all sources of ignition. Evacuate unprotected personnel. Water spray may be used. To contain run-off, cover with an absorbent material and place in containers for proper disposal. Flush area with water to remove residue.

WASTE DISPOSAL METHOD:

Dispose in accordance with local applicable regulations.

Dispose of using an approved incineration process or in accordance with local, state, and federal regulations regarding health and pollution.

=====

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:

In outdoor or open areas use Bureau of Mines approved mechanical filter respirator to remove solid airborne particulates of overspray. Indoors, where ventilation is inadequate, use Bureau of Mines approved chemical-mechanical respirators designed to remove both particulate and vapor.

VENTILATION:

PROTECTIVE GLOVES:

Recommended if skin contact is likely.

EYE PROTECTION:

Chemical splash goggles recommended if potential for splash or eye contact is likely.

OTHER PROTECTIVE EQUIPMENT:

Recommended as needed to avoid contact.

=====

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING OR STORING:

Store in a cool dry place away from heat, sparks and open flame. Keep containers closed and upright to prevent leakage. Outside or detached

storage is preferred. Inside storage should be in a standard flammable liquid storeroom or cabinet. Metal containers should be grounded when transferring material from one container to another. Do not reuse product container for any purpose.

OTHER PRECAUTIONS:

PREPARED BY: TECHNICAL STAFF

REFERENCE DATE: 7/28/06

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON DATA BELIEVED TO BE CORRECT. HOWEVER, NO GUARANTEE OR WARRANTY OF ANY KIND, EXPRESSED OR IMPLIED, IS MADE WITH RESPECT TO THE INFORMATION ABOVE.

TO WHOM IT MAY CONCERN: EFFECTIVE JAN 1, 1989, WE ARE REQUIRED BY SARA TITLE III SECTION 313 OF THE RIGHT TO KNOW LEGISLATION, TO INFORM YOU OF THE PERCENTAGE OF ANY INGREDIENT IN A PRODUCT WHICH IS IN THE 313 LIST OR AS AN LISTING AS A COMPONENT OF A MATERIAL WHICH IS IN A CATEGORY OF CHEMICAL LIST.

PRODUCT: 74004 GLYPTAL

1.2% ZINC COMPOUND (CAS# 7440-66-6)
8.8% CELLOSOLVE (CAS # 110-80-5)
8.8% MIBK(CAS#108-10-1)
9.1% XYLENE (CAS NUMBER 1330-20-7)
15.2% BARIUM COMPOUND (CAS #7727-43-7)

IF YOU WILL MULTIPLY YOUR TOTAL PURCHASES FROM US AS WELL AS FROM OTHER SUPPLIERS BY THE PERCENTAGE OF EACH INGREDIENT FOUND IN EACH PRODUCT AND IF THE TOTAL QUANTITY EXCEEDS THE REPORTABLE QUANTITY FOR THAT INGREDIENT YOU ARE REQUIRED TO FILE FORM R REPORTS.