



Revision Date: 10/12/2006

Issue date: 10/12/2006

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name:	LOCTITE® 592™ PST® PIPE SEALANT WITH PTFE	Item No. :	59231 / IDH No. 209761
Product type:	Anaerobic Sealant	Region:	United States
Company address:	Henkel Corporation 1001 Trout Brook Crossing Rocky Hill, Connecticut 06067	Contact Information:	Telephone: (860) 571-5100 Emergency telephone: (860) 571-5100 Internet: www.loctite.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous components</u>	<u>%</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Bisphenol A fumarate resin 39382-25-7	10-30	None	None	None
Silica,mica 12001-26-2	10-30	3 mg/m ³ TWA	= 20 mppcf TWA	None
Polyglycol dimethacrylate 25852-47-5	10-30	None	None	None
Octanol 111-87-5	10-30	None	None	0.5 ppm, skin TWA, (WEEL)
Polyglycol dioctanoate 18268-70-7	10-30	None	None	None
Poly(tetrafluoroethylene) 9002-84-0	5-10	None	None	AEL (DuPont): 10 mg/m ³ , 8 Hr TWA, total dust; 5mg/m ³ , 8 hr. TWA respirable dust 6 mg/m ³
Silica, amorphous, treated 68909-20-6	1-5	10 mg/m ³ (Inhal)	20mppcf	
Titanium dioxide 13463-67-7	1-5	10 mg/m ³ TWA	15 mg/m ³ TWA total dust	None
Propylene glycol 57-55-6	1-5	None	None	10 mg/m ³ TWA, (WEEL)
Fragrance UNKNOWN	1-5	None	None	None
Silica, quartz 14808-60-7	0.1-1	0.025 mg/m ³ TWA respirable fraction	0.1mg/m ³ TWA (respirable)	None

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state: Paste
Color: White
Odor: Mild

HMIS:

HEALTH: 2*

FLAMMABILITY: 1

PHYSICAL HAZARD: 1

Personal Protection: See Section 8

WARNING: CAUSES EYE IRRITATION.
MAY CAUSE ALLERGIC SKIN REACTION.
MAY CAUSE RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: May cause respiratory tract irritation. Vapors may cause headaches, nausea, dizziness and respiratory tract irritation. May cause symptoms of intoxication.
Skin contact: May cause allergic skin reaction. May cause skin irritation with discomfort or rash.
Eye contact: Contact with eyes will cause irritation.
Ingestion: Not expected to be harmful by ingestion.

Existing conditions aggravated by exposure: Eye, skin, and respiratory disorders.

See Section 11 for additional toxicological information.

4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If symptoms develop and persist, get medical attention.
Skin contact: Wash with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if symptoms occur.
Eye contact: Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time. Get medical attention.
Ingestion: Do not induce vomiting. Keep individual calm. Obtain medical attention.

5. FIRE-FIGHTING MEASURES

Flash point: Greater than 93°C (200°F) Tagliabue closed cup
Autoignition temperature: Not available
Flammable/Explosive limits-lower %: Not available
Flammable/Explosive limits-upper %: Not available
Extinguishing media: Foam, dry chemical or carbon dioxide.
Special fire fighting procedures: None
Unusual fire or explosion hazards: None
Hazardous combustion products: Oxides of carbon. Toxic fluorine compounds. Irritating organic vapors.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions: Prevent product from entering drains or open waters.
Clean-up methods: Soak up with inert absorbent. Store in a partly filled, closed container until disposal.

7. HANDLING AND STORAGE

Handling:	Avoid contact with eyes, skin and clothing. Use only with adequate ventilation.
Storage:	For safe storage, store at or below 38°C (100°F).
Incompatible products:	Refer to Section 10.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls:	No specific ventilation requirements noted, but forced ventilation may still be required if concentrations exceed occupational exposure limits.
Respiratory protection:	Use a NIOSH approved air purifying respirator with an organic vapor cartridge if the potential to exceed established exposure limits exists.
Skin protection:	Use impermeable gloves and protective clothing as necessary to prevent skin contact. Neoprene, Butyl-rubber, or nitrile-rubber gloves.
Eye/face protection:	Safety goggles or safety glasses with side shields.

See Section 2 for exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	White
Odor:	Mild
Vapor pressure:	Less than 10 mm Hg at 27°C (80°F)
pH:	Not applicable
Boiling point/range:	Greater than 149°C (300°F)
Melting point/range:	Not available
Specific gravity:	1.21
Vapor density:	Not available
Evaporation rate:	Not available
Solubility in water:	Slight
Partition coefficient (n-octanol/water):	Not available
VOC content:	0.719%; 6.8632 grams/liter

10. STABILITY AND REACTIVITY

Stability:	Stable.
Hazardous polymerization:	Will not occur.
Hazardous decomposition products:	Oxides of carbon. Toxic fluorine compounds. Irritating organic vapors.
Incompatibility:	Strong oxidizers.
Conditions to avoid:	See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

11. TOXICOLOGICAL INFORMATION

Product toxicity data:	Acute oral LD50 greater than 10,000 mg/kg (rat). Acute dermal LD50 greater than 5000 mg/kg (rabbit).
-------------------------------	--

Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Bisphenol A fumarate resin 39382-25-7	No	No	No
Silica,mica 12001-26-2	No	No	No
Polyglycol dimethacrylate 25852-47-5	No	No	No
Octanol 111-87-5	No	No	No
Polyglycol dioctanoate 18268-70-7	No	No	No
Poly(tetrafluoroethylene) 9002-84-0	No	No	No
Silica, amorphous, treated 68909-20-6	No	No	No
Titanium dioxide 13463-67-7	No	Group 2B	Yes
Propylene glycol 57-55-6	No	No	No
Fragrance UNKNOWN	No	No	No
Silica, quartz 14808-60-7	Known Carcinogen	Group 1	Yes

Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Bisphenol A fumarate resin 39382-25-7	Allergen, Irritant
Silica,mica 12001-26-2	Lung
Polyglycol dimethacrylate 25852-47-5	Allergen, Irritant
Octanol 111-87-5	Central nervous system, Irritant
Polyglycol dioctanoate 18268-70-7	Irritant
Poly(tetrafluoroethylene) 9002-84-0	No Target Organs
Silica, amorphous, treated 68909-20-6	No Target Organs
Titanium dioxide 13463-67-7	Irritant, Respiratory
Propylene glycol 57-55-6	Irritant
Fragrance UNKNOWN	No data
Silica, quartz 14808-60-7	Some evidence of carcinogenicity, Lung, Immune system

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

EPA hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name: Unrestricted
Hazard class or division: None
Identification number: None

Item No. : 59231 / IDH No. 209761

Product name: LOCTITE® 592™ PST® PIPE SEALANT WITH PTFE

Packing group: None

International Air Transportation (ICAO/IATA):

Proper shipping name: Unrestricted
Hazard class or division: None
Identification number: None
Packing group: None

WaterTransportation (IMO/IMDG):

Proper shipping name: Unrestricted
Hazard class or division: None
Identification number: None
Packing group: None
Marine pollutant: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification: 4-Methoxyphenol (150-76-5).

CERCLA/SARA Section 302 EHS: None above reporting de minimus.
CERCLA/SARA Section 311/312: Immediate Health Hazard, Delayed Health Hazard
CERCLA/SARA 313: None above reporting de minimus.

California Proposition 65: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Domestic Substances List.
WHMIS hazard class: D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 8

Prepared by: Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.