

11/30/2006 12:19 FAX

IDEAL

016/024

## MATERIAL SAFETY DATA SHEET

C15644  
01 00MANUFACTURER'S NAME  
IDEAL INDUSTRIES, INC  
Becker Place  
Sycamore, IL 60178EMERGENCY TELEPHONE NO.  
(815) 895-5181DATE OF PREPARATION  
17-DEC-93 Reviewed 10-28-96INFORMATION TELEPHONE NO.  
(815) 895-5181

## Section I -- PRODUCT IDENTIFICATION

PRODUCT NUMBER \* - Trade Mark  
C15644  
PRODUCT NAME  
40-695 HAND CLEANER  
PRODUCT CLASS  
Aerosol Cleaner

## Section II -- HAZARDOUS INGREDIENTS

INGREDIENT CAS No.	% by WT	ACGIH TLV	OSHA PEL	UNITS	V.P.
Propane 74-98-6	2		1000	PPM	760.00
2-Methylpropane 75-28-5	8	Not Established			760.00
Paraffin Oil 8012-95-1	2	Not Established			0.00

## Section III -- PHYSICAL DATA

PRODUCT WEIGHT -- 7.83 lb./gal. EVAPORATION RATE -- Faster than Ether  
SPECIFIC GRAVITY -- 0.94 VAPOR DENSITY -- Heavier than Air  
BOILING POINT -- <0 -601 F MELTING POINT -- N.A.  
VOLATILE VOLUME -- 85 % SOLUBILITY IN WATER -- N.A.  
VOLATILE WEIGHT -- 10.20 % (less Federally Exempt Solvents)  
HMIS -- 3 2 0

## Section IV -- FIRE AND EXPLOSION HAZARD DATA

FLASH POINT LEL UEL  
184 F TCC 1.8 9.5

## EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Alcohol Foam

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

## SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Continued on page 2

C15644

page 2

Section V -- HEALTH HAZARD DATA

ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

ACUTE Health Hazards

EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

EMERGENCY AND FIRST AID PROCEDURES

If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

If on SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.

If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

If SWALLOWED: Get medical attention.

CHRONIC Health Hazards

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Section VI -- REACTIVITY DATA

STABILITY -- Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

Section VII -- SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Continued on page 3

C15644

page 3

=====

Section VIII -- PROTECTION INFORMATION

-----

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II.

PROTECTIVE GLOVES

None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

EYE PROTECTION

Wear safety spectacles with unperforated side shields.

=====

Section IX -- PRECAUTIONS

-----

DOL STORAGE CATEGORY

A

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep away from heat and open flame.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.