

(APPROVED BY U. S. DEPARTMENT OF LABOR ESSENTIALLY SIMILAR TO FORM OSHA-20)

(PAGE 1 OF 3)

LAB NO. : 33755

* 40 * 1000 * * NONE* 00075-71-E

55 +/- 3 PSIG

WEIGHT PER
GALLON: N. A.

CUSTOMER NO: 06255 NAME: IDEAL INDUSTRIES

LAB NO. 33755 161

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

(PAGE 2 OF 3)

DOT CATEGORY: CONSUMER COMMODITY FLASH POINT: NONE

ORM-D-AIR

LEL: SEE
SECTION II

SMOTHERING MEDIA: NOT APPLICABLE

UNUSUAL FIRE AND

EXPLOSION HAZARDS: KEEP AT ROOM TEMPERATURE AS EXPOSURE TO DIRECT SUNLIGHT OR
OTHER HEAT MAY CAUSE BURSTING (SEE, SECTION VI, IX).

SPECIAL FIRE FIGHTING

PROCEDURES: WATER MAY BE INEFFECTIVE - WATER MAY BE USED TO KEEP FIRE
EXPOSED CONTAINERS COOL.

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE. (SEE SECTION II HAZARDOUS INGREDIENTS)

EFFECTS OF OVEREXPOSURE: IN A CONFINED AREA VAPORS IN HIGH CONCENTRATION ARE
ANESTHETIC. IRRITANT TO SKIN AND UPPER RESPIRATORY SYSTEM. OVER-EXPOSURE MAY
RESULT IN LIGHT-HEADEDNESS, STAGGERING GAIT, GIDDINESS AND POSSIBLE NAUSEA.
HARMFUL OR FATAL IF SWALLOWED

CHRONIC: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED
OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND
NERVOUS SYSTEM DAMAGE.

EMERGENCY AND FIRST AID PROCEDURES:

BREATHING: REMOVE PATIENT TO FRESH AIR.

EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES.

SKIN: WASH WITH SOAP AND WATER.

SWALLOWING: CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

SECTION VI - REACTIVITY DATA

STABILITY: STABLE CONDITIONS TO AVOID: DO NOT STORE ABOVE 120 F

INCOMPATIBILITY (MATERIALS TO AVOID):

HAZARDOUS DECOMPOSITION PRODUCTS BY OPEN FLAME: NONFLAMMABLE - HOWEVER IF
SPRAYED INTO OPEN FLAME, FUMES MAY CONTAIN
TOXIC FUMES OF CHLORIDES AND FLUORIDES.
HYDROGEN CHLORIDE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
CONDITIONS TO AVOID

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

VENTILATE AREA - ESPECIALLY LOW PLACES WHERE VAPORS WILL COLLECT.

AVOID BREATHING OF VAPORS AND REMOVE WITH INERT ABSORBENT

WASTE DISPOSAL METHOD:

DO NOT INCINERATE - DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND
LOCAL REGULATIONS REGARDING POLLUTION

CUSTOMER NO. 06255

NAME: IDEAL INDUSTRIES

LAB NO.: 33755

161

SECTION VIII - SPECIAL PROTECTION INFORMATION

(PAGE 3 OF 3)

RESPIRATORY PROTECTION: AVOID BREATHING OF VAPOR OR SPRAY MIST

VENTILATION: PROVIDE LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP TLV OF MOST HAZARDOUS INGREDIENTS IN SECTION II BELOW ACCEPTABLE LIMIT, AND LEL IN SECTION IV BELOW STATED LIMIT.

PROTECTIVE GLOVES: RECOMMENDED FOR PROLONGED OR REPEATED CONTACT.

EYE PROTECTION: FOR PROLONGED USE IN CLOSE QUARTERS RECOMMEND SAFETY GLASSES WITH UNPERFORATED SIDESHIELDS.

OTHER PROTECTIVE EQUIPMENT:

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

DO NOT STORE ABOVE 120 F. KEEP AT ROOM TEMPERATURE AS EXPOSURE TO DIRECT SUNLIGHT OR HEAT MAY CAUSE BURSTING

OTHER PRECAUTIONS: KEEP AWAY FROM CHILDREN.

DO NOT PUNCTURE OR INCINERATE.

DO NOT SPRAY NEAR FIRE OR OPEN FLAME.

SECTION X HAZARDOUS MATERIAL IDENTIFICATION

COMMUNICATION OF PHYSICAL PROPERTY, HEALTH, AND SAFETY INFORMATION IS A KEY FACTOR IN OUR PRODUCT SAFETY PROGRAM. WITH THIS INFORMATION YOU CAN BETTER FULFILL YOUR OBLIGATION TO EDUCATE EXPOSED PERSONNEL IN THE PROPER HANDLING TECHNIQUES REQUIRED TO MAINTAIN SAFETY IN THE WORKPLACE LISTED IN THIS SECTION IS NPCA-HMIS CLASSIFICATION FOR THIS PRODUCT.

HMIS CLASSIFICATION CODE

HEALTH:	1
FLAMMABILITY:	0
REACTIVITY:	0
PERSONAL PROTECTION:	0

THE ABOVE INFORMATION PERTAINS TO THIS PRODUCT AS CURRENTLY FORMULATED, AND IS BASED ON THE INFORMATION AVAILABLE AT THIS TIME. ADDITION OF REDUCERS OR OTHER ADDITIVES TO THIS PRODUCT MAY SUBSTANTIALLY ALTER THE COMPOSITION AND HAZARDS OF THE PRODUCT. SINCE CONDITIONS OF USE ARE OUTSIDE OUR CONTROL, WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUME NO LIABILITY IN CONNECTION WITH ANY USE OF THIS INFORMATION.