MSDS No: SOL140E5 Issue Date: 15 July 2005 Page: 1 of 4

MATERIAL SAFETY DATA SHEET

SECTION 1	PRODUCT AND COMPANY IDENTIFICATION		
Trade Name:	OATEY ROSIN CORE SOLDER		
Product Use:	General purpose solder		
Formula:	See Section 2		
Synonyms:	Leaded solder		
Firm Name &	OATEY CO. 4700 West 160th Street P.O. Box 35906 Cleveland,		
Mailing Address:	Ohio 44135, U.S.A. http://www.oatey.com		
Oatey Phone Number:	(216) 267-7100 or (800) 321-9532		
Emergency Phone	For Emergency First Aid call 1-303-623-5716 COLLECT. For		
Numbers:	chemical transportation emergencies ONLY, call Chemtrec at		
	1-800-424-9300. Outside the U.S. 1-703-527-3887.		
Prepared By:	Corporate Director - Safety and Environmental Compliance		
Preparation Date:	July 15, 2005		

SECTION 2	COMPOSITION/IN	FORMATION ON	INGREDIENTS	
INGREDIENTS:	<pre>% wt/wt:</pre>	CAS NUMBER:	ACGIH TLV TWA:	OSHA PEL TWA:
Tin	30% - 60%	7440-31-5	2 mg/m3	2 mg/m3
Lead	30% - 60%	7439-92-1	0.05 mg/m3	0.05 mg/m3
Rosin Flux	< 1%	Unknown	None	None
			Established	Established

SECTION 3 HAZARDS IDENTIFICATION

Emergency Overview:

Silver-gray wire metal. The fumes may be hazardous during soldering operations. Fumes can cause eye irritation and may cause headache and respiratory system irritation. Chronic inhalation of heated lead fumes causes brain, liver, or kidney damage. Lead is a reproductive toxin and a possible cancer hazard. Ingestion of metal alloys may be harmful.

OSHA Hazard Classification:	Harmful if swallowed or inhaled.	Organ effects.
	Fumes may be irritating.	

SECTION 4	FIRST AID MEASURES
	CALL 1-303-623-5716 COLLECT
Skin:	If irritation arises, wash thoroughly with soap and water. Seek medical
	attention if irritation persists.
Eyes:	If material gets into eyes, immediately flush eyes with water while
	holding eyelids open until material is removed. If irritation
	persists, seek medical attention.
Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not
	breathing, give artificial respiration. Keep victim quiet and warm. Call
	a poison control center or physician immediately.
Ingestion:	DO NOT INDUCE VOMITING. Ingestion is not a likely route of entry. Never

Ingestion: DO NOT INDUCE VOMITING. Ingestion is not a likely route of entry. Never give anything by mouth to a person who is unconscious or drowsy. Get medical attention by calling a Poison Control Center, or hospital emergency room.

MSDS No: SOL140E5 Issue Date: 15 July 2005 Page: 2 of 4

SECTION 5	F	IRE FIGHTING MEASURES			
Flashpoint /	Method:	Not applicable			
Flammability	: I	.EL = Not applicable, UEL = Not applicable			
Extinguishing	g t	Jse appropriate means of extinguishing surrounding fire.			
Media:					
Special Fire					
Fighting	1	Not applicable			
Procedure:					
Unusual Fire					
Explosion	1	None known			
Hazards:					
Hazardous		Material will not decompose under normal conditions. If			
Decomposition	1 0	overheated, oxides of tin and lead may result.			
Products:					
SECTION 6	Δ	CCIDENTAL RELEASE MEASURES			
Spill or		solid and place in properly labeled containers for recycle			
Leak	or dispo				
Procedures:	or arefe				
SECTION 7	н	ANDLING AND STORAGE			
Handling:	Avoid ir	halation of fumes and vapors. Keep away from children.			
		proughly after handling before eating, drinking, or smoking.			
Storage:	Store in	n a cool, dry place away from heat or open flame.			
Other:	None.				
	_				
SECTION 8		XPOSURE CONTROLS/PERSONAL PROTECTION			
Ventilation:		eneral ventilation (equivalent to outdoors) should be adequate			
		mal use. For operations where the TLV may be exceeded,			
		cal ventilation such as local exhaust may be needed to maintain ce levels below applicable limits.			
Respiratory		erations where the TLV may be exceeded, a NIOSH approved			
Protection:		ator or supplied air respirator is recommended. Equipment			
11000001011		on depends on contaminant type and concentration, select in			
		ance with 29 CFR 1910.134 and good industrial hygiene practice.			
Skin		loves and long sleeves to avoid direct contact with skin.			
Protection:	_				
Еуе	Safety	glasses with sideshields or safety goggles.			
Protection:					
Other:	Eye was	sh and safety shower should be available.			
	_				
SECTION 9		HYSICAL AND CHEMICAL PROPERTIES Not determined			
Boiling Point Melting Point		361 to 421 Degrees F (183 to 216 Degrees C)			
Vapor Pressui		Not determined			
Vapor Density:		(Air = 1) Greater than 1			
Volatile Components:					
Solubility In Water:					
pH:		Not applicable			
Specific Gravity:		9 to 11.5			
Evaporation Rate:		Not applicable			
Appearance:		Silver-gray wire metal			
Odor:		None			
Will Dissolve	e In:	Not applicable			
Material Is:		Solid			

MSDS No: SOL140E5 Issue Date: 15 July 2005 Page: 3 of 4

SECTION 10	STABILITY AND REACTIVITY		
Stability:	Stable.		
Conditions To Avo Hazardous			
Decomposition Products:	If overheated, oxides of tin and lead.		
Incompatibility/ Materials To Avoi	Strong acids and strong oxidizing agents. d:		
Hazardous Polymerization:	Will not occur.		
SECTION 11	TOXICOLOGICAL INFORMATION		
Inhalation:	Fumes from soldering operations may be irritating to the		
	respiratory system. Prolonged exposure to fumes may cause		
	stannosis, a mild benign pneumoconiosis. Repeated inhalation of		
	fumes may cause occupational asthma. Symptoms may be delayed.		
Skin:	Fumes may cause irritation.		
Eye:	Fumes may cause irritation.		
Ingestion:	Ingestion may cause abdominal pain, nausea, vomiting, diarrhea, gastrointestinitis, or internal cuts.		
Toxicity Data:	a: No data available		
Sensitization:	None of the components are known to cause sensitization.		
Carcinogenicity:	Lead is listed as an IARC Group 2B carcinogen (possibly carcinogenic to humans). This classification is based primarily on the carcinogenicity of certain soluble lead salts in lab animals. Neither lead nor its insoluble salts appear to be carcinogenic to humans or lab animals. ACGIH has classified lead as an A3 carcinogen, Confirmed Animal Carcinogen with Unknown Relevance to Humans.		
Mutagenicity: Reproductive Toxicity: Medical Conditions Aggravated By	None of the components have been found to be mutagenic. Lead causes reproductive harm in males and females. It exhibits embryotoxicity in animals. Persons with pre-existing skin, lung, kidney or liver disorders may be at increased risk from exposure to the fumes of this product.		
Exposure:			

SECTION 12 ECOLOGICAL INFORMATION No data available. Keep out of waterways.

SECTION 13 DISPOSAL CONSIDERATIONS

EPA Hazard Waste Class: Toxic waste

MSDS No: SOL140E5 Issue Date: 15 July 2005 Page: 4 of 4

SECTION DOT	14	TRANSPORT	INFORMATION
	Shipping Na	ame:	Not regulated unless containing more than 10 lbs lead, then: Environmentally Hazardous Substance, Solid, n.o.s (contains lead)
UN/NA 1		ng Group:	Class 9 UN3077
IMDG	Labels:		9 - Miscellaneous
-	Shipping Na Class/Packi per:		Not regulated None None
Label:			None
		-	
			Response Guidebook Number: 171
SECTION	-		INFORMATION CONTRACTOR
Hazard (311/312:		Section	Acute and chronic health hazards.
	302 Extreme us Substance	-	This product does not contain chemicals regulated under SARA Section 302.
Section	313 Toxic C	Chemicals:	This product contains the following chemicals
			subject to SARA Title III Section 313 Reporting
			requirements:
			Chemical CAS # % wt Lead 7439-92-1 30 - 60%
			Lead 7439-92-1 30 - 60%
	103 Reportab	ole	This product contains the following chemical subject
Quantity	<u>/</u> :		to CERCLA reporting:
			<u>Chemical</u> <u>RQ, lbs.</u> Lead <u>10</u>
Califorr	nia Proposit	ion 65:	Lead is listed by the state of California as known to
	-		cause cancer and birth defects, or other reproductive
			harm. If this product is further manufactured,
			processed or repackaged, notification must be clearly communicated for occupational exposure through MSDS's
			and labels and for consumers by a conspicuous label
			or in-store display.
TSCA Inv	ventory:		All of the components of this product are listed on the TSCA inventory.
Canadiar	n WHMIS Clas	sification	
			This product has been classified in accordance with
			the hazard criteria of the Controlled Products
			Regulations (CPR) and the MSDS contains all the
			information required by the CPR.

SECTION 16 OTHER INFORMATION NFPA and HMIS: NFPA Hazard Signal: Health: 1 Flammability: 0 Reactivity: 0 Special: None HMIS Hazard Signal: Health: 1 Flammability: 0 Reactivity: 0 PPE: B

DISCLAIMER

The information herein has been compiled from sources believed to be reliable, upto-date, and is accurate to the best of our knowledge. However, Oatey cannot give any guarantees regarding information from other sources, and expressly does not make warranties, nor assumes any liability for its use.