## MATERIAL SAFETY DATA SHEET THE CORTEC CORPORATION 4119 WHITE BEAR PARKWAY

ST. PAUL, MINNESOTA 55110 PHONE: 612-429-1100 OR TOLL FREE 1-800-4-CORTEC

FAX: 612-429-1122

EMERGENCY PHONE NO.: CHEMTREC (FOR SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT): 1-800-424-9300 (DAY OR

\* \* \* \* \* \* \* \* \* VCI-110 Emitter (AHCI10E) \* \* \* \* \*

SECTION I - PRODUCT IDENTIFICATION PRODUCT NAME: VCI-110 EMITTER

PRODUCT DESCRIPTION: An adhesive-backed polyurethane foam with a proprietary corrosion inhibitor.

## SECTION II - HAZARDOUS INGREDIENTS OF POWDER

INGREDIENT NAME(S)	WEIGHT	OCCUPATIONAL EXPOSURE LIMITS	
	PERCENT		
		TLV OR PEL	ORAL LD-50
Trade Secret	-	10 mg/m <sup>3</sup>	
		(as	
		nuisance	N.E.
		dust)	
Trade Secret	3.5%	10 mg/m³	
		(ACGIH)	
		15 mg.m³	
		(OSHA)	560 mg/kg-rat
		(as	
		nuisance	
		dust)	

Carcinogenic: OSHA = no NTP = no IARC = no

SECTION III - PHYSICAL DATA

COLOR: Yellow PHYSICAL FORM: Open cell foam ODOR: Slight NON-VOLATILE (weight): N.A. pH: N.A. VAPOR DENSITY: N.E.

MELTING RANGE: N.A. VAPOR PRESSURE: N.E. BOILING RANGE: N.E. EVAPORATION RATE: N.E.

DENSITY: N.A.

SECTION IV - FIRE AND EXPLOSION DATA HMIS FLAMMABILITY RATING: 1

FLASH POINT: N.E.

FLAMMABLE LIMITS: LEL: N.E. UEL: N.E.

EXTINGUISHING MEDIA: Water, carbon dioxide or other dry chemical fire fighting agents.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Polyurethane foam burns very rapidly forming thick smoke and possible toxic decomposition products.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should wear self-contained breathing apparatus.

## SECTION V - HEALTH HAZARD DATA EMERGENCY AND FIRST AID PROCEDURES:

Eye Contact: Flush eyes with water for at least 15 minutes. Consult a physician. Skin Contact: Wash affected area with soap and water. If irritation persists, consult a physician. Inhalation: Remove to an uncontaminated area; administer oxygen if necessary. If victim has stopped breathing begin CPR. Get medical attention. Ingestion: If swallowed, give water or milk and induce vomiting. Get immediate medical attention. MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: None known

PRIMARY ROUTES OF ENTRY: Skin contact

HEALTH HAZARDS (acute and chronic) / EFFECTS OF OVEREXPOSURE:

- 1. Eye contact with this product may produce irritation.
- 2. Repeated or prolonged contact may cause mild skin irritation.
- 3. Inhalation of product vapors is not expected to pose a significant health hazard due to the low vapor pressure of the product.
- 4. Ingestion of this product may be harmful

## SECTION VI - REACTIVITY DATA

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur. HAZARDOUS DECOMPOSITION PRODUCTS (Under fire conditions): Burning polyurethane foams produce toxic decomposition products that are not significantly different from those of other nitrogen-containing polymer such as wool leather, nylon, and ABS. The major toxicants are carbon monoxide, oxides of nitrogen, hydrogen cyanide. INCOMPATIBILITY: Strong acids, alkalis and oxidizing

CONDITIONS TO AVOID: Contact with incompatible materials.

SECTION VII - SPILL OR LEAK PROCEDURES STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Collect as normal solid waste. WASTE DISPOSAL: Dispose of in accordance with existing Federal, State and Local environmental regulations.

SECTION VIII - SAFE HANDLING AND USE INFORMATION RESPIRATORY PROTECTION: N.A. PROTECTIVE GLOVES: Not required. EYE PROTECTION: Not required.

OTHER PROTECTIVE EQUIPMENT: N.A.

SECTION IX - SPECIAL PRECAUTIONS AND STORAGE DATA

PRECAUTIONS TO BE TAKEN IN HANDLING:

Avoid eye contact and prolonged or repeated skin contact. Workers should thoroughly wash hands with soap and water prior to eating, drinking, smoking and using lavatory.

PRECAUTIONS TO BE TAKEN IN STORING: Keep storage containers tightly closed. Store in a cool dry place. Store away from foodstuffs

SECTION X - SHIPPING DATA

DOT/IMDG/IATA SHIPPING NAME: N.A.

U.N. / N.A. NUMBER: N.A.

DOT/IMDG/IATA HAZARD CLASS.: N.A.

T.S.C.A. STATUS: Listed

DOT/IMDG/IATA REQUIRED LABELS: N.A.

TECHNICAL SHIPPING NAME: N.A.

FREIGHT CLASS BULK: Same as above

LTL: 70 TL: 40 MW: 30

PREPARED BY: Margarita Kharshan, R&D Manager

APPROVED BY: Boris Miksic, President

DATE PREPARED: 9/21/98 SUPERSEDES: 1/22/97 DISCLAIMER: This information is furnished without

warranty, expressed or implied, except that it is accurate to the best knowledge of the Cortec Corporation. The data on this sheet relates only to the specific material designated herein. The Cortec Corporation assumes no legal responsibility for use or reliance upon this data.

N.E. = NOT ESTABLISHED N.A. = NOT APPLICABLE

AHCI10E 10/27/03