	Section 1	PRODUCT AND	COMPANY	IDENTIFI	CATION	
PRODUCT N	JMBER	DATE OF	PREPARA	ATION	HMIS CODES	
S00708		10-	-FEB-08		Health Flammability Reactivity	2 4 0
PRODUCT NA SPRAYOI	AME N® Q.T.L. Dry	Lube				Ū
THE SHI Consume	RER'S NAME ERWIN-WILLIAM er Group - In and, OH 44115					
Product (80) Regulat (21) Medica	NUMBERS and t Information 0) 251-2486 tory Informat 6) 566-2902 l Emergency	ion	intdocs	COM		
Transpo	6) 566-2917 ortation Emer 0) 424-9300				ency ONLY (spill, accident)	leak,
% by WT	Section 2 CAS No.	COMPOSITION/I	INFORMAT	ION ON I UNITS		ESSURE
19	74-98-6	ACGIH TI	LV 250 EL 100			760 mm
18	106-97-8	Butane ACGIH TI OSHA PI	LV 8(EL 8(760 mm
48	142-82-5	Heptane ACGIH TI ACGIH TI OSHA PI OSHA PI	LV 50 EL 40	0 ppm S 0 ppm		50 mm
2	108-88-3	Toluene ACGIH TI OSHA PI		20 ppm 00 ppm (22 mm
12	67-63-0	2-Propanol ACGIH TI ACGIH TI	LV 20	00 ppm 00 ppm S		33 mm

Section 3 -- HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.

EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE

EYES: Irritation.

SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system.

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver, urinary, cardiovascular and reproductive systems.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

Section 4 -- FIRST AID MEASURES

EYES:	Flush eyes with large amounts of water for 15 minutes.
	Get medical attention.
SKIN:	Wash affected area thoroughly with soap and water.
	Remove contaminated clothing and launder before re-use.
INHALATION:	If affected, remove from exposure. Restore breathing.
	Keep warm and quiet.
INGESTION:	Do not induce vomiting.
	Get medical attention immediately.

Section 5 -- FIRE FIGHTING MEASURES

FLASH POINTLELUELPropellant < 0 F</td>1.012.7EXTINGUISHING MEDIAEXTINGUISHING MEDIAInstruction of the second se

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Continued on page 3

S	0	0	7	0	8

page :	3
--------	---

Section 6 ACCIDENTAL RELEASE MEASURES
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Remove all sources of ignition. Ventilate the area. Remove with inert absorbent.
Section 7 HANDLING AND STORAGE
STORAGE CATEGORY Not Available
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE
Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.
During use and until all vapors are gone: Keep area ventilated - Do not
smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves,

electric tools and appliances, and any other sources of ignition. Consult NFPA Code. Use approved Bonding and Grounding procedures. Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take

internally. Keep out of the reach of children.

Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist. Wash hands after using.

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108. RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2. PROTECTIVE GLOVES

None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields. OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

PRODUCT WEIGHT	5.31 lb/gal 636 g/l
SPECIFIC GRAVITY	0.64
BOILING POINT	<0 - 238 F <-18 - 114 C
MELTING POINT	Not Available
VOLATILE VOLUME	99 %
EVAPORATION RATE	Faster than ether
VAPOR DENSITY	Heavier than air
SOLUBILITY IN WATER	N.A.
	(VOC Theoretical - As Packaged)
Volatile Weight 98.41%	Less Water and Federally Exempt Solvents

Section 10 -- STABILITY AND REACTIVITY

STABILITY -- Stable CONDITIONS TO AVOID None known. INCOMPATIBILITY None known. HAZARDOUS DECOMPOSITION PRODUCTS By fire: Carbon Dioxide, Carbon Monoxide HAZARDOUS POLYMERIZATION Will not occur

Section 11 -- TOXICOLOGICAL INFORMATION

CHRONIC HEALTH HAZARDS

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

TOXICOLOGY DATA					
CAS No.	Ingredient N	lame			
74-98-6	Propane				
		LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
106-97-8	Butane				
		LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
142-82-5	Heptane				
		LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
108-88-3	Toluene			_	
		LC50	RAT	4HR	4000 ppm
		LD50	RAT		5000 mg/kg
67-63-0	2-Propanol			4	
		LC50	RAT	4HR	Not Available
		LD50	RAT		5045 mg/kg

Section 12 -- ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION No data available.

Section 13 -- DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

Section 14 -- TRANSPORT INFORMATION

US Ground (DOT)

May be classed as Consumer Commodity, ORM-D UN1950, AEROSOLS, 2.1, LIMITED QUANTITY, (ERG#126)

Canada (TDG)

May be classed as Consumer Commodity, ORM-D UN1950, AEROSOLS, CLASS 2.1, LIMITED QUANTITY, (ERG#126)

IMO

May be shipped as Limited Quantity UN1950, AEROSOLS, CLASS 2.1, LIMITED QUANTITY, EmS F-D, S-U

Section 15 -- REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
108-88-3	Toluene	2	

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

Section 16 -- OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

Continued on page 6

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.