

780555 770

TREMSTOP MP 7.25" x 7.25" x .2" - 12/CSTREMSTOP MP 7.25" x 7.25" x .2" -12/CS

Version 2.

REVISION DATE: 06/10/2010

Print Date 07/16/2010

SECTION 1 - PRODUCT IDENTIFICATION

Trade name

: TREMSTOP MP 7.25" x 7.25" x .2" - 12/CSTREMSTOP MP 7.25" x 7.25" x .2"

- 12/CS

Product code

: 780555 770

COMPANY

: Tremco Incorporated 3735 Green Road Cleveland, OH 44122

Telephone

: (216) 292-5000 8:30 - 5:00 EST : (216) 765-6727 8:30 - 5:00 EST

Emergency Phone:

After Hours: Chemtrec 1-800-424-9300

Product use

: Tape

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

Rust Red. Solid. No serious effects anticipated under normal conditions of use. Generally not required under normal conditions of use.

Acute Potential Health Effects/ Routes of Entry

Inhalation

No serious effects anticipated under normal conditions of use.

Eyes

Not applicable under normal conditions of use. Direct contact may cause temporary

redness and discomfort.

Ingestion

No known adverse effects.

Skin

RPITT Company

No effects anticipated.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %	
Polybutene	9003-29-6	15.0 - 40.0	
Calcium Carbonate (Limestone)	1317-65-3	15.0 - 40.0	
Fire retardant	NJ TSRN# 51721300-5035P	10.0 - 30.0	
Clay	1332-58-7	10.0 - 30.0	
Inert Filler	NJ TSRN# 51721300-5013P	5.0 - 10.0	
Magnesium aluminum silicate	12174-11-7	3.0 - 7.0	
Water	7732-18-5	3.0 - 7.0	

1/6



Version 2. Print Date 07/16/2010

REVISION DATE: 06/10/2010

 Amine phosphate
 NJ TSRN# 51721300-5352P
 3.0 - 7.0

 1,3-Propanediol, 2,2,bis (hydroxymethyl) 115-77-5
 1.0 - 5.0

 Zinc borate
 1332-07-6
 1.0 - 5.0

 Crystalline Silica (Quartz)/ Silica Sand
 14808-60-7
 0.1 - 1.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation : Generally not required under normal conditions of use.

Eye contact : Generally not required under normal conditions of use.

Skin contact : Wash area of contact thoroughly with hand cleaner followed by soap and water. If

irritation, rash or other disorders develop, get medical attention immediately.

Ingestion : Get medical attention. Do not induce vomiting.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point : Not available. Method : Not applicable.

Burning rate : Non-flammable solid

Lower explosion limit : Not available.

Upper explosion limit : Not available.

Autoignition temperature : Not available.

Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.

Hazardous combustion

products

Smoke, fumes.Carbon monoxide and carbon dioxide can form.

Protective equipment for

firefighters

Use accepted fire fighting techniques. Wear full firefighting protective

clothing, including self-contained breathing apparatus (SCBA).

Fire and explosion conditions : This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Transfer to appropriate container for disposal.

SECTION 7 - HANDLING AND STORAGE

Handle in compliance with common hygienic practices. Clean hands thoroughly after handling. Store under dry warehouse conditions away from heat and all ignition sources.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

An **P2TT** company 2/6 780555 770



Version 2.

REVISION DATE: 06/10/2010

Print Date 07/16/2010

Respiratory protection

: Not required under normal conditions of use.

Hand protection

: Protect hands with impervious gloves.

Eye protection

Generally not required under normal conditions of use. Use safety glasses if

eye contact is likely.

Skin and body protection

: Not required.

Protective measures

Other equipment not normally required. Use professional judgment in the

selection, care, and use.

Engineering measures

Not required under normal conditions of use. Use only in well ventilated areas.

Provide maximum ventilation in enclosed areas.

Exposure Limits

Chemical Name	CAS Number	Regulation	<u>Limit</u>	<u>Form</u>
Calcium Carbonate	1317-65-3	OSHA PEL:	5 mg/m3	Respirable fraction.
(Limestone)		OSHA PEL:	15 mg/m3	Total dust.
, ————————————————————————————————————		ACGIH TWA:	3 mg/m3	Respirable particles.
		ACGIH TWA:	10 mg/m3	Inhalable particles.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
Clay	1332-58-7	ACGIH TWA:	2 mg/m3	Respirable fraction.
•		OSHA PEL:	15 mg/m3	Total dust.
		OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
Inert Filler	NJ TSRN#	ACGIH TWA:	10 mg/m3	
	51721300-5013P	OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
1,3-Propanediol, 2,2,bis	115-77-5	ACGIH TWA:	10 mg/m3	
(hydroxymethyl)-		OSHA PEL:	5 mg/m3	Respirable fraction.
(-,,		OSHA PEL:	15 mg/m3	Total dust.
Crystalline Silica	14808-60-7	OSHA TWA:	0.1 mg/m3	Respirable.
(Quartz)/ Silica Sand		OSHA TWA:	0.3 mg/m3	Total dust.
(OSHA PEL:	15 mg/m3	Total dust.
		OSHA PEL:	5 mg/m3	Respirable fraction.
		ACGIH TWA:	0.025 mg/m3	Respirable fraction.
	1			

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form

: Solid

Color

: Rust Red

Odor

: Negligible

pН

: Not available.

An RPM Company

3/6

780555 770



Version 2. REVISION DATE: 06/10/2010

Print Date 07/16/2010

Vapour pressure

: Not available.

Vapor density

: Heavier than air

Melting point/range

: Not available.

Freezing point

: Not available.

Boiling point/range

: Not available.

Water solubility

: Insoluble

Specific Gravity

: 1.39 at 25 °C

% Volatile Weight

: 4%

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid

: Oxidizing agents.

Stability

: Material is stable under normal storage, handling, and use.

Hazardous polymerization

: Will not occur under normal conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

1,3-Propanediol, 2,2,bis (hydroxymethyl)-, CAS-No.: 115-77-5

Acute oral toxicity (LD-50 oral)

25,500 mg/kg (Mouse) 11,300 mg/kg (Guinea pig)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method

: Waste not regulated under RCRA. Incinerate at EPA approved facility or dispose of

waste in compliance with state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

TDG / DOT Shipping Description:

NOT REGULATED

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

An RPM Company

4/6

780555 770



Version 2.

REVISION DATE: 06/10/2010

Print Date 07/16/2010

SARA 313 Components

: Zinc borate

1332-07-6

SARA 311/312 Hazards

Acute Health Hazard Chronic Health Hazard

OSHA Hazardous Components:

Calcium Carbonate (Limestone)

1317-65-3

Clay

1332-58-7

Inert Filler

NJ TSRN# 51721300-5013P

Magnesium aluminum silicate 1,3-Propanediol, 2,2,bis (hydroxymethyl)-

12174-11-7 115-77-5

Zinc borate

1332-07-6

Crystalline Silica (Quartz)/ Silica Sand

14808-60-7

OSHA Status: Considered

: Irritant

hazardous based on the

Carcinogen

following criteria:

OSHA Flammability

Not Regulated

Regulatory VOC (less water and

: 5 g/l

exempt solvent)

: 0%

VOC Method 310

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen: Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

U.S. State Regulations:

MASS RTK Components

Calcium Carbonate (Limestone)

1317-65-3 1332-58-7

Clay

Inert Filler

NJ TSRN# 51721300-5013P

1,3-Propanediol, 2,2,bis (hydroxymethyl)-Zinc borate

115-77-5 1332-07-6

Formaldehyde

50-00-0

Penn RTK Components

NJ RTK Components

Polybutene

9003-29-6 Calcium Carbonate (Limestone) 1317-65-3

Fire retardant

NJ TSRN# 51721300-5035P

Clay

1332-58-7 NJ TSRN# 51721300-5013P

Inert Filler

12174-11-7

Magnesium aluminum silicate

7732-18-5

Water

NJ TSRN# 51721300-5352P

Amine phosphate 1,3-Propanediol, 2,2,bis (hydroxymethyl)-

115-77-5

1332-07-6

Zinc borate

: Polybutene

9003-29-6

Calcium Carbonate (Limestone)

1317-65-3

Fire retardant

NJ TSRN# 51721300-5035P

Clay

1332-58-7

Inert Filler

NJ TSRN# 51721300-5013P

Crystalline Silica (Quartz)/ Silica Sand Petroleum distillates

4

14808-60-7 64742-47-8

RPM Company

5/6

780555 770



Version 2.

Print Date 07/16/2010

REVISION DATE: 06/10/2010

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

SECTION 16 - OTHER INFORMATION

HMIS Rating:

Health	1
Flammability	0
Reactivity	0
PPE	

0 = Minimum

1 = Slight

2 = Moderate

3 = Serious

4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

DOT - Department of Transportation

DSL - Domestic Substance List

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information

System

