

MATERIAL SAFETY DATA SHEET

pg. 1 of 2

57

United States Gypsum Company
101 S. Wacker Drive, Chicago, IL 60606

Day 312/321-4383
Night 312/321-4382

SECTION I

PRODUCT: Sodate Retarder
DATE ISSUED: March 12, 1986
CHEMICAL FAMILY: Mixture

Killark SC8 03

SECTION II
HAZARDOUS INGREDIENTS

MATERIAL:	%	TLV:	CAS #
None			

SECTION III
PHYSICAL DATA

SOLUBILITY IN WATER: 10%
SPECIFIC GRAVITY (H2O = 1): 2.6
APPEARANCE AND ODOR: White powder, low odor

SECTION IV
FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED): Not combustible
EXTINGUISHING MEDIA: Not combustible
SPECIAL FIRE FIGHTING PROCEDURES: None
UNUSUAL FIRE AND EXPLOSION HAZARDS: None

SECTION V
HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

ACUTE:

EYES: Particles can cause transient irritation.
SKIN: May cause irritation.
INGESTION: Unknown.
INHALATION: Nuisance dust.

CHRONIC:

None known, nuisance dust

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush with water for 15 minutes. If irritation persists, see physician.
SKIN: Wash with soap and water.
INGESTION: See physician.
INHALATION: Remove to fresh air.

PRODUCT NO: 20037

PRODUCT: Sodate Retarder

Page: 212⁰¹
57

SECTION VI
REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY: Temperatures above 2000 ° F.

HAZARDOUS DECOMPOSITION PRODUCTS: SO₂

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION VII
SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Sweep up. Avoid creating excessive dust.

WASTE DISPOSAL METHOD: To sanitary landfill in accordance with federal, state and local regulations.

SECTION VIII
SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: NIOSH approved nuisance respirator if TLV is exceeded.

VENTILATION: Local exhaust if above nuisance dust, TLV.

PROTECTIVE EQUIPMENT: Safety glasses.

SECTION IX
SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in a dry place.