Printing date December 7, 2015

Reviewed on December 7, 2015

1 Identification

- · Product identifier
- · Trade name: Spede-Heat™ Continuous Discharge Chemical Grenade, CN
- · Article number: 1071 (1011565)
- · Recommended use and restriction on use
- · Recommended use: Crowd Control Device
- · Restrictions on use: Contact manufacturer
- Details of the supplier of the Safety Data Sheet
- Manufacturer/Supplier:

Safariland, LLC 13386 International Parkway Jacksonville, FL 32218 Customer Care (800) 347-1200



ChemTel Inc.

+1 (800)255-3924, +1 (813)248-0585



2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Sol. 2 H228 Flammable solid.



GHS06 Skull and crossbones

Acute Tox. 3 H301 Toxic if swallowed.

Acute Tox. 3 H311 Toxic in contact with skin.

Acute Tox. 2 H330 Fatal if inhaled.



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

(Cont'd. on page 2)

Printing date December 7, 2015

Reviewed on December 7, 2015

Trade name: Spede-Heat™ Continuous Discharge Chemical Grenade, CN

(Cont'd. of page 1)

· Additional information:

There are no other hazards not otherwise classified that have been identified.

0 % of the mixture consists of component(s) of unknown toxicity.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms:











GHS02 GHS05 GHS06 GHS07 GHS08

· Signal word: Danger

Hazard-determining components of labeling:

2-chloroacetophenone potassium chlorate

· Hazard statements:

Flammable solid. H228

H301+H311 Toxic if swallowed or in contact with skin.

Fatal if inhaled. H330

H315 Causes skin irritation.

H318 Causes serious eve damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction. H317 May cause respiratory irritation. H335

· Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not breathe dust/fume/gas/mist/vapors/spray. P260

Wear respiratory protection. P284 Wash thoroughly after handling. P264

Wear protective gloves / eye protection / face protection. P280 Do not eat, drink or smoke when using this product. P270 P271 Use only outdoors or in a well-ventilated area.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P320 Specific treatment is urgent (see on this label).

IF ON SKIN: Wash with plenty of water. P302+P352

IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+P340

P330 Rinse mouth.

If experiencing respiratory symptoms: Call a POISON CENTER/doctor. P342+P311

If skin irritation or rash occurs: Get medical advice/attention. P333+P313 P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P361+P364 Take off immediately all contaminated clothing and wash it before reuse.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

(Cont'd. on page 3)

Printing date December 7, 2015

Reviewed on December 7, 2015

Trade name: Spede-Heat™ Continuous Discharge Chemical Grenade, CN

(Cont'd. of page 2)

- · Classification system
- NFPA ratings (scale 0 4)



Health = 3 Fire = 0 Reactivity = 3

The substance possesses oxidizing properties.

· HMIS-ratings (scale 0 - 4)



* - Indicates a long term health hazard from repeated or prolonged exposures.

· Explosive Product Notice

PREVENTION OF ACCIDENTS IN THE USE OF EXPLOSIVES - The prevention of accidents in the use of explosives is a result of careful planning and observance of the best known practices. The explosives user must remember that he is dealing with a powerful force and that various devices and methods have been developed to assist him in directing this force. He should realize that this force, if misdirected, may either kill or injure both him and his fellow workers.

WARNING - All explosives are dangerous and must be carefully handled and used following approved safety procedures either by or under the direction of competent, experienced persons in accordance with all applicable federal, state, and local laws, regulations, or ordinances. If you have any questions or doubts as to how to use any explosive product, DO NOT USE IT before consulting with your supervisor, or the manufacturer, if you do not have a supervisor. If your supervisor has any questions or doubts, he should consult the manufacturer before use.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Product will contain various combinations of the following substances. Not all substances will be in each product.

Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
532-27-4	2-chloroacetophenone Acute Tox. 2, H300; Acute Tox. 2, H310; Acute Tox. 2, H330 Resp. Sens. 1, H334 Eye Dam. 1, H318 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	20-40%
3811-04-9	potassium chlorate Ox. Sol. 1, H271 Acute Tox. 4, H302; Acute Tox. 4, H332	20-40%
9004-70-0	Nitrocellulose, colloided, granular	10-20%
57-50-1	sucrose, pure	10-20%
(Cont'd. on page 4)		

Printing date December 7, 2015

Reviewed on December 7, 2015

Trade name: Spede-Heat™ Continuous Discharge Chemical Grenade, CN

		(Cor	nt'd. of page 3)
7440-21-3 silicon		·	0.1-1.0%
∳ Flan	n. Sol. 2, H228		
557-04-0 magnes	sium distearate, pure		0.1-1.0%
Additional information:			
For the wording of	the listed Hazard Statemer	nts refer to section 16.	
For the listed ingre	dient(s), the identity and ex	cact percentage(s) are being withheld as a trade s	ecret.
· Notable Trace Co	mponents (≤ 0,1% w/w)		
7758-97-6 lead chromate		H373	

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air.

Seek immediate medical advice.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Provide oxygen treatment if affected person has difficulty breathing.

· After skin contact:

Immediately rinse with water.

If skin irritation continues, consult a doctor.

· After eye contact:

Protect unharmed eve.

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Unlikely route of exposure.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

· Information for doctor

· Most important symptoms and effects, both acute and delayed:

Asthma attacks

Blast injury if mishandled.

Dizziness

Irritant to eyes.

Irritant to skin and mucous membranes.

Breathing difficulty

Coughing

Allergic reactions

Disorientation

Danger:

Danger of blast or crush-type injuries.

Danger of pulmonary edema.

Danger of disturbed cardiac rhythm.

(Cont'd. on page 5)

Printing date December 7, 2015

Reviewed on December 7, 2015

Trade name: Spede-Heat™ Continuous Discharge Chemical Grenade, CN

(Cont'd. of page 4)

Danger of convulsion.

Danger of impaired breathing.

Danger of cerebral edema.

· Indication of any immediate medical attention and special treatment needed:

Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible.

If necessary oxygen respiration treatment.

Contains lead chromate.

Later observation for pneumonia and pulmonary edema.

Product may produce physical injury if mishandled. Treatment of these injuries should be based on the blast and compression effects.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:

DO NOT fight fire when fire reaches explosives.

Flood area with water. If no water is available, carbon dioxide, dry chemical or earth may be used. If the fire reaches the cargo, withdraw and let fire burn.

- · For safety reasons unsuitable extinguishing agents: None.
- · Special hazards arising from the substance or mixture

Product may explode if burned in confined space. Individual cartridges may explode. Mass explosion of many cartridges at once is unlikely.

Hazardous combustions products: Metal Compounds, Carbon Monoxide, Carbon Dioxide, Nitrous Oxides, Various complex oxides of metals, Nitrogen.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information:

Evacuate area and fight fire from from the upwind side.

Cool endangered receptacles with water spray.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures:

Use respiratory protective device against the effects of fumes/dust/aerosol.

Isolate area and prevent access.

Keep people at a distance and stay upwind.

Wear protective equipment. Keep unprotected persons away.

Remove persons from danger area.

Ensure adequate ventilation.

Protect from heat.

Keep away from ignition sources.

Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Suppress gases/fumes/haze with water spray.

· Methods and material for containment and cleaning up:

Pick up mechanically.

(Cont'd. on page 6)

Printing date December 7, 2015

Reviewed on December 7, 2015

Trade name: Spede-Heat™ Continuous Discharge Chemical Grenade, CN

(Cont'd. of page 5)

Send for recovery or disposal in suitable receptacles.

Dispose contaminated material as waste according to item 13.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling
- · Precautions for safe handling:

Use only outdoors or in a well-ventilated area.

Handle with care. Avoid jolting, friction and impact.

Keep away from heat and direct sunlight.

· Information about protection against explosions and fires:

Prevent impact and friction.

Keep respiratory protective device available.

Emergency cooling must be available in case of nearby fire.

Protect from heat.

Keep ignition sources away - Do not smoke.

- · Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and receptacles:

Provide ventilation for receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from flammable substances.

Do not store together with oxidizing and acidic materials.

Store away from water.

· Further information about storage conditions:

Protect from heat and direct sunlight.

Store in dry conditions.

Store receptacle in a well ventilated area.

· Specific end use(s): No relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:		
532-27-4 2-chloroacetophenone		
PEL (USA)	Long-term value: 0.3 mg/m³, 0.05 ppm	
REL (USA)	Long-term value: 0.3 mg/m³, 0.05 ppm	

(Cont'd. on page 7)

Printing date December 7, 2015

Reviewed on December 7, 2015

Trade name: Spede-Heat™ Continuous Discharge Chemical Grenade, CN

	(Cont'd. of page 6)
TLV (USA)	Long-term value: 0.32 mg/m³, 0.05 ppm
EL (Canada)	Long-term value: 0.05 ppm S
EV (Canada)	Long-term value: 0.32 mg/m³, 0.05 ppm
LMPE (Mexico)	Long-term value: 0.05 ppm A4
57-50-1 sucros	e, pure
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
TLV (USA)	Long-term value: 10 mg/m³
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction
EV (Canada)	Long-term value: 10 mg/m³ total dust
LMPE (Mexico)	Long-term value: 10 mg/m³ A4
7440-21-3 silico	on
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
TLV (USA)	TLV withdrawn
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction
EV (Canada)	Long-term value: 10 mg/m³ total dust
LMPE (Mexico)	Short-term value: 20 mg/m³ Long-term value: 10 mg/m³ (e)
	esium distearate, pure
TLV (USA)	Long-term value: 10 mg/m³
LMPE (Mexico)	Long-term value: 10 mg/m³ A4

- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Avoid close or long term contact with the skin.

Avoid contact with the eyes.

Do not inhale dust / smoke / mist.

Immediately remove all soiled and contaminated clothing.

(Cont'd. on page 8)

Printing date December 7, 2015

Reviewed on December 7, 2015

Trade name: Spede-Heat™ Continuous Discharge Chemical Grenade, CN

(Cont'd. of page 7)

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

- · Engineering controls: Provide adequate ventilation.
- Breathing equipment:



Combined Organic Vapor and Particulate Respirator is recommended for use during all processing activities.

Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in large quantities.

Respiratory protection required.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Safety glasses

- · Body protection: Protective work clothing
- · Limitation and supervision of exposure into the environment No relevant information available.
- Risk management measures

See Section 7 for additional information.

Organizational measures should be in place for all activities involving this product.

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General information
- · Appearance:

Form: Solid material

Color: Gray

(Cont'd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date December 7, 2015

Reviewed on December 7, 2015

Trade name: Spede-Heat™ Continuous Discharge Chemical Grenade, CN

	(Cont'd. of page 8)
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not applicable.
 Change in condition: Melting point/Melting range: 	Not determined.
Boiling point/Boiling range:	Not determined.
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not determined.
· Auto-ignition temperature:	Not determined.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not self-igniting.
· Danger of explosion:	Extreme risk of explosion by shock, friction, fire or other sources of ignition.
· Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapor pressure:	Not applicable.
 Density: Relative density: Vapor density: Evaporation rate: 	Not determined. Not determined. Not applicable. Not applicable.
· Solubility in / Miscibility with: Water:	Insoluble.
· Partition coefficient (n-octanol/water)	: Not determined.
· Viscosity: Dynamic: Kinematic: · Other information	Not applicable. Not applicable. No relevant information available.

10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability:
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Possibility of hazardous reactions:

Flammable solid.

Contact with acids releases toxic gases.

Toxic fumes may be released if heated above the decomposition point.

Can react violently with oxygen rich (oxidizing) material. Danger of Explosion.

(Cont'd. on page 10)

Printing date December 7, 2015

Reviewed on December 7, 2015

Trade name: Spede-Heat™ Continuous Discharge Chemical Grenade, CN

(Cont'd. of page 9)

Strong exothermic reaction with acids.

Develops toxic gases / fumes.

Conditions to avoid:

Keep ignition sources away - Do not smoke.

Store away from oxidizing agents.

Keep away from heat and direct sunlight.

Cartridge may detonate if case is punctured or severely damaged.

- · Incompatible materials: Contact with acids liberates toxic gas.
- · Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Hydrocarbons

Leadoxide vapor

Bariumoxide vapor

Nitrogen oxides (NOx)

Chlorine compounds

Poisonous gases/vapors

Irritant gases/vapors

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

532-27-4 2-chloroacetophenone

Oral LD50 50 mg/kg (rat)

3811-04-9 potassium chlorate

Oral LD50 1870 mg/kg (rat)

- Primary irritant effect:
- · On the skin: Irritant to skin and mucous membranes.
- · On the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization: May cause sensitisation by inhalation and skin contact.
- · Additional toxicological information: Toxic and/or corrosive effects may be delayed up to 24 hours.
- · Carcinogenic categories
- IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.

Inhalation.

Eye contact.

Skin contact.

(Cont'd. on page 11)

Printing date December 7, 2015

Reviewed on December 7, 2015

Trade name: Spede-Heat™ Continuous Discharge Chemical Grenade, CN

(Cont'd. of page 10)

· Acute effects (acute toxicity, irritation and corrosivity):

Fatal if inhaled.

May cause sensitisation by inhalation and skin contact.

Causes serious eye damage.

Toxic if swallowed or in contact with skin.

May cause respiratory irritation.

· Repeated dose toxicity:

Repeated exposures may result in skin and/or respiratory sensitivity.

May cause damage to organs through prolonged or repeated exposure.

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- Aquatic toxicity:

Toxic for aquatic organisms

The product contains materials that are harmful to the environment.

- · Persistence and degradability: The product is partially biodegradable. Significant residuals remain.
- · Behavior in environmental systems
- · Bioaccumulative potential: May be accumulated in organism
- Mobility in soil: No relevant information available.
- **Ecotoxical effects:**
- · Remark: Toxic for fish
- · Additional ecological information
- · General notes:

This statement was deduced from the properties of the single components.

The product contains heavy metals. Avoid transfer into the environment. Specific preliminary treatments are necessary.

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Other adverse effects: No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Hand over to hazardous waste disposers.

(Cont'd. on page 12)

Printing date December 7, 2015

Reviewed on December 7, 2015

Trade name: Spede-Heat™ Continuous Discharge Chemical Grenade, CN

(Cont'd. of page 11)

(Cont'd. on page 13)

After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- · Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.

4 Transport information	
· UN-Number · DOT, ADR, IMDG, IATA	UN1700
· UN proper shipping name · DOT · ADR · IMDG, IATA	Tear gas candles 1700 TEAR GAS CANDLES TEAR GAS CANDLES
· Transport hazard class(es)	
· DOT	
· Class · Label	6.1 Toxic substances 6.1, 4.1
· ADR	
· Class	6.1 (TF3) Toxic substances
· Label	6.1+4.1
· IMDG	
Class Label	6.1 Toxic substances 6.1/4.1
· IATA	
· Class	6.1 Toxic substances

Printing date December 7, 2015

Reviewed on December 7, 2015

Trade name: Spede-Heat™ Continuous Discharge Chemical Grenade, CN

	(Cont'd. of	page 1
·Label	6.1 (4.1)	
· Packing group · DOT, ADR, IMDG, IATA	II	
· Environmental hazards	Not applicable.	
· Special precautions for user	Warning: Toxic substances	
· Danger code (Kemler): · EMS Number:	- F-A,S-G	
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	Not applicable.	
· Transport/Additional information:		
· ADR · Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity	
· UN "Model Regulation"	UN1700, Tear gas candles, 6.1 (4.1), II	

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 304 (emergency release notification):

None of the ingredients are listed.

· Sections 311/312 (hazardous chemical threshold planning quantity in pounds):

manganese 10000

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

532-27-4 2-chloroacetophenone

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

- Proposition 65 (California)
- · Chemicals known to cause cancer:

Contains trace quantities of substances known to the State of California to cause cancer.

592-87-0	lead dithiocyanate
10294-40-3	barium chromate
7758-97-6	lead chromate

(Cont'd. on page 14)

Printing date December 7, 2015

Reviewed on December 7, 2015

Trade name: Spede-Heat™ Continuous Discharge Chemical Grenade, CN

(Cont'd. of page 13)

· Chemicals known to cause reproductive toxicity for females:

Present in trace quantities.

10294-40-3 barium chromate 7758-97-6 lead chromate

Chemicals known to cause reproductive toxicity for males:

Present in trace quantities.

10294-40-3 barium chromate 7758-97-6 lead chromate

· Chemicals known to cause developmental toxicity:

Present in trace quantities.

10294-40-3 barium chromate 7758-97-6 lead chromate

· Carcinogenic categories

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· Canadian substance listings

Canadian Domestic Substances List (DSL):

All ingredients are listed.

· Canadian Ingredient Disclosure list (limit 0.1%):

None of the ingredients are listed.

· Canadian Ingredient Disclosure list (limit 1%):

532-27-4 2-chloroacetophenone

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision December 7, 2015 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Cont'd. on page 15)

Printing date December 7, 2015

Reviewed on December 7, 2015

Trade name: Spede-Heat™ Continuous Discharge Chemical Grenade, CN

(Cont'd. of page 14)

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Expl. 1.1: Explosives, Division 1.1

Plam. Sol. 2: Flammable solids, Hazard Category 2
Ox. Sol. 1: Oxidising Solids, Hazard Category 1
Acute Tox. 2: Acute toxicity, Hazard Category 2
Acute Tox. 3: Acute toxicity, Hazard Category 3
Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

·Sources

SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com