Printing date December 4, 2015

Revision: December 4, 2015

Article number: 11 1.2 Relevant identi No further relevant Application of the Uses advised agai 1.3 Details of the s Manufacturer/Sup Safariland, LLC 13386 International Jacksonville, FL 32: Customer Care (80) Further informatio 1.4 Emergency tele ChemTel Inc. +1 (800)255-3924, SECTION 2: Ha 2.1 Classification acce	 de-Heat[™] 37mm Long-Range Round, CN 81 (1012229) ified uses of the substance or mixture and uses advised against information available. substance / the mixture: Crowd Control Device inst Contact manufacturer. supplier of the Safety Data Sheet plier: Parkway 218 0) 347-1200 m obtainable from: Customer Care Department ephone number:
Article number: 11 1.2 Relevant identi No further relevant Application of the Uses advised agai 1.3 Details of the s Manufacturer/Sup Safariland, LLC 13386 International Jacksonville, FL 32: Customer Care (80) Further informatio 1.4 Emergency tele ChemTel Inc. +1 (800)255-3924, SECTION 2: Ha 2.1 Classification acce	 81 (1012229) ified uses of the substance or mixture and uses advised against information available. substance / the mixture: Crowd Control Device inst Contact manufacturer. supplier of the Safety Data Sheet plier: Parkway 218 0) 347-1200 on obtainable from: Customer Care Department ephone number: +1 (813)248-0585 zards identification of the substance or mixture
 Uses advised agai 1.3 Details of the s Manufacturer/Sup Safariland, LLC 13386 International Jacksonville, FL 32: Customer Care (80) Further informatio 1.4 Emergency tele ChemTel Inc. +1 (800)255-3924, SECTION 2: Ha 2.1 Classification access 	Anst Contact manufacturer. Supplier of the Safety Data Sheet plier: Parkway 218 0) 347-1200 on obtainable from: Customer Care Department ephone number: +1 (813)248-0585 zards identification of the substance or mixture
 Manufacturer/Sup Safariland, LLC 13386 International Jacksonville, FL 322 Customer Care (800 Further informatio 1.4 Emergency tele ChemTel Inc. +1 (800)255-3924, SECTION 2: Ha 2.1 Classification acce 	plier: Parkway 218 0) 347-1200 on obtainable from: Customer Care Department ephone number: +1 (813)248-0585 zards identification of the substance or mixture
SECTION 2: Ha	zards identification of the substance or mixture
· 2.1 Classification (of the substance or mixture
· Classification acc	
regulation: H412.	ard Statements are applicable only to the EU regulations and not the US G
exploding b	omb
Expl. 1.4	H204 Fire or projection hazard.
skull and cr	ossbones
Acute Tox. 3	H301 Toxic if swallowed.
Acute Tox. 3	H311 Toxic in contact with skin.
Acute Tox. 2	H330 Fatal if inhaled.
health haza	rd
Resp. Sens. 1	H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
corrosion	
Eye Dam. 1	H318 Causes serious eye damage.

Printing date December 4, 2015

Revision: December 4, 2015

	(Cont'd. from page 1)
\wedge	
Skin Irrit. 2	H315 Causes skin irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.
STOT SE 3	H335 May cause respiratory irritation.
	3 H412 Harmful to aquatic life with long lasting effects. rmation: 0 % of the mixture consists of component(s) of unknown toxicity.
· 2.2 Label elem	
	rding to Regulation (EC) No 1272/2008 classified and labelled according to the CLP regulation.
· Hazard pictogr	
nazaru pictogi	
\wedge	\wedge
</th <td></td>	
GHS01 GHS05	GHS06 GHS08
· Signal word Da	anger
•	
	ining components of labelling:
2-chloroacetoph	
potassium chlor	
· Hazard statem	
	Hazard Statements are applicable only to the EU regulations and not the US GHS
regulation: H412 H204 Fire	e or projection hazard.
-	xic if swallowed or in contact with skin.
	tal if inhaled.
	uses skin irritation.
	uses serious eye damage.
	y cause allergy or asthma symptoms or breathing difficulties if inhaled.
	y cause an allergic skin reaction.
	y cause respiratory irritation.
	rmful to aquatic life with long lasting effects.
· Precautionary	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.
P250	Do not subject to grinding/shock/friction.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P284	[In case of inadequate ventilation] wear respiratory protection.
P264	Wash thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P273	Avoid release to the environment.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
	(Cont'd. on page 3)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat[™] 37mm Long-Range Round, CN

(Cont'd. from page 2) P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P373 DO NOT fight fire when fire reaches explosives. P370+P380 In case of fire: Evacuate area. P302+P352 IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+P340 Rinse mouth. P330 P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor. Explosion risk in case of fire. P372 Call a POISON CENTER/doctor if you feel unwell. P312 P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P361+P364 Take off immediately all contaminated clothing and wash it before reuse. P401 Store in accordance with local/regional/national/international regulations. P405 Store locked up. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · Additional information: Can become highly flammable in use. NFPA ratings (scale 0 - 4) Health = 3 Fire = 0Reactivity = 3 · HMIS-ratings (scale 0 - 4) HEALTH 3 Health = 3 • Fire = 0 FIRE REACTIVITY 3 Reactivity = 3 * - Indicates a long term health hazard from repeated or prolonged exposures. 2.3 Other hazards Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable. **Explosive Product Notice** (Cont'd. on page 4)

GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat[™] 37mm Long-Range Round, CN

(Cont'd. from page 3)

PREVENTION OF ACCIDENTS IN THE USE OF EXPLOSIVES - The prevention of accidents in the use of explosives is a result of careful planning and observance of the best known practices. The explosives user must remember that he is dealing with a powerful force and that various devices and methods have been developed to assist him in directing this force. He should realize that this force, if misdirected, may either kill or injure both him and his fellow workers.

WARNING - All explosives are dangerous and must be carefully handled and used following approved safety procedures either by or under the direction of competent, experienced persons in accordance with all applicable federal, state, and local laws, regulations, or ordinances. If you have any questions or doubts as to how to use any explosive product, DO NOT USE IT before consulting with your supervisor, or the manufacturer, if you do not have a supervisor. If your supervisor has any questions or doubts, he should consult the manufacturer before use.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Description:

Mixture of substances listed below with nonhazardous additions.

Product will contain various combinations of the following substances. Not all substances will be in each product.

· Dangerous components:		
CAS: 532-27-4 EINECS: 208-531-1	2-chloroacetophenone Acute Tox. 2, H300; Acute Tox. 3, H311; Acute Tox. 1, H330 Resp. Sens. 1, H334 Eye Dam. 1, H318 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	_ 25-50%
CAS: 3811-04-9 EINECS: 223-289-7 Index number: 017-004-00-3	potassium chlorate Ox. Sol. 1, H271	_ 10-25%
CAS: 57-50-1 EINECS: 200-334-9	sucrose, pure substance with a Community workplace exposure limit	10-25%
CAS: 9004-70-0 EC number: 603-037-0	Nitrocellulose, colloided, granular	_ 10-25%
CAS: 7757-79-1 EINECS: 231-818-8	potassium nitrate Ox. Sol. 2, H272	2,5-10%
CAS: 7440-21-3 EINECS: 231-130-8	silicon	_ ≤ 2,5%
CAS: 557-04-0 EINECS: 209-150-3	magnesium distearate, pure substance with a Community workplace exposure limit	≤ 2,5%
· Additional information: For	the wording of the listed Hazard Statements refer to section 16.	
• Notable Trace Components	s (≤ 0,1% w/w)	
	(Cor	t'd. on page 5)

Printing date December 4, 2015

Revision: December 4, 2015

	(Cont'd. from page 4)
CAS: 122-39-4	diphenylamine
EINECS: 204-539-4 Index number: 612-026-00-5	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 STOT RE 2, H373
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410
CAS: 12403-82-6	dihydroxy[styphnato(2-)]dilead / lead styphnate
EINECS: 235-642-2	Ounst. Expl., H200 Acute Tox. 3, H301; Acute Tox. 2, H330
	Carc. 1B, H350; Repr. 2, H361; STOT RE 2, H373 Aquatic Acute 1, H400; Aquatic Chronic 1, H410

SECTION 4: First aid measures	
4.1 Description of first aid measures	
General information:	
Immediately remove any clothing soiled by the product.	
Take affected persons out into the fresh air.	
Symptoms of poisoning may even occur after several hours; therefore medical obse	rvation for at least 4
hours after the accident.	
After inhalation:	
Supply fresh air.	
Seek immediate medical advice.	
Seek medical help for symptoms or if unconscious.	
Provide oxygen treatment if affected person has difficulty breathing.	
In case of irregular breathing or respiratory arrest provide artificial respiration.	
After skin contact:	
Immediately wash with water and soap and rinse thoroughly.	
Seek immediate medical advice.	
Seek immediate medical help for blistering or open wounds.	
After eye contact:	
Remove contact lenses if worn.	
Rinse opened eye for several minutes under running water. Then consult a doctor.	
After swallowing:	
Unlikely route of exposure.	
Rinse out mouth and then drink plenty of water.	
Do not induce vomiting; call for medical help immediately.	
4.2 Most important symptoms and effects, both acute and delayed	
Asthma attacks	
Breathing difficulty	
Coughing	
Gastric or intestinal disorders when ingested.	
Nausea in case of ingestion.	
Allergic reactions	
Eye damage.	
Irritating to respiratory system and skin.	
Hazards	
Danger of blast or crush-type injuries.	
Danger of impaired breathing.	
Danger of imparied breathing.	(Cont'd. on page
	(contrat on page

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat[™] 37mm Long-Range Round, CN

(Cont'd. from page 5)

Danger of disturbed cardiac rhythm. Danger of pulmonary oedema. Toxic if swallowed or in contact with skin. Fatal if inhaled.

• 4.3 Indication of any immediate medical attention and special treatment needed

Contains 2-chloroacetophenone. May produce an allergic reaction.

If necessary oxygen respiration treatment.

Product may produce physical injury if mishandled. Treatment of these injuries should be based on the blast and compression effects.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

Flood area with water. If no water is available, carbon dioxide, dry chemical or earth may be used. If the fire reaches the cargo, withdraw and let fire burn.

DO NOT fight fire when fire reaches explosives.

• For safety reasons unsuitable extinguishing agents: None.

5.2 Special hazards arising from the substance or mixture

Fire or projection hazard.

Product may explode if burned in confined space. Individual cartridges may explode. Mass explosion of many cartridges at once is unlikely.

During heating or in case of fire poisonous gases are produced.

· 5.3 Advice for firefighters

· Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Eliminate all ignition sources if safe to do so.

Evacuate area and fight fire from from the upwind side.

Cool endangered product with water spray.

Flammability Classification: (defined by 29 CFR 1910.1200) Explosive. Can explode under fire conditions. Individual devices will randomly explode. Will not mass explode if multiple devices are involved. Burning material may produce toxic and irritating vapors. In unusual cases, shrapnel may be thrown from exploding devices under containment. See 2008 Emergency response Guidebook for further information.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures

FOR ALL TRANSPORTATION ACCIDENTS, CALL CHEMTEL AT 1-800-255-3924. Spills of this material should be handled carefully. Do not subject materials to mechanical shock or extreme heat. A spill of this material will normally not require emergency response team capabilities. Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Protect from heat.

(Cont'd. on page 7)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat[™] 37mm Long-Range Round, CN

(Cont'd. from page 6)

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep away from heat and direct sunlight. Handle with care. Avoid jolting, friction and impact. Use only outdoors or in a well-ventilated area.

Information about fire - and explosion protection: Protect from heat.

Emergency cooling must be available in case of nearby fire.

Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities · Storage:

• Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

Protect from humidity and water.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

Store away from flammable substances.

• Further information about storage conditions: Store in dry conditions.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see section 7.

· 8.1 Control parameters

· Ingredients	Ingredients with limit values that require monitoring at the workplace:	
532-27-4 2-chloroacetophenone		
PEL (USA)	Long-term value: 0,3 mg/m ³ , 0,05 ppm	
REL (USA)	Long-term value: 0,3 mg/m³, 0,05 ppm	
TLV (USA)	Long-term value: 0,32 mg/m³, 0,05 ppm	
	(Cont'd, on page 8)	

(Cont'd. on page 8)

Printing date December 4, 2015

Revision: December 4, 2015

		(Cont'd. from page 7
EL (Canada) Long-term value: 0,05 ppm		
EV (Canada)	Long-term value: 0,32 mg/m³, 0,05 ppm	
57-50-1 sucr		
PEL (USA) Long-term value: 15* 5** mg/m ³		
	*total dust **respirable fraction	
REL (USA)	Long-term value: 10* 5** mg/m ³	
*total dust **respirable fraction		
TLV (USA)	Long-term value: 10 mg/m ³	
· · ·	Long-term value: 10* 3** mg/m ³ *total dust;**respirable fraction	
EV (Canada)	Long-term value: 10 mg/m ³	
	total dust	
7440-21-3 sil		
PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction	
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction	
TLV (USA)	TLV withdrawn	
EL (Canada)	Long-term value: 10* 3** mg/m ³ *total dust;**respirable fraction	
EV (Canada)	Long-term value: 10 mg/m³ total dust	
557-04-0 mag	gnesium distearate, pure	
TLV (USA)	Long-term value: 10 mg/m ³	
· DNELs No fu	rther relevant information available.	
· PNECs No fu	rther relevant information available.	
· 8.2 Exposure		
• Engineering		
	t to grinding/shock/friction. loors or in a well-ventilated area.	
	tective equipment:	
	ective and hygienic measures:	
The usual pre	cautionary measures are to be adhered to when handling chemicals.	
	om foodstuffs, beverages and feed.	
	emove all soiled and contaminated clothing.	
	before breaks and at the end of work.	
	dust / smoke / mist. with the eyes and skin.	
		(Cont'd. on page

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date December 4, 2015

· Respiratory protection:

Revision: December 4, 2015

Trade name: Spede-Heat™ 37mm Long-Range Round, CN

(Cont'd. from page 8)



Respiratory protection required.

Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in large quantities.

Protection of hands:

None required for handling unused product; where possible, use protective gloves for handling spent rounds.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Safety glasses

• **Body protection:** Protective work clothing

· Limitation and supervision of exposure into the environment

No further relevant information available.

· Risk management measures

See Section 7 for additional information.

Organizational measures should be in place for all activities involving this product.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

General Information

Form: Colour: Odour: Odour threshold:	Solid metal container containing liquid and solid contents. According to product specification Odourless Not determined.
pH-value:	Not applicable.
Change in condition	
Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	Not determined.
Flash point:	Not applicable.
	(Cont'd. on pag

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat[™] 37mm Long-Range Round, CN

		(Cont'd. from page
· Flammability (solid, gaseous):	Not determined.	
· Auto/Self-ignition temperature:	Not determined.	
· Decomposition temperature:	Not determined.	
· Self-igniting:	Product is not self-igniting.	
· Danger of explosion:	Fire or projection hazard.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Oxidising properties	Contains oxidizing agent.	
· Vapour pressure:	Not applicable.	
· Density:	Not determined.	
Relative density	Not determined.	
· Vapour density	Not applicable.	
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
water:	Insoluble.	
· Partition coefficient (n-octanol/wa	ter): Not determined.	
· Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
 9.2 Other information 	No further relevant information available.	

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available. · 10.2 Chemical stability · Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications. · 10.3 Possibility of hazardous reactions Fire or projection hazard. Toxic fumes may be released if heated above the decomposition point. Reacts with flammable substances. Reacts with strong acids and alkali. 10.4 Conditions to avoid Store away from oxidising agents. Keep ignition sources away - Do not smoke. Cartridge may detonate if case is punctured or severely damaged. • 10.5 Incompatible materials: No further relevant information available. 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide Toxic metal oxide smoke

(Cont'd. on page 11)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 37mm Long-Range Round, CN

(Cont'd. from page 10)

Chlorine compounds Nitrogen oxides

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity

Toxic if swallowed or in contact with skin. Fatal if inhaled.

· LD/LC50 values relevant for classification:

532-27-4 2-chloroacetophenone

Oral LD50 50 mg/kg (rat)

3811-04-9 potassium chlorate

Oral LD50 1870 mg/kg (rat)

Primary irritant effect:

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Additional toxicological information:

Normal handling of the undeployed product poses little or no health hazards, One should avoid inhalation by wearing appropriate respiratory protection when exposed to the chemical ingredients of the product above listed TLV's or when exposed to the post ignition by-products. This product is a cansister which contains the various components completely sealed within. Therefore, under normal handling of this product, no exposure to any harmful materials will occur. When the product is used, particles may be generated which may be irritating to the eyes and the respiratory tract.

Toxic and/or corrosive effects may be delayed up to 24 hours.

Danger through skin adsorption.

Acute effects (acute toxicity, irritation and corrosivity):

Danger of blast or crush-type injuries.

Toxic if swallowed, in contact with skin or if inhaled.

Causes serious eye damage.

Irritating to skin.

May cause respiratory irritation.

• Repeated dose toxicity: Repeated exposures may result in skin and/or respiratory sensitivity.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):

• Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

• Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

(Cont'd. on page 12)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date December 4, 2015

Revision: December 4, 2015

(Cont'd. from page 11)

Trade name: Spede-Heat™ 37mm Long-Range Round, CN

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity: No further relevant information available.

- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Harmful to aquatic organisms

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number	
· DOT, ADR, IMDG, IATA	UN0301
· 14.2 UN proper shipping name	
DOT	Ammunition Tear-producing with burster, expelli charge or propelling charge

Printing date December 4, 2015

Revision: December 4, 2015

	(Cont'd. from page 1
ADR	0301 AMMUNITION TEAR-PRODUCING with burster expelling
	charge or propelling charge
· IMDG, IATA	AMMUNITION TEAR-PRODUCING with burster
	expelling
	charge or propelling charge
 14.3 Transport hazard class(es) 	
· DOT	
1.4	
· Class	1.4
· Label	1.4G, 6.1, 8
· ADR	
Class	1.4 (_)
·Label	1.4G+6.1+8
·IMDG	
· Class	1.4
· Label	1.4G/6.1/8
Class	1.4
[·] Label	1.4G (6.1, 8)
 14.4 Packing group DOT, ADR, IMDG, IATA 	II
14.5 Environmental hazards:	
· Marine pollutant:	No
• Special marking (IATA):	
Cargo Aircraft Only.	
	(Cont'd. on page 1

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat[™] 37mm Long-Range Round, CN

	(Cont'd. from page 13
 14.6 Special precautions for user EMS Number: 	Not applicable. F-B,S-Z
 14.7 Transport in bulk according to Ann Marpol and the IBC Code 	nex II of Not applicable.
· Transport/Additional information:	
 ADR Limited quantities (LQ) Excepted quantities (EQ) 	0 Code: E0 Not permitted as Excepted Quantity
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	0 Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN0301, 0301, ENVIRONMENTALLY HAZARDOUS 1.4G (6.1+8), II

SECTION 15: Regulatory information

 $^{\cdot}$ 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture $^{\cdot}$ United States (USA)

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

532-27-4 2-chloroacetophenone

7757-79-1 potassium nitrate

• TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65 (California):

• Chemicals known to cause cancer:

15245-44-0 lead 2,4,6-trinitro-m-phenylene dioxide/ lead styphnate

• Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

• Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

• Chemicals known to cause developmental toxicity: Present in trace quantities.

15245-44-0 lead 2,4,6-trinitro-m-phenylene dioxide/ lead styphnate

(Cont'd. on page 15)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date December 4, 2015

Carcinogenic Categories

Revision: December 4, 2015

Trade name: Spede-Heat™ 37mm Long-Range Round, CN

(Cont'd. from page 14)

EPA (Environmental Protection Agency)

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· Canada

· Canadian Domestic Substances List (DSL)

Some components are listed on the NDSL.

All ingredients are listed.

• Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients are listed.

Canadian Ingredient Disclosure list (limit 1%)

532-27-4 2-chloroacetophenone

· Other regulations, limitations and prohibitive regulations

• Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients are listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H201 Explosive; mass explosion hazard.

H228 Flammable solid.

H271 May cause fire or explosion; strong oxidiser.

H272 May intensify fire; oxidiser.

H300 Fatal if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

• Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

(Cont'd. on page 16)

GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat[™] 37mm Long-Range Round, CN

(Cont'd. from page 15) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety Expl. 1.1: Explosives, Division 1.1 Expl. 1.4: Explosives, Division 1.4 Flam. Sol. 2: Flammable solids, Hazard Category 2 Ox. Sol. 1: Oxidising Solids, Hazard Category 1 Ox. Sol. 2: Oxidising Solids, Hazard Category 2 Acute Tox. 2: Acute toxicity, Hazard Category 2 Acute Tox. 4: Acute toxicity, Hazard Category 4 Acute Tox. 3: Acute toxicity, Hazard Category 3 Acute Tox. 1: Acute toxicity, Hazard Category 1 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3 Sources SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com