

Revision: August 26, 2014

SECTION undertakin	1: Identification of the substance/mixture and of the company
· 1.1 Product i	identifier
· Trade name:	Defense Technology Aerial Warning / Signaling Munition CN - 200 Meters
	per: 6030CN identified uses of the substance or mixture and uses advised against evant information available.
• Application of Crowd Contro Explosive pro	
 Manufacture Safariland, LL 13386 Interna Jacksonville, Customer Ca 	_Cational Parkway
ChemTel Inc.	cy telephone number: 94, +1 (813)248-0585
SECTION 2	2: Hazards identification
	ation of the substance or mixture n according to Regulation (EC) No 1272/2008
explo	ding bomb
Expl. 1.4	H204 Fire or projection hazard.
skull a	and crossbones
	H301 Toxic if swallowed.
Acute Tox. 2	H330 Fatal if inhaled.
health	n hazard
Resp. Sens.	1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
	H318 Causes serious eye damage.

Printing date: August 26, 2014

Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CN - 200 Meters

	(Contd. of page 1)
\wedge	
	. 4 H312 Harmful in contact with skin.
Skin Irrit. 2 Skin Sens	 H315 Causes skin irritation. H317 May cause an allergic skin reaction.
	ition according to Directive 67/548/EEC or Directive 1999/45/EC
0	ery toxic
R26:	Very toxic by inhalation.
喿 T; Tox	kic (
R24/25:	Toxic in contact with skin and if swallowed.
🗙 Xn; Se	ensitising
R42/43:	May cause sensitisation by inhalation and skin contact.
🗙 Xi; Irri	tant
R41-38:	Risk of serious damage to eyes. Irritating to skin.
The produ preparation Classifica The class literature d The class supplemen	ification is in accordance with the latest editions of international substances lists, and is need by information from technical literature and by information provided by the company.
The follow regulation:	according to Regulation (EC) No 1272/2008 wing Hazard Statements are applicable only to the EU regulations and not the US GHS H412. ct is classified and labelled according to the CLP regulation.
GHS01 GH	HS05 GHS06 GHS08
[.] Signal wo	rd Danger
2-chloroac potassium · Hazard st a	etermining components of labelling: cetophenone perchlorate atements or projection hazard. (Contd. on page 3)

GHS

Printing date: August 26, 2014

Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CN - 200 Meters (Contd. of page 2) H301 Toxic if swallowed. H312 Harmful in contact with skin. H330 Fatal if inhaled. H315 Causes skin irritation. H318 Causes serious eye damage. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317 May cause an allergic skin reaction. **Precautionary statements** P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P250 Do not subject to grinding/shock/friction. P285 In case of inadequate ventilation wear respiratory protection. Wear eye protection / face protection. P280 DO NOT fight fire when fire reaches explosives. P373 P370+P380 In case of fire: Evacuate area. P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor. P372 Explosion risk in case of fire. · Additional information: Can become highly flammable in use. · Hazard description: WHMIS-symbols: D1A - Very toxic material causing immediate and serious toxic effects D2A - Very toxic material causing other toxic effects E - Corrosive material NFPA ratings (scale 0 - 4) Health = 4Fire = 0Reactivity = 0 · HMIS-ratings (scale 0 - 4) ^{*4} Health = *4 HEALTH • Fire = 0 FIRE **REACTIVITY** Reactivity = 0 * - Indicates a long term health hazard from repeated or prolonged exposures. HMIS Long Term Health Hazard Substances 7778-74-7 potassium perchlorate · 2.3 Other hazards · Results of PBT and vPvB assessment • **PBT:** Not applicable. · vPvB: Not applicable. Explosive Product Notice PREVENTION OF ACCIDENTS IN THE USE OF EXPLOSIVES - The prevention of accidents in the use of explosives is a result of careful planning and observance of the best known practices. The explosives user must remember that he is dealing with a powerful force and that various devices and methods have (Contd. on page 4)

Printing date: August 26, 2014

Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CN - 200 Meters

(Contd. of page 3) been developed to assist him in directing this force. He should realize that this force, if misdirected, may either kill or injure both him and his fellow workers.

WARNING - All explosives are dangerous and must be carefully handled and used following approved safety procedures either by or under the direction of competent, experienced persons in accordance with all applicable federal, state, and local laws, regulations, or ordinances. If you have any questions or doubts as to how to use any explosive product, DO NOT USE IT before consulting with your supervisor, or the manufacturer, if you do not have a supervisor. If your supervisor has any questions or doubts, he should consult the manufacturer before use.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
EINECS: 231-912-9 Index number: 017-008-00-5	potassium perchlorate Xn R22; A O R9 Ox. Sol. 1, H271 Acute Tox. 4, H302	10-25%
EINECS: 231-818-8	otassium nitrate O R8 � Ox. Sol. 2, H272	10-25%
EINECS: 208-531-1	2-chloroacetophenone T + R26; T R24/25; X N R42/43; Xi R37/38-41 Acute Tox. 2, H300; Acute Tox. 3, H311; Acute Tox. 1, H330 Resp. Sens. 1, H334 Eye Dam. 1, H318 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	2,5-10%
EINECS: 231-104-6	magnesium powder (pyrophoric) F R15-17 Pyr. Sol. 1, H250; Water-react. 1, H260	2,5-10%
	sulfur Xi R38 I Skin Irrit. 2, H315	2,5-10%
CAS: 7429-90-5 EINECS: 231-072-3	aluminium powder (pyrophoric) F R15-17 Pyr. Sol. 1, H250; Water-react. 2, H261	2,5-10%
EC number: 603-037-0	Nitrocellulose, colloided, granular E R3 È Expl. 1.1, H201	≤ 2,5%
	magnesium oxide substance with a Community workplace exposure limit	10-25%
CAS: 7631-86-9 EINECS: 231-545-4	silicon dioxide	2,5-10%

Revision: August 26, 2014

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CN - 200 Meters

	(Contd. of page 4)
• Additional information: For	the wording of the listed risk phrases refer to section 16.
• Notable Trace Components	s (≤ 0,1% w/w)
CAS: 122-39-4 EINECS: 204-539-4 Index number: 612-026-00-5	diphenylamine T R23/24/25; N R50/53 R33 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 STOT RE 2, H373 Aquatic Acute 1, H400; Aquatic Chronic 1, H410
CAS: 12403-82-6 EINECS: 235-642-2	dihydroxy[styphnato(2-)]dilead / lead styphnate T R23/25; ☆ Xn R40-48-62; ∰ E R3; ☆ N R50/53 R33 ↓ Unst. Expl., H200 ↓ Acute Tox. 3, H301; Acute Tox. 2, H330 ↓ Carc. 1B, H350; Repr. 2, H361; STOT RE 2, H373 ↓ Aquatic Acute 1, H400; Aquatic Chronic 1, H410

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

Seek immediate medical help for blistering or open wounds.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Unlikely route of exposure.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

- 4.2 Most important symptoms and effects, both acute and delayed
- Asthma attacks

Irritant to skin and mucous membranes.

Irritant to eyes.

Breathing difficulty

Coughing

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

(Contd. on page 6)

Printing date: August 26, 2014

Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CN - 200 Meters

(Contd. of page 5)

Allergic reactions

· Hazards

Danger of impaired breathing.

Danger of disturbed cardiac rhythm.

Danger of pulmonary oedema.

Danger of blast or crush-type injuries.

4.3 Indication of any immediate medical attention and special treatment needed

Contains 2-chloroacetophenone. May produce an allergic reaction.

If necessary oxygen respiration treatment.

Product may produce physical injury if mishandled. Treatment of these injuries should be based on the blast and compression effects.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

• For safety reasons unsuitable extinguishing agents: None.

5.2 Special hazards arising from the substance or mixture

Product may explode if burned in confined space. Individual cartridges may explode. Mass explosion of many cartridges at once is unlikely.

During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters

· Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Eliminate all ignition sources if safe to do so.

Flammability Classification: (defined by 29 CFR 1910.1200) Explosive. Can explode under fire conditions. Individual devices will randomly explode. Will not mass explode if multiple devices are involved. Burning material may produce toxic and irritating vapors. In unusual cases, shrapnel may be thrown from exploding devices under containment. See 2008 Emergency response Guidebook for further information.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

FOR ALL TRANSPORTATION ACCIDENTS, CALL CHEMTEL AT 1-800-255-3924. Spills of this material should be handled carefully. Do not subject materials to mechanical shock or extreme heat. A spill of this material will normally not require emergency response team capabilities.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Protect from heat.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 7)

GHS

Printing date: August 26, 2014

Revision: August 26, 2014

(Contd. of page 6)

Trade name: Defense Technology Aerial Warning / Signaling Munition CN - 200 Meters

 6.3 Methods and material for containment and cleaning up: Pick up mechanically.
 Send for recovery or disposal in suitable receptacles.
 Dispose contaminated material as waste according to item 13.
 Clean the affected area carefully; suitable cleaners are: Warm water and cleansing agent
 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight. Handle with care. Avoid jolting, friction and impact. Information about fire - and explosion protection:

Protect from heat.

Substance/product can reduce the ignition temperature of flammable substances. Emergency cooling must be available in case of nearby fire. Keep respiratory protective device available.

• 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

Protect from humidity and water.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

Store away from flammable substances.

• Further information about storage conditions: Store in dry conditions.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

532-27-4 2-chloroacetophenone

PEL (USA)	Long-term value: 0,3 mg/m ³ , 0,05 ppm
REL (USA)	Long-term value: 0,3 mg/m ³ , 0,05 ppm
TLV (USA)	Long-term value: 0,32 mg/m ³ , 0,05 ppm
EL (Canada)	Long-term value: 0,05 ppm
	S

(Contd. on page 8)

Revision: August 26, 2014

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CN - 200 Meters

		td. of page 7)
, ,	Long-term value: 0,32 mg/m³, 0,05 ppm	
	agnesium oxide	
PEL (USA)	Long-term value: 15* mg/m³ fume; *total particulate	
TLV (USA)	Long-term value: 10* mg/m³ *as inhalable fraction	
EL (Canada)	Short-term value: 10** mg/m³ Long-term value: 10* 3** mg/m³ *inhalable fume;**respirable dust and fume	
EV (Canada)) Long-term value: 10 mg/m³ inhalable	
7429-90-5 al	uminium powder (pyrophoric)	
PEL (USA)	Long-term value: 15*; 15** mg/m ³ *Total dust; ** Respirable fraction	
REL (USA)	Long-term value: 10* 5** mg/m³ as Al*Total dust**Respirable/pyro powd./welding f.	
TLV (USA)	Long-term value: 1* mg/m³ as Al; *as respirable fraction	
EL (Canada)	Long-term value: 1,0 mg/m ³ respirable, as Al	
EV (Canada)	Long-term value: 5 mg/m³ aluminium-containing (as aluminium)	
 PNECs No fu Additional in 8.2 Exposur Personal prodition General prodition The usual produced by the set of t	otective equipment: tective and hygienic measures: ecautionary measures are to be adhered to when handling chemicals. rom foodstuffs, beverages and feed. remove all soiled and contaminated clothing. before breaks and at the end of work. e dust / smoke / mist. t with the eyes and skin.	
Res	piratory protection required.	
quantities. Protection o Gloves not re	equired under normal conditions of use. tive gloves to handle contents of damaged or leaking units.	uct in large d. on page 9)

GHS

Printing date: August 26, 2014

Revision: August 26, 2014

(Contd. of page 8)

Trade name: Defense Technology Aerial Warning / Signaling Munition CN - 200 Meters

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Safety glasses

· Body protection: Protective work clothing

· Limitation and supervision of exposure into the environment

No further relevant information available.

· Risk management measures

See Section 7 for additional information.

Organizational measures should be in place for all activities involving this product.

No further relevant information available.

9.1 Information on basic physical a	and chemical properties
General Information Appearance:	
Form:	Solid metal container containing liquid and solid contents.
Colour:	According to product specification
Odour:	Odourless
Odour threshold:	Not determined.
pH-value:	Not applicable.
Change in condition	
Melting point/Melting range:	Not Determined.
Boiling point/Boiling range:	Undetermined.
Flash point:	Not applicable.
Flammability (solid, gaseous):	Not determined.
Auto/Self-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
Self-igniting:	Product is not self-igniting.
Danger of explosion:	Heating may cause an explosion. Risk of explosion by shock, friction, fire or other sources o ignition.
	(Contd. on page 10

Printing date: August 26, 2014

Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CN - 200 Meters (Contd. of page 9) • Explosion limits: Not determined. Lower: Upper: Not determined. · Vapour pressure: Not applicable. · Density: Not determined. · Relative density Not determined. · Vapour density Not applicable. · Evaporation rate Not applicable. · Solubility in / Miscibility with water: Insoluble. · Partition coefficient (n-octanol/water): Not determined. · Viscosity: **Dynamic:** Not applicable. Not applicable. Kinematic: 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity · 10.1 Reactivity · 10.2 Chemical stability · Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications. 10.3 Possibility of hazardous reactions Toxic fumes may be released if heated above the decomposition point. Can react violently with oxygen rich (oxidizing) material. Danger of Explosion. Reacts with flammable substances. 10.4 Conditions to avoid Store away from oxidizing agents. Keep ignition sources away - Do not smoke. Cartridge may detonate if case is punctured or severely damaged. • 10.5 Incompatible materials: No further relevant information available. 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide Toxic metal oxide smoke Chlorine compounds Nitrogen oxides

(Contd. on page 11)

Printing date: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CN - 200 Meters

(Contd. of page 10)

Revision: August 26, 2014

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity:

· LD/LC50 values relevant for classification:

532-27-4 2-chloroacetophenone

Oral LD50 50 mg/kg (rat)

Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

· on the eye: Irritating effect.

· Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Harmful

Irritant

Normal handling of the undeployed product poses little or no health hazards, One should avoid inhalation by wearing appropriate respiratory protection when exposed to the chemical ingredients of the product above listed TLV's or when exposed to the post ignition by-products. This product is a cansister which contains the various components completely sealed within. Therefore, under normal handling of this product, no exposure to any harmful materials will occur. When the product is used, particles may be generated which may be irritating to the eyes and the respiratory tract.

Acute effects (acute toxicity, irritation and corrosivity): Harmful if inhaled.

• Repeated dose toxicity: Repeated exposures may result in skin and/or respiratory sensitivity.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity: No further relevant information available.

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

(Contd. on page 12)

GHS

Printing date: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CN - 200 Meters

· **vPvB:** Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations


· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.



(Contd. of page 11)

Printing date: August 26, 2014

Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CN - 200 Meters (Contd. of page 12) ·IMDG · Class 1.4 1.4G+6.1+8 · Label · IATA · Class FORBIDDEN · Label FORBIDDEN · 14.4 Packing group · DOT, ADR, IMDG Ш FORBIDDEN · IATA · 14.5 Environmental hazards: • Marine pollutant: No Symbol (fish and tree) · Special marking (ADR): 14.6 Special precautions for user Not applicable. · EMS Number: F-A,S-Q · Segregation groups Chlorates 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. **UN "Model Regulation":** UN0301, Ammunition Tear-producing with burster, expelling charge or propelling charge, 1.4G, II

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 United States (USA)
 SARA
 Section 355 (extremely hazardous substances): None of the ingredients is listed.
 Section 313 (Specific toxic chemical listings):

7757-79-1 potassium nitrate

532-27-4 2-chloroacetophenone

7429-90-5 aluminium powder (pyrophoric)

• TSCA (Toxic Substances Control Act):

All ingredients are listed.

(Contd. on page 14)

Revision: August 26, 2014

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CN - 200 Meters

· Proposition 65 (California):	(Contd. of page 1
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
• Chemicals known to cause reproductive toxicity for females:	
None of the ingredients are listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
Present in trace quantities.	
None of the ingredients is listed.	
· Carcinogenic Categories	
· EPA (Environmental Protection Agency)	
7778-74-7 potassium perchlorate	NI
· IARC (International Agency for Research on Cancer)	
7631-86-9 silicon dioxide	;
TLV (Threshold Limit Value established by ACGIH)	·
532-27-4 2-chloroacetophenone	A
1309-48-4 magnesium oxide	A
7429-90-5 aluminium powder (pyrophoric)	A
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
· Canada	
· Canadian Domestic Substances List (DSL)	
All ingredients are listed.	
· Canadian Ingredient Disclosure list (limit 0.1%)	
None of the ingredients is listed.	
· Canadian Ingredient Disclosure list (limit 1%)	
532-27-4 2-chloroacetophenone	
1309-48-4 magnesium oxide	
7429-90-5 aluminium powder (pyrophoric)	
7631-86-9 silicon dioxide	
 Other regulations, limitations and prohibitive regulations This product has been classified in accordance with hazard criteria of the Controlle and the SDS contains all the information required by the Controlled Products Regu 	
· Substances of very high concern (SVHC) according to REACH, Article 57	
None of the ingredients is listed.	
· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been	carried out.

Printing date: August 26, 2014

Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CN - 200 Meters

(Contd. of page 14)

SECT	ION 16: Other information
	formation is based on our present knowledge. However, this shall not constitute a guarantee for an c product features and shall not establish a legally valid contractual relationship.
Releva	int phrases
H201	Explosive; mass explosion hazard.
H250	Catches fire spontaneously if exposed to air.
H260	In contact with water releases flammable gases which may ignite spontaneously.
H261	In contact with water releases flammable gases.
H271	May cause fire or explosion; strong oxidiser.
H272	May intensify fire; oxidiser.
H300	Fatal if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
R15	Contact with water liberates extremely flammable gases.
R17	Spontaneously flammable in air.
R22	Harmful if swallowed.
R24/25	5 Toxic in contact with skin and if swallowed.
R26	Very toxic by inhalation.
R3	Extreme risk of explosion by shock, friction, fire or other sources of ignition.
	B Irritating to respiratory system and skin.
R38	Irritating to skin.
R41	Risk of serious damage to eyes.
	May cause sensitisation by inhalation and skin contact.
R8	Contact with combustible material may cause fire.
R9	Explosive when mixed with combustible material.
	viations and acronyms:
	ccord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning t onal Carriage of Dangerous Goods by Road)
	Iternational Maritime Code for Dangerous Goods
DOT: US	S Department of Transportation
	ternational Air Transport Association
	obally Harmonized System of Classification and Labelling of Chemicals American Conference of Governmental Industrial Hygienists
	: European Inventory of Existing Commercial Chemical Substances
	European List of Notified Chemical Substances
	emical Abstracts Service (division of the American Chemical Society) lational Fire Protection Association (USA)
	azardous Materials Identification System (USA)
	Workplace Hazardous Materials Information System (Canada)
	Derived No-Effect Level (REACH)
	Predicted No-Effect Concentration (REACH) ethal concentration, 50 percent
	ethal concentration, so percent
	: Explosives, Division 1.1
	(Contd. on page 1

GHS

Printing date: August 26, 2014

Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CN - 200 Meters

(Contd. of page 15) Expl. 1.4: Explosives, Division 1.4 Pyr. Sol. 1: Pyorphoric Solids, Hazard Category 1 Water-react. 1: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 1 Water-react. 2: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 2 Ox. Sol. 1: Oxidising Solids, Hazard Category 1 Ox. Sol. 2: Oxidising Solids, Hazard Category 2 Acute Tox. 2: Acute toxicity, Hazard Category 2 Acute Tox. 4: Acute toxicity, Hazard Category 4 Acute Tox. 3: Acute toxicity, Hazard Category 3 Acute Tox. 1: Acute toxicity, Hazard Category 1 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 Sources SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com