according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Revision: July 21, 2015

(Cont'd. on page 2)

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking 1.1 Product identifier • Trade name: Defense Technology 40MM Ground Marker Blue Colored Smoke - 300 Meters · Article number: 6683BL · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Explosive product. 1.3 Details of the supplier of the Safety Data Sheet · Manufacturer/Supplier: Safariland, LLC 13386 International Parkway Jacksonville, FL 32218 Customer Care (800) 347-1200 · Further information obtainable from: Customer Care Department · 1.4 Emergency telephone number: ChemTel Inc. (800)255-3924, +1 (813)248-0585 Poison Control Centres: In the United Kingdom: 844 892 0111 In Australia: 131126 In New Zealand: +0800 764 766 SECTION 2: Hazards identification · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412. exploding bomb Expl. 1.4 H204 Fire or projection hazard. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412. The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS01

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Revision: July 21, 2015

### Trade name: Defense Technology 40MM Ground Marker Blue Colored Smoke - 300 Meters

(Cont'd. from page 1) · Signal word Warning · Hazard statements The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412. H204 Fire or projection hazard. H412 Harmful to aquatic life with long lasting effects. **Precautionary statements** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210 smoking. P250 Do not subject to grinding/shock/friction. Wear eye protection / face protection. P280 P373 DO NOT fight fire when fire reaches explosives. P370+P380 In case of fire: Evacuate area. P372 Explosion risk in case of fire. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · Additional information: Can become highly flammable in use. • NFPA ratings (scale 0 - 4) Health = 1 Fire = 3Reactivity = 3 · HMIS-ratings (scale 0 - 4) HEALTH 1 Health = 1 <sup>3</sup> Fire = 3 FIRE **REACTIVITY** 3 Reactivity = 3 HMIS Long Term Health Hazard Substances None of the ingredients are listed. · 2.3 Other hazards Results of PBT and vPvB assessment • **PBT:** Not applicable. vPvB: Not applicable. **Explosive Product Notice** (Cont'd. on page 3) GHS

Printing date July 21, 2015

Revision: July 21, 2015

### Trade name: Defense Technology 40MM Ground Marker Blue Colored Smoke - 300 Meters

(Cont'd. from page 2)

PREVENTION OF ACCIDENTS IN THE USE OF EXPLOSIVES - The prevention of accidents in the use of explosives is a result of careful planning and observance of the best known practices. The explosives user must remember that he is dealing with a powerful force and that various devices and methods have been developed to assist him in directing this force. He should realize that this force, if misdirected, may either kill or injure both him and his fellow workers.

WARNING - All explosives are dangerous and must be carefully handled and used following approved safety procedures either by or under the direction of competent, experienced persons in accordance with all applicable federal, state, and local laws, regulations, or ordinances. If you have any questions or doubts as to how to use any explosive product, DO NOT USE IT before consulting with your supervisor, or the manufacturer, if you do not have a supervisor. If your supervisor has any questions or doubts, he should consult the manufacturer before use.

### **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

<sup>•</sup> Dangerous components:		
CAS: 9004-70-0	Nitrocellulose, colloided, granular	20-40%
EC number: 603-037-0	🔗 Expl. 1.1, H201	
CAS: 100-21-0	terephthalic acid	20-40%
EINECS: 202-830-0	substance with a Community workplace exposure limit	
CAS: 3811-04-9	potassium chlorate	10-20%
EINECS: 223-289-7	Ox. Sol. 1, H271	
Index number: 017-004-00-3		
	Acute Tox. 4, H302; Acute Tox. 4, H332	
CAS: 57-50-1	sucrose, pure	5-10%
EINECS: 200-334-9	substance with a Community workplace exposure limit	
CAS: 598-62-9	manganese carbonate	5-10%
EINECS: 209-942-9	substance with a Community workplace exposure limit	
CAS: 7757-79-1	potassium nitrate	1-5%
EINECS: 231-818-8	🕸 Ox. Sol. 2, H272	
CAS: 7440-21-3	silicon	1-5%
EINECS: 231-130-8	🚯 Flam. Sol. 2, H228	
CAS: 7429-90-5	aluminium powder (pyrophoric)	< 1,0%
EINECS: 231-072-3	🐵 Pyr. Sol. 1, H250; Water-react. 2, H261	
Index number: 013-001-00-6		
	the wording of the listed Hazard Statements refer to section 16.	
<sup>·</sup> Notable Trace Components (≤ 0,1% w/w)		
	(0	cont'd. on page 4)

GHS

Printing date July 21, 2015

Revision: July 21, 2015

### Trade name: Defense Technology 40MM Ground Marker Blue Colored Smoke - 300 Meters

	(Cont'd. from page 3)
CAS: 122-39-4	diphenylamine
EINECS: 204-539-4 Index number: 612-026-00-5	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 STOT RE 2, H373 Aquatic Acute 1, H400; Aquatic Chronic 1, H410
CAS: 12403-82-6 EINECS: 235-642-2	dihydroxy[styphnato(2-)]dilead / lead styphnate Unst. Expl., H200 Acute Tox. 3, H301; Acute Tox. 2, H330 Carc. 1B, H350; Repr. 2, H361; STOT RE 2, H373 Aquatic Acute 1, H400; Aquatic Chronic 1, H410

### **SECTION 4: First aid measures**

### · 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

### • After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

### After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

### · After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

### • After swallowing:

Unlikely route of exposure.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

Coughing

Slight irritant effect on eyes.

· Hazards Danger of blast or crush-type injuries.

### 4.3 Indication of any immediate medical attention and special treatment needed

If necessary oxygen respiration treatment.

Product may produce physical injury if mishandled. Treatment of these injuries should be based on the blast and compression effects.

# **SECTION 5: Firefighting measures**

### · 5.1 Extinguishing media

### · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

# • For safety reasons unsuitable extinguishing agents: None.

5.2 Special hazards arising from the substance or mixture

Product may explode if burned in confined space. Individual cartridges may explode. Mass explosion of many cartridges at once is unlikely.

Formation of toxic gases is possible during heating or in case of fire.

(Cont'd. on page 5)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Revision: July 21, 2015

### Trade name: Defense Technology 40MM Ground Marker Blue Colored Smoke - 300 Meters

(Cont'd. from page 4)

### 5.3 Advice for firefighters

• Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

# Additional information

Eliminate all ignition sources if safe to do so.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Flammability Classification: (defined by 29 CFR 1910.1200) Explosive. Can explode under fire conditions. Individual devices will randomly explode. Will not mass explode if multiple devices are involved. Burning material may produce toxic and irritating vapors. In unusual cases, shrapnel may be thrown from exploding devices under containment. See 2008 Emergency response Guidebook for further information.

### **SECTION 6: Accidental release measures**

### · 6.1 Personal precautions, protective equipment and emergency procedures

FOR ALL TRANSPORTATION ACCIDENTS, CALL CHEMTEL AT 1-800-255-3924. Spills of this material should be handled carefully. Do not subject materials to mechanical shock or extreme heat. A spill of this material will normally not require emergency response team capabilities.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Protect from heat.

### · 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

### 6.3 Methods and material for containment and cleaning up:

Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Dispose contaminated material as waste according to section 13.

Clean the affected area carefully; suitable cleaners are:

Warm water and cleansing agent

### · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

### · 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Handle with care. Avoid jolting, friction and impact.

### Information about fire - and explosion protection:

Protect from heat.

Substance/product can reduce the ignition temperature of flammable substances. Emergency cooling must be available in case of nearby fire.

(Cont'd. on page 6)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Revision: July 21, 2015

### Trade name: Defense Technology 40MM Ground Marker Blue Colored Smoke - 300 Meters

(Cont'd. from page 5)
7.2 Conditions for safe storage, including any incompatibilities
Storage:
Requirements to be met by storerooms and receptacles: Avoid storage near extreme heat, ignition sources or open flame. Protect from humidity and water.
Information about storage in one common storage facility: Store away from foodstuffs. Store away from oxidising agents. Store away from oxidising agents.
Further information about storage conditions: Store in dry conditions.
7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

• Additional information about design of technical facilities: No further data; see section 7.

## 8.1 Control parameters

· 8.1 Control p	· 8.1 Control parameters	
· Ingredients v	Ingredients with limit values that require monitoring at the workplace:	
100-21-0 terephthalic acid		
TLV (USA)	Long-term value: 10 mg/m <sup>3</sup>	
EL (Canada)	Long-term value: 10 mg/m <sup>3</sup>	
EV (Canada)	Long-term value: 10 mg/m <sup>3</sup>	
57-50-1 sucro	ose, pure	
PEL (USA)	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction	
REL (USA)	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction	
TLV (USA)	Long-term value: 10 mg/m <sup>3</sup>	
EL (Canada)	Long-term value: 10 mg/m <sup>3</sup>	
EV (Canada)	Long-term value: 10 mg/m³ total dust	
598-62-9 mar	nganese carbonate	
PEL (USA)	Ceiling limit: 5 mg/m <sup>3</sup> as Mn	
REL (USA)	Short-term value: 3 mg/m <sup>3</sup> Long-term value: 1 mg/m <sup>3</sup> as Mn	
TLV (USA)	Long-term value: 0,02* 0,1* mg/m³ as Mn; *respirable **inhalable fraction	
EL (Canada)	Long-term value: 0,2 mg/m³ as Mn; R	
	(Cont'd. on page 7)	

Revision: July 21, 2015

# Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date July 21, 2015

Trade name: Defense Technology 40MM Ground Marker Blue Colored Smoke - 300 Meters

	(Cont'd. from page
7440-21-3 sil	
PEL (USA)	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV (USA)	TLV withdrawn
EL (Canada)	Long-term value: 10 mg/m <sup>3</sup>
EV (Canada)	Long-term value: 10 mg/m³ total dust
7429-90-5 alı	uminium powder (pyrophoric)
PEL (USA)	Long-term value: 15*; 15** mg/m <sup>3</sup> *Total dust; ** Respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m³ *Total dust **Respirable fraction
TLV (USA)	Long-term value: 1* mg/m³ as Al; *as respirable fraction
EL (Canada)	Long-term value: 1,0 mg/m³ metal and insoluble compdounds, respirable
EV (Canada)	Long-term value: 5 mg/m³ aluminium-containing (as aluminium)
8.2 Exposure	
	tective equipment: ective and hygienic measures:
	ecautionary measures are to be adhered to when handling chemicals.
	om foodstuffs, beverages and feed.
	emove all soiled and contaminated clothing.
	before breaks and at the end of work. dust / smoke / mist.
	with the eyes.
Respiratory	
	under normal conditions of use. e pressure NIOSH or European EN149 vapor respirators when deploying product in lar
Protection of	f hands:
	quired under normal conditions of use.
	ve gloves to handle contents of damaged or leaking units.
quality and v substances, t	n of the suitable gloves does not only depend on the material, but also on further marks varies from manufacturer to manufacturer. As the product is a preparation of seve he resistance of the glove material can not be calculated in advance and has therefore to
checked prior	to the application. (Cont'd. on page

(Cont'd. on page 8)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Revision: July 21, 2015

### Trade name: Defense Technology 40MM Ground Marker Blue Colored Smoke - 300 Meters

(Cont'd. from page 7)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

# · Eye protection:

Safety glasses

· Body protection: Protective work clothing

• **Limitation and supervision of exposure into the environment** No further relevant information available.

· Risk management measures

See Section 7 for additional information.

Organizational measures should be in place for all activities involving this product.

No further relevant information available.

# **SECTION 9: Physical and chemical properties**

### · 9.1 Information on basic physical and chemical properties · General Information · Appearance: Form: Solid metal container containing liquid and solid contents. Colour: According to product specification Odourless · Odour: · Odour threshold: Not determined. · pH-value: Not applicable. · Change in condition Melting point/Melting range: Not Determined. Undetermined. Boiling point/Boiling range: · Flash point: Not applicable. · Flammability (solid, gaseous): Not determined. · Auto/Self-ignition temperature: Not determined. · Decomposition temperature: Not determined. · Self-igniting: Product is not self-igniting. · Danger of explosion: Heating may cause an explosion. · Explosion limits: Lower: Not determined. Upper: Not determined. · Vapour pressure: Not applicable. · Density: Not determined. · Relative density Not determined. · Vapour density Not applicable. (Cont'd. on page 9)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Revision: July 21, 2015

### Trade name: Defense Technology 40MM Ground Marker Blue Colored Smoke - 300 Meters

		(Cont'd. from page 8)
Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
water:	Insoluble.	
Partition coefficient (n-octano	I/water): Not determined.	
Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
9.2 Other information	No further relevant information available.	

# **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

### 10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point. Reacts with flammable substances.

Can react violently with oxygen rich (oxidising) material. Danger of Explosion.

### · 10.4 Conditions to avoid

Store away from oxidising agents.

Keep ignition sources away - Do not smoke.

Cartridge may detonate if case is punctured or severely damaged.

• **10.5 Incompatible materials:** No further relevant information available.

### 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides

Toxic metal oxide smoke

Chlorine compounds

# **SECTION 11: Toxicological information**

· 11.1 Information on toxicological effects

· Acute toxicity

### · LD/LC50 values relevant for classification:

### 3811-04-9 potassium chlorate

Oral LD50 1870 mg/kg (rat)

Primary irritant effect:

### · Skin corrosion/irritation

Not a skin irritant in unused form. Vapors/particles from used product are possibly irritating to skin. • Serious eye damage/irritation

Not an eye irritant in unused form. Vapors/particles from used product are possibly irritating to eyes.

• Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

(Cont'd. on page 10)

GHŚ

Printing date July 21, 2015

Trade name: Defense Technology 40MM Ground Marker Blue Colored Smoke - 300 Meters

(Cont'd. from page 9)

Revision: July 21, 2015

Additional toxicological information:

Normal handling of the undeployed product poses little or no health hazards, One should avoid inhalation by wearing appropriate respiratory protection when exposed to the chemical ingredients of the product above listed TLV's or when exposed to the post ignition by-products. This product is a cansister which contains the various components completely sealed within. Therefore, under normal handling of this product, no exposure to any harmful materials will occur. When the product is used, particles may be generated which may be irritating to the eyes and the respiratory tract.

• Acute effects (acute toxicity, irritation and corrosivity): May be harmful if inhaled.

### CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

· Carcinogenicity

Based on available data, the classification criteria are not met.

· Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

· STOT-repeated exposure

Based on available data, the classification criteria are not met.

• Aspiration hazard

Based on available data, the classification criteria are not met.

# **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.

• **12.4 Mobility in soil** No further relevant information available.

- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

# 12.5 Results of PBT and vPvB assessment

- · PBT: Not applicable.
- vPvB: Not applicable.

• **12.6 Other adverse effects** No further relevant information available.

# **SECTION 13: Disposal considerations**

# · 13.1 Waste treatment methods

# · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Trade name: Defense Technology 40MM Ground Marker Blue Colored Smoke - 300 Meters

(Cont'd. from page 10)

Revision: July 21, 2015

# Uncleaned packaging:

· Recommendation: Disposal must be made according to local official regulations.

SECTION 14: Transport information	
· 14.1 UN-Number	
· DOT, ADR, IMDG	UN0303
·IATA	FORBIDDEN
<ul> <li>14.2 UN proper shipping name</li> </ul>	
· DOT, IMDG	Ammunition Smoke with or without burster, expelling
	charge or propelling charge
ADR	0303, 1.4G, Ammunition Smoke with or without burster,
	expelling charge or propelling charge
	FORBIDDEN
<ul> <li>14.3 Transport hazard class(es)</li> </ul>	
DOT, ADR, IMDG	
1.4	
Class	1.4
Label	1.4G
ΙΑΤΑ	
Class	FORBIDDEN
Label	-
14.4 Packing group	
DOT, ADR, IMDG	II
IATA	FORBIDDEN
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
EMS Number:	F-A,S-Q
Segregation groups	Chlorates
14.7 Transport in bulk according to Annex II	
Marpol and the IBC Code	Not applicable.
· UN "Model Regulation":	UN0303, 0303, 1.4G, II

# **SECTION 15: Regulatory information**

 $\cdot$  15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  United States (USA)

· SARA

# · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

(Cont'd. on page 12)

Revision: July 21, 2015

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date July 21, 2015

Trade name: Defense Technology 40MM Ground Marker Blue Colored Smoke - 300 Meters

	(Cont'd. from page
Section 313 (Specific toxic chemical listings):	
None of the ingredients are listed.	
· TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
· Proposition 65 (California):	
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients are listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients are listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients are listed.	
· Carcinogenic Categories	
· EPA (Environmental Protection Agency)	
598-62-9 manganese carbonate	
· IARC (International Agency for Research on Cancer)	
None of the ingredients are listed.	
· TLV (Threshold Limit Value established by ACGIH)	
57-50-1 sucrose, pure	A
7429-90-5 aluminium powder (pyrophoric)	P
NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients are listed.	
· Canada	
· Canadian Domestic Substances List (DSL)	
All ingredients are listed.	
· Canadian Ingredient Disclosure list (limit 0.1%)	
598-62-9 manganese carbonate	
Canadian Ingredient Disclosure list (limit 1%)	
100-21-0 terephthalic acid	
• Other regulations, limitations and prohibitive regulations	
Substances of very high concern (SVHC) according to REACH, Artic	le 57
None of the ingredients are listed.	

(Cont'd. on page 13)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date July 21, 2015

Revision: July 21, 2015

### Trade name: Defense Technology 40MM Ground Marker Blue Colored Smoke - 300 Meters

(Cont'd. from page 12)

SECTION 1	6: Other information
This informatio	n is based on our present knowledge. However, this shall not constitute a guarantee for an t features and shall not establish a legally valid contractual relationship.
Relevant phra	Ses
	e; mass explosion hazard.
H228 Flammab	
H250 Catches	fire spontaneously if exposed to air.
H261 In contac	t with water releases flammable gases.
H271 May caus	se fire or explosion; strong oxidiser.
	nsify fire; oxidiser.
H302 Harmful i	f swallowed.
H332 Harmful i	f inhaled.
H411 Toxic to a	aquatic life with long lasting effects.
	and acronyms:
	opéen sur le transport des marchandises dangereuses par Route (European Agreement concerning t age of Dangerous Goods by Road)
	al Maritime Code for Dangerous Goods
DOT: US Departme	ent of Transportation
	I Air Transport Association
	monised System of Classification and Labelling of Chemicals Conference of Governmental Industrial Hygienists
	n Inventory of Existing Commercial Chemical Substances
	n List of Notified Chemical Substances
	stracts Service (division of the American Chemical Society)
	re Protection Association (USA) Materials Identification System (USA)
	e Hazardous Materials Information System (Canada)
	-Effect Level (REACH)
	No-Effect Concentration (REACH)
LC50: Lethal conce LD50: Lethal dose,	Entration, 50 percent
Expl. 1.1: Explosive	
Expl. 1.4: Explosive	
	mable solids, Hazard Category 2
	oric Solids, Hazard Category 1 bstances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 2
	ng Solids, Hazard Category 1
	ng Solids, Hazard Category 2 e toxicity, Hazard Category 4
	Hazardous to the aquatic environment - Chronic Hazard, Category 2
	Hazardous to the aquatic environment - Chronic Hazard, Category 3
Sources	
SDS Prepared	uy.
ChemTel Inc.	ride Avenue
1305 North Flo	
	NUSA 33602-2902
	America 1-888-255-3924 Intl. +01 813-248-0573
website: www.	chemtelinc.com