according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

1 Identification

· Product identifier

· Trade name: NIK Test D 1st Ampoule · Product code: 800-6074 (1006152)

· Recommended use and restriction on use

· Recommended use: Forensics.

· Restrictions on use: Contact manufacturer/supplier

Details of the supplier of the Safety Data Sheet

· Manufacturer/Supplier:

Safariland, LLC

13386 International Parkway Jacksonville, FL 32218 Customer Care (800) 347-1200



ChemTel Inc.

(800)255-3924 (North America)

+1 (813)248-0585 (International)



2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

Eye Irrit. 2A H319 Causes serious eye irritation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:





GHS02 GHS07

· Signal word: Danger

· Hazard statements:

H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation.

· Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash thoroughly after handling.

P280 Wear protective gloves and eye protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

(Cont'd. on page 2)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 1st Ampoule

(Cont'd. of page 1)

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use for extinction: Alcohol resistant foam or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:			
64-17-5		>60%	
	Flam. Liq. 2, H225 Eye Irrit. 2A, H319		
100-10-7	4-dimethylaminobenzaldehyde	3-7%	
	Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319		

Additional information: For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

- Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

If experiencing respiratory symptoms: Call a doctor.

· After skin contact:

Immediately remove any clothing soiled by the product.

Immediately rinse with water.

If skin irritation continues, consult a doctor.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

Most important symptoms and effects, both acute and delayed:

Headache

Causes eye irritation.

Causes mild skin irritation.

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

Dizziness

Disorientation

Unconsciousness

(Cont'd. on page 3)

Page: 3/10

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 1st Ampoule

(Cont'd. of page 2)

· **Danger:** No relevant information available.

· Indication of any immediate medical attention and special treatment needed:

If medical advice is needed, have product container or label at hand.

Medical supervision for at least 48 hours.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: None.
- · Special hazards arising from the substance or mixture

Highly flammable liquid and vapor.

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information:

Eliminate all ignition sources if safe to do so.

Cool endangered receptacles with water spray.

Use large quantities of foam as it is partially destroyed by the product.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Keep away from ignition sources.

Protect from heat.

· Environmental precautions

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Methods and material for containment and cleaning up

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders). Pick up mechanically.

Dispose contaminated material as waste according to item 13.

Send for recovery or disposal in suitable receptacles.

Used rags or other cleaning materials should be soaked with water and placed in a sealed container.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

(Cont'd. on page 4)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 1st Ampoule

(Cont'd. of page 3)

- · Handling
- Precautions for safe handling:

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

· Information about protection against explosions and fires:

Highly flammable liquid and vapor.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Flammable gas-air mixtures may be formed in empty containers/receptacles.

Fumes can combine with air to form an explosive mixture.

- · Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles:

Store in a cool location.

Provide ventilation for receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

Do not store together with acids.

- · Further information about storage conditions: Keep containers tightly sealed.
- · Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:			
64-17-5 Ethanol			
PEL (USA)	Long-term value: 1900 mg/m³, 1000 ppm		
REL (USA)	Long-term value: 1900 mg/m³, 1000 ppm		
TLV (USA)	Short-term value: 1880 mg/m³, 1000 ppm		
EL (Canada)	Short-term value: 1000 ppm		
EV (Canada) Long-term value: 1,900 mg/m³, 1,000 ppm			
LMPE (Mexico) Long-term value: 1000 ppm A3			

- Exposure controls
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Pregnant women should strictly avoid inhalation or skin contact.

Engineering controls: Provide adequate ventilation.

(Cont'd. on page 5)

Page: 5/10

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

(Cont'd. of page 4)

Trade name: NIK Test D 1st Ampoule

· Breathing equipment:

Not required under normal conditions of use.

Use suitable respiratory protective device when aerosol or mist is formed.

Use suitable respiratory protective device when high concentrations are present.

For spills, respiratory protection may be advisable.

Protection of hands:



Protective gloves

· Material of gloves

Nitrile rubber, NBR

Butyl rubber, BR

Neoprene gloves Natural rubber, NR

Sensibilization by the components in the glove materials is possible.

· Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

- · Body protection: Protection may be required for spills.
- Limitation and supervision of exposure into the environment

No relevant information available.

Risk management measures

See Section 7 for additional information.

No relevant information available.

9 Physical and chemical properties

Appearance:		
Form:	Liquid	
Color:	Colorless	
Odor:	Alcohol-like	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Melting point/Melting range:	Not determined.	
Boiling point/Boiling range:	78 °C (172.4 °F)	
Flash point:	13 °C (55.4 °F)	
Flammability (solid, gaseous):	Not applicable.	
Auto-ignition temperature:	Not determined.	
Decomposition temperature:	Not determined.	

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 1st Ampoule

	(Cont'd. of page		
Danger of explosion:	Product is not explosive. However, formation of explosive air vapor mixtures are possible.		
Explosion limits			
Lower:	3.5 Vol %		
Upper:	15.0 Vol %		
Oxidizing properties:	Non-oxidizing.		
Vapor pressure at 20 °C (68 °F):	59 hPa (44.3 mm Hg)		
Density at 20 °C (68 °F):	0.8 g/cm³ (6.68 lbs/gal)		
Relative density:	Not determined.		
Vapor density:	Not determined.		
Evaporation rate:	Not determined.		
Solubility in / Miscibility with			
Water:	Fully miscible.		
Partition coefficient (n-octanol/water	er): Not determined.		
Viscosity			
Dynamic:	Not determined.		
Kinematic:	Not determined.		
Other information	No relevant information available.		

10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability:
- Thermal decomposition / conditions to be avoided: Keep away from heat and direct sunlight.
- · Possibility of hazardous reactions

Highly flammable liquid and vapor.

Reacts violently with oxidizing agents.

Reacts with acids.

Used empty containers may contain product gases which form explosive mixtures with air.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.

Toxic fumes may be released if heated above the decomposition point.

· Conditions to avoid

Keep ignition sources away - Do not smoke.

Store away from oxidizing agents.

Keep away from heat and direct sunlight.

Incompatible materials

Acids.

Oxidizers

· Hazardous decomposition products

Under fire conditions only:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Page: 7/10

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 1st Ampoule

(Cont'd. of page 6)

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- On the skin:

Causes mild skin irritation.

Based on available data, the classification criteria are not met.

- · On the eye: Causes eye irritation.
- · Sensitization: Based on available data, the classification criteria are not met.
- · IARC (International Agency for Research on Cancer):

64-17-5 Ethanol

|1

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.

Inhalation.

Eye contact.

Skin contact.

- · Acute effects (acute toxicity, irritation and corrosivity): Causes serious eye irritation.
- · Repeated dose toxicity: No relevant information available.
- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- Carcinogenicity: Based on available data, the classification criteria are not met.
- Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure: Based on available data, the classification criteria are not met.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity No relevant information available.
- · Persistence and degradability Biodegradable.
- · Bioaccumulative potential: No relevant information available.
- · Mobility in soil: No relevant information available.
- Additional ecological information
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Due to available data on eliminability/decomposition and bioaccumulation potential, a prolonged damage of the environment is unlikely.

Other adverse effects No relevant information available.

Page: 8/10

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 1st Ampoule

(Cont'd. of page 7)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Incinerate in accordance with local, state and federal regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- Uncleaned packagings
- Recommendation: Disposal must be made according to official regulations.

4 Transport information	
· UN-Number · DOT, ADR/RID/ADN, IMDG, IATA	UN1170
· UN proper shipping name · DOT · ADR/RID/ADN	Ethanol solutions 1170 ETHANOL SOLUTION (ETHYL ALCOHO SOLUTION)
·IMDG	ETHANOĹ SOLUTION (ETHYL ALCOHO SOLUTION)
· IATA · Transport hazard class(es)	ETHANOL SOLUTION
DOT	
200000000	
· Class · Label	3 3
ADR/RID/ADN	
· Class · Label	3 (F1) 3
· IMDG, IATA	
A 1	3
· Class	•

Page: 9/10

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 1st Ampoule

		(Cont'd. of page 8
Packing group DOT, ADR/RID/ADN, IMDG, IATA	II	
Environmental hazards Marine pollutant:	No	
Special precautions for user	Warning: Flammable liquids	
Danger code (Kemler): EMS Number:	33 F-E.S-D	

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt.

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

Ethanol - listing refers specifically to alcoholic beverage consumption and is not applicable for product.

64-17-5 Ethanol

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

Ethanol - listing refers specifically to alcoholic beverage consumption and is not applicable for product.

64-17-5 Ethanol

EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

64-17-5 Ethanol

· Canadian Domestic Substances List (DSL):

(Cont'd. on page 10)

Page: 10/10

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 1st Ampoule

(Cont'd. of page 9)

All ingredients listed on DSL or NDSL.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety & Health Administration

Flam. Liq. 2: Flammable liquids – Category 2 Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

· Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

1 Identification

· Product identifier

· Trade name: NIK Test D 2nd Ampoule · Product code: 800-6074 (1006152)

· Recommended use and restriction on use

· Recommended use: Forensics.

· Restrictions on use: Contact manufacturer/supplier

Details of the supplier of the Safety Data Sheet

· Manufacturer/Supplier:

Safariland, LLC

13386 International Parkway Jacksonville, FL 32218 Customer Care (800) 347-1200

Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America) +1 (813)248-0585 (International)



2 Hazard(s) identification

· Classification of the substance or mixture

Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms:





GHS05 GHS07

· Signal word: Danger

· Hazard statements:

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

· Precautionary statements:

P234 Keep only in original container.
P260 Do not breathe mist/vapors/spray.
P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves and eye protection.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

(Cont'd. on page 2)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 2nd Ampoule

(Cont'd. of page 1)

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.
P363 Wash contaminated clothing before reuse.
P390 Absorb spillage to prevent material damage.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P406 Store in corrosive resistant container with a resistant inner liner.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:

7647-01-0 hydrochloric acid

30-60%

Met. Corr.1, H290; Skin Corr. 1B, H314; Eye Dam. 1, H318

Acute Tox. 4, H302; STOT SE 3, H335

· Additional information: For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

- Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately remove any clothing soiled by the product.

Immediately rinse with water.

If skin irritation is experienced, consult a doctor.

Seek immediate help for blistering or open wounds.

· After eye contact:

Protect unharmed eye.

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

· Most important symptoms and effects, both acute and delayed:

Coughing

Breathing difficulty

Strong caustic effect on skin and mucous membranes.

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

· Danger:

Danger of gastric perforation.

Danger of impaired breathing.

Causes serious eye damage.

(Cont'd. on page 3)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 2nd Ampoule

(Cont'd. of page 2)

May cause respiratory irritation.

May be harmful if inhaled.

Indication of any immediate medical attention and special treatment needed:

If necessary oxygen respiration treatment.

If medical advice is needed, have product container or label at hand.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- For safety reasons unsuitable extinguishing agents: None.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information: No relevant information available.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up

Use limestone to neutralize and/or absorb spill.

Clean the affected area carefully; suitable cleaners are:

Warm water

Dispose contaminated material as waste according to item 13.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- ·Handling
- Precautions for safe handling:

Use only in well ventilated areas.

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.

(Cont'd. on page 4)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 2nd Ampoule

(Cont'd. of page 3)

· Information about storage in one common storage facility:

Store away from foodstuffs.

Do not store together with alkalis (caustic solutions).

Store away from metals.

- · Further information about storage conditions: Keep containers tightly sealed.
- · Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:				
7647-01-0 hydrochloric acid				
PEL (USA)	Ceiling limit value: 7 mg/m³, 5 ppm			
REL (USA)	Ceiling limit value: 7 mg/m³, 5 ppm			
TLV (USA)	TLV (USA) Ceiling limit value: 2.98 mg/m³, 2 ppm			
EL (Canada)	EL (Canada) Ceiling limit value: 2 ppm			
EV (Canada)	EV (Canada) Ceiling limit value: 2 ppm			
LMPE (Mexico)	LMPE (Mexico) Ceiling limit value: 2 ppm			
	A4			

- Exposure controls
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

- Engineering controls: Provide adequate ventilation.
- Breathing equipment:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device when aerosol or mist is formed.

For spills, respiratory protection may be advisable.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

Neoprene gloves

Fluorocarbon rubber (Viton)

Natural rubber, NR

(Cont'd. on page 5)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 2nd Ampoule

(Cont'd. of page 4)

Sensibilization by the components in the glove materials is possible.

Not suitable are gloves made of the following materials:

PVA gloves

Leather gloves

· Eye protection:

Contact lenses should not be worn.



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

- · Body protection: Protection may be required for spills.
- Limitation and supervision of exposure into the environment No relevant information available.
- · Risk management measures No relevant information available.

Information on basic physical a	nd chemical properties			
Appearance:	···			
Form: Liquid				
Color:	Colorless Pungent			
Odor:				
Odor threshold:	Not determined.	Not determined.		
pH-value at 20 °C (68 °F):	< 1			
Melting point/Melting range:	Not determined.			
Boiling point/Boiling range:	Not determined.			
Flash point:	Not applicable.			
Flammability (solid, gaseous):	Not applicable.			
Auto-ignition temperature:	Not determined.			
Decomposition temperature:	Not determined.			
Danger of explosion:	Product does not present an explosion hazard.			
Explosion limits				
Lower:	Not determined.			
Upper:	Not determined.			
Oxidizing properties:	Non-oxidizing.			
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)			
Density at 20 °C (68 °F):	1.16 g/cm³ (9.68 lbs/gal)			
Relative density: Not determined.				
Vapor density:	Not determined.			
Evaporation rate:	Not determined.			
Solubility in / Miscibility with				
Water:	Fully miscible.			

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 2nd Ampoule

(Cont'd. of page 5)

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity

Dynamic: Not determined. **Kinematic:** Not determined.

• Other information No relevant information available.

10 Stability and reactivity

- · Reactivity: No relevant information available.
- Chemical stability:
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point.

Reacts with alkali (lyes).

Reacts with strong oxidizing agents.

Reacts with amines.

Corrosive action on metals.

Reacts with metals forming hydrogen.

- · Conditions to avoid No relevant information available.
- · Incompatible materials Alkalis.
- · Hazardous decomposition products

Chlorine compounds

Hydrogen chloride (HCI)

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification:

7647-01-0 hydrochloric acid

Oral LD50 900 mg/kg (rabbit)

- Primary irritant effect:
- · On the skin: Strong caustic effect on skin and mucous membranes.
- · On the eye: Strong caustic effect.
- · Sensitization: No sensitizing effects known.
- IARC (International Agency for Research on Cancer):

7647-01-0 hydrochloric acid

3

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

(Cont'd. on page 7)

Page: 7/10

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 2nd Ampoule

(Cont'd. of page 6)

Ingestion.

Inhalation.

Eye contact.

Skin contact.

· Acute effects (acute toxicity, irritation and corrosivity):

May be harmful if inhaled.

Irritating to respiratory system.

Causes severe skin burns and eye damage.

- Repeated dose toxicity: No relevant information available.
- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure: May cause respiratory irritation.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity The product contains materials that are harmful to the environment.
- Persistence and degradability A part of the components is biodegradable.
- · Bioaccumulative potential: Does not accumulate in organisms
- · Mobility in soil: No relevant information available.
- · Ecotoxical effects:
- · Remark: After neutralization a reduction of the harming action may be recognized
- Additional ecological information
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. If the dilution of the use-level pH-value is considerably increased after use, the aqueous waste, emptied into drains, is only low water-dangerous.

• Other adverse effects No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- Uncleaned packagings
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water only.

Page: 8/10

Safety Data Sheet according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 2nd Ampoule

(Cont'd. of page 7)

4 Transport information	
· UN-Number · DOT, ADR/RID/ADN, IMDG, IATA	UN1789
· UN proper shipping name · DOT · ADR/RID/ADN · IMDG, IATA	Hydrochloric acid, solution 1789 HYDROCHLORIC ACID, solution HYDROCHLORIC ACID, solution
· Transport hazard class(es)	
· DOT	
20-30- 20-30-00-18	
· Class	8
· Label	8
· ADR/RID/ADN	
· Class	8 (C1)
· Label	8
· IMDG, IATA	
· Class	8
· Label	8
Packing group DOT, ADR/RID/ADN, IMDG, IATA	II
· Environmental hazards · Marine pollutant:	No
· Special precautions for user · Danger code (Kemler): · EMS Number: · Segregation groups	Warning: Corrosive substances 80 F-A,S-B Acids
Transport in bulk according to Anne MARPOL73/78 and the IBC Code	ex II of Not applicable.

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or (Cont'd. on page 9) mixture

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 2nd Ampoule

(Cont'd. of page 8)

- United States (USA)
- ·SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

7647-01-0 hydrochloric acid

Section 313 (Specific toxic chemical listings):

7647-01-0 hydrochloric acid

TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt.

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

7647-01-0 hydrochloric acid

3

· Canadian Domestic Substances List (DSL):

All ingredients listed on DSL or NDSL.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety & Health Administration

Met. Corr.1: Corrosive to metals - Category 1

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

(Cont'd. on page 10)

Page: 10/10

Safety Data Sheet according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 2nd Ampoule

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Cont'd. of page 9)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

1 Identification

· Product identifier

· Trade name: NIK Test D 3rd Ampoule · Product code: 800-6074 (1006152)

· Recommended use and restriction on use

· Recommended use: Forensics.

· Restrictions on use: Contact manufacturer/supplier

Details of the supplier of the Safety Data Sheet

· Manufacturer/Supplier:

Safariland, LLC

13386 International Parkway Jacksonville, FL 32218 Customer Care (800) 347-1200

Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America) +1 (813)248-0585 (International)



2 Hazard(s) identification

· Classification of the substance or mixture

Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



GHS05

· Signal word: Danger

· Hazard statements:

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

· Precautionary statements:

P234 Keep only in original container.
P260 Do not breathe mist/vapors/spray.
P264 Wash thoroughly after handling.

P280 Wear protective gloves and eye protection.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

(Cont'd. on page 2)

>60%

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 3rd Ampoule

	(Cont'd. of page 1)
P310	Immediately call a poison center/doctor.
P363	Wash contaminated clothing before reuse.
P390	Absorb spillage to prevent material damage.
P405	Store locked up.
P406	Store in corrosive resistant container with a resistant inner liner.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:

7664-38-2 Phosphoric acid

Net. Corr.1, H290; Skin Corr. 1B, H314; Eye Dam. 1, H318

· Additional information: For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

- Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately rinse with water.

If skin irritation continues, consult a doctor.

Seek immediate help for blistering or open wounds.

After eye contact:

Protect unharmed eye.

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

Most important symptoms and effects, both acute and delayed:

Strong caustic effect on skin and mucous membranes.

Gastric or intestinal disorders when ingested.

· Danger:

Danger of gastric perforation.

Causes serious eye damage.

May be harmful if inhaled.

· Indication of any immediate medical attention and special treatment needed:

If medical advice is needed, have product container or label at hand.

5 Fire-fighting measures

Extinguishing media

(Cont'd. on page 3)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 3rd Ampoule

(Cont'd. of page 2)

- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · For safety reasons unsuitable extinguishing agents: None.
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information: No relevant information available.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

For large spills, wear protective clothing.

For large spills, use respiratory protective device against the effects of fumes/dust/aerosol. Ensure adequate ventilation.

- Environmental precautions Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up

Use limestone to neutralize and/or absorb spill.

Dispose contaminated material as waste according to item 13.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- ·Handling
- · Precautions for safe handling:

Avoid splashes or spray in enclosed areas.

Prevent formation of aerosols.

Use only in well ventilated areas.

- · Information about protection against explosions and fires: No special measures required.
- Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Unsuitable material for receptacle: aluminium.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

Store away from metals.

Do not store together with alkalis (caustic solutions).

· Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

(Cont'd. on page 4)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 3rd Ampoule

(Cont'd. of page 3)

· Control parameters

· Components with limit values that require monitoring at the workplace:			
7664-38-2 Phos	7664-38-2 Phosphoric acid		
PEL (USA)	Long-term value: 1 mg/m³		
REL (USA)	Short-term value: 3 mg/m³ Long-term value: 1 mg/m³		
TLV (USA)	Short-term value: 3 mg/m³ Long-term value: 1 mg/m³		
EL (Canada)	Short-term value: 3 mg/m³ Long-term value: 1 mg/m³		
EV (Canada)	Short-term value: 3 mg/m³ Long-term value: 1 mg/m³		
LMPE (Mexico)	Short-term value: 3 mg/m³ Long-term value: 1 mg/m³		

Exposure controls

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Do not inhale gases / fumes / aerosols.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Engineering controls: Provide adequate ventilation.
- Breathing equipment:

Not required under normal conditions of use.

Use suitable respiratory protective device when aerosol or mist is formed.

For spills, respiratory protection may be advisable.

Protection of hands:



Protective gloves

· Material of gloves

Nitrile rubber, NBR

Neoprene gloves

Butyl rubber, BR

Fluorocarbon rubber (Viton)

Natural rubber, NR

Sensibilization by the components in the glove materials is possible.

· Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

- · Body protection: Protective work clothing
- Limitation and supervision of exposure into the environment

(Cont'd. on page 5)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 3rd Ampoule

(Cont'd. of page 4)

No relevant information available.

Risk management measures

See Section 7 for additional information.

No relevant information available.

9 Physical and chemical properties

· Information on	basic ph	vsical and	chemical	properties

· Appearance:

Form: Liquid Colorless
• Odor: Acrid

· Odor threshold: Not determined.

pH-value: Not determined.
Melting point/Melting range: Not determined.
Boiling point/Boiling range: Not determined.

· Flash point: Not applicable.

· Flammability (solid, gaseous): Not applicable.

· Auto-ignition temperature: Not determined.· Decomposition temperature: Not determined.

• **Danger of explosion:** Product does not present an explosion hazard.

· Explosion limits

Lower: Not determined.
Upper: Not determined.
Oxidizing properties: Non-oxidizing.

· Vapor pressure at 20 °C (68 °F): 23 hPa (17.3 mm Hg)

• Density at 20 °C (68 °F): 1.75 g/cm³ (14.6 lbs/gal)

Relative density: Not determined.
 Vapor density: Not determined.
 Evaporation rate: Not determined.

· Solubility in / Miscibility with

Water: Fully miscible.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity

Dynamic: Not determined. **Kinematic:** Not determined.

• Other information No relevant information available.

10 Stability and reactivity

· Reactivity: No relevant information available.

(Cont'd. on page 6)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 3rd Ampoule

(Cont'd. of page 5)

- · Chemical stability:
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· Possibility of hazardous reactions

Reacts with alkali (lyes).

Reacts with metals forming hydrogen.

Corrosive action on metals.

Toxic fumes may be released if heated above the decomposition point.

- · Conditions to avoid No relevant information available.
- Incompatible materials

Alkalis.

Metals.

· Hazardous decomposition products

Under fire conditions only:

Phosphorus oxides (e.g. P2O5)

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.
- LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- · On the skin: Strong caustic effect on skin and mucous membranes.
- · On the eye: Strong caustic effect.
- · Sensitization: No sensitizing effects known.
- · IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.

Inhalation.

Eye contact.

Skin contact.

- · Acute effects (acute toxicity, irritation and corrosivity): Causes severe skin burns and eye damage.
- · Repeated dose toxicity: No relevant information available.
- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure: Based on available data, the classification criteria are not met.
- STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

(Cont'd. on page 7)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 3rd Ampoule

(Cont'd. of page 6)

- ·Toxicity
- Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- · Mobility in soil: No relevant information available.
- · Ecotoxical effects:
- · Remark: After neutralization a reduction of the harming action may be recognized
- Additional ecological information
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. If the dilution of the use-level pH-value is considerably increased after use, the aqueous waste, emptied into drains, is only low water-dangerous.

• Other adverse effects No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Dilute concentrate with water and neutralize afterwards with suitable alkali material (sodium hydroxide solution, lime). The formed neutral salts are relatively environment-friendly.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- Uncleaned packagings
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information	
· UN-Number · DOT, ADR/RID/ADN, IMDG, IATA	UN1805
UN proper shipping name	
·DOT	Phosphoric acid solution
· ADR/RID/ADN	1805 PHOSPHORIC ACID, SOLUTION
· IMDG, IATA	PHOSPHORIC ACID, SOLUTION

(Cont'd. on page 8)

Page: 8/9

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 3rd Ampoule

(Cont'd. of page 7) · DOT · Class 8 · Label 8 · ADR/RID/ADN · Class 8 (C1) · Label · IMDG, IATA 8 · Class · Label 8 · Packing group DOT, ADR/RID/ADN, IMDG, IATA Ш · Environmental hazards · Marine pollutant: No Special precautions for user Warning: Corrosive substances · Danger code (Kemler): · EMS Number: F-A,S-B · Segregation groups Acids Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

(Cont'd. on page 9)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 05, 2019

Trade name: NIK Test D 3rd Ampoule

7664-38-2 Phosphoric acid

(Cont'd. of page 8)

· TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt.

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· Canadian Domestic Substances List (DSL):

All ingredients listed on DSL or NDSL.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety & Health Administration

Met. Corr.1: Corrosive to metals - Category 1

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

· Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com