



SAFETY DATA SHEET

1. Identification

Product identifier Copper-Coat® Gasket Compound

Other means of identification

Product code 401504, 401516

Recommended use Gasket sealing compound

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.
Address 885 Louis Dr.
Warminster, PA 18974 US

Telephone

General Information 215-674-4300

Technical Assistance 800-521-3168

Customer Service

800-272-4620

24-Hour Emergency (CHEMTREC) 800-424-9300 (US)

703-527-3887 (International)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Skin corrosion/irritation	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 1
OSHA defined hazards	Not classified.	

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Causes skin irritation. May cause drowsiness or dizziness. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wash thoroughly after handling. Wear protective gloves/eye protection/face protection. Avoid release to the environment.

Response

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical attention. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. In case of fire: Do not use water jet as an extinguisher, as this will spread the fire. Collect spillage.

Storage

Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal	Dispose of contents/container in accordance with local/regional/national regulations.
Hazard(s) not otherwise classified (HNOC)	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information

38.94% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 30.54% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
n-Heptane		142-82-5	20 - 30
3-Methylhexane		589-34-4	10 - 20
Methylcyclohexane		108-87-2	10 - 20
Naphtha (petroleum), hydrotreated light		64742-49-0	10 - 20
Cyclohexane		110-82-7	5 - 10
Glycerol ester of partially hydrogenated wood rosin		65997-13-9	5 - 10
Copper		7440-50-8	1 - 3
Distillates (petroleum), hydrotreated heavy naphthenic		64742-52-5	< 1
2-Methylhexane		591-76-4	< 0.2
3-Ethylpentane		617-78-7	< 0.2
n-Octane		111-65-9	< 0.2

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.
Ingestion	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
General fire hazards	Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Take precautionary measures against static discharges. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Avoid release to the environment. Use care in handling/storage. For product usage instructions, please see the product label.
Conditions for safe storage, including any incompatibilities	Keep away from heat, sparks and open flame. Eliminate sources of ignition. Avoid spark promoters. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Copper (CAS 7440-50-8)	PEL	1 mg/m ³ 0.1 mg/m ³	Dust and mist. Fume.
Cyclohexane (CAS 110-82-7)	PEL	1050 mg/m ³ 300 ppm	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m ³ 2000 mg/m ³ 500 ppm	Mist.
Methylcyclohexane (CAS 108-87-2)	PEL	2000 mg/m ³ 500 ppm	
n-Heptane (CAS 142-82-5)	PEL	2000 mg/m ³ 500 ppm	
n-Octane (CAS 111-65-9)	PEL	2350 mg/m ³	

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
		500 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
2-Methylhexane (CAS 591-76-4)	STEL	500 ppm	
	TWA	400 ppm	
3-Ethylpentane (CAS 617-78-7)	STEL	500 ppm	
	TWA	400 ppm	
3-Methylhexane (CAS 589-34-4)	STEL	500 ppm	
	TWA	400 ppm	
Cyclohexane (CAS 110-82-7)	TWA	100 ppm	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
Methylcyclohexane (CAS 108-87-2)	STEL	500 ppm	
	TWA	400 ppm	
n-Heptane (CAS 142-82-5)	STEL	500 ppm	
	TWA	400 ppm	
n-Octane (CAS 111-65-9)	TWA	300 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Copper (CAS 7440-50-8)	TWA	1 mg/m3	Dust and mist.
Cyclohexane (CAS 110-82-7)	TWA	1050 mg/m3	
		300 ppm	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
Methylcyclohexane (CAS 108-87-2)	TWA	1600 mg/m3	
		400 ppm	
n-Heptane (CAS 142-82-5)	Ceiling	1800 mg/m3	
		440 ppm	
	TWA	350 mg/m3	
		85 ppm	
n-Octane (CAS 111-65-9)	Ceiling	1800 mg/m3	
		385 ppm	
	TWA	350 mg/m3	
		75 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection	
Hand protection	Wear protective gloves such as: Nitrile. Polyvinyl alcohol (PVA). Viton®.
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Color	Copper.
Odor	Hydrocarbon-like.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-195.9 °F (-126.6 °C) estimated
Initial boiling point and boiling range	201.2 °F (94 °C) estimated
Flash point	30 °F (-1.1 °C) Tag Closed Cup
Evaporation rate	Moderate.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.1 % estimated
Flammability limit - upper (%)	6.7 % estimated
Vapor pressure	48.3 hPa estimated
Vapor density	> 1 (air = 1)
Relative density	0.76
Solubility (water)	Insoluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	539.6 °F (282 °C) estimated
Decomposition temperature	Not available.
Viscosity (kinematic)	Not available.
Percent volatile	74.9 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.
Incompatible materials	Acids. Oxidizing agents. Halogenated materials. Chromates. Perchlorates. Peroxides. Oxygen.
Hazardous decomposition products	Carbon oxides. Phenolic compounds. Aldehydes. Carboxylic acids. Formaldehyde.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics Headache. May cause drowsiness and dizziness. Nausea, vomiting. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Narcotic effects.

Product	Species	Test Results
Copper-Coat® Gasket Compound		
Acute		
Dermal		
LD50	Rabbit	2670 mg/kg estimated
Inhalation		
LC50	Rat	79 mg/l, 4 Hours estimated
Oral		
LD50	Rat	6605 mg/kg estimated

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Based on available data, the classification criteria are not met.

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Product	Species	Test Results
Copper-Coat® Gasket Compound		
Aquatic		
Crustacea	EC50 Daphnia	8.2421 mg/l, 48 hours estimated
<i>Acute</i>		
Fish	LC50 Fish	9.2781 mg/l, 96 hours estimated
Components		
Species		
Test Results		
Copper (CAS 7440-50-8)		
Aquatic		
Crustacea	EC50 Water flea (Daphnia magna)	0.036 mg/l, 48 hours
Fish	LC50 Fathead minnow (Pimephales promelas)	0.0319 - 0.0544 mg/l, 96 hours

Components	Species	Test Results
Cyclohexane (CAS 110-82-7)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 23.03 - 42.07 mg/l, 96 hours
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)		
Aquatic		
<i>Acute</i>		
Fish	LC50	<i>Pimephales promelas</i> > 30000 mg/l, 96 hours
Glycerol ester of partially hydrogenated wood rosin (CAS 65997-13-9)		
<i>Acute</i>		
Other		<i>Pseudomonas putida</i> 4797 mg/l
Aquatic		
<i>Acute</i>		
Fish	LC50	Carp (<i>Cyprinus carpio</i>) 2600 mg/l
Methylcyclohexane (CAS 108-87-2)		
Aquatic		
Fish	LC50	Striped bass (<i>Morone saxatilis</i>) 5.8 mg/l, 96 hours
n-Heptane (CAS 142-82-5)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 2.1 - 2.98 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Cyclohexane	3.44
Methylcyclohexane	3.61
n-Heptane	4.66
n-Octane	5.18

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products If discarded, this product is considered a RCRA ignitable waste, D001. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1993
UN proper shipping name	Flammable liquids, n.o.s. (Heptanes, Cyclohexane), Limited Quantity, MARINE POLLUTANT (Heptanes, Copper)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Environmental hazards	
Marine pollutant	Yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Special provisions	IB2, T7, TP1, TP8, TP28
Packaging exceptions	150
Packaging non bulk	202
Packaging bulk	242

IATA

UN number	UN1993
UN proper shipping name	Flammable liquid, n.o.s. (Heptanes, Cyclohexane), Limited Quantity
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	Yes
ERG Code	3H
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

IMDG

UN number	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (Heptanes, Cyclohexane), LIMITED QUANTITY, MARINE POLLUTANT
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	Yes
EmS	F-E, S-E
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Copper (CAS 7440-50-8)

Cyclohexane (CAS 110-82-7)

CERCLA Hazardous Substance List (40 CFR 302.4)

Copper (CAS 7440-50-8)

Listed.

Cyclohexane (CAS 110-82-7)

Listed.

CERCLA Hazardous Substances: Reportable quantity

Copper (CAS 7440-50-8)

5000 LBS

Cyclohexane (CAS 110-82-7)

1000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA) Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - Yes
Hazard categories Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Copper (CAS 7440-50-8)
Glycerol ester of partially hydrogenated wood rosin (CAS 65997-13-9)
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)
Not listed.

US. New Jersey Worker and Community Right-to-Know Act

3-Methylhexane (CAS 589-34-4)
Methylcyclohexane (CAS 108-87-2)
n-Heptane (CAS 142-82-5)
Copper (CAS 7440-50-8)
Cyclohexane (CAS 110-82-7)
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)
Talc (not containing asbestos fibers) (CAS 14807-96-6)

US. Massachusetts RTK - Substance List

3-Methylhexane (CAS 589-34-4)
Copper (CAS 7440-50-8)
Cyclohexane (CAS 110-82-7)
Methylcyclohexane (CAS 108-87-2)
n-Heptane (CAS 142-82-5)

US. Pennsylvania Worker and Community Right-to-Know Law

Cyclohexane (CAS 110-82-7)
Copper (CAS 7440-50-8)
Toluene (CAS 108-88-3)
3-Methylhexane (CAS 589-34-4)
Methylcyclohexane (CAS 108-87-2)
n-Heptane (CAS 142-82-5)

US. Rhode Island RTK

Copper (CAS 7440-50-8)
Cyclohexane (CAS 110-82-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2)	Listed: February 27, 1987
Cumene (CAS 98-82-8)	Listed: April 6, 2010
Ethylbenzene (CAS 100-41-4)	Listed: June 11, 2004
Naphthalene (CAS 91-20-3)	Listed: April 19, 2002

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2)	Listed: December 26, 1997
Toluene (CAS 108-88-3)	Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3)	Listed: August 7, 2009
------------------------	------------------------

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2)	Listed: December 26, 1997
-----------------------	---------------------------

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 51.100(s))	74.2 %
Consumer products (40 CFR 59, Subpt. C)	Not regulated

State

Consumer products	Not regulated
VOC content (CA)	74.2 %
VOC content (OTC)	74.2 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	06-01-2015
Prepared by	Allison Cho
Version #	01
Further information	CRC # 915
HMIS® ratings	Health: 1 Flammability: 3 Physical hazard: 0 Personal protection: B
NFPA ratings	Health: 1 Flammability: 3 Instability: 0
NFPA ratings	

Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.