



Safety Data Sheet

Dynatex® 49403 Super Glue

Section 1. Identification

Product Identifier Dynatex® 49403 Super Glue
Synonyms 49403AB12
Manufacturer Stock
Numbers 49403AB12

Recommended use Refer to Technical Information
Uses advised against Refer to Technical Information

Manufacturer Contact
Address Dynatex a division of Soudal Accumetric
350 Ring Road
Elizabethtown, KY, 42701
USA

Phone
(270) 769-3385

Emergency Phone
(800) 424-9300
CHEMTREC

Fax
(270) 769-6418

Section 2. Hazards Identification

Classification EYE DAMAGE/IRRITATION - Category 2A
FLAMMABLE LIQUIDS - Category 4
SKIN CORROSION/IRRITATION - Category 2
SPECIFIC TARGET ORGAN TOXICITY (Single Exposure) - Category 3

Signal Word Warning

Pictogram



Hazard Statements	Causes serious eye irritation Causes skin irritation Combustible liquid May cause respiratory irritation.
Precautionary Statements Response	Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If inhaled: Remove person to fresh air and keep comfortable for breathing. If on skin: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Read label before use. Take off contaminated clothing and wash it before reuse.
Prevention	Avoid breathing dust/fume/gas/mist/ vapors/spray. Keep away from heat. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. Wear eye protection/face protection. Wear protective gloves. Wear protective gloves/eye protection/face protection
Storage	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national /international regulations.
Ingredients of unknown toxicity	0%
Hazards not Otherwise Classified Additional Information	None known

Section 3. Ingredients

CAS	Ingredient Name	Weight %
7085-85-0	Ethyl-2-Cyanoacrylate	50% - 100%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Eye Contact	Rinse with water for 15 minutes. Obtain medical attention.
Skin Contact	Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use. Get medical attention if irritation develops.

Inhalation Remove to fresh air. If symptoms persist, obtain appropriate medical attention.
 Ingestion Do not induce vomiting. Keep individual calm. Obtain medical attention.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media Carbon Dioxide, Dry Chemical, Foam
 Use water fog to cool material in vicinity of fire.
 Unsuitable Extinguishing Media None known
 Special Fire Fighting Procedures None
 Unusual Fire or Explosion Hazards None known
 Hazardous Decomposition Products Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products:
 Irritating organic vapors
 oxides of carbon, sulfur and nitrogen.

Section 6. Accidental Release Measures

Steps to be taken in case of spill or release Observe all personal protection equipment recommendations. Soak up with inert absorbent. Store in a partly filled, closed container until disposal. Prevent product from entering drains. Local, state and federal regulations may apply to releases and disposal of this material, as well as those materials and items employed in cleanup of releases.

Section 7. Handling and Storage

Storage Store at or below 100F. Keep away from heat, sparks and open flames.
 Handling Avoid contact with skin, eyes, and clothing. Avoid breathing vapor or mist.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Ethyl-2-Cyanoacrylate	0.2 ppm	None	N/A
Personal Protective Equipment	Goggles, Gloves			
Eye Protection	Safety goggles or glasses with side shields are recommended.			
Skin Protection	Rubber, polyethylene, or neoprene gloves.			
Ventilation	Local exhaust ventilation is recommended to maintain vapor level below TLV.			
Respiratory Protection	Use NIOSH approved respirator for individuals who are sensitive.			

Section 9. Physical and Chemical Properties

Physical State	Liquid
Color	Clear
Odor	Characteristic
Odor Threshold	Not determined
Solubility	Not miscible
Partition coefficient Water/n-octanol	Not determined
VOC%	< 20 g/L (estimated)
Viscosity	Not determined
Specific Gravity	1.05
Density lbs/Gal	8.762
Pounds per Cubic Foot	N/A
Flash Point	87C 189F
FP Method	N/A
Ph	Not determined
Melting Point	Undetermined
Boiling Point	>150C >302F
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	Not determined
Flammability	Not applicable
Decomposition Temperature	Not determined
Auto-ignition Temperature	Product is not self igniting
Vapor Pressure	0.3 hPa @ 20C
Vapor Density	Not determined

Note The above information is not intended for use in preparing product specifications. Contact Soudal Accumetric before writing specifications.

Section 10. Stability and Reactivity

Chemical Stability Stable
Conditions to Avoid None known
Hazardous polymerization Will not occur
Hazardous Decomposition Products Oxides of carbon, sulfur, and nitrogen

Section 11. Toxicological Information

Special Hazard Information on Components No known applicable information.

Component Toxicology Information No known applicable information.

Section 12. Ecological Information

Fate and Effects in Waste Water Treatment Plants Complete information is not yet available.

Environmental Effects Complete information is not yet available.

Environmental Fate and Distribution Complete information is not yet available.

Section 13. Disposal

Waste Disposal Method We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

Section 14. Transport Information

UN Number 1993

UN Proper Shipping Name Combustible Liquid, NOS

DOT Classification N/A

Packing Group III

Air Shipment (IATA) Not subject to IATA regulations.

Ocean Shipment (IMDG) Not subject to IMDG code.

Section 15. Regulatory Information

TSCA Status All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

SARA Title III Section 302 Extremely Hazardous Substances None

SARA Titre III Section 304 CERCLA Substances dangereuses None

SARA Title III Section 312 Hazard Class Acute: Yes
Chronic: No
Fire: No

	Pressure: No
	Reactive: No
SARA Title III Section 313 Toxic Chemicals	Cumene Hydroperoxide (80-15-9)
California Proposition 65	This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: Saccharin. Proper usage necessitates no Proposition 65 warning.
New Jersey	Cumene hydroperoxide (80-15-9) Saccharin (81-07-2)
Pennsylvania	Cumene hydroperoxide (80-15-9) Saccharin (81-07-2)

Section 16. Other Information

Revision Date 12/21/2015

Disclaimer The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.