acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 06, 2016

Revision: April 06, 2016

1 Identification Product identifier · Trade name: Spede-Heat[™] Continuous Discharge Chemical Grenade, OC · Product code: 1070 (1180155) · Recommended use and restriction on use · Recommended use: Crowd Control Device · Restrictions on use: Contact manufacturer · Details of the supplier of the Safety Data Sheet · Manufacturer/Supplier: Safariland, LLC 13386 International Parkway Jacksonville, FL 32218 Customer Care (800) 347-1200 · Emergency telephone number: ChemTel Inc. +1 (800)255-3924, +1 (813)248-0585 2 Hazard(s) identification · Classification of the substance or mixture Expl. 1.4 H204 Fire or projection hazard. Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H335 May cause respiratory irritation. · Additional information: There are no other hazards not otherwise classified that have been identified. 0 % of the mixture consists of component(s) of unknown toxicity. · Label elements · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms: GHS01 GHS07 Signal word: Warning · Hazard-determining components of labeling: **Oleoresin Capsicum** · Hazard statements: H204 Fire or projection hazard. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. · Precautionary statements: P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. (Cont'd. on page 2)

Printing date: April 06, 2016

Revision: April 06, 2016

Trade name: Spede-Heat[™] Continuous Discharge Chemical Grenade, OC

(Cont'd. of page 1)

P261	Avoid breathing dust.			
P264	Wash thoroughly after handling.			
P280	Wear protective gloves / eye protection / face protection.			
P271	Use only outdoors or in a well-ventilated area.			
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if			
	present and easy to do. Continue rinsing.			
P373	DO NOT fight fire when fire reaches explosives.			
P321	Specific treatment (see on this label).			
P370+P380	In case of fire: Evacuate area.			
P374	Fight fire with normal precautions from a reasonable distance.			
P302+P352	IF ON SKIN: Wash with plenty of water.			
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.			
P372	Explosion risk in case of fire.			
P312	Call a POISON CENTER/doctor if you feel unwell.			
P332+P313	If skin irritation occurs: Get medical advice/attention.			
P337+P313	If eye irritation persists: Get medical advice/attention.			
P362+P364	Take off contaminated clothing and wash it before reuse.			
P401	Store in accordance with local/regional/national/international regulations.			
P405	Store locked up.			
P403+P233	Store in a well-ventilated place. Keep container tightly closed.			
P501	Dispose of contents/container in accordance with local/regional/national/international			
	regulations.			
· Classification s	ystem			
· NFPA ratings (sc	ale 0 - 4)			
Health :	- 2			
	—			
Fire = 0 Reactiv				
	ssesses oxidizing properties.			
 HMIS-ratings (sca 	ale 0 - 4)			
HEALTH 2 Health				
FIRE O Fire =				
Reactivity 4 React	ivity = 4			
* - Indicates a long	g term health hazard from repeated or prolonged exposures.			
Other hazards	t Nation			
· Explosive Produc				
	(Cont'd. on page 3)			

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 06, 2016

Revision: April 06, 2016

Trade name: Spede-Heat[™] Continuous Discharge Chemical Grenade, OC

(Cont'd. of page 2)

PREVENTION OF ACCIDENTS IN THE USE OF EXPLOSIVES - The prevention of accidents in the use of explosives is a result of careful planning and observance of the best known practices. The explosives user must remember that he is dealing with a powerful force and that various devices and methods have been developed to assist him in directing this force. He should realize that this force, if misdirected, may either kill or injure both him and his fellow workers.

WARNING - All explosives are dangerous and must be carefully handled and used following approved safety procedures either by or under the direction of competent, experienced persons in accordance with all applicable federal, state, and local laws, regulations, or ordinances. If you have any questions or doubts as to how to use any explosive product, DO NOT USE IT before consulting with your supervisor, or the manufacturer, if you do not have a supervisor. If your supervisor has any questions or doubts, he should consult the manufacturer before use.

3 Composition/information on ingredients

• Chemical characterization: Mixtures

· Components:			
100-21-0	terephthalic acid		20-<25%
9004-70-0		20-<25%	
3811-04-9	3811-04-9 potassium chlorate 10-2 Ox. Sol. 1, H271 Acute Tox. 4, H302; Acute Tox. 4, H332		
57-50-1	sucrose, pure		10-20%
546-93-0	Magnesium carbonate		5-<10%
8023-77-6	Oleoresin Capsicum 5-<10% Eye Dam. 1, H318 5-<10%		
7757-79-1	1 potassium nitrate 2.5-5 ② Ox. Sol. 2, H272		
7440-21-3			
557-04-0			1-2.5%
7429-90-5	aluminium powder (pyrophoric)0.1-1%Over Sol. 1, H250; Water-react. 2, H2610.1-1%		0.1-1%
7440-50-8	7440-50-8 copper 0.1-1		
 Additional information: For the wording of the listed Hazard Statements refer to section 16. For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. 			
	ace Components (≤ 0,1% w/w)		
7758-97-6	lead chromate	🗞 Carc. 1B, H350; Repr. 1A, H360; STOT RE	2, H373

(Cont'd. on page 4)

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 06, 2016

Revision: April 06, 2016

Trade name: Spede-Heat™ Continuous Discharge Chemical Grenade, OC

(Cont'd. of page 3)

Supply fresh air. Seek immediate medical advice. In case of irregular breathing or respiratory arrest provide artificial respiration. Provide oxygen treatment if affected person has difficulty breathing. After skin contact:	ervation for at least
Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observer hours after the accident. After inhalation: Supply fresh air. Seek immediate medical advice. In case of irregular breathing or respiratory arrest provide artificial respiration. Provide oxygen treatment if affected person has difficulty breathing. After skin contact:	ervation for at least
Symptoms of poisoning may even occur after several hours; therefore medical observours after the accident. After inhalation: Supply fresh air. Seek immediate medical advice. In case of irregular breathing or respiratory arrest provide artificial respiration. Provide oxygen treatment if affected person has difficulty breathing. After skin contact:	ervation for at least
hours after the accident. After inhalation: Supply fresh air. Seek immediate medical advice. In case of irregular breathing or respiratory arrest provide artificial respiration. Provide oxygen treatment if affected person has difficulty breathing. After skin contact:	
After inhalation:Supply fresh air.Seek immediate medical advice.In case of irregular breathing or respiratory arrest provide artificial respiration.Provide oxygen treatment if affected person has difficulty breathing.After skin contact:	
Seek immediate medical advice. In case of irregular breathing or respiratory arrest provide artificial respiration. Provide oxygen treatment if affected person has difficulty breathing. After skin contact:	
Seek immediate medical advice. In case of irregular breathing or respiratory arrest provide artificial respiration. Provide oxygen treatment if affected person has difficulty breathing. After skin contact:	
In case of irregular breathing or respiratory arrest provide artificial respiration. Provide oxygen treatment if affected person has difficulty breathing. After skin contact:	
Provide oxygen treatment if affected person has difficulty breathing. After skin contact:	
After skin contact:	
Immediately rinse with water.	
If skin irritation continues, consult a doctor.	
After eye contact:	
Protect unharmed eye.	
Remove contact lenses if worn.	
Rinse opened eye for several minutes under running water. Then consult a doctor.	
After swallowing:	
Unlikely route of exposure.	
Rinse out mouth and then drink plenty of water.	
Do not induce vomiting; immediately call for medical help.	
Most important symptoms and effects, both acute and delayed:	
Blast injury if mishandled.	
Irritating to eyes, respiratory system and skin.	
Breathing difficulty	
Coughing	
Allergic reactions	
Disorientation	
Danger:	
Danger of blast or crush-type injuries.	
Danger of impaired breathing.	
Indication of any immediate medical attention and special treatment needed:	
If necessary oxygen respiration treatment.	
Product may produce physical injury if mishandled. Treatment of these injuries sh	ould be based on t
blast and compression effects.	
Fire-fighting measures	

· Suitable extinguishing agents:

DO NOT fight fire when fire reaches explosives.

Flood area with water. If no water is available, carbon dioxide, dry chemical or earth may be used. If the fire reaches the cargo, withdraw and let fire burn.

• For safety reasons unsuitable extinguishing agents: None.

(Cont'd. on page 5)

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 06, 2016

Revision: April 06, 2016

Trade name: Spede-Heat[™] Continuous Discharge Chemical Grenade, OC

(Cont'd. of page 4)

Special hazards arising from the substance or mixture Fire or projection hazard. Product may explode if burned in confined space. Individual cartridges may explode. Mass explosion of many cartridges at once is unlikely. Hazardous combustions products: Metal Compounds, Carbon Monoxide, Carbon Dioxide, Nitrous Oxides, Various complex oxides of metals, Nitrogen. [•] Advice for firefighters · Protective equipment: Wear self-contained respiratory protective device. Wear fully protective suit. • Additional information: Evacuate area and fight fire from from the upwind side. Cool endangered receptacles with water spray. 6 Accidental release measures Personal precautions, protective equipment and emergency procedures: Use respiratory protective device against the effects of fumes/dust/aerosol. Isolate area and prevent access. Keep people at a distance and stay upwind.

Wear protective equipment. Keep unprotected persons away.

Remove persons from danger area.

Ensure adequate ventilation.

Protect from heat.

Keep away from ignition sources.

Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Suppress gases/fumes/haze with water spray.

Methods and material for containment and cleaning up:

Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Dispose contaminated material as waste according to item 13.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling

 Precautions for safe handling: Handle with care. Avoid jolting, friction and impact. Keep away from heat and direct sunlight. Use only in well ventilated areas.
 Information about protection against explosions and fires: Prevent impact and friction.

Keep respiratory protective device available.

(Cont'd. on page 6)

Printing date: April 06, 2016

TLV (USA)

EL (Canada)

EV (Canada)

LMPE (Mexico)

Long-term value: 10 mg/m³

Long-term value: 10 mg/m³

Long-term value: 10 mg/m³

total dust

A4

Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction

Revision: April 06, 2016

rinting date: April 0	6, 2016	Revision: April 06, 201
rade name: Spec	de-Heat™ Continuous Discharge Chemical Grena	ade, OC
		(Cont'd. of page
	ing must be available in case of nearby fire.	
Protect from hea	at. urces away - Do not smoke.	
	r safe storage, including any incompatibilitie	es
· Storage	to be met by storerooms and receptacles:	
	on for receptacles.	
	ear extreme heat, ignition sources or open flame.	
	out storage in one common storage facility:	
Store away from	n flammable substances.	
	ether with oxidizing and acidic materials.	
Store away from		
	ation about storage conditions:	
Store in dry con	at and direct sunlight. ditions	
	e in a well ventilated area.	
Specific end u	JSe(s): No relevant information available.	
8 Exposure co	ntrols/personal protection	
•	· ·	
Control paran		
	ith limit values that require monitoring at the wo constituents are the only constituents of the prod	
recommended e		
At this time, the	other constituents have no known exposure limits.	
100-21-0 terepł	ithalic acid	
TLV (USA)	Long-term value: 10 mg/m ³	
EL (Canada)	Long-term value: 10* 3** mg/m ³	
	*total dust; **respirable fraction	
EV (Canada)	Long-term value: 10 mg/m ³	
· · ·	Long-term value: 10 mg/m³	
57-50-1 sucros		
PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction	
REL (USA)	Long-term value: 10* 5** mg/m ³	
	*total dust **respirable fraction	

(Cont'd. on page 7)

Printing date: April 06, 2016

Revision: April 06, 2016

Trade name: Spede-Heat[™] Continuous Discharge Chemical Grenade, OC

		(Cont'd. of page 6)		
-	546-93-0 Magnesium carbonate			
PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction			
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction			
TLV (USA)	TLV withdrawn			
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust, **respirable fraction			
EV (Canada)	Long-term value: 10 mg/m³ total dust			
LMPE (Mexico)	Short-term value: 20 mg/m³ Long-term value: 10 mg/m³ (e)			
7440-21-3 silico	on and a second s			
PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction			
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction			
TLV (USA)	TLV withdrawn			
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction			
EV (Canada)	Long-term value: 10 mg/m³ total dust			
LMPE (Mexico) Short-term value: 20 mg/m ³ Long-term value: 10 mg/m ³ (e)				
557-04-0 magne	esium distearate, pure			
TLV (USA)	Long-term value: 10 mg/m³			
LMPE (Mexico)	Long-term value: 10 mg/m³ A4			
7429-90-5 alum	inium powder (pyrophoric)			
PEL (USA)	Long-term value: 15*; 5** mg/m³ *Total dust; ** Respirable fraction			
REL (USA)	Long-term value: 10* 5** mg/m³ as Al*Total dust**Respirable/pyro powd./welding f.			
TLV (USA)	Long-term value: 1* mg/m³ as Al; *as respirable fraction			
EL (Canada)	Long-term value: 1.0 mg/m³ respirable, as Al			
EV (Canada)	Long-term value: 5 mg/m³ aluminium-containing (as aluminium)			
LMPE (Mexico)	Long-term value: 1* mg/m³ A4, *fracciòn respirable			
L		(Cont'd. on page 8)		

Printing date: April 06, 2016

Revision: April 06, 2016

Trade name: Spede-Heat[™] Continuous Discharge Chemical Grenade, OC

	(Cont'd. of page 7)
7440-50-8 copp	ier
PEL (USA)	Long-term value: 1* 0.1** mg/m³ as Cu *dusts and mists **fume
REL (USA)	Long-term value: 1* 0.1** mg/m ³ as Cu *dusts and mists **fume
TLV (USA)	Long-term value: 1* 0.2** mg/m³ *dusts and mists; **fume; as Cu
EL (Canada)	Long-term value: 1* 0.2** mg/m³ *dusts and mists; **fume, as Cu
EV (Canada)	Long-term value: 0.2* 1** mg/m³ as copper, *fume;**dust and mists
LMPE (Mexico)	Long-term value: 0.2* 1** mg/m³ *humo (como Cu);**polvo y niebla (como Cu)
General protec The usual protec Keep away from Avoid close or lo Avoid contact w Do not inhale du Immediately ren Wash hands be Store protective Engineering co Breathing equi Wear positive p quantities. Protection of h	ctive equipment: tive and hygienic measures: nutionary measures for handling chemicals should be followed. n foodstuffs, beverages and feed. ong term contact with the skin. ith the eyes. ust / smoke / mist. nove all soiled and contaminated clothing. fore breaks and at the end of work. clothing separately. ontrols: Provide adequate ventilation. pment: pressure NIOSH or European EN149 vapor respirators when deploying product in large ands:
The glove mater Due to missing preparation/ the Selection of the degradation Material of glov The selection o quality and var substances, the checked prior to Penetration tim	rial has to be impermeable and resistant to the product/ the substance/ the preparation. g tests no recommendation to the glove material can be given for the product/ the chemical mixture. e glove material on consideration of the penetration times, rates of diffusion and the ves f the suitable gloves does not only depend on the material, but also on further marks of ries from manufacturer to manufactu rer. As the product is a preparation of several resistance of the glove material can not be calculated in advance and has therefore to be o the application. be of glove material k through time has to be found out by the manufacturer of the protective gloves and has to
be observed.	

(Cont'd. on page 9)

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 06, 2016

Revision: April 06, 2016

Trade name: Spede-Heat[™] Continuous Discharge Chemical Grenade, OC

(Cont'd. of page 8)

· Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear. • **Body protection:** Protective work clothing

· Limitation and supervision of exposure into the environment

No relevant information available.

· Risk management measures

See Section 7 for additional information.

Organizational measures should be in place for all activities involving this product.

9 Physical and chemical properties		
[·] Information on basic physical and chemical properties		
Appearance:		
Form:	Solid material	
Color:	Gray	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Not applicable.	
• Melting point/Melting range:	Not determined.	
· Boiling point/Boiling range:	Not determined.	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not determined.	
· Auto-ignition temperature:	Not determined.	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not self-igniting.	
[.] Danger of explosion:	Extreme risk of explosion by shock, friction, fire or othe sources of ignition.	
· Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure:	Not applicable.	
· Density:	Not determined.	
· Relative density:	Not determined.	
· Vapor density:	Not applicable.	
Evaporation rate:	Not applicable.	
· Solubility in / Miscibility with		
Water:	Insoluble.	
	(Cont'd. on page 1	

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 06, 2016

Revision: April 06, 2016

Trade name: Spede-Heat™ Continuous Discharge Chemical Grenade, OC

(Cont'd. of page 9)

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity

Dynamic: Kinematic: Other information Not applicable. Not applicable. No relevant information available.

10 Stability and reactivity

· Reactivity: No relevant information available. · Chemical stability: Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications. · Possibility of hazardous reactions: Fire or projection hazard. Contact with acids releases toxic gases. Toxic fumes may be released if heated above the decomposition point. Strong exothermic reaction with acids. Develops toxic gases / fumes. Conditions to avoid: Keep ignition sources away - Do not smoke. Store away from oxidizing agents. Keep away from heat and direct sunlight. Cartridge may detonate if case is punctured or severely damaged. · Incompatible materials: Contact with acids liberates toxic gas. Hazardous decomposition products: Carbon monoxide and carbon dioxide Hydrocarbons Leadoxide vapor Bariumoxide vapor Nitrogen oxides (NOx) Chlorine compounds Poisonous gases/vapors Irritant gases/vapors

11 Toxicological information

Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

3811-04-9 potassium chlorate

Oral LD50 1870 mg/kg (rat)

8023-77-6 Oleoresin Capsicum Oral LD50 3000 mg/kg (rat)

(Cont'd. on page 11)

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 06, 2016

Revision: April 06, 2016

Trade name: Spede-Heat™ Continuous Discharge Chemical Grenade, OC

(Cont'd. of page 10)

Κ

Dermal LD50 >2500 mg/kg (mouse) 7758-97-6 lead chromate

Oral LD50 12000 mg/kg (mouse)

Primary irritant effect:

• On the skin: Irritant to skin and mucous membranes.

- On the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization: Not determined.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

• NTP (National Toxicology Program):

7758-97-6 lead chromate

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

• Probable route(s) of exposure:

Ingestion.

Inhalation.

Eye contact.

Skin contact.

Acute effects (acute toxicity, irritation and corrosivity):

Danger of blast or crush-type injuries.

Irritating to eyes, respiratory system and skin.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.

· Carcinogenicity: Based on available data, the classification criteria are not met.

- Reproductive toxicity: Based on available data, the classification criteria are not met.
- STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

[.] Toxicity

· Aquatic toxicity

Toxic for aquatic organisms

The product contains materials that are harmful to the environment.

- Persistence and degradability The product is partially biodegradable. Significant residuals remain.
- · Bioaccumulative potential: May be accumulated in organism
- Mobility in soil: No relevant information available.
- Ecotoxical effects:
- · Remark: Toxic for fish

[•] Additional ecological information

· General notes:

This statement was deduced from the properties of the single components.

The product contains heavy metals. Avoid transfer into the environment. Specific preliminary treatments are necessary.

(Cont'd. on page 12)

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 06, 2016

Revision: April 06, 2016

Trade name: Spede-Heat[™] Continuous Discharge Chemical Grenade, OC

(Cont'd. of page 11)

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

Other adverse effects: No relevant information available.

13 Disposal considerations

[·] Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Hand over to hazardous waste disposers.

After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

[·] Uncleaned packagings

• Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT, ADR, IMDG, IATA	UN0301
UN proper shipping name	
DOT, IMDG, IATA	AMMUNITION TEAR-PRODUCING with burst
ADR	charge or propelling charge 0301 AMMUNITION TEAR-PRODUCING with burst
	expelling
	charge or propelling charge
Transport hazard class(es)	
DOT	
1.4	
Class	1 Explosive substances und articles
	(Cont'd. on page

Printing date: April 06, 2016

Г

Revision: April 06, 2016

ade name: Spede-Heat™ Continuous Disc	narge chemical crenade, oc	
		(Cont'd. of page 12
· Label	1.4G	
· ADR		
1.4 G		
Class	1 () Explosive substances und article	<u>s</u>
· Label	1.4G	
· IMDG, IATA		
1.4 G		
· Class	1 Explosive substances und articles	
· Label	1.4G	
 Packing group DOT, ADR, IMDG, IATA 	П	
· Environmental hazards	Not applicable.	
· Special precautions for user	Warning: Explosive substances und a	articles
· Danger code (Kemler): · EMS Number:	F-B,S-Z	
• Transport in bulk according to Annex II of		
MARPOL73/78 and the IBC Code	Not applicable.	
Transport/Additional information:		
· DOT · PHSMA EX #	EX2015080661	
· ADR · Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity	

15 Regulatory information			
 Safety, health and environmental regulations/legislation specific for the substance mixture United States (USA) SARA 	e or		
· Section 355 (extremely hazardous substances):			
None of the ingredients are listed.			
· Section 313 (Specific toxic chemical listings):			
598-62-9 manganese carbonate			
(Cont'd. on pag	je 14)		

Printing date: April 06, 2016

Revision: April 06, 2016

Trade name: Spede-Heat[™] Continuous Discharge Chemical Grenade, OC

		(Cont'd. of page 13)		
7440-50-8	copper			
13424-46-9	lead diazide / lead azide			
7440-66-6	zinc metal			
· TSCA (Tox	TSCA (Toxic Substances Control Act)			
•	All ingredients are listed.			
· Proposition	· Proposition 65 (California)			
Chemicals	known to cause cancer:			
13424-46-9	lead diazide / lead azide			
592-87-0	lead dithiocyanate			
10294-40-3	barium chromate			
7758-97-6	lead chromate			
	known to cause reproductive toxicity for	or females:		
	ace quantities.			
	barium chromate			
	lead chromate			
	known to cause reproductive toxicity for ace quantities.	or males:		
10294-40-3	barium chromate			
7758-97-6	lead chromate			
	known to cause developmental toxicity ace quantities.	r:		
13424-46-9	lead diazide / lead azide			
10294-40-3	barium chromate			
7758-97-6	lead chromate			
· Carcinoger	ic categories			
· EPA (Envir	onmental Protection Agency):			
	manganese carbonate	D		
7440-50-8		D		
13424-46-9	lead diazide / lead azide	B2		
	zinc metal	D, I, II		
7778-74-7	potassium perchlorate	NL		
10294-40-3	barium chromate	A(inh), D(oral), K/L(inh), CBD(oral)		
· IARC (Inter	national Agency for Research on Cance	er):		
13424-46-9	lead diazide / lead azide	2A		
10294-40-3	barium chromate	1		
NIOSH-Ca	National Institute for Occupational Safe	ety and Health):		
	barium chromate			
L	(Cont'd. on page 15)			

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 06, 2016

Revision: April 06, 2016

Trade name: Spede-Heat[™] Continuous Discharge Chemical Grenade, OC

(Cont'd. of page 14)

· Canadian substance listings

· Canadian Domestic Substances List (DSL):

All ingredients are listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision 04/06/2016 / -

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Expl. 1.1: Explosives, Division 1.1 Expl. 1.4: Explosives, Division 1.4 Flam. Sol. 2: Flammable solids, Hazard Category 2 Pyr. Sol. 1: Pyorphoric Solids, Hazard Category 1 Water-react. 2: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 2 Ox. Sol. 1: Oxidising Solids, Hazard Category 1 Ox. Sol. 2: Oxidising Solids, Hazard Category 2 Acute Tox. 4: Acute toxicity, Hazard Category 4 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 Sources SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com