
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date December 4, 2015

Revision: December 4, 2015



(Cont'd. on page 2)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date December 4, 2015

Trade name: Spede-Heat[™] 37mm Long-Range Round, OC

Revision: December 4, 2015

(Cont'd. from page 1) · Signal word Warning · Hazard-determining components of labelling: Oleoresin Capsicum Hazard statements H204 Fire or projection hazard. H315 Causes skin irritation. H319 Causes serious eve irritation. H335 May cause respiratory irritation. H412 Harmful to aquatic life with long lasting effects. · Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210 smokina. P250 Do not subject to grinding/shock/friction. P261 Avoid breathing dust. P264 Wash thoroughly after handling. P280 Wear protective gloves / eye protection. Use only outdoors or in a well-ventilated area. P271 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P373 DO NOT fight fire when fire reaches explosives. In case of fire: Evacuate area. P370+P380 P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Explosion risk in case of fire. P372 P312 Call a POISON CENTER/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. P332+P313 If eye irritation persists: Get medical advice/attention. P337+P313 P362+P364 Take off contaminated clothing and wash it before reuse. P401 Store in accordance with local/regional/national/international regulations. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · Additional information: Contains lead. Should not be used on surfaces liable to be chewed or sucked by children. Can become highly flammable in use. · NFPA ratings (scale 0 - 4) Health = 2Fire = 0Reactivity = 3 The substance demonstrates unusual reactivity with water. · HMIS-ratings (scale 0 - 4) HEALTH 1 Health = 1 FIRE Fire = 0 REACTIVITY 3 Reactivity = 3

Warning: Contains lead salt(s). Long-term health hazard.

(Cont'd. on page 3)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHŚ

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat[™] 37mm Long-Range Round, OC

(Cont'd. from page 2)

· 2.3 Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

Explosive Product Notice

PREVENTION OF ACCIDENTS IN THE USE OF EXPLOSIVES - The prevention of accidents in the use of explosives is a result of careful planning and observance of the best known practices. The explosives user must remember that he is dealing with a powerful force and that various devices and methods have been developed to assist him in directing this force. He should realize that this force, if misdirected, may either kill or injure both him and his fellow workers.

WARNING - All explosives are dangerous and must be carefully handled and used following approved safety procedures either by or under the direction of competent, experienced persons in accordance with all applicable federal, state, and local laws, regulations, or ordinances. If you have any questions or doubts as to how to use any explosive product, DO NOT USE IT before consulting with your supervisor, or the manufacturer, if you do not have a supervisor. If your supervisor has any questions or doubts, he should consult the manufacturer before use.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description:

Product will contain various combinations of the following substances. Not all substances will be in each product.

Mixture of substances listed below with nonhazardous additions.

CAS: 3811-04-9	potassium chlorate	10-25%
EINECS: 223-289-7	(1) Ox. Sol. 1, H271	
Index number: 017-004-00-3		
	Acute Tox. 4, H302; Acute Tox. 4, H332	
CAS: 9004-70-0	Nitrocellulose, colloided, granular	10-25%
EC number: 603-037-0	🔗 Expl. 1.1, H201	
CAS: 57-50-1	sucrose, pure	10-259
EINECS: 200-334-9	substance with a Community workplace exposure limit	
CAS: 100-21-0	terephthalic acid	10-25%
EINECS: 202-830-0	substance with a Community workplace exposure limit	
CAS: 8023-77-6	Oleoresin Capsicum	2,5-10
EINECS: 288-920-0	🔶 Eye Dam. 1, H318	
	Acute Tox. 4, H302; Skin Irrit. 2, H315	
CAS: 598-62-9	manganese carbonate	2,5-10
EINECS: 209-942-9	substance with a Community workplace exposure limit	
CAS: 7757-79-1	potassium nitrate	2,5-10
EINECS: 231-818-8	🚯 Ox. Sol. 2, H272	

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 37mm Long-Range Round, OC

	(Cont'd.	from page 3)
CAS: 557-04-0	magnesium distearate, pure	≤ 2 ,5%
EINECS: 209-150-3	substance with a Community workplace exposure limit	
CAS: 7440-21-3	silicon	≤ 2,5%
EINECS: 231-130-8	Flam. Sol. 2, H228	
CAS: 7429-90-5	aluminium powder (pyrophoric)	≤ 2,5%
EINECS: 231-072-3	Pyr. Sol. 1, H250; Water-react. 2, H261	
Index number: 013-001-00-6	y	
	he identity and exact percentages are being withheld as a trade secr Hazard Statements refer to section 16.	ret.
· Notable Trace Component	s (≤ 0,1% w/w)	
CAS: 15245-44-0	lead 2,4,6-trinitro-m-phenylene dioxide/ lead styphnate	
EINECS: 239-290-0	🔗 Unst. Expl., H200	
Index number: 609-019-00-4	🚯 Repr. 1A, H360Df; STOT RE 2, H373	
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
	Acute Tox. 4, H302; Acute Tox. 4, H332	

SECTION 4: First aid measures · 4.1 Description of first aid measures · General information: Immediately remove any clothing soiled by the product. Take affected persons out into the fresh air. · After inhalation: Remove victim to fresh air. Seek medical help for symptoms or if unconscious. After skin contact: Brush off loose particles from skin. If skin irritation continues, consult a doctor. • After eye contact: Remove contact lenses if worn. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. · After swallowing: Rinse out mouth and then drink plenty of water. Do not induce vomiting; call for medical help immediately. 4.2 Most important symptoms and effects, both acute and delayed Blast injury if mishandled. May cause respiratory irritation. Coughing Nausea Dizziness Cramp Breathing difficulty Irritant to skin and mucous membranes. Irritant to eyes. (Cont'd. on page 5)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 37mm Long-Range Round, OC

(Cont'd. from page 4)

· Hazards

Danger of blast or crush-type injuries. Danger of impaired breathing.

· 4.3 Indication of any immediate medical attention and special treatment needed

If necessary oxygen respiration treatment.

Product may produce physical injury if mishandled. Treatment of these injuries should be based on the blast and compression effects.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

DO NOT fight fire when fire reaches explosives.

Flood area with water. If no water is available, carbon dioxide, dry chemical or earth may be used. If the fire reaches the cargo, withdraw and let fire burn.

• For safety reasons unsuitable extinguishing agents: None.

· 5.2 Special hazards arising from the substance or mixture

Fire or projection hazard.

Formation of toxic gases is possible during heating or in case of fire.

Product may explode if burned in confined space. Individual cartridges may explode. Mass explosion of many cartridges at once is unlikely.

5.3 Advice for firefighters

• Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Eliminate all ignition sources if safe to do so.

Cool endangered receptacles with water spray.

Evacuate area and fight fire from from the upwind side.

Flammability Classification: (defined by 29 CFR 1910.1200) Explosive. Can explode under fire conditions. Individual devices will randomly explode. Will not mass explode if multiple devices are involved. Burning material may produce toxic and irritating vapors. In unusual cases, shrapnel may be thrown from exploding devices under containment. See 2008 Emergency response Guidebook for further information.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

FOR ALL TRANSPORTATION ACCIDENTS, CALL CHEMTEL AT 1-800-255-3924. Spills of this material should be handled carefully. Do not subject materials to mechanical shock or extreme heat. A spill of this material will normally not require emergency response team capabilities.

Remove persons from danger area.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Protect from heat.

Keep away from ignition sources.

Isolate area and prevent access.

(Cont'd. on page 6)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 37mm Long-Range Round, OC

(Cont'd. from page 5)

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles. Dispose contaminated material as waste according to section 13.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling
Use only outdoors or in a well-ventilated area.
Handle with care. Avoid jolting, friction and impact.
Information about fire - and explosion protection:
Protect from heat.
Keep respiratory protective device available.
Emergency cooling must be available in case of nearby fire.
7.2 Conditions for safe storage, including any incompatibilities
Storage:

Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

• Information about storage in one common storage facility: Store away from foodstuffs.

• Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see section 7.

· 8.1 Control parameters · Ingredients with limit values that require monitoring at the workplace: 57-50-1 sucrose, pure Long-term value: 15* 5** mg/m³ PEL (USA) *total dust **respirable fraction Long-term value: 10* 5** mg/m³ REL (USA) *total dust **respirable fraction TLV (USA) Long-term value: 10 mg/m³ Long-term value: 10* 3** mg/m³ EL (Canada) *total dust;**respirable fraction EV (Canada) Long-term value: 10 mg/m³ total dust (Cont'd. on page 7)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 37mm Long-Range Round, OC

100-21-0 tere	phthalic acid	(Cont'd. from pag
	Long-term value: 10 mg/m ³	
. ,	Long-term value: 10* 3** mg/m ³ *total dust; **respirable fraction	
EV (Canada)	Long-term value: 10 mg/m ³	
598-62-9 mar	nganese carbonate	
PEL (USA)	Ceiling limit: 5 mg/m³ as Mn	
REL (USA)	Short-term value: 3 mg/m³ Long-term value: 1 mg/m³ as Mn	
TLV (USA)	Long-term value: 0,02* 0,1* mg/m³ as Mn; *respirable **inhalable fraction	
EL (Canada)	Long-term value: 0,2 mg/m³ as Mn; R	
	nesium distearate, pure	
TLV (USA)	Long-term value: 10 mg/m ³	
7440-21-3 sil	icon	
PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction	
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction	
TLV (USA)	TLV withdrawn	
EL (Canada)	Long-term value: 10* 3** mg/m ³ *total dust;**respirable fraction	
EV (Canada)	Long-term value: 10 mg/m³ total dust	
7429-90-5 alu	iminium powder (pyrophoric)	
PEL (USA)	Long-term value: 15*; 5** mg/m ³ *Total dust; ** Respirable fraction	
REL (USA)	Long-term value: 10* 5** mg/m³ as Al*Total dust**Respirable/pyro powd./welding f.	
TLV (USA)	Long-term value: 1* mg/m³ as Al; *as respirable fraction	
EL (Canada)	Long-term value: 1,0 mg/m³ respirable, as Al	
	Long-term value: 5 mg/m³ aluminium-containing (as aluminium)	
	rther relevant information available.	
PNECs No fu	rther relevant information available.	(Cont'd. on pag
		(Cont d. on pag

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat[™] 37mm Long-Range Round, OC

(Cont'd. from page 7) · 8.2 Exposure controls · Personal protective equipment: · General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Do not inhale dust / smoke / mist. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. **Respiratory protection:** Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in large quantities. Protection of hands: Protective gloves Wear gloves when handling deployed rounds. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. · Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. Eve protection: Safety glasses · Limitation and supervision of exposure into the environment No special requirements. No further relevant information available. **Risk management measures** See Section 7 for additional information. Organizational measures should be in place for all activities involving this product.

No further relevant information available.

(Cont'd. on page 9)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 37mm Long-Range Round, OC

(Cont'd. from page 8)

9.1 Information on basic physical a	ind chemical properties
General Information	
Appearance:	
Form:	Solid material
Colour:	Dark grey
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not applicable.
Change in condition	
Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	Not determined.
Flash point:	Not applicable.
Flammability (solid, gaseous):	Highly flammable.
	Contact with water liberates extremely flammable gases.
Auto/Self-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
Self-igniting:	Product is not self-igniting.
Danger of explosion:	Fire or projection hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not applicable.
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not applicable.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Insoluble.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

(Cont'd. on page 10)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat[™] 37mm Long-Range Round, OC

(Cont'd. from page 9)

 10.2 Chemical stability
 Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.
 10.3 Possibility of hazardous reactions Toxic fumes may be released if heated above the decomposition point. Fire or projection hazard. Reacts with strong acids and alkali. Reacts violently with oxidising agents.
 10.4 Conditions to avoid Sources of ignition, open flame, incompatible

10.4 Conditions to avoid Sources of ignition, open flame, incompatible materials.

• 10.5 Incompatible materials: Oxidizers

· 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide Nitrogen oxides

Sulphur oxides (SOx)

SECTION 11: Toxicological information

• 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

3811-04-9 potassium chlorate

Oral LD50 1870 mg/kg (rat)

8023-77-6 Oleoresin Capsicum

Oral LD50 3000 mg/kg (rat)

Dermal LD50 >2500 mg/kg (mouse)

Primary irritant effect:

Effects based on exposure to dusts/mists/spray/vapours released during deployment. Unused product does not possess these effects.

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

• Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

• Acute effects (acute toxicity, irritation and corrosivity): Irritating to eyes, respiratory system and skin.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

• Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure

May cause respiratory irritation.

• **STOT-repeated exposure** Based on available data, the classification criteria are not met.

· Aspiration hazard Based on available data, the classification criteria are not met.

(Cont'd. on page 11)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat[™] 37mm Long-Range Round, OC

(Cont'd. from page 10)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity: The product contains materials that are harmful to the environment.

• **12.2 Persistence and degradability** The product is partially biodegradable. Significant residuals remain.

· 12.3 Bioaccumulative potential May be accumulated in organism

· 12.4 Mobility in soil No further relevant information available.

• Additional ecological information:

· General notes:

This statement was deduced from the properties of the single components.

The product contains heavy metals. Avoid transfer into the environment. Specific preliminary treatments are necessary

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport informat	tion
· 14.1 UN-Number · DOT, ADR, IMDG, IATA	UN0301
 14.2 UN proper shipping name DOT, IMDG, IATA 	Ammunition Tear-producing with burster, expelling charge or propelling charge
ADR	0301 Ammunition Tear-producing with burste expelling charge or propelling charge
	expelling


according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat[™] 37mm Long-Range Round, OC



according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat[™] 37mm Long-Range Round, OC

	(Cont'd. from page 12)
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	0 Code: E2 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 500 g
· UN "Model Regulation":	UN0301, Ammunition Tear-producing with burster, expelling charge or propelling charge, 1.4G (6.1+8), II

SECTION 15: Regulatory information

 $^{\cdot}$ 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture $^{\cdot}$ United States (USA)

SARA	
· Section 355 (extremely hazardous substances):	٦
None of the ingredients are listed.	
· Section 313 (Specific toxic chemical listings):	Ē
598-62-9 manganese carbonate	
7757-79-1 potassium nitrate	
· TSCA (Toxic Substances Control Act):	٦
3811-04-9 potassium chlorate	
9004-70-0 Nitrocellulose, colloided, granular	
57-50-1 sucrose, pure	
100-21-0 terephthalic acid	
7757-69-9 carbonic acid, magnesium salt	
8023-77-6 Oleoresin Capsicum	
598-62-9 manganese carbonate	
7757-79-1 potassium nitrate	
557-04-0 magnesium distearate, pure	
7440-21-3 silicon	
7440-44-0 carbon	
1317-61-9 triiron tetraoxide	
7704-34-9 sulfur	
7429-90-5 aluminium powder (pyrophoric)	
16291-96-6 charcoal	
Proposition 65 (California):	
· Chemicals known to cause cancer:	
Present in trace quantities.	_
15245-44-0 lead 2,4,6-trinitro-m-phenylene dioxide/ lead styphnate	
(Cont'd. on page 1	4)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 37mm Long-Range Round, OC

	(Cont'd. from page
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients are listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients are listed.	
 Chemicals known to cause developmental toxicity: Present in trace quantities. 	
15245-44-0 lead 2,4,6-trinitro-m-phenylene dioxide/ lead styphnate	
· Carcinogenic Categories	
· EPA (Environmental Protection Agency)	
598-62-9 manganese carbonate	
· IARC (International Agency for Research on Cancer)	
None of the ingredients are listed.	
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients are listed.	
Canada	
· Canadian Domestic Substances List (DSL)	
3811-04-9 potassium chlorate	
9004-70-0 Nitrocellulose, colloided, granular	
57-50-1 sucrose, pure	
100-21-0 terephthalic acid	
7757-69-9 carbonic acid, magnesium salt	
8023-77-6 Oleoresin Capsicum	
598-62-9 manganese carbonate	
7757-79-1 potassium nitrate	
557-04-0 magnesium distearate, pure	
7440-21-3 silicon	
7440-44-0 carbon	
1317-61-9 triiron tetraoxide	
7704-34-9 sulfur	
7429-90-5 aluminium powder (pyrophoric)	
16291-96-6 charcoal	
Canadian Ingredient Disclosure list (limit 0.1%)	
598-62-9 manganese carbonate	
[.] Canadian Ingredient Disclosure list (limit 1%)	
100-21-0 terephthalic acid	
Other regulations, limitations and prohibitive regulations	
· Substances of very high concern (SVHC) according to REACH, Article 57	
None of the ingredients are listed.	
	(Cont'd. on page

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 37mm Long-Range Round, OC

(Cont'd. from page 14)

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H201 Explosive; mass explosion hazard.

- H228 Flammable solid.
- H250 Catches fire spontaneously if exposed to air.
- H261 In contact with water releases flammable gases.
- H271 May cause fire or explosion; strong oxidiser.
- H272 May intensify fire; oxidiser.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety Expl. 1.1: Explosives, Division 1.1 Expl. 1.4: Explosives, Division 1.4 Flam. Sol. 2: Flammable solids, Hazard Category 2 Pyr. Sol. 1: Pyorphoric Solids, Hazard Category 1 Water-react. 2: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 2 Ox. Sol. 1: Oxidising Solids, Hazard Category 1 Ox. Sol. 2: Oxidising Solids, Hazard Category 2 Acute Tox. 4: Acute toxicity, Hazard Category 4 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

(Cont'd. on page 16)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date December 4, 2015

· Sources

Revision: December 4, 2015

Trade name: Spede-Heat[™] 37mm Long-Range Round, OC

(Cont'd. from page 15)

SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com