

Safety Data Sheet according to Australia WHS Regulations

Revision: 10 December 2020

1 Identification		
· Product identifier		
 Trade name: <u>Spede-Heat™ 37mm Short-Range Round, CS</u> Product code: 2002 (1011709) Recommended use: Crowd Control Device Restrictions on use: Contact manufacturer/supplier 		
 Details of the supplier of the Safety Data Sheet Manufacturer/Supplier: Safariland, LLC 13386 International Parkway Jacksonville, FL 32218 USA Customer Care (800) 347-1200 Importer/Distributor: Distributed within Australia by: Aquaterro Advanced Product Supplies - ABN: 31 064 779 746 77 National Avenue Pakenham, Victoria, 3810 Australia Tel +61 (03) 9754 2922 Toll-Free 1300 TACTICAL (Australia) 		
Distributed within Australia by: Grycol International Pty Ltd 3 Zenith Business Park, 34 Alliance Avenue Morisset, New South Wales 2264, Australia		
(Mailing Address) P.O. Box 723 Morisset NSW 2264, Australia Tel +61 2 4970 4377 Fax: +61 2 4913 5310		
Emergency telephone number: ChemTel 1-800-526-4727 (North America) 1-314-985-1511 (International) Emergencies within Australia - 131126 (NSW Poison Control Centre) Emergencies within New Zealand - 0800 764 766 (National Poison Control Centre)		

2 Hazard(s) Identification

[•] Classification (Australia, New Zealand)

Australia NOHSC – Hazardous Substance (Classified according to Worksafe Australia NOHSC 2018 National Code of Practice)

Australia ADG – Dangerous Goods (Classified according to National Transport Commision Australian Dangerous Goods Code)

[•] Classification of the substance or mixture

Expl. 1.4 H204 Fire or projection hazard.

Acute Tox. 3 H301 Toxic if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 3 H331 Toxic if inhaled.

(Cont'd. on page 2)

according to Australia WHS Regulations

Revision: 10 December 2020

Trade name: Spede-Heat[™] 37mm Short-Range Round, CS (Cont'd. from page 1) Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2A H319 Causes serious eye irritation. Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation. · Additional information: There are no other hazards not otherwise classified that have been identified. 0 % of the mixture consists of component(s) of unknown toxicity. · Hazard pictograms GHS01 GHS06 GHS08 · Signal word Danger · Hazard statements H204 Fire or projection hazard. H301 Toxic if swallowed. H312 Harmful in contact with skin. H331 Toxic if inhaled. H315 Causes skin irritation. H319 Causes serious eye irritation. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. **Precautionary statements** Keep away from heat/sparks/open flames/hot surfaces. No smoking. P210 P250 Do not subject to grinding/shock/friction. Avoid breathing dust. P261 Wash thoroughly after handling. P264 P270 Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. P271 P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection/face protection. P284 Wear respiratory protection. IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P301+P310 IF ON SKIN: Wash with plenty of soap and water. P302+P352 Specific treatment - See Section 4 of this Safety Data Sheet. P321 P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTRE/doctor if you feel unwell. P330 Rinse mouth. P362+P364 Take off contaminated clothing and wash it before reuse. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. P337+P313 P342+P311 If experiencing respiratory symptoms: Call a POISON CENTRE/doctor. P370+P380 In case of fire: Evacuate area. P372 Explosion risk in case of fire. (Cont'd. on page 3)

according to Australia WHS Regulations

Revision: 10 December 2020

Trade name: Spede-Heat[™] 37mm Short-Range Round, CS (Cont'd. from page 2) P373 DO NOT fight fire when fire reaches explosives. P401 Store in accordance with local/regional/national/international regulations. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · Additional information: Contains [(2-chlorophenyl)methylene]malononitrile. May produce an allergic reaction. • Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable. · Explosive Product Notice PREVENTION OF ACCIDENTS IN THE USE OF EXPLOSIVES - The prevention of accidents in the use of explosives is a result of careful planning and observance of the best known practices. The explosives user must remember that they are dealing with a powerful force and that various devices and methods have been developed to assist them in directing this force. They should realize that this force, if misdirected, may either kill or injure both themself and their fellow workers. WARNING - All explosives are dangerous and must be carefully handled and used following approved safety procedures either by or under the direction of competent, experienced persons in accordance with all applicable federal, state, and local laws, regulations, or ordinances. If you have any questions or doubts as to how to use any explosive product, DO NOT USE IT before consulting with your supervisor, or the manufacturer, if you do not have a supervisor. If your supervisor has any questions or doubts, they should consult the manufacturer before use.

3 Composition and Information on Ingredients

· Chemical characterisation: Mixtures

2698-41-1	[(2-chlorophenyl)methylene]malononitrile	10-30
	Acute Tox. 3, H301; Acute Tox. 2, H330 Resp. Sens. 1, H334; STOT RE 2, H373	
	Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	
3811-04-9	potassium chlorate	10-30
	 Ox. Liq. 1, H271; Ox. Sol. 1, H271 Acute Tox. 4, H302; Acute Tox. 4, H332 	
57-50-1	Sucrose, pure	10-30
9004-70-0	Nitrocellulose, colloided, granular	10-30
	🔶 Expl. 1.1, H201	
546-93-0	Magnesium carbonate	10-30
7757-79-1	Potassium nitrate	<10%
	🚸 Ox. Sol. 2, H272	
7440-21-3	Silicon	<10%
	🚸 Flam. Sol. 2, H228	
Additional information:		
For the wording of the listed Hazard Statements refer to section 16.		

according to Australia WHS Regulations

Revision: 10 December 2020

Trade name: Spede-Heat™ 37mm Short-Range Round, CS

(Cont'd. from page 3)

For the listed ingredient(s), the identity and/or exact percentages are being withheld as a trade secret.

	· Notable Trace Components (< 0,1% w/w)		
15245-44-0	lead 2,4,6-trinitro-m-phenylene dioxide/ lead styphnate		
	 Unst. Expl., H200 Repr. 1A, H360; STOT RE 2, H373 Acute Tox. 4, H302; Acute Tox. 4, H332 		
592-87-0	lead dithiocyanate		
	 Repr. 1A, H360Df; STOT RE 2, H373 Acute Tox. 4, H302; Acute Tox. 4, H332 		

4 First Aid Measures

[•] Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

Do not leave affected persons unattended.

Remove breathing equipment only after contaminated clothing have been completely removed.

After inhalation:

Seek immediate medical advice.

Remove victim to fresh air.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

After skin contact:

Immediately remove any clothing soiled by the product.

Brush off loose particles from skin.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

• After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

Most important symptoms and effects, both acute and delayed

Asthma attacks

Blast injury if mishandled.

Allergic reactions

May cause respiratory irritation.

Breathing difficulty

Coughing

Causes eye irritation.

Irritant to skin and mucous membranes.

Hazards:

Explosive crush or blast injury.

Harmful in contact with skin.

Danger of impaired breathing.

· Indication of any immediate medical attention and special treatment needed

Product may produce physical injury if mishandled. Treatment of these injuries should be based on the

(Cont'd. on page 5)

according to Australia WHS Regulations

Revision: 10 December 2020

Trade name: Spede-Heat™ 37mm Short-Range Round, CS

(Cont'd. from page 4)

blast and compression effects. Contains [(2-chlorophenyl)methylene]malononitrile. May produce an allergic reaction. Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible. In cases of irritation to the lungs, initial treatment with cortical steroid inhalants. Monitor circulation, possible shock treatment. Treat skin and mucous membrane with antihistamine and corticoid preparations. If necessary oxygen respiration treatment. Medical supervision for at least 48 hours.

5 Fire Fighting Measures

• Extinguishing media

· Suitable extinguishing agents:

Flood area with water. If no water is available, carbon dioxide, dry chemical or earth may be used. If the fire reaches the cargo, withdraw and let fire burn.

• For safety reasons unsuitable extinguishing agents: None.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

Product may explode if burned in confined space. Individual cartridges may explode. Mass explosion of many cartridges at once is unlikely.

Advice for firefighters

· Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information:

Eliminate all ignition sources if safe to do so.

Cool endangered receptacles with water spray.

Evacuate area and fight fire from from the upwind side.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Flammability Classification: (defined by 29 CFR 1910.1200) Explosive. Can explode under fire conditions. Individual devices will randomly explode. Will not mass explode if multiple devices are involved. Burning material may produce toxic and irritating vapours. In unusual cases, shrapnel may be thrown from exploding devices under containment. See Emergency Response Guidebook for further information.

6 Accidental Release Measures

• Personal precautions, protective equipment and emergency procedures

FOR ALL TRANSPORTATION ACCIDENTS, CALL CHEMTEL AT 1-800-255-3924. Spills of this material should be handled carefully. Do not subject materials to mechanical shock or extreme heat. A spill of this material will normally not require emergency response team capabilities. Isolate area and prevent access.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Remove persons from danger area.

Ensure adequate ventilation

Protect from heat.

· Environmental precautions No special measures required.

[•] Methods and material for containment and cleaning up

(Cont'd. on page 6)

according to Australia WHS Regulations

Revision: 10 December 2020

Trade name: Spede-Heat™ 37mm Short-Range Round, CS

(Cont'd. from page 5)

Pick up mechanically. Dispose contaminated material as waste according to section 13. Clean the affected area carefully; suitable cleaners are: Warm water and cleansing agent Send for recovery or disposal in suitable receptacles. **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and Storage

· Handling:

Precautions for safe handling Handle with care. Avoid jolting, friction and impact. Avoid breathing dust. Use only in well ventilated areas.
Information about fire - and explosion protection: Protect from heat. Keep respiratory protective device available. Emergency cooling must be available in case of nearby fire.

[•] Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from flammable substances.

• Further information about storage conditions: Store in dry conditions.

• Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

Control parameters

Ingredients with limit values that require monitoring at the workplace:			
2698-41-1 [(2-chlorophenyl)methylene]malononitrile			
WES (Australia)	Peak limitation: 0.39 mg/m³, 0.05 ppm Sk		
PEL (USA)	Long-term value: 0.4 mg/m³, 0.05 ppm		
REL (USA)	Peak limitation: 0.4 mg/m³, 0.05 ppm Skin		
TLV (USA)	Peak limitation: 0.39* mg/m³, 0.05* ppm *inhalable fraction and vapor;Skin		
WES (New Zealand)	Peak limitation: 0.39 mg/m³, 0.05 ppm skin		
57-50-1 Sucrose, pu	re		
WES (Australia)	Long-term value: 10 mg/m ³		
	(Cont'd. on page 7)		

Safety Data Sheet according to Australia WHS Regulations

Revision: 10 December 2020

Trade name: Spede-Heat™ 37mm Short-Range Round, CS

	(Cont'd. from page 6)		
PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction		
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction		
TLV (USA)	Long-term value: 10 mg/m³		
WES (New Zealand)	Long-term value: 10 mg/m³		
546-93-0 Magnesiun	n carbonate		
WES (Australia)	Long-term value: 10 mg/m ³		
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction		
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction		
TLV (USA)	TLV withdrawn		
WES (New Zealand)	Long-term value: 10 mg/m³		
7440-21-3 Silicon			
WES (Australia)	Long-term value: 10 mg/m ³		
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction		
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction		
TLV (USA)	TLV withdrawn		
WES (New Zealand)	Long-term value: 10 mg/m³		
 Exposure controls Engineering measures Provide adequate ventilation. General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Immediately remove all soiled and contaminated clothing. Do not inhale dust / smoke / mist. Avoid contact with the eyes and skin. Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Respiratory protection: 			
Respiratory protection required.			
Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. • Protection of hands:			
Protective gloves			
Wear gloves when handling deployed rounds.			

Wear gloves when handling deployed rounds. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

(Cont'd. on page 8)

according to Australia WHS Regulations

Revision: 10 December 2020

Trade name: Spede-Heat™ 37mm Short-Range Round, CS

(Cont'd. from page 7)

• Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Safety glasses

· Body protection: Protective work clothing

Limitation and supervision of exposure into the environment:

No further relevant information available.

[•] Risk management measures:

See Section 7 for additional information.

Organizational measures should be in place for all activities involving this product.

No further relevant information available.

9 Physical and Chemical Properties		
[·] Information on basic physical and chemical properties · Appearance		
Colour:	According to product specification	
Odour:	Odourless	
Odour threshold:	Not determined.	
pH-value:	Not applicable.	
Melting point/freezing point:	Not determined.	
Initial boiling point and boiling range	: Not determined.	
Flash point:	Not applicable.	
Flammability (solid, gas):	Not determined.	
Auto/Self-ignition temperature:	Not determined.	
Decomposition temperature:	Not determined.	
Explosive properties:	Heating may cause an explosion.	
Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
Oxidising properties	Contains oxidizing agent.	
Vapour pressure:	Not applicable.	
Density:	Not determined.	
Relative density:	Not determined.	
	(Cont'd. on page	

according to Australia WHS Regulations

Revision: 10 December 2020

Trade name: Spede-Heat[™] 37mm Short-Range Round, CS (Cont'd. from page 8) · Vapour density: Not applicable. • Evaporation rate: Not applicable. · Solubility in / Miscibility with Insoluble. water: · Partition coefficient: n-octanol/water: Not determined. · Viscosity Dynamic: Not applicable. Kinematic: Not applicable. Other information No further relevant information available. 10 Stability and Reactivity • **Reactivity** No further relevant information available. · Chemical stability · Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications. Possibility of hazardous reactions Danger of explosion. Toxic fumes may be released if heated above the decomposition point. Contact with acids releases toxic gases. Acts as an oxidising agent on organic materials such as wood, paper and fats. Reacts with strong alkali. · Conditions to avoid Sources of ignition, open flame, incompatible materials. · Incompatible materials No further relevant information available. · Hazardous decomposition products Carbon monoxide and carbon dioxide Nitrogen oxides Sulphur oxides (SOx) 11 Toxicological Information Information on toxicological effects · Acute toxicity:

Toxic if inhaled. Toxic if swallowed.

Harmful in contact with skin.

· LD/LC50 values relevant for classification:

2698-41-1 [(2-chlorophenyl)methylene]malononitrile

Oral LD50 178 mg/kg (rat)

3811-04-9 potassium chlorate

Oral LD50 1870 mg/kg (rat)

7440-21-3 Silicon

Oral LD50 3160 mg/kg (rat)

(Cont'd. on page 10)

according to Australia WHS Regulations

Revision: 10 December 2020

Trade name: Spede-Heat[™] 37mm Short-Range Round, CS (Cont'd. from page 9) · Primary irritant effect Effects based on exposure to dusts/mists/spray/vapours released during deployment. Unused product does not possess these effects. · Skin corrosion/irritation: Irritant to skin and mucous membranes. · Serious eye damage/irritation: Causes eye irritation. • **Respiratory or skin sensitisation:** May cause sensitisation by inhalation and skin contact. · IARC (International Agency for Research on Cancer): 15245-44-0 lead 2,4,6-trinitro-m-phenylene dioxide/ lead styphnate 2B 592-87-0 lead dithiocyanate 2A · Probable routes of exposure: Ingestion. Inhalation. Eve contact. Skin contact. • Acute effects (acute toxicity, irritation and corrosivity): Explosive crush or blast injury. Irritating to eyes, respiratory system and skin. Harmful in contact with skin. Toxic if swallowed or if inhaled. · Repeated dose toxicity: Repeated exposures may result in skin and/or respiratory sensitivity. · Germ cell mutagenicity: Based on available data, the classification criteria are not met. · Carcinogenicity: Based on available data, the classification criteria are not met. • **Reproductive toxicity:** Based on available data, the classification criteria are not met. · **STOT-single exposure:** May cause respiratory irritation. • **STOT-repeated exposure:** Based on available data, the classification criteria are not met. · Aspiration hazard: Based on available data, the classification criteria are not met. **12 Ecological Information** · Toxicitv · Aquatic toxicity: The product contains materials that are harmful to the environment. 2698-41-1 [(2-chlorophenyl)methylene]malononitrile EC50 0.2-0.3 mg/kg (Oncorhynchus mykiss) · Persistence and degradability No further relevant information available. · Bioaccumulative potential May be accumulated in organism · Mobility in soil No further relevant information available. Ecotoxical effects: · Remark: Harmful to fish Additional ecological information: · General notes: Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. The product contains heavy metals. Avoid transfer into the environment. Specific preliminary treatments are necessary Harmful to aquatic organisms Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term (Cont'd. on page 11)

according to Australia WHS Regulations

Revision: 10 December 2020

Trade name: Spede-Heat™ 37mm Short-Range Round, CS

damage of the environment can not be excluded.

Other adverse effects No further relevant information available.

13 Disposal considerations

[·] Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

[•] Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

1 Transport information	
[·] UN-Number · DOT, ADG, IMDG, IATA	UN0301
 UN proper shipping name DOT 	Ammunition Tear-producing with burster, expelling charge or propelling charge
· ADG · IMDG, IATA	0301 Ammunition Tear-producing with burste expelling charge or propelling charge Ammunition Tear-producing with burster, expellin charge or propelling charge
[·] Transport hazard class(es)	
· DOT	
· Class	1.4
·Label	1.4G+6.1+8
Class	1.4
· Label	1.4G+6.1+8
	(Cont'd. on page 1

(Cont'd. from page 10)

according to Australia WHS Regulations

Revision: 10 December 2020

Trade name: Spede-Heat™ 37mm Short-Range Round, CS (Cont'd. from page 11) ·IATA 1.4G · Class · Label 1.4G+6.1+8 Packing group · DOT, ADG, IMDG, IATA Ш • Environmental hazards: · Marine pollutant: No • Special precautions for user Not applicable. · EMS Number: F-A,S-Q [•] Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

· IARC (Inter	· IARC (International Agency for Research on Cancer)			
15245-44-0	lead 2,4,6-trinitro-m-phenylene dioxide/ lead styphnate	2B		
592-87-0	lead dithiocyanate	2A		
· Australia				

· Australian Inventory of Chemical Substances

All ingredients are listed.

Standard for the Uniform Scheduling of Medicines and Poisons

3811-04-9 potassium chlorate

Australia: Priority Existing Chemicals

None of the ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H200 Unstable explosives.

- H201 Explosive; mass explosion hazard.
- H228 Flammable solid.
- May cause fire or explosion; strong oxidiser. H271
- H272 May intensify fire; oxidiser.
- H301 Toxic if swallowed.

(Cont'd. on page 13)

S2, S5

according to Australia WHS Regulations

Revision: 10 December 2020

Trade name: Spede-Heat[™] 37mm Short-Range Round, CS (Cont'd. from page 12) H302 Harmful if swallowed. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H330 Fatal if inhaled. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. H335 H360 May damage fertility or the unborn child. H360Df May damage the unborn child. Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. Abbreviations and acronyms: ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration. 50 percent LD50: Lethal dose, 50 percent PBT: Persistant, Bio-accumulable, Toxic vPvB: very Persistent and very Bioaccumulative Expl. 1.1: Explosives - Division 1.1 Expl. 1.4: Explosives – Division 1.4 Flam. Sol. 2: Flammable solids - Category 2 Ox. Liq. 1: Oxidizing liquids - Category 1 Ox. Sol. 1: Oxidizing solids - Category 1 Ox. Sol. 2: Oxidizing solids - Category 2 Acute Tox. 3: Acute toxicity - oral – Category 3 Acute Tox. 4: Acute toxicity - oral – Category 4 Acute Tox. 2: Acute toxicity - inhalation - Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2A. Serious eye damage/eye irritation - Category 2A Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2