

Printing date: September 26, 2014 Revision: September 26, 2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: 12 GA CN Powder Barricade
- · Article number: 3091
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Explosive product.
- · 1.3 Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

Safariland, LLC

13386 International Parkway

Jacksonville, FL 32218

Customer Care (800) 347-1200

- · Further information obtainable from: Customer Care Department
- · 1.4 Emergency telephone number:

ChemTel Inc.

(800)255-3924, +1 (813)248-0585

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H411.



exploding bomb

Expl. 1.4 H204 Fire or projection hazard.



skull and crossbones

Acute Tox. 3 H301 Toxic if swallowed.

Acute Tox. 3 H311 Toxic in contact with skin.

Acute Tox. 2 H330 Fatal if inhaled.



health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

Printing date: September 26, 2014 Revision: September 26, 2014

Trade name: 12 GA CN Powder Barricade

(Contd. of page 1)



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

T+; Very toxic

R26: Very toxic by inhalation.

🐼 T; Toxic

R24/25: Toxic in contact with skin and if swallowed.

Xn; Sensitising

R42/43: May cause sensitisation by inhalation and skin contact.

Xi; Irritant

R36/37/38: Irritating to eyes, respiratory system and skin.

R5-44-52/53: Heating may cause an explosion. Risk of explosion if heated under confinement. Harmful

to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H411.

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



This pictogram only applicable for EU regulations. Not for use in the United States (OSHA GHS).

(Contd. on page 3)

Printing date: September 26, 2014 Revision: September 26, 2014

Trade name: 12 GA CN Powder Barricade

(Contd. of page 2)









GHS01 GHS06 GHS08 GHS09

Signal word Danger

· Hazard-determining components of labelling:

glycerol trinitrate

2-chloroacetophenone

Rosin

diphenylamine

· Hazard statements

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H411.

H204 Fire or projection hazard.

H301+H311 Toxic if swallowed or in contact with skin.

Fatal if inhaled. H330 H315 Causes skin irritation. H319

Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction. H317 H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

The following Precautionary Statements are applicable only to the general GHS regulations and not the specific CLP regulation: P374.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P250 Do not subject to grinding/shock/friction.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P284 Wear respiratory protection.

Wear protective gloves/protective clothing/eye protection/face protection. P280

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P373 DO NOT fight fire when fire reaches explosives.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Fight fire with normal precautions from a reasonable distance. P374

P372 Explosion risk in case of fire.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water. P302+P352

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

· Additional information:

Can become highly flammable in use.

· Hazard description:

· WHMIS-symbols:

D1A - Very toxic material causing immediate and serious toxic effects

D2A - Very toxic material causing other toxic effects

(Contd. on page 4)

Printing date: September 26, 2014 Revision: September 26, 2014

Trade name: 12 GA CN Powder Barricade

(Contd. of page 3)

E - Corrosive material

F - Dangerously reactive material



· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



Warning: Contains lead salt(s). Long-term health hazard.

* - Indicates a long term health hazard from repeated or prolonged exposures.

· HMIS Long Term Health Hazard Substances

122-39-4 diphenylamine

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Explosive Product Notice

PREVENTION OF ACCIDENTS IN THE USE OF EXPLOSIVES - The prevention of accidents in the use of explosives is a result of careful planning and observance of the best known practices. The explosives user must remember that he is dealing with a powerful force and that various devices and methods have been developed to assist him in directing this force. He should realize that this force, if misdirected, may either kill or injure both him and his fellow workers.

WARNING - All explosives are dangerous and must be carefully handled and used following approved safety procedures either by or under the direction of competent, experienced persons in accordance with all applicable federal, state, and local laws, regulations, or ordinances. If you have any questions or doubts as to how to use any explosive product, DO NOT USE IT before consulting with your supervisor, or the manufacturer, if you do not have a supervisor. If your supervisor has any questions or doubts, he should consult the manufacturer before use.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 5)

(Contd. on page 6)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date: September 26, 2014 Revision: September 26, 2014

Trade name: 12 GA CN Powder Barricade

Dangerous components:	(Con	td. of pag
CAS: 9004-70-0	Nitrocellulose, colloided, granular	20-40
	E R3	20-40
	Expl. 1.1, H201	
CAS: 55-63-0 EINECS: 200-240-8 Index number: 603-034-00-X	glycerol trinitrate	20-409
	Unst. Expl., H200 Acute Tox. 2, H300; Acute Tox. 1, H310; Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Chronic 2, H411 Flam. Liq. 2, H225	
CAS: 532-27-4 EINECS: 208-531-1	2-chloroacetophenone ☐ T+ R26; ☐ T R24/25; ☐ Xn R42/43; ☐ Xi R37/38-41 ☐ Acute Tox. 2, H300; Acute Tox. 3, H311; Acute Tox. 1, H330 ☐ Resp. Sens. 1, H334 ☐ Eye Dam. 1, H318 ☐ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	10-20
CAS: 1309-48-4 EINECS: 215-171-9 ndex number: 025-199-09-0	magnesium oxide substance with a Community workplace exposure limit	5-10
CAS: 112945-52-5	Silicon Dioxide (Amorphous)	1-5%
CAS: 7757-79-1 EINECS: 231-818-8	potassium nitrate O R8	1-5%
240 0050 00 7	♦ Ox. Sol. 2, H272	4.50
CAS: 8050-09-7 EINECS: 232-475-7	Rosin	1-5%
	♦ Skin Sens. 1, H317	
CAS: 7440-50-8 EINECS: 231-159-6	copper substance with a Community workplace exposure limit	0,5-2
CAS: 122-39-4 EINECS: 204-539-4 ndex number: 612-026-00-5	diphenylamine T R23/24/25; N R50/53 R33	< 1,0
	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 STOT RE 2, H373 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
CAS: 85-98-3 EINECS: 201-645-2	1,3-diethyldiphenylurea Xn R22	< 1,0
	Aquatic Chronic 3, H412	
CAS: 7440-66-6	zinc metal N R50/53	< 1,0
EINECS: 201-645-2 CAS: 7440-66-6	1,3-diethyldiphenylurea Xn R22 Acute Tox. 4, H302 Aquatic Chronic 3, H412 zinc metal	

Printing date: September 26, 2014 Revision: September 26, 2014

Trade name: 12 GA CN Powder Barricade

(Contd. of page 5)

Notable Trace Components (≤ 0,1% w/w)

CAS: 15245-44-0 EINECS: 239-290-0

Index number: 609-019-00-4

lead 2,4,6-trinitro-m-phenylene dioxide

T Repr. Cat. 1, 3 R61; Xn R62-20/22; E R3; N R50/53 R33

Unst. Expl., H200

& Carc. 1B, H350; Repr. 1A, H360Df; STOT RE 2, H373

Aquatic Acute 1, H400; Aquatic Chronic 1, H410

Acute Tox. 4, H302; Acute Tox. 4, H332

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

Do not leave affected persons unattended.

Remove breathing equipment only after contaminated clothing have been completely removed.

· After inhalation:

Remove victim to fresh air.

Seek immediate medical advice.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After skin contact:

Immediately remove any clothing soiled by the product.

Brush off loose particles from skin.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Asthma attacks

Allergic reactions

Blast injury if mishandled.

May cause respiratory irritation.

Breathing difficulty

Coughing

Irritant to eyes.

Irritant to skin and mucous membranes.

· Hazards

Danger of blast or crush-type injuries.

Danger of impaired breathing.

(Contd. on page 7)

Printing date: September 26, 2014 Revision: September 26, 2014

Trade name: 12 GA CN Powder Barricade

(Contd. of page 6)

· 4.3 Indication of any immediate medical attention and special treatment needed

Product may produce physical injury if mishandled. Treatment of these injuries should be based on the blast and compression effects.

Contains [(2-chlorophenyl)methylene]malononitrile. May produce an allergic reaction.

Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible.

In cases of irritation to the lungs, initial treatment with cortical steroid inhalants.

Monitor circulation, possible shock treatment.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

If necessary oxygen respiration treatment.

Medical supervision for at least 48 hours.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

Flood area with water. If no water is available, carbon dioxide, dry chemical or earth may be used. If the fire reaches the cargo, withdraw and let fire burn.

- · For safety reasons unsuitable extinguishing agents: None.
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

Product may explode if burned in confined space. Individual cartridges may explode. Mass explosion of many cartridges at once is unlikely.

- 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information

Cool endangered receptacles with water spray.

Evacuate area and fight fire from from the upwind side.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Eliminate all ignition sources if safe to do so.

Flammability Classification: (defined by 29 CFR 1910.1200) Explosive. Can explode under fire conditions. Individual devices will randomly explode. Will not mass explode if multiple devices are involved. Burning material may produce toxic and irritating vapors. In unusual cases, shrapnel may be thrown from exploding devices under containment. See 2008 Emergency response Guidebook for further information.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

FOR ALL TRANSPORTATION ACCIDENTS, CALL CHEMTEL AT 1-800-255-3924. Spills of this material should be handled carefully. Do not subject materials to mechanical shock or extreme heat. A spill of this material will normally not require emergency response team capabilities.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Remove persons from danger area.

Ensure adequate ventilation

Protect from heat.

(Contd. on page 8)

Printing date: September 26, 2014 Revision: September 26, 2014

Trade name: 12 GA CN Powder Barricade

(Contd. of page 7)

Isolate area and prevent access.

- 6.2 Environmental precautions: No special measures required.
- · 6.3 Methods and material for containment and cleaning up:

Pick up mechanically.

Dispose contaminated material as waste according to item 13.

Send for recovery or disposal in suitable receptacles.

Clean the affected area carefully; suitable cleaners are:

Warm water and cleansing agent

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Handle with care. Avoid jolting, friction and impact.

Avoid breathing dust

Use only in well ventilated areas.

· Information about fire - and explosion protection:

Protect from heat.

Keep respiratory protective device available.

Emergency cooling must be available in case of nearby fire.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from flammable substances.

- · Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

1309-48-4 magnesium oxide

PEL (USA) Long-term value: 15* mg/m³ fume; *total particulate

(Contd. on page 9)

Printing date: September 26, 2014 Revision: September 26, 2014

Trade name: 12 GA CN Powder Barricade

		(Contd. of page
TLV (USA)	Long-term value: 10* mg/m³	
EL (O)	*as inhalable fraction	
EL (Canada)	Short-term value: 10** mg/m³ Long-term value: 10* 3** mg/m³	
	*inhalable fume;**respirable dust and fume	
FV (Canada)	Long-term value: 10 mg/m³	
EV (Gariada)	inhalable	
532-27-4 2-cl	nloroacetophenone	
PEL (USA)	Long-term value: 0,3 mg/m³, 0,05 ppm	
REL (USA)	Long-term value: 0,3 mg/m³, 0,05 ppm	
TLV (USA)	Long-term value: 0,32 mg/m³, 0,05 ppm	
, ,	Long-term value: 0,05 ppm	
,	S	
EV (Canada)	Long-term value: 0,32 mg/m³, 0,05 ppm	
55-63-0 glyce	erol trinitrate	
PEL (USA)	Ceiling limit: 2 mg/m³, 0,2 ppm	
	Skin	
REL (USA)	Short-term value: 0,1 mg/m³ Skin	
TLV (USA)	Long-term value: 0,46 mg/m³, 0,05 ppm Skin	
EL (Canada)	Long-term value: 0,05 ppm Skin	
EV (Canada)	Long-term value: 0,5 mg/m³, 0,05 ppm Skin	
8050-09-7 Rd	osin	
TLV (USA)	DSEN, RSEN, L	
EL (Canada)		
122-39-4 dip		
_	Long-term value: 10 mg/m³	
TLV (USA)	•	
` ,	Long-term value: 10 mg/m³	
,	Long-term value: 10 mg/m³	
7440-50-8 co		
PEL (USA)	Long-term value: 1* 0,1** mg/m³	
(00,1)	as Cu *dusts and mists **fume	
REL (USA)	Long-term value: 1* 0,1** mg/m³	
` ,	as Cu *dusts and mists **fume	
TLV (USA)	Long-term value: 1* 0,2** mg/m³	
	*dusts and mists; **fume; as Cu	
		(Contd. on page

Printing date: September 26, 2014 Revision: September 26, 2014

Trade name: 12 GA CN Powder Barricade

(Contd. of page 9)

EL (Canada) Long-term value: 1* 0,2** mg/m³ *dusts and mists; **fume, as Cu

EV (Canada) Long-term value: 0,2* 1** mg/m³ as copper, *fume;**dust and mists

- · DNELs No further relevant information available.
- · PNECs No further relevant information available.
- \cdot Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Immediately remove all soiled and contaminated clothing.

Do not inhale dust / smoke / mist.

Avoid contact with the eyes and skin.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Respiratory protection:



Respiratory protection required.

· Protection of hands:



Protective gloves

Wear gloves when handling deployed rounds.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Safety glasses

- Body protection: Protective work clothing
- · Limitation and supervision of exposure into the environment

No further relevant information available.

· Risk management measures

See Section 7 for additional information.

(Contd. on page 11)

Printing date: September 26, 2014 Revision: September 26, 2014

Trade name: 12 GA CN Powder Barricade

(Contd. of page 10)

Organizational measures should be in place for all activities involving this product. No further relevant information available.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Solid metal container containing liquid and solid contents.

Colour: According to product specification

Odour:
 Odour threshold:
 pH-value:
 Odourless
 Not determined.
 Not applicable.

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:
Undetermined.

Flash point:
Flammability (solid, gaseous):
Auto/Self-ignition temperature:
Not determined.

Not determined.

Not determined.

• **Self-igniting:** Product is not self-igniting.

• **Danger of explosion:** Heating may cause an explosion.

· Explosion limits:

Lower:
Upper:
Not determined.
Not determined.

Vapour pressure:
Not applicable.

Density:
Relative density
Vapour density
Vapour density
Evaporation rate
Not determined.
Not applicable.

· Solubility in / Miscibility with

water: Insoluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not applicable. **Kinematic:** Not applicable.

• **9.2 Other information** No further relevant information available.

(Contd. on page 12)

Printing date: September 26, 2014 Revision: September 26, 2014

Trade name: 12 GA CN Powder Barricade

(Contd. of page 11)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Danger of explosion.

Toxic fumes may be released if heated above the decomposition point.

Contact with acids releases toxic gases.

Acts as an oxidising agent on organic materials such as wood, paper and fats.

Reacts with strong alkali.

- 10.4 Conditions to avoid Sources of ignition, open flame, incompatible materials.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides

Sulphur oxides (SOx)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values	rolovant for	classification:
· LD/LCJU valucs	I CICVAIIL IUI	Ciassilication.

532-27-4 2-chloroacetophenone

Oral LD50 50 mg/kg (rat)

55-63-0 glycerol trinitrate

Oral LD50 115 mg/kg (mouse)

105 mg/kg (rat)

Dermal LD50 29 mg/kg (rat)

280 mg/kg (rabbit)

122-39-4 diphenylamine

Oral LD50 | 1120 mg/kg (rat)

Primary irritant effect:

Effects based on exposure to dusts/mists/spray/vapours released during deployment. Unused product does not posess these effects.

- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitisation:

Sensitisation possible through inhalation.

Sensitisation possible through skin contact.

· Additional toxicological information:

Normal handling of the undeployed product poses little or no health hazards, One should avoid inhalation by wearing appropriate respiratory protection when exposed to the chemical ingredients of the product above listed TLV's or when exposed to the post ignition by-products. This product is a cansister which

(Contd. on page 13)

Printing date: September 26, 2014 Revision: September 26, 2014

Trade name: 12 GA CN Powder Barricade

(Contd. of page 12)

contains the various components completely sealed within. Therefore, under normal handling of this product, no exposure to any harmful materials will occur. When the product is used, particles may be generated which may be irritating to the eyes and the respiratory tract.

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Harmful

Danger through skin adsorption.

Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible.

· Acute effects (acute toxicity, irritation and corrosivity):

Inhalation may cause irritation to the respiratory system.

· Repeated dose toxicity:

May cause damage to organs through prolonged or repeated exposure.

Repeated exposures may result in skin and/or respiratory sensitivity.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: The product contains materials that are harmful to the environment.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential May be accumulated in organism
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

The product contains heavy metals. Avoid transfer into the environment. Specific preliminary treatments are necessary

Harmful to aquatic organisms

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 14)

Printing date: September 26, 2014 Revision: September 26, 2014

Trade name: 12 GA CN Powder Barricade

(Contd. of page 13)

After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

UN0301

charge or propelling charge

expelling charge or propelling charge

Ammunition Tear-producing with burster, expelling

0301 Ammunition Tear-producing with burster,

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

· DOT, ADR, IMDG, IATA

· 14.2 UN proper shipping name

· DOT, IMDG, IATA

· 14.3 Transport hazard class(es)

· DOT

· ADR





· Class 1.4

· Label 1.4G+6.1+8

· ADR, IMDG







· Class 1.4

· Label 1.4G+6.1+8

·IATA





· Class 1.4G · Label 1.4G+6.1+8

· 14.4 Packing group

· DOT, ADR, IMDG, IATA Ш

· 14.5 Environmental hazards:

· Marine pollutant: No

(Contd. on page 15)

Printing date: September 26, 2014 Revision: September 26, 2014

Trade name: 12 GA CN Powder Barricade

· Special marking (IATA):

(Contd. of page 14)



Cargo Aircraft Only.

· 14.6 Special precautions for user

Not applicable.

· EMS Number:

F-A,S-Q

· 14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code

Not applicable.

· UN "Model Regulation":

UN0301, Ammunition Tear-producing with burster, expelling charge or propelling charge, 1.4G (6.1+8), II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

532-27-4 2-chloroacetophenone

55-63-0 glycerol trinitrate

7757-79-1 potassium nitrate

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65 (California):
- · Chemicals known to cause cancer:

Present in trace quantities.

15245-44-0 lead 2,4,6-trinitro-m-phenylene dioxide

· Chemicals known to cause reproductive toxicity for females:

Present in trace quantities.

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

Present in trace quantities.

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

Present in trace quantities.

15245-44-0 lead 2,4,6-trinitro-m-phenylene dioxide

- · Carcinogenic Categories
- · EPA (Environmental Protection Agency)

7440-50-8 copper

(Contd. on page 16)

D

Printing date: September 26, 2014 Revision: September 26, 2014

Trade name: 12 GA CN Powder Barricade

		(Contd. of page
· IARC (Int	ernational Agency for Research on Cancer)	
None of the	ne ingredients are listed.	
· TLV (Thre	eshold Limit Value established by ACGIH)	
1309-48-4	4 magnesium oxide	ļ.
532-27-4	4 2-chloroacetophenone	l l
122-39-4	diphenylamine	A
· NIOSH-C	a (National Institute for Occupational Safety and Health)	,
None of the	ne ingredients are listed.	
· Canada		
· Canadian	n Domestic Substances List (DSL)	
All ingredi	ients are listed.	
· Canadian	n Ingredient Disclosure list (limit 0.1%)	
122-39-4	diphenylamine	
· Canadian	n Ingredient Disclosure list (limit 1%)	
1309-48-4	4 magnesium oxide	
532-27-4	4 2-chloroacetophenone	

· Other regulations, limitations and prohibitive regulations

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

- · Substances of very high concern (SVHC) according to REACH, Article 57 None of the ingredients are listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H331

H200	Unstable explosives.
H201	Explosive; mass explosion hazard.
H225	Highly flammable liquid and vapour.
H272	May intensify fire; oxidiser.
H300	Fatal if swallowed.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.

Toxic if inhaled.

(Contd. on page 17)

Printing date: September 26, 2014 Revision: September 26, 2014

Trade name: 12 GA CN Powder Barricade

Trade fiame. 12 GA CN Fowder barricade	
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation.	(Contd. of page 16)
H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life.	
H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.	
H412 Harmful to aquatic life with long lasting effects.	
R22 Harmful if swallowed. R23/24/25 Toxic by inhalation, in contact with skin and if swallowed. R24/25 Toxic in contact with skin and if swallowed.	
R26 Very toxic by inhalation.	
R26/27/28 Very toxic by inhalation, in contact with skin and if swallowed. R3 Extreme risk of explosion by shock, friction, fire or other sources of ignition. R33 Danger of cumulative effects.	
R37/38 Irritating to respiratory system and skin. R41 Risk of serious damage to eyes.	
R42/43 May cause sensitisation by inhalation and skin contact.	
R43 May cause sensitisation by skin contact. R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects	s in the aquatic
environment. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquati	ic environment.
R8 Contact with combustible material may cause fire.	
 Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreen International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation 	nent concerning the
IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)	
WHMIS: Workplace Hazardous Materials Information System (Canada) DNEL: Derived No-Effect Level (REACH) DNEC: Product of No Effect Consentation (REACH)	
PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent Expl. 1.1: Explosives, Division 1.1	
Expl. 1.4: Explosives, Division 1.4 Unst. Explosives, Unstable explosives	
Flam. Liq. 2: Flammable liquids, Hazard Category 2 Ox. Sol. 2: Oxidising Solids, Hazard Category 2	
Acute Tox. 2: Acute toxicity, Hazard Category 2 Acute Tox. 4: Acute toxicity, Hazard Category 4	
Acute Tox. 1: Acute toxicity, Hazard Category 1 Acute Tox. 3: Acute toxicity, Hazard Category 3	
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1	
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1	
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1	(Contd. on page 18)

(Contd. on page 18)

Printing date: September 26, 2014 Revision: September 26, 2014

Trade name: 12 GA CN Powder Barricade

(Contd. of page 17)

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

Sources

SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com