

Printing date: August 26, 2014 Revision: August 26, 2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Defense Technology Aerial Warning / Signaling Munition CS 200 Meters
- · Article number: 6030CS
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture

Crowd Control Device Explosive product.

- · 1.3 Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

Safariland, LLC

13386 International Parkway

Jacksonville, FL 32218

Customer Care (800) 347-1200

- · Further information obtainable from: Customer Care Department
- · 1.4 Emergency telephone number:

ChemTel Inc.

(800)255-3924, +1 (813)248-0585

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



exploding bomb

Expl. 1.4 H204 Fire or projection hazard.



health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.Skin Sens. 1 H317 May cause an allergic skin reaction.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xn; Harmful

R20/22: Harmful by inhalation and if swallowed.

(Contd. on page 2)

Printing date: August 26, 2014 Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CS - 200 Meters

(Contd. of page 1)

Xn; Sensitising

R42/43: May cause sensitisation by inhalation and skin contact.

Xi; Irritant

R36/38: Irritating to eyes and skin.

R5-44: Heating may cause an explosion. Risk of explosion if heated under confinement.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS01 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

potassium perchlorate

[(2-chlorophenyl)methylene]malononitrile

· Hazard statements

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412.

H204 Fire or projection hazard.

H302 Harmful if swallowed.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P250 Do not subject to grinding/shock/friction.

P285 In case of inadequate ventilation wear respiratory protection.

P280 Wear eye protection / face protection.

P373 DO NOT fight fire when fire reaches explosives.

P370+P380 In case of fire: Evacuate area.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

(Contd. on page 3)

Printing date: August 26, 2014 Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CS - 200 Meters

(Contd. of page 2)

P372 Explosion risk in case of fire.

Additional information:

Can become highly flammable in use.

- · Hazard description:
- WHMIS-symbols:

D1A - Very toxic material causing immediate and serious toxic effects

D2A - Very toxic material causing other toxic effects

E - Corrosive material



· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



- * Indicates a long term health hazard from repeated or prolonged exposures.
- · HMIS Long Term Health Hazard Substances

7778-74-7 potassium perchlorate

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.
- · Explosive Product Notice

PREVENTION OF ACCIDENTS IN THE USE OF EXPLOSIVES - The prevention of accidents in the use of explosives is a result of careful planning and observance of the best known practices. The explosives user must remember that he is dealing with a powerful force and that various devices and methods have been developed to assist him in directing this force. He should realize that this force, if misdirected, may either kill or injure both him and his fellow workers.

WARNING - All explosives are dangerous and must be carefully handled and used following approved safety procedures either by or under the direction of competent, experienced persons in accordance with all applicable federal, state, and local laws, regulations, or ordinances. If you have any questions or doubts as to how to use any explosive product, DO NOT USE IT before consulting with your supervisor, or the manufacturer, if you do not have a supervisor. If your supervisor has any questions or doubts, he should consult the manufacturer before use.

(Contd. on page 4)

Printing date: August 26, 2014 Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CS - 200 Meters

(Contd. of page 3)

(Contd. on page 5)

3.2 Mixtures Description: Mixture of substances listed below with nonhazardous additions.		
Dangerous components:		
CAS: 7778-74-7 EINECS: 231-912-9 Index number: 017-008-00-5	potassium perchlorate Xn R22; O R9 Ox. Sol. 1, H271 Acute Tox. 4, H302	10-25%
CAS: 7757-79-1 EINECS: 231-818-8	potassium nitrate O R8 O Ox. Sol. 2, H272	10-25%
CAS: 2698-41-1 EINECS: 220-278-9	[(2-chlorophenyl)methylene]malononitrile ☐ T R25; ★ Xn R42/43; Ŋ N R50 ☐ Acute Tox. 3, H301 ☐ Resp. Sens. 1, H334 ☐ Aquatic Acute 1, H400 ☐ Skin Sens. 1, H317	2,5-10
CAS: 7439-95-4 EINECS: 231-104-6 Index number: 012-001-00-3	magnesium powder (pyrophoric) F R15-17 Pyr. Sol. 1, H250; Water-react. 1, H260	2,5-10
CAS: 7704-34-9 EINECS: 231-722-6 Index number: 016-094-00-1	sulfur ★ Xi R38	2,5-10
CAS: 7429-90-5 EINECS: 231-072-3	aluminium powder (pyrophoric) F R15-17 Pyr. Sol. 1, H250; Water-react. 2, H261	2,5-10
CAS: 9004-70-0 EC number: 603-037-0	Nitrocellulose, colloided, granular E R3 Expl. 1.1, H201	≤ 2,5%
CAS: 1309-48-4 EINECS: 215-171-9 Index number: 025-199-09-0	magnesium oxide substance with a Community workplace exposure limit	10-259
CAS: 7631-86-9 EINECS: 231-545-4	silicon dioxide	2,5-10

Printing date: August 26, 2014 Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CS - 200 Meters

	(Contd. of page 4)
CAS: 122-39-4	diphenylamine
EINECS: 204-539-4 Index number: 612-026-00-5	T R23/24/25; N R50/53 R33
	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 STOT RE 2, H373
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410
CAS: 12403-82-6	dihydroxy[styphnato(2-)]dilead / lead styphnate
EINECS: 235-642-2	T R23/25; Xn R40-48-62; ₩ E R3; ₩ N R50/53 R33
	Unst. Expl., H200 Acute Tox. 3, H301; Acute Tox. 2, H330
	Carc. 1B, H350; Repr. 2, H361; STOT RE 2, H373 Aquatic Acute 1, H400; Aquatic Chronic 1, H410

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

Seek immediate medical help for blistering or open wounds.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Unlikely route of exposure.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Asthma attacks

Irritant to skin and mucous membranes.

Irritant to eyes.

Breathing difficulty

Coughing

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

Allergic reactions

(Contd. on page 6)

Printing date: August 26, 2014 Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CS - 200 Meters

(Contd. of page 5)

· Hazards

Danger of impaired breathing.

Danger of disturbed cardiac rhythm.

Danger of pulmonary oedema.

Danger of blast or crush-type injuries.

· 4.3 Indication of any immediate medical attention and special treatment needed

Contains [(2-chlorophenyl)methylene]malononitrile. May produce an allergic reaction.

If necessary oxygen respiration treatment.

Product may produce physical injury if mishandled. Treatment of these injuries should be based on the blast and compression effects.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: None.
- · 5.2 Special hazards arising from the substance or mixture

Product may explode if burned in confined space. Individual cartridges may explode. Mass explosion of many cartridges at once is unlikely.

During heating or in case of fire poisonous gases are produced.

- 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Eliminate all ignition sources if safe to do so.

Flammability Classification: (defined by 29 CFR 1910.1200) Explosive. Can explode under fire conditions. Individual devices will randomly explode. Will not mass explode if multiple devices are involved. Burning material may produce toxic and irritating vapors. In unusual cases, shrapnel may be thrown from exploding devices under containment. See 2008 Emergency response Guidebook for further information.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

FOR ALL TRANSPORTATION ACCIDENTS, CALL CHEMTEL AT 1-800-255-3924. Spills of this material should be handled carefully. Do not subject materials to mechanical shock or extreme heat. A spill of this material will normally not require emergency response team capabilities.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Protect from heat.

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 7)

Printing date: August 26, 2014 Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CS - 200 Meters

(Contd. of page 6)

· 6.3 Methods and material for containment and cleaning up:

Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Dispose contaminated material as waste according to item 13.

Clean the affected area carefully; suitable cleaners are:

Warm water and cleansing agent

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Handle with care. Avoid jolting, friction and impact.

Information about fire - and explosion protection:

Protect from heat.

Substance/product can reduce the ignition temperature of flammable substances.

Emergency cooling must be available in case of nearby fire.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

Protect from humidity and water.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

Store away from flammable substances.

- · Further information about storage conditions: Store in dry conditions.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

1309-48-4 magnesium oxide

PEL (USA) Long-term value: 15* mg/m³ fume; *total particulate

(Contd. on page 8)

Printing date: August 26, 2014 Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CS - 200 Meters

	(Contd. of page 7)
TLV (USA)	Long-term value: 10* mg/m³
	*as inhalable fraction
EL (Canada)	
	Long-term value: 10* 3** mg/m³ *inhalable fume;**respirable dust and fume
EV (Canada)	Long-term value: 10 mg/m³
EV (Cariada)	inhalable
2698-41-1 [(2	-chlorophenyl)methylene]malononitrile
PEL (USA)	Long-term value: 0,4 mg/m³, 0,05 ppm
REL (USA)	Ceiling limit: 0,4 mg/m³, 0,05 ppm Skin
TLV (USA)	Ceiling limit: 0,39 mg/m³, 0,05 ppm Skin
EL (Canada)	Ceiling limit: 0,05 ppm Skin
EV (Canada)	Ceiling limit: 0,4 mg/m³, 0,05 ppm Skin
7429-90-5 alu	uminium powder (pyrophoric)
PEL (USA)	Long-term value: 15*; 15** mg/m³ *Total dust; ** Respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m³ as Al*Total dust**Respirable/pyro powd./welding f.
TLV (USA)	Long-term value: 1* mg/m³ as Al; *as respirable fraction
EL (Canada)	Long-term value: 1,0 mg/m³ respirable, as Al
EV (Canada)	Long-term value: 5 mg/m³
	aluminium-containing (as aluminium)

- **DNELs** No further relevant information available.
- · **PNECs** No further relevant information available.
- · **Additional information:** The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale dust / smoke / mist.

Avoid contact with the eyes and skin.

(Contd. on page 9)

Printing date: August 26, 2014 Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CS - 200 Meters

(Contd. of page 8)

· Respiratory protection:



Respiratory protection required.

Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in large quantities.

Protection of hands:

Gloves not required under normal conditions of use.

Wear protective gloves to handle contents of damaged or leaking units.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Safety glasses

- · Body protection: Protective work clothing
- · Limitation and supervision of exposure into the environment

No further relevant information available.

Risk management measures

See Section 7 for additional information.

Organizational measures should be in place for all activities involving this product.

No further relevant information available.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Appearance:

Form: Solid metal container containing liquid and solid contents.

Colour: According to product specification

Odour:Odour threshold:pH-value:Odour threshold:Not determined.Not applicable.

Change in condition

Melting point/Melting range:
Boiling point/Boiling range:

Variable Variabl

(Contd. on page 10)

Printing date: August 26, 2014 Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CS - 200 Meters

(Contd. of page 9)

Flammability (solid, gaseous): Not determined.
 Auto/Self-ignition temperature: Not determined.
 Decomposition temperature: Not determined.

· **Self-igniting**: Product is not self-igniting.

• **Danger of explosion:** Heating may cause an explosion.

Risk of explosion by shock, friction, fire or other sources of

ignition.

· Explosion limits:

Lower:
Upper:
Not determined.
Not determined.

Vapour pressure:
Not applicable.

Density:
Relative density
Vapour density
Vapour density
Evaporation rate
Not determined.
Not applicable.
Not applicable.

· Solubility in / Miscibility with

water: Insoluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not applicable. **Kinematic:** Not applicable.

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· 10.3 Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point.

Can react violently with oxygen rich (oxidizing) material. Danger of Explosion.

Reacts with flammable substances.

· 10.4 Conditions to avoid

Store away from oxidizing agents.

Keep ignition sources away - Do not smoke.

Cartridge may detonate if case is punctured or severely damaged.

- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Toxic metal oxide smoke Chlorine compounds

(Contd. on page 11)

Printing date: August 26, 2014 Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CS - 200 Meters

(Contd. of page 10)

Nitrogen oxides

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- LD/LC50 values relevant for classification:

2698-41-1 [(2-chlorophenyl)methylene]malononitrile

Oral LD50 178 mg/kg (rat)

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

Normal handling of the undeployed product poses little or no health hazards, One should avoid inhalation by wearing appropriate respiratory protection when exposed to the chemical ingredients of the product above listed TLV's or when exposed to the post ignition by-products. This product is a cansister which contains the various components completely sealed within. Therefore, under normal handling of this product, no exposure to any harmful materials will occur. When the product is used, particles may be generated which may be irritating to the eyes and the respiratory tract.

- · Acute effects (acute toxicity, irritation and corrosivity): Harmful if inhaled.
- · Repeated dose toxicity: Repeated exposures may result in skin and/or respiratory sensitivity.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

2698-41-1 [(2-chlorophenyl)methylene]malononitrile

EC50 0,2-0,3 mg/kg (Oncorhynchus mykiss)

96 H

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

(Contd. on page 12)

Printing date: August 26, 2014 Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CS - 200 Meters

(Contd. of page 11)

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

UN0301

FORBIDDEN

FORBIDDEN

charge or propelling charge

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

· DOT, ADR, IMDG

· IATA

· 14.2 UN proper shipping name

DOT, IMDG

· ADR

· IATA

· 14.3 Transport hazard class(es)

· DOT



· Class 1.4

· **Label** 1.4G+6.1+8

(Contd. on page 13)

Ammunition Tear-producing with burster, expelling

UN0301, Ammunition Tear-producing with burster,

expelling charge or propelling charge, 1.4G, II

Printing date: August 26, 2014 Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CS - 200 Meters

(Contd. of page 12)

· ADR



· Class 1.4

· Label 1.4G+6.1+8

· IMDG



· Class 1.4

· Label 1.4G+6.1+8

· IATA

· Class **FORBIDDEN** · Label **FORBIDDEN**

· 14.4 Packing group

· DOT, ADR, IMDG

FORBIDDEN ·IATA

· 14.5 Environmental hazards:

· Marine pollutant: No

Special marking (ADR): Symbol (fish and tree) 14.6 Special precautions for user Not applicable.

EMS Number: F-A,S-Q · Segregation groups Chlorates

· 14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code

Not applicable. UN "Model Regulation": UN0301, Ammunition Tear-producing with burster,

expelling charge or propelling charge, 1.4G, II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- ·SARA
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

7757-79-1 potassium nitrate

(Contd. on page 14)

Printing date: August 26, 2014 Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CS - 200 Meters

	(Contd. of page
7429-90-5 aluminium powder (pyrophoric)	
· TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
· Proposition 65 (California):	
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients are listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity: Present in trace quantities.	
None of the ingredients is listed.	
· Carcinogenic Categories	
EPA (Environmental Protection Agency)	
7778-74-7 potassium perchlorate	N
· IARC (International Agency for Research on Cancer)	
7631-86-9 silicon dioxide	,
· TLV (Threshold Limit Value established by ACGIH)	·
1309-48-4 magnesium oxide	A
2698-41-1 [(2-chlorophenyl)methylene]malononitrile	A
7429-90-5 aluminium powder (pyrophoric)	A
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
· Canada	
· Canadian Domestic Substances List (DSL)	
All ingredients are listed.	
· Canadian Ingredient Disclosure list (limit 0.1%)	
None of the ingredients is listed.	
· Canadian Ingredient Disclosure list (limit 1%)	
1309-48-4 magnesium oxide	
2698-41-1 [(2-chlorophenyl)methylene]malononitrile	
7429-90-5 aluminium powder (pyrophoric)	
7631-86-9 silicon dioxide	
Other regulations, limitations and prohibitive regulations This product has been classified in accordance with hazard criteria of the Control and the SDS contains all the information required by the Controlled Products Reg	
Substances of very high concern (SVHC) according to REACH, Article 57	
None of the ingredients is listed.	

Printing date: August 26, 2014 Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CS - 200 Meters

(Contd. of page 14)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H201 Explosive; mass explosion hazard.
- H250 Catches fire spontaneously if exposed to air.
- H260 In contact with water releases flammable gases which may ignite spontaneously.
- H261 In contact with water releases flammable gases.
- H271 May cause fire or explosion; strong oxidiser.
- H272 May intensify fire; oxidiser.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H400 Very toxic to aquatic life.
- R15 Contact with water liberates extremely flammable gases.
- R17 Spontaneously flammable in air.
- R22 Harmful if swallowed.
- R25 Toxic if swallowed.
- R3 Extreme risk of explosion by shock, friction, fire or other sources of ignition.
- R38 Irritating to skin.
- R42/43 May cause sensitisation by inhalation and skin contact.
- R50 Very toxic to aquatic organisms.
- R8 Contact with combustible material may cause fire.
- R9 Explosive when mixed with combustible material.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Expl. 1.1: Explosives, Division 1.1

Expl. 1.4: Explosives, Division 1.4

Pyr. Sol. 1: Pyorphoric Solids, Hazard Category 1

(Contd. on page 16)

Printing date: August 26, 2014 Revision: August 26, 2014

Trade name: Defense Technology Aerial Warning / Signaling Munition CS - 200 Meters

(Contd. of page 15)

Water-react. 1: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 1

Water-react. 2: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 2

Ox. Sol. 1: Oxidising Solids, Hazard Category 1 Ox. Sol. 2: Oxidising Solids, Hazard Category 2 Acute Tox. 3: Acute toxicity, Hazard Category 3 Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

· Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com