according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Revision: July 21, 2015

SECTION 1: Identification of the substance/mixture and of the company/ undertaking 1.1 Product identifier • Trade name: Defense Technology 40MM Ground Marker Yellow Colored Smoke - 200 Meters · Article number: 6583Y · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Explosive product. 1.3 Details of the supplier of the Safety Data Sheet · Manufacturer/Supplier: Safariland, LLC 13386 International Parkway Jacksonville, FL 32218 Customer Care (800) 347-1200 · Further information obtainable from: Customer Care Department · 1.4 Emergency telephone number: ChemTel Inc. (800)255-3924, +1 (813)248-0585 Poison Control Centres: In the United Kingdom: 844 892 0111 In Australia: 131126 In New Zealand: +0800 764 766 SECTION 2: Hazards identification · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412. exploding bomb Expl. 1.4 H204 Fire or projection hazard. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412. The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS01 (Cont'd. on page 2)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Revision: July 21, 2015

Trade name: Defense Technology 40MM Ground Marker Yellow Colored Smoke - 200 Meters

(Cont'd. from page 1) · Signal word Warning · Hazard statements The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412. H204 Fire or projection hazard. H412 Harmful to aquatic life with long lasting effects. **Precautionary statements** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210 smoking. P250 Do not subject to grinding/shock/friction. Wear eye protection / face protection. P280 P373 DO NOT fight fire when fire reaches explosives. P370+P380 In case of fire: Evacuate area. P372 Explosion risk in case of fire. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · Additional information: Can become highly flammable in use. • NFPA ratings (scale 0 - 4) Health = 1 Fire = 3Reactivity = 3 · HMIS-ratings (scale 0 - 4) HEALTH 1 Health = 1 ³ Fire = 3 FIRE **REACTIVITY** 3 Reactivity = 3 HMIS Long Term Health Hazard Substances None of the ingredients are listed. · 2.3 Other hazards Results of PBT and vPvB assessment • **PBT:** Not applicable. vPvB: Not applicable. **Explosive Product Notice** (Cont'd. on page 3)

GHS

Printing date July 21, 2015

Revision: July 21, 2015

Trade name: Defense Technology 40MM Ground Marker Yellow Colored Smoke - 200 Meters

(Cont'd. from page 2)

PREVENTION OF ACCIDENTS IN THE USE OF EXPLOSIVES - The prevention of accidents in the use of explosives is a result of careful planning and observance of the best known practices. The explosives user must remember that he is dealing with a powerful force and that various devices and methods have been developed to assist him in directing this force. He should realize that this force, if misdirected, may either kill or injure both him and his fellow workers.

WARNING - All explosives are dangerous and must be carefully handled and used following approved safety procedures either by or under the direction of competent, experienced persons in accordance with all applicable federal, state, and local laws, regulations, or ordinances. If you have any questions or doubts as to how to use any explosive product, DO NOT USE IT before consulting with your supervisor, or the manufacturer, if you do not have a supervisor. If your supervisor has any questions or doubts, he should consult the manufacturer before use.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 9004-70-0	Nitrocellulose, colloided, granular	20-40%
EC number: 603-037-0	🔗 Expl. 1.1, H201	-
CAS: 100-21-0	terephthalic acid	20-40%
EINECS: 202-830-0	substance with a Community workplace exposure limit	40.000/
CAS: 3811-04-9	potassium chlorate	10-20%
EINECS: 223-289-7 Index number: 017-004-00-3	Ox. Sol. 1, H271 Aquatic Chronic 2, H411	
	Acute Tox. 4, H302; Acute Tox. 4, H332	
CAS: 57-50-1	sucrose, pure	5-10%
EINECS: 200-334-9	substance with a Community workplace exposure limit	0-1070
CAS: 598-62-9	manganese carbonate	5-10%
EINECS: 209-942-9	substance with a Community workplace exposure limit	
CAS: 7757-79-1	potassium nitrate	1-5%
EINECS: 231-818-8	🗞 Ox. Sol. 2, H272	
CAS: 7440-21-3	silicon	1-5%
EINECS: 231-130-8	🚸 Flam. Sol. 2, H228	
CAS: 7429-90-5	aluminium powder (pyrophoric)	< 1,0%
EINECS: 231-072-3	🚸 Pyr. Sol. 1, H250; Water-react. 2, H261	1
Index number: 013-001-00-6		
· Additional information: For	the wording of the listed Hazard Statements refer to section 16.	
· Notable Trace Components	s (≤ 0,1% w/w)	
	(Cont	d. on page

GHS

Printing date July 21, 2015

Revision: July 21, 2015

Trade name: Defense Technology 40MM Ground Marker Yellow Colored Smoke - 200 Meters

	(Cont'd. from page 3)
CAS: 122-39-4	diphenylamine
EINECS: 204-539-4 Index number: 612-026-00-5	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 STOT RE 2, H373 Aquatic Acute 1, H400; Aquatic Chronic 1, H410
CAS: 12403-82-6 EINECS: 235-642-2	dihydroxy[styphnato(2-)]dilead / lead styphnate Unst. Expl., H200 Acute Tox. 3, H301; Acute Tox. 2, H330 Carc. 1B, H350; Repr. 2, H361; STOT RE 2, H373 Aquatic Acute 1, H400; Aquatic Chronic 1, H410

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

• After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing:

Unlikely route of exposure.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Coughing

Irritant to skin and mucous membranes.

Irritant to eyes.

• Hazards Danger of blast or crush-type injuries.

4.3 Indication of any immediate medical attention and special treatment needed

If necessary oxygen respiration treatment.

Product may produce physical injury if mishandled. Treatment of these injuries should be based on the blast and compression effects.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: None.
- 5.2 Special hazards arising from the substance or mixture

Product may explode if burned in confined space. Individual cartridges may explode. Mass explosion of many cartridges at once is unlikely.

(Cont'd. on page 5)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Revision: July 21, 2015

(Cont'd. from page 4)

Trade name: Defense Technology 40MM Ground Marker Yellow Colored Smoke - 200 Meters

Formation of toxic gases is possible during heating or in case of fire.

• 5.3 Advice for firefighters

• Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information

Eliminate all ignition sources if safe to do so.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Flammability Classification: (defined by 29 CFR 1910.1200) Explosive. Can explode under fire conditions. Individual devices will randomly explode. Will not mass explode if multiple devices are involved. Burning material may produce toxic and irritating vapors. In unusual cases, shrapnel may be thrown from exploding devices under containment. See 2008 Emergency response Guidebook for further information.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

FOR ALL TRANSPORTATION ACCIDENTS, CALL CHEMTEL AT 1-800-255-3924. Spills of this material should be handled carefully. Do not subject materials to mechanical shock or extreme heat. A spill of this material will normally not require emergency response team capabilities.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Protect from heat.

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Dispose contaminated material as waste according to section 13.

Clean the affected area carefully; suitable cleaners are:

Warm water and cleansing agent

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

• **7.1 Precautions for safe handling** Keep away from heat and direct sunlight.

Handle with care. Avoid jolting, friction and impact.

Information about fire - and explosion protection:

Protect from heat.

Substance/product can reduce the ignition temperature of flammable substances. Emergency cooling must be available in case of nearby fire.

(Cont'd. on page 6)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Revision: July 21, 2015

Trade name: Defense Technology 40MM Ground Marker Yellow Colored Smoke - 200 Meters

(Cont'd. from page 5)
7.2 Conditions for safe storage, including any incompatibilities
Storage:
Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.
Protect from humidity and water.

Information about storage in one common storage facility:

Store away from foodstuffs.
Store away from oxidising agents.
Store away from flammable substances.

Further information about storage conditions: Store in dry conditions.
7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see section 7.

· 8.1 Control parameters

· 8.1 Control p	
· Ingredients v	vith limit values that require monitoring at the workplace:
100-21-0 tere	phthalic acid
TLV (USA)	Long-term value: 10 mg/m ³
EL (Canada)	Long-term value: 10 mg/m ³
EV (Canada)	Long-term value: 10 mg/m ³
57-50-1 sucre	ose, pure
PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	Long-term value: 10 mg/m ³
EL (Canada)	Long-term value: 10 mg/m ³
EV (Canada)	Long-term value: 10 mg/m³ total dust
598-62-9 mar	nganese carbonate
PEL (USA)	Ceiling limit: 5 mg/m³ as Mn
REL (USA)	Short-term value: 3 mg/m³ Long-term value: 1 mg/m³ as Mn
TLV (USA)	Long-term value: 0,02* 0,1* mg/m³ as Mn; *respirable **inhalable fraction
EL (Canada)	Long-term value: 0,2 mg/m³ as Mn; R
	(Cont'd. on page 7)

Revision: July 21, 2015

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date July 21, 2015

Trade name: Defense Technology 40MM Ground Marker Yellow Colored Smoke - 200 Meters

*total dust **respirable fractionREL (USA)Long-term value: 10* 5** mg/m³ *total dust **respirable fractionTLV (USA)TLV withdrawnEL (Canada)Long-term value: 10 mg/m³ total dustEV (Canada)Long-term value: 10 mg/m³ total dust 7429-90-5 aluminium powder (pyrophoric) PEL (USA)Long-term value: 15*; 15** mg/m³ *Total dust; ** Respirable fractionREL (USA)Long-term value: 10* 5** mg/m³ *Total dust; ** Respirable fraction		(Cont'd. from page
"total dust **respirable fraction REL (USA) Long-term value: 10* 5** mg/m³ 'total dust **respirable fraction TLV (USA) EL (Canada) Long-term value: 10 mg/m³ total dust 7429-90-5 aluminium powder (pyrophoric) PEL (USA) Long-term value: 15*; 15** mg/m³ * Total dust ** Respirable fraction Long-term value: 10* 5** mg/m³ * Total dust ** Respirable fraction LUGA-term value: 10* 5** mg/m³ * Total dust ** Respirable fraction LUNg-term value: 10, mg/m³ as Al; *as respirable fraction LU (USA) Long-term value: 1,0 mg/m³ metal and insoluble compdounds, respirable EV (Canada) Long-term value: 5 mg/m³ aluminium-containing (as aluminium) DNELs No further relevant information available. PMECS No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls General protective equipment: General protective equipment: General protective equipment: General protective ext and at the end of		
REL (USA) Long-term value: 10* 5** mg/m³ *total dust **respirable fraction TLV USA) TLV withdrawn EL (Canada) Long-term value: 10 mg/m³ EV (Canada) Long-term value: 10 mg/m³ total dust 7429-90-5 aluminium powder (pyrophoric) PEL (USA) Long-term value: 15*; 15** mg/m³ *Total dust; ** Respirable fraction REL (USA) Long-term value: 15*; 15** mg/m³ *Total dust **Respirable fraction REL (USA) Long-term value: 1* mg/m³ as Al; *as respirable fraction EL (Canada) Long-term value: 1* mg/m³ as Al; *as respirable fraction EL (Canada) Long-term value: 10 mg/m³ metal and insoluble compdounds, respirable EV (Canada) Long-term value: 1,0 mg/m³ metal and insoluble compdounds, respirable EV (Canada) Long-term value: 1,0 mg/m³ metal and insoluble compdounds, respirable EV (Canada) Long-term value: 1,0 mg/m³ aluminium-containing (as aluminium) DNELs No further relevant information available. Additional information : The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective equipment: General protective equipment: General protective equipment: Avoid contact with the eyes. Respiratory protection: Not required under normal conditions of use. Wear protection: Not required under normal conditions of use. Wear protection of hands: Protection of hands: Protection of hands: Protection of hands: Material of gloves The selection of the glove solves not noly depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of seve substances, the resistance of the glove material can not be calculated in advance and has therefore to checked prior to the application.	PEL (USA)	
*total dust **respirable fraction TLV (USA) TLV withdrawn EL (Canada) Long-term value: 10 mg/m³ EV (Canada) Deng-term value: 10 mg/m³ total dust 729-90-5 aluminium powder (pyrophoric) PEL (USA) Long-term value: 10* 5** mg/m³ *Total dust; ** Respirable fraction REL (USA) Long-term value: 10* 5** mg/m³ *Total dust **Respirable fraction TLV (USA) Long-term value: 1, 0 mg/m³ metal and insoluble compdounds, respirable EV (Canada) Long-term value: 5 mg/m³ metal and insoluble compdounds, respirable EV (Canada) Deng-term value: 5 mg/m³ metal and insoluble compdounds, respirable EV (Canada) Deng-term value: 5 mg/m³ aluminium-Containing (as aluminium) DELs No further relevant information available. PNECs No further relevant information available. Presonal protective equipment: General protective equipment: General protective equipment: General protective equipment: Respiratory protection:		
TLV (USA) TLV withdrawn EL (Canada) Long-term value: 10 mg/m³ EV (Canada) Long-term value: 10 mg/m³ T429-90-5 aluminium powder (pyrophoric) PEL (USA) Long-term value: 15°; 15°* mg/m³ *Total dust; ** Respirable fraction REL (USA) Long-term value: 10 * 5°* mg/m³ *Total dust; ** Respirable fraction TLV (USA) Long-term value: 10 mg/m³ *Total dust **Respirable fraction TLV (USA) Long-term value: 10 mg/m³ *Total dust **Respirable fraction EL (Canada) Long-term value: 10 mg/m³ metal and insoluble compdounds, respirable EV (Canada) Long-term value: 5 mg/m³ aluminium-containing (as aluminium) DNELs No further relevant information available. PMECS No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective and hygienic measures: The usual proceautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all solide and contaminated clothing.	REL (USA)	
EL (Canada) EV (Canada) Long-term value: 10 mg/m ³ total dust 7429-90-5 aluminium powder (pyrophoric) PEL (USA) Long-term value: 15*; 15** mg/m ³ "Total dust; ** Respirable fraction REL (USA) Long-term value: 10* 5** mg/m ³ "Total dust **Respirable fraction TLV (USA) Long-term value: 10 mg/m ³ metal and insoluble compdounds, respirable EL (Canada) Long-term value: 1.0 mg/m ³ metal and insoluble compdounds, respirable EV (Canada) Long-term value: 5 mg/m ³ aluminium-containing (as aluminium) DNELs No further relevant information available. PNECs No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale dust / smoke / mist. Avoid contact with the eyes. Respiratory protection: Not required under normal conditions of use. Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Protection of hands: Gloves not required under normal conditions of use. Wear protective gloves to handle contents of damaged or leaking units. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of sever substances, the resistance of the glove material can not be calculated in advance and has therefore to checked prior to the application.		
EV (Canada) Long-term value: 10 mg/m³ total dust 7429-90-5 aluminium powder (pyrophoric) PEL (USA) Long-term value: 15'; 15** mg/m³ *Total dust; ** Respirable fraction REL (USA) Long-term value: 10* 5** mg/m³ *Total dust ** Respirable fraction TLV (USA) Long-term value: 1* mg/m³ as Al; *as respirable fraction EL (Canada) Long-term value: 1,0 mg/m³ metal and insoluble compdounds, respirable EV (Canada) Long-term value: 5 mg/m³ aluminium) DNELs No further relevant information available. PMECS No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale dust / smoke / mist. Avoid contact with the eyes. Respiratory protection: Not required under normal conditions of use. Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Protection of hands: Gl	. ,	
Iteration Iteration 7429-0-5 aluminium powder (pyrophoric) PEL (USA) Long-term value: 15*; 15** mg/m³ *Total dust, ** Respirable fraction REL (USA) Long-term value: 10* 5** mg/m³ *Total dust ** Respirable fraction TLV (USA) Long-term value: 10 mg/m³ as Al; *as respirable fraction EL (Canada) Long-term value: 1,0 mg/m³ metal and insoluble compdounds, respirable EV (Canada) Long-term value: 5 mg/m³ aluminium-containing (as aluminium) DNELs No further relevant information available. PNECS No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale dust / smoke / mist. Avoid contact with the eyes. Respiratory protection: Not required under normal conditions of use. <th></th> <td></td>		
PEL (USA) Long-term value: 15*: 15** mg/m ³ *Total dust; ** Respirable fraction REL (USA) Long-term value: 10* 5** mg/m ³ *Total dust **Respirable fraction Long-term value: 11* mg/m ³ as Al; *as respirable fraction EL (Canada) Long-term value: 1,0 mg/m ³ metal and insoluble compdounds, respirable EV (Canada) Long-term value: 5 mg/m ³ aluminium-containing (as aluminium) DNELs No further relevant information available. PNECs No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale dust / smoke / mist. Avoid contact with the eyes. Respiratory protection: Gloves not required under normal conditions of use. Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Protection of hands: Gloves not required under normal conditions of use. Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Meterial of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of seves substances, the resistance of the glove material can not be calculated in advance and has therefore to substances, the resistance of the glove material can not be calculated in advance and has therefore to substances, the resistance of the glove material can not be calculated in advance and has therefore to substances, the resistance of the glove material can not be calculated in advance and has therefore to substances, the resistance of the glove material can not be calculated in advance and has therefore to substance	EV (Canada)	
 *Total dust; ** Respirable fraction REL (USA) Long-term value: 10* 5** mg/m³ *Total dust **Respirable fraction TLV (USA) Long-term value: 1,0 mg/m³ as Al; *as respirable fraction EL (Canada) Long-term value: 1,0 mg/m³ metal and insoluble compdounds, respirable EV (Canada) Long-term value: 5 mg/m³ aluminium-containing (as aluminium) DNELs No further relevant information available. PNECS No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective equipment: General protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale dust / smoke / mist. Avoid contact with the eyes. Respiratory protection: Not required under normal conditions of use. Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Protection of hands: Gloves not required under normal conditions of use. Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Protection of hands: Gloves not required under normal conditions of use. Wear positive pressure to be adoened or leaking units. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of sevel substances, the resistance of the glove material can not be calculated in advan	7429-90-5 al	uminium powder (pyrophoric)
REL (USA) Long-term value: 10* 5** mg/m³ *Total dust **Respirable fraction TLV (USA) Long-term value: 1* mg/m³ as Al; *as respirable fraction EL (Canada) Long-term value: 1.0 mg/m³ metal and insoluble compdounds, respirable EV (Canada) Long-term value: 5 mg/m³ aluminium-containing (as aluminium) DNELs No further relevant information available. PMECs No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale dust / smoke / mist. Avoid contact with the eyes. Respiratory protection: Not required under normal conditions of use. Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Protection of hands: Gloves not required under normal conditions of use.	PEL (USA)	
 *Total dust **Respirable fraction TLV (USA) Long-term value: 1* mg/m³ as Al; *as respirable fraction EL (Canada) Long-term value: 5 mg/m³ aluminium-containing (as aluminium) DNELs No further relevant information available. PNECs No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Do to inhale dust / smoke / mist. Avoid contact with the eyes. Respiratory protection: Not required under normal conditions of use. Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Protection of hands: Gloves not required under normal conditions of use. Wear protective gloves to handle contents of damaged or leaking units. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of severe substances, the resistance of the glove material can not be calculated in advance and has therefore to checked prior to the application. 	REL (USA)	
as Ai; *as respirable fraction EL (Canada) Long-term value: 1,0 mg/m³ metal and insoluble compdounds, respirable EV (Canada) Long-term value: 5 mg/m³ aluminium-containing (as aluminium) DNELs No further relevant information available. PNECs No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale dust / smoke / mist. Avoid contact with the eyes. Respiratory protection: Not required under normal conditions of use. Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Protection of hands: Gloves not required under normal conditions of use. Wear protective gloves to handle contents of damaged or leaking units. Material of gloves The selection of the suitable gloves does not only depend on t	· · · · ·	
EL (Canada) Long-term value: 1,0 mg/m ³ metal and insoluble compdounds, respirable EV (Canada) Long-term value: 5 mg/m ³ aluminium-containing (as aluminium) DNELs No further relevant information available. PNECS No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective equipment: General protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale dust / smoke / mist. Avoid contact with the eyes. Respiratory protection: Not required under normal conditions of use. Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Protection of hands: Gloves not required under normal conditions of use. Wear protective gloves to handle contents of damaged or leaking units. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of seve substances, the resistance of the glove material can not be calculated in advance and has therefore to checked prior to the application.	TLV (USA)	
metal and insoluble compdounds, respirable EV (Canada) Long-term value: 5 mg/m³ aluminium-containing (as aluminium) DNELs No further relevant information available. PNECS No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale dust / smoke / mist. Avoid contact with the eyes. Respiratory protection: Not required under normal conditions of use. Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Protection of hands: Gloves not required under normal conditions of use. Wear protective gloves to handle contents of damaged or leaking units. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of sever substances, the resistance of the glove material		
aluminium-containing (as aluminium) DNELs No further relevant information available. PNECs No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale dust / smoke / mist. Avoid contact with the eyes. Respiratory protection: Not required under normal conditions of use. Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Protection of hands: Gloves not required under normal conditions of use. Wear protective gloves to handle contents of damaged or leaking units. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of sever substances, the resistance of the glove material can not be calculated in advance and has therefore to checked prior to the application.	EL (Canada)	
 PNECs No further relevant information available. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale dust / smoke / mist. Avoid contact with the eyes. Respiratory protection: Not required under normal conditions of use. Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Protection of hands: Gloves not required under normal conditions of use. Wear protective gloves to handle contents of damaged or leaking units. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of sever substances, the resistance of the glove material can not be calculated in advance and has therefore to checked prior to the application. 	EV (Canada)	
 Personal protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale dust / smoke / mist. Avoid contact with the eyes. Respiratory protection: Not required under normal conditions of use. Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Protection of hands: Gloves not required under normal conditions of use. Wear protective gloves to handle contents of damaged or leaking units. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of sevel substances, the resistance of the glove material can not be calculated in advance and has therefore to checked prior to the application. 	Additional in	formation: The lists valid during the making were used as basis.
 General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale dust / smoke / mist. Avoid contact with the eyes. Respiratory protection: Not required under normal conditions of use. Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Protection of hands: Gloves not required under normal conditions of use. Wear protective gloves to handle contents of damaged or leaking units. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of sevel substances, the resistance of the glove material can not be calculated in advance and has therefore to checked prior to the application. 		
The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale dust / smoke / mist. Avoid contact with the eyes. Respiratory protection: Not required under normal conditions of use. Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Protection of hands: Gloves not required under normal conditions of use. Wear protective gloves to handle contents of damaged or leaking units. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of sever substances, the resistance of the glove material can not be calculated in advance and has therefore to checked prior to the application.		
 Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale dust / smoke / mist. Avoid contact with the eyes. Respiratory protection: Not required under normal conditions of use. Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Protection of hands: Gloves not required under normal conditions of use. Wear protective gloves to handle contents of damaged or leaking units. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of severations substances, the resistance of the glove material can not be calculated in advance and has therefore to checked prior to the application. 		
Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale dust / smoke / mist. Avoid contact with the eyes. Respiratory protection: Not required under normal conditions of use. Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Protection of hands: Gloves not required under normal conditions of use. Wear protective gloves to handle contents of damaged or leaking units. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of sever substances, the resistance of the glove material can not be calculated in advance and has therefore to checked prior to the application.		
Do not inhale dust / smoke / mist. Avoid contact with the eyes. Respiratory protection: Not required under normal conditions of use. Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Protection of hands: Gloves not required under normal conditions of use. Wear protective gloves to handle contents of damaged or leaking units. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of sever substances, the resistance of the glove material can not be calculated in advance and has therefore to checked prior to the application.	Immediately I	emove all soiled and contaminated clothing.
Avoid contact with the eyes. Respiratory protection: Not required under normal conditions of use. Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Protection of hands: Gloves not required under normal conditions of use. Wear protective gloves to handle contents of damaged or leaking units. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of sever substances, the resistance of the glove material can not be calculated in advance and has therefore to checked prior to the application.		
Respiratory protection: Not required under normal conditions of use. Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Protection of hands: Gloves not required under normal conditions of use. Wear protective gloves to handle contents of damaged or leaking units. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of sever substances, the resistance of the glove material can not be calculated in advance and has therefore to checked prior to the application.		
Not required under normal conditions of use. Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Protection of hands: Gloves not required under normal conditions of use. Wear protective gloves to handle contents of damaged or leaking units. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of sever substances, the resistance of the glove material can not be calculated in advance and has therefore to checked prior to the application.		
Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in lar quantities. Protection of hands: Gloves not required under normal conditions of use. Wear protective gloves to handle contents of damaged or leaking units. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of sever substances, the resistance of the glove material can not be calculated in advance and has therefore to checked prior to the application.		
Protection of hands: Gloves not required under normal conditions of use. Wear protective gloves to handle contents of damaged or leaking units. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of sever substances, the resistance of the glove material can not be calculated in advance and has therefore to checked prior to the application.	Wear positiv	
Gloves not required under normal conditions of use. Wear protective gloves to handle contents of damaged or leaking units. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of sever substances, the resistance of the glove material can not be calculated in advance and has therefore to checked prior to the application.		
Wear protective gloves to handle contents of damaged or leaking units. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of sever substances, the resistance of the glove material can not be calculated in advance and has therefore to checked prior to the application.		
Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of seven substances, the resistance of the glove material can not be calculated in advance and has therefore to checked prior to the application.		
The selection of the suitable gloves does not only depend on the material, but also on further marks quality and varies from manufacturer to manufacturer. As the product is a preparation of sever substances, the resistance of the glove material can not be calculated in advance and has therefore to checked prior to the application.	•	
	The selection quality and substances, f	n of the suitable gloves does not only depend on the material, but also on further marks varies from manufacturer to manufacturer. As the product is a preparation of sever the resistance of the glove material can not be calculated in advance and has therefore to l
	checked prior	

(Cont'd. on page 8)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Revision: July 21, 2015

Trade name: Defense Technology 40MM Ground Marker Yellow Colored Smoke - 200 Meters

• Penetration time of glove material
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
 • Eye protection:

Safety glasses

· Body protection: Protective work clothing

• **Limitation and supervision of exposure into the environment** No further relevant information available.

· Risk management measures

See Section 7 for additional information.

Organizational measures should be in place for all activities involving this product.

No further relevant information available.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties · General Information · Appearance: Form: Solid metal container containing liquid and solid contents. Colour: According to product specification Odourless · Odour: · Odour threshold: Not determined. · pH-value: Not applicable. · Change in condition Melting point/Melting range: Not Determined. Undetermined. Boiling point/Boiling range: · Flash point: Not applicable. · Flammability (solid, gaseous): Not determined. · Auto/Self-ignition temperature: Not determined. · Decomposition temperature: Not determined. · Self-igniting: Product is not self-igniting. · Danger of explosion: Heating may cause an explosion. · Explosion limits: Lower: Not determined. Upper: Not determined. · Vapour pressure: Not applicable. · Density: Not determined. · Relative density Not determined. · Vapour density Not applicable. (Cont'd. on page 9)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Revision: July 21, 2015

Trade name: Defense Technology 40MM Ground Marker Yellow Colored Smoke - 200 Meters

	Net and Packle	(Cont'd. from page 8)
Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
water:	Insoluble.	
Partition coefficient (n-octanol	/water): Not determined.	
Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point. Reacts with flammable substances.

Can react violently with oxygen rich (oxidising) material. Danger of Explosion.

10.4 Conditions to avoid

Store away from oxidising agents.

Keep ignition sources away - Do not smoke.

Cartridge may detonate if case is punctured or severely damaged.

• **10.5 Incompatible materials:** No further relevant information available.

10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides

Toxic metal oxide smoke

Chlorine compounds

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

· LD/LC50 values relevant for classification:

3811-04-9 potassium chlorate

Oral LD50 1870 mg/kg (rat)

- · Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation
- Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Acute effects (acute toxicity, irritation and corrosivity): May be harmful if inhaled.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

(Cont'd. on page 10)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Revision: July 21, 2015

(Cont'd. from page 9)

Trade name: Defense Technology 40MM Ground Marker Yellow Colored Smoke - 200 Meters

Carcinogenicity
 Based on available data, the classification criteria are not met.
 Reproductive toxicity
 Based on available data, the classification criteria are not met.
 STOT-single exposure
 Based on available data, the classification criteria are not met.
 STOT-repeated exposure
 Based on available data, the classification criteria are not met.
 STOT-repeated exposure
 Based on available data, the classification criteria are not met.
 Aspiration hazard
 Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:
- Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
- Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

· 12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- vPvB: Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to local official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · DOT, ADR, IMDG · IATA

UN0303 FORBIDDEN

(Cont'd. on page 11)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Revision: July 21, 2015

Trade name: Defense Technology 40MM Ground Marker Yellow Colored Smoke - 200 Meters (Cont'd. from page 10) · 14.2 UN proper shipping name DOT, IMDG Ammunition Smoke with or without burster, expelling charge or propelling charge · ADR 0303, 1.4G, Ammunition Smoke with or without burster, expelling charge or propelling charge FORBIDDEN ·IATA · 14.3 Transport hazard class(es) · DOT, ADR, IMDG · Class 1.4 1.4G · Label ·IATA · Class FORBIDDEN · Label 14.4 Packing group · DOT, ADR, IMDG Ш ·IATA FORBIDDEN · 14.5 Environmental hazards: • Marine pollutant: No · 14.6 Special precautions for user Not applicable. EMS Number: F-A,S-Q · Segregation groups Chlorates · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. UN "Model Regulation": UN0303, 0303, 1.4G, II

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
United States (USA)
SARA
Section 355 (extremely hazardous substances):
None of the ingredients are listed.
Section 313 (Specific toxic chemical listings):
None of the ingredients are listed.
TSCA (Toxic Substances Control Act):
All ingredients are listed.
Proposition 65 (California):
Chemicals known to cause cancer:

None of the ingredients is listed.

(Cont'd. on page 12)

Revision: July 21, 2015

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Trade name: Defense Technology 40MM Ground Marker Yellow Colored Smoke - 200 Meters

	(Cont'd. from page
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients are listed.	
 Chemicals known to cause reproductive toxicity for males: 	
None of the ingredients are listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients are listed.	
· Carcinogenic Categories	
· EPA (Environmental Protection Agency)	
598-62-9 manganese carbonate	
· IARC (International Agency for Research on Cancer)	
None of the ingredients are listed.	
· TLV (Threshold Limit Value established by ACGIH)	
57-50-1 sucrose, pure	A
7429-90-5 aluminium powder (pyrophoric)	P
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients are listed.	
[·] Canada	
· Canadian Domestic Substances List (DSL)	
All ingredients are listed.	
· Canadian Ingredient Disclosure list (limit 0.1%)	
598-62-9 manganese carbonate	
· Canadian Ingredient Disclosure list (limit 1%)	
100-21-0 terephthalic acid	
· Other regulations, limitations and prohibitive regulations	
Substances of very high concern (SVHC) according to REACH, Article	57
None of the ingredients are listed.	
· 15.2 Chemical safety assessment: A Chemical Safety Assessment has no	ot been carried out

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H201 Explosive; mass explosion hazard.

H228 Flammable solid.

H250 Catches fire spontaneously if exposed to air.

- H261 In contact with water releases flammable gases.
- H271 May cause fire or explosion; strong oxidiser.
- H272 May intensify fire; oxidiser.
- H302 Harmful if swallowed.

(Cont'd. on page 13)

Revision: July 21, 2015

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Trade name: Defense Technology 40MM Ground Marker Yellow Colored Smoke - 200 Meters

(Cont'd. from page 12) H332 Harmful if inhaled. H411 Toxic to aquatic life with long lasting effects. Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent. Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Expl. 1.1: Explosives, Division 1.1 Expl. 1.4: Explosives, Division 1.4 Flam. Sol. 2: Flammable solids, Hazard Category 2 Pyr. Sol. 1: Pyorphoric Solids, Hazard Category 1 Water-react. 2: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 2 Ox. Sol. 1: Oxidising Solids, Hazard Category 1 Ox. Sol. 2: Oxidising Solids, Hazard Category 2 Acute Tox. 4: Acute toxicity, Hazard Category 4 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3 · Sources SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com