Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date July 21, 2015

| undertaking   |   |
|---|---|
|   |   |
|   | efense Technology 40MM Ground Marker OC - 300 Meters  |
|   | : 6680<br>Ientified uses of the substance or mixture and uses advised against<br>ant information available.   |
| Application of<br>Crowd Control I<br>Explosive produ  |   |
| Manufacturer/S<br>Safariland, LLC<br>13386 Internation<br>Jacksonville, FL<br>Customer Care   | onal Parkway  |
| ChemTel Inc.  |   |
| SECTION 2:  | +1 (813)248-0585<br>Hazards identification  |
| SECTION 2:<br>2.1 Classification<br>Classification<br>The following<br>regulation: H41  | Hazards identification<br>on of the substance or mixture<br>according to Regulation (EC) No 1272/2008<br>Hazard Statements are applicable only to the EU regulations and not the US G   |
| SECTION 2:<br>2.1 Classification<br>The following<br>regulation: H41<br>()<br>()<br>Expl. 1.4   | Hazards identification<br>on of the substance or mixture<br>according to Regulation (EC) No 1272/2008<br>Hazard Statements are applicable only to the EU regulations and not the US G<br>2.<br>Ing bomb<br>H204 Fire or projection hazard.  |
| SECTION 2:<br>2.1 Classification<br>The following<br>regulation: H41<br>()<br>Expl. 1.4<br>()<br>Skin Irrit. 2  | Hazards identification         on of the substance or mixture         according to Regulation (EC) No 1272/2008         Hazard Statements are applicable only to the EU regulations and not the US G         Ing bomb         H204       Fire or projection hazard.         H315       Causes skin irritation.  |
| SECTION 2:<br>2.1 Classification<br>The following<br>regulation: H41<br>()<br>()<br>()<br>()<br>()<br>()<br>()<br>()<br>()<br>()<br>()<br>()<br>()  | Hazards identification         on of the substance or mixture         according to Regulation (EC) No 1272/2008         Hazard Statements are applicable only to the EU regulations and not the US G2.         ng bomb       H204         H204       Fire or projection hazard.         H315       Causes skin irritation.         H319       Causes serious eye irritation.  |
| SECTION 2:<br>2.1 Classification<br>The following<br>regulation: H41<br>Expl. 1.4<br>Skin Irrit. 2<br>Eye Irrit. 2<br>Aquatic Chronic   | Hazards identification         on of the substance or mixture         according to Regulation (EC) No 1272/2008         Hazard Statements are applicable only to the EU regulations and not the US G         Hazard Statements are applicable only to the EU regulations and not the US G         ng bomb         H204       Fire or projection hazard.         H315       Causes skin irritation.         H319       Causes serious eye irritation.         e 3       H412   |
| SECTION 2:<br>2.1 Classification<br>The following<br>regulation: H41<br>Contemport<br>explodin<br>Expl. 1.4<br>Skin Irrit. 2<br>Eye Irrit. 2<br>Aquatic Chronic<br>2.2 Label elem<br>Labelling acco | Hazards identification         on of the substance or mixture         according to Regulation (EC) No 1272/2008         Hazard Statements are applicable only to the EU regulations and not the US C         Image bomb         H204 Fire or projection hazard.         H315 Causes skin irritation.         H315 Causes skin irritation.         H319 Causes serious eye irritation.         Image and the substance of the substan |

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Revision: July 21, 2015

## Trade name: Defense Technology 40MM Ground Marker OC - 300 Meters (Cont'd. from page 1) · Hazard pictograms GHS01 GHS07 · Signal word Warning · Hazard-determining components of labelling: **Oleoresin Capsicum** Hazard statements The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412. H204 Fire or projection hazard. H315 Causes skin irritation. H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects. · Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P250 Do not subject to grinding/shock/friction. P280 Wear eye protection / face protection. DO NOT fight fire when fire reaches explosives. P373 P370+P380 In case of fire: Evacuate area. Explosion risk in case of fire. P372 P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · Additional information: Can become highly flammable in use. · NFPA ratings (scale 0 - 4) Health = 2 Fire = 0Reactivity = 3 · HMIS-ratings (scale 0 - 4) HEALTH 2 Health = 2 • Fire = 0 FIRE **REACTIVITY Reactivity = 3** · HMIS Long Term Health Hazard Substances None of the ingredients are listed. · 2.3 Other hazards Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. · Explosive Product Notice PREVENTION OF ACCIDENTS IN THE USE OF EXPLOSIVES - The prevention of accidents in the use of explosives is a result of careful planning and observance of the best known practices. The explosives (Cont'd. on page 3)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

## Trade name: Defense Technology 40MM Ground Marker OC - 300 Meters

(Cont'd. from page 2)

Revision: July 21, 2015

user must remember that he is dealing with a powerful force and that various devices and methods have been developed to assist him in directing this force. He should realize that this force, if misdirected, may either kill or injure both him and his fellow workers.

WARNING - All explosives are dangerous and must be carefully handled and used following approved safety procedures either by or under the direction of competent, experienced persons in accordance with all applicable federal, state, and local laws, regulations, or ordinances. If you have any questions or doubts as to how to use any explosive product, DO NOT USE IT before consulting with your supervisor, or the manufacturer, if you do not have a supervisor. If your supervisor has any questions or doubts, he should consult the manufacturer before use.

## SECTION 3: Composition/information on ingredients

## · 3.2 Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

| CAS: 100-21-0   | terephthalic acid   | 20-40% |
|---|---|--------|
| EINECS: 202-830-0   | substance with a Community workplace exposure limit   |        |
| CAS: 3811-04-9<br>EINECS: 223-289-7<br>Index number: 017-004-00-3 | potassium chlorate<br>Ox. Sol. 1, H271<br>Aquatic Chronic 2, H411<br>Acute Tox. 4, H302; Acute Tox. 4, H332 | 20-40% |
| CAS: 57-50-1<br>EINECS: 200-334-9                                 | sucrose, pure<br>substance with a Community workplace exposure limit  | 10-20% |
| CAS: 598-62-9<br>EINECS: 209-942-9                                | manganese carbonate<br>substance with a Community workplace exposure limit                                  | 10-20% |
| CAS: 8023-77-6<br>EINECS: 288-920-0                               | Oleoresin Capsicum<br>Eye Dam. 1, H318<br>Acute Tox. 4, H302; Skin Irrit. 2, H315                           | 5-10%  |
| CAS: 9004-70-0<br>EC number: 603-037-0                            | Nitrocellulose, colloided, granular   | 5-10%  |
| CAS: 7757-79-1<br>EINECS: 231-818-8                               | potassium nitrate<br>Ox. Sol. 2, H272   | 1-5%   |
| CAS: 7440-21-3<br>EINECS: 231-130-8                               | silicon<br>Flam. Sol. 2, H228   | 1-5%   |
| CAS: 7429-90-5<br>EINECS: 231-072-3<br>Index number: 013-001-00-6 | aluminium powder (pyrophoric)<br>Pyr. Sol. 1, H250; Water-react. 2, H261                                    | < 1,0% |
| Additional information: Fo  | r the wording of the listed Hazard Statements refer to section 10   | δ.<br> |
| Notable Trace Component   | s (≤ 0,1% w/w)  |        |

Printing date July 21, 2015

Revision: July 21, 2015

## Trade name: Defense Technology 40MM Ground Marker OC - 300 Meters

|                            | (Cont'd. from page 3)                                      |
|----------------------------|--|
| CAS: 122-39-4              | diphenylamine  |
|                            | Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 |
| Index number: 612-026-00-5 | 🚯 STOT RE 2, H373  |
|                            | Aquatic Acute 1, H400; Aquatic Chronic 1, H410             |
| CAS: 12403-82-6            | dihydroxy[styphnato(2-)]dilead / lead styphnate            |
| EINECS: 235-642-2          | 🔗 Unst. Expl., H200  |
|                            | Acute Tox. 3, H301; Acute Tox. 2, H330                     |
|                            | 🕉 Carc. 1B, H350; Repr. 2, H361; STOT RE 2, H373           |
|                            | Aquatic Acute 1, H400; Aquatic Chronic 1, H410             |
|                            | *  |

| 4.1 Description of first aid measures<br>General information:   |                       |
|---|-----------------------|
|   |                       |
| Immediately remove any clothing soiled by the product.<br>Symptoms of poisoning may even occur after several hours; therefore medical obs | onvotion for at logat |
| hours after the accident.   |                       |
| After inhalation:   |                       |
| Supply fresh air; consult doctor in case of complaints.   |                       |
| Provide oxygen treatment if affected person has difficulty breathing.   |                       |
| After skin contact:   |                       |
|   |                       |
| Immediately wash with water and soap and rinse thoroughly.<br>If skin irritation continues, consult a doctor.                             |                       |
|   |                       |
| Seek immediate medical help for blistering or open wounds.  |                       |
| After eye contact:  |                       |
| Remove contact lenses if worn.  | noult a doctor        |
| Rinse opened eye for several minutes under running water. If symptoms persist, co   | nsult a doctor.       |
| After swallowing:   |                       |
| Unlikely route of exposure.   |                       |
| Rinse out mouth and then drink plenty of water.   |                       |
| Do not induce vomiting; call for medical help immediately.  |                       |
| 4.2 Most important symptoms and effects, both acute and delayed   |                       |
| Asthma attacks  |                       |
| Irritant to skin and mucous membranes.  |                       |
| Irritant to eyes.   |                       |
| Breathing difficulty  |                       |
| Coughing  |                       |
| Gastric or intestinal disorders when ingested.  |                       |
| Nausea in case of ingestion.  |                       |
| Allergic reactions  |                       |
| Hazards   |                       |
| Danger of blast or crush-type injuries.   |                       |
| Danger of impaired breathing.   |                       |
| 4.3 Indication of any immediate medical attention and special treatment need  | ed                    |
| If necessary oxygen respiration treatment.  |                       |
|   | (Cont'd. on page      |

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Revision: July 21, 2015

Trade name: Defense Technology 40MM Ground Marker OC - 300 Meters

(Cont'd. from page 4) Product may produce physical injury if mishandled. Treatment of these injuries should be based on the blast and compression effects.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: None.
- 5.2 Special hazards arising from the substance or mixture

Product may explode if burned in confined space. Individual cartridges may explode. Mass explosion of many cartridges at once is unlikely.

During heating or in case of fire poisonous gases are produced.

## 5.3 Advice for firefighters

· Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

## Additional information

Eliminate all ignition sources if safe to do so.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Flammability Classification: (defined by 29 CFR 1910.1200) Explosive. Can explode under fire conditions. Individual devices will randomly explode. Will not mass explode if multiple devices are involved. Burning material may produce toxic and irritating vapors. In unusual cases, shrapnel may be thrown from exploding devices under containment. See 2008 Emergency response Guidebook for further information.

## **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and emergency procedures

FOR ALL TRANSPORTATION ACCIDENTS, CALL CHEMTEL AT 1-800-255-3924. Spills of this material should be handled carefully. Do not subject materials to mechanical shock or extreme heat. A spill of this material will normally not require emergency response team capabilities.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Protect from heat.

## · 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

## · 6.3 Methods and material for containment and cleaning up:

Pick up mechanically.

Send for recovery or disposal in suitable receptacles. Dispose contaminated material as waste according to section 13.

Clean the affected area carefully; suitable cleaners are:

Warm water and cleansing agent

## 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Cont'd. on page 6)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Trade name: Defense Technology 40MM Ground Marker OC - 300 Meters

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

**7.1 Precautions for safe handling** Keep away from heat and direct sunlight. Handle with care. Avoid jolting, friction and impact. **Information about fire - and explosion protection:** Protect from heat.

Substance/product can reduce the ignition temperature of flammable substances. Emergency cooling must be available in case of nearby fire.

## • 7.2 Conditions for safe storage, including any incompatibilities • Storage:

Storage:

• Requirements to be met by storerooms and receptacles: Avoid storage near extreme heat, ignition sources or open flame.

Protect from humidity and water.

- Information about storage in one common storage facility:
- Store away from foodstuffs.

Store away from oxidising agents.

Store away from flammable substances.

• Further information about storage conditions: Store in dry conditions.

• 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

• Additional information about design of technical facilities: No further data; see section 7.

## · 8.1 Control parameters

| · Ingredients v | with limit values that require monitoring at the workplace:                     |
|-----------------|---|
| 100-21-0 tere   | phthalic acid   |
| TLV (USA)       | Long-term value: 10 mg/m <sup>3</sup>   |
| EL (Canada)     | Long-term value: 10 mg/m <sup>3</sup>   |
| EV (Canada)     | Long-term value: 10 mg/m³   |
| 57-50-1 sucr    | ose, pure   |
| PEL (USA)       | Long-term value: 15* 5** mg/m <sup>3</sup><br>*total dust **respirable fraction |
| REL (USA)       | Long-term value: 10* 5** mg/m <sup>3</sup><br>*total dust **respirable fraction |
| TLV (USA)       | Long-term value: 10 mg/m <sup>3</sup>   |
| EL (Canada)     | Long-term value: 10 mg/m <sup>3</sup>   |
| EV (Canada)     | Long-term value: 10 mg/m³<br>total dust   |
|                 | (Cont'd. on page 7)   |

(Cont'd. from page 5)

# Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date July 21, 2015

Revision: July 21, 2015

Trade name: Defense Technology 40MM Ground Marker OC - 300 Meters

| 508 62 0 may                     | aganasa carbanata  | (Cont'd. from page |
|----------------------------------|--|--------------------|
| PEL (USA)                        | nganese carbonate<br>Ceiling limit: 5 mg/m³  |                    |
| FEL (USA)                        | as Mn  |                    |
| REL (USA)                        | Short-term value: 3 mg/m <sup>3</sup>  |                    |
| ( )                              | Long-term value: 1 mg/m <sup>3</sup>   |                    |
|                                  | as Mn  |                    |
| TLV (USA)                        | Long-term value: 0,02* 0,1* mg/m <sup>3</sup>  |                    |
|                                  | as Mn; *respirable **inhalable fraction  |                    |
| EL (Canada)                      | Long-term value: 0,2 mg/m³<br>as Mn; R   |                    |
| 7440-21-3 sil                    | icon   |                    |
| PEL (USA)                        | Long-term value: 15* 5** mg/m <sup>3</sup>   |                    |
|                                  | *total dust **respirable fraction  |                    |
| REL (USA)                        | Long-term value: 10* 5** mg/m <sup>3</sup>   |                    |
| TIMUOA                           | *total dust **respirable fraction  |                    |
| TLV (USA)                        | TLV withdrawn  |                    |
| , ,                              | Long-term value: 10 mg/m <sup>3</sup>  |                    |
| · · · · ·                        | Long-term value: 10 mg/m³<br>total dust  |                    |
|                                  | iminium powder (pyrophoric)  |                    |
| PEL (USA)                        | Long-term value: 15*; 15** mg/m <sup>3</sup><br>*Total dust; ** Respirable fraction  |                    |
| REL (USA)                        | Long-term value: 10* 5** mg/m <sup>3</sup><br>*Total dust **Respirable fraction      |                    |
| TLV (USA)                        | Long-term value: 1* mg/m³<br>as Al; *as respirable fraction                          |                    |
| EL (Canada)                      | Long-term value: 1,0 mg/m <sup>3</sup><br>metal and insoluble compdounds, respirable |                    |
| EV (Canada)                      | Long-term value: 5 mg/m³<br>aluminium-containing (as aluminium)                      |                    |
| PNECs No fu                      | rther relevant information available.<br>rther relevant information available.       |                    |
|                                  | formation: The lists valid during the making were used as basis.                     |                    |
| · 8.2 Exposure<br>· Personal pro | tective equipment:   |                    |
|                                  | ective and hygienic measures:  |                    |
| The usual pre                    | cautionary measures are to be adhered to when handling chemicals.                    |                    |
|                                  | om foodstuffs, beverages and feed.   |                    |
|                                  | emove all soiled and contaminated clothing.<br>before breaks and at the end of work. |                    |
|                                  | dust / smoke / mist.   |                    |
|                                  | with the eyes and skin.  |                    |
|                                  |  | (Cont'd. on page   |

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Trade name: Defense Technology 40MM Ground Marker OC - 300 Meters

· Respiratory protection:

Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in large quantities.

## Protection of hands:

Gloves not required under normal conditions of use.

Wear protective gloves to handle contents of damaged or leaking units.

## · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

## · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

## Eye protection:

Safety glasses

· Body protection: Protective work clothing

## · Limitation and supervision of exposure into the environment

No further relevant information available.

· Risk management measures

See Section 7 for additional information.

Organizational measures should be in place for all activities involving this product.

No further relevant information available.

## **SECTION 9: Physical and chemical properties**

## · 9.1 Information on basic physical and chemical properties

- General Information
- · Appearance:

| Form:<br>Colour:<br>· Odour:<br>· Odour threshold:  | Solid metal container containing liquid and solid contents.<br>According to product specification<br>Odourless<br>Not determined. |
|---|---|
| · pH-value:   | Not applicable.   |
| <ul> <li>Change in condition</li> <li>Melting point/Melting range:</li> <li>Boiling point/Boiling range:</li> </ul> | Not Determined.<br>Undetermined.  |
| · Flash point:  | Not applicable.   |
| · Flammability (solid, gaseous):  | Not determined.   |
| · Auto/Self-ignition temperature:   | Not determined.   |
| · Decomposition temperature:  | Not determined.<br>(Cont'd. on page 9)  |

(Cont'd. from page 7)

Revision: July 21, 2015

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

## Trade name: Defense Technology 40MM Ground Marker OC - 300 Meters

(Cont'd. from page 8) · Self-igniting: Product is not self-igniting. · Danger of explosion: Heating may cause an explosion. Risk of explosion by shock, friction, fire or other sources of ignition. • Explosion limits: Lower: Not determined. Upper: Not determined. · Vapour pressure: Not applicable. · Density: Not determined. · Relative density Not determined. · Vapour density Not applicable. · Evaporation rate Not applicable. · Solubility in / Miscibility with Insoluble. water: Partition coefficient (n-octanol/water): Not determined. · Viscosity: **Dynamic:** Not applicable. Kinematic: Not applicable. · 9.2 Other information No further relevant information available.

## **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· 10.3 Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point.

Can react violently with oxygen rich (oxidising) material. Danger of Explosion.

Reacts with flammable substances.

## · 10.4 Conditions to avoid

Store away from oxidising agents.

Keep ignition sources away - Do not smoke.

Cartridge may detonate if case is punctured or severely damaged.

• 10.5 Incompatible materials: No further relevant information available.

## · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Toxic metal oxide smoke

Chlorine compounds

Nitrogen oxides

(Cont'd. on page 10)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Trade name: Defense Technology 40MM Ground Marker OC - 300 Meters

(Cont'd. from page 9)

| <ul> <li>Skin corrosion/irritation Causes skin irritation.</li> <li>Serious eye damage/irritation Causes serious eye irritation.</li> <li>Respiratory or skin sensitisation Based on available data, the classification criteria are not Additional toxicological information: Normal handling of the undeployed product poses little or no health hazards, One should av by wearing appropriate respiratory protection when exposed to the chemical ingredients of above listed TLV's or when exposed to the post ignition by-products. This product is a ca contains the various components completely sealed within. Therefore, under normal ha product, no exposure to any harmful materials will occur. When the product is used, par generated which may be irritating to the eyes and the respiratory tract.</li> <li>Acute effects (acute toxicity, irritation and corrosivity): May be harmful if inhaled.</li> <li>Repeated dose toxicity: Repeated exposures may result in skin and/or respiratory sensitivit CMR effects (carcinogenity, mutagenicity and toxicity for reproduction): Germ cell mutagenicity</li> </ul>   |   |  |  |
|---|---|--|--|
| Oral       LD50       1870 mg/kg (rat)         8023-77-6 Oleoresin Capsicum         Oral       LD50       47,2 mg/kg (mouse)         3000 mg/kg (rat)       3000 mg/kg (rat)         Dermal       LD50       512 mg/kg (mouse)         * Primary irritant effect:       Skin corrosion/irritation         Causes skin irritation.       Serious eye damage/irritation         Causes serious eye irritation.       Serious eye damage/irritation         Causes serious eye irritation.       Serious eye damage/irritation         Normal handling of the undeployed product poses little or no health hazards, One should ave by wearing appropriate respiratory protection when exposed to the chemical ingredients or above listed TLV's or when exposed to the post ignition by-products. This product is a car contains the various components completely sealed within. Therefore, under normal ha product, no exposure to any harmful materials will occur. When the product is used, par generated which may be irritating to the eyes and the respiratory tract.         Acute effects (acute toxicity, irritation and corrosivity): May be harmful if inhaled.         Repeated dose toxicity: Repeated exposures may result in skin and/or respiratory sensitivit         CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):         Germ cell mutagenicity |   |  |  |
| Oral       LD50       47,2 mg/kg (mouse)<br>3000 mg/kg (rat)         Dermal       LD50       512 mg/kg (mouse)         * Primary irritant effect:       Skin corrosion/irritation<br>Causes skin irritation.         * Serious eye damage/irritation<br>Causes serious eye irritation.         * Respiratory or skin sensitisation Based on available data, the classification criteria are not<br>Additional toxicological information:         Normal handling of the undeployed product poses little or no health hazards, One should av<br>by wearing appropriate respiratory protection when exposed to the chemical ingredients of<br>above listed TLV's or when exposed to the post ignition by-products. This product is a car<br>contains the various components completely sealed within. Therefore, under normal ha<br>product, no exposure to any harmful materials will occur. When the product is used, par<br>generated which may be irritating to the eyes and the respiratory tract.         • Acute effects (acute toxicity, irritation and corrosivity): May be harmful if inhaled.         • Repeated dose toxicity: Repeated exposures may result in skin and/or respiratory sensitivit<br>• CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):  |   |  |  |
| 3000 mg/kg (rat)         Dermal       LD50         512 mg/kg (mouse)         Primary irritant effect:         Skin corrosion/irritation         Causes skin irritation.         Serious eye damage/irritation         Causes serious eye irritation.         Respiratory or skin sensitisation Based on available data, the classification criteria are not         Additional toxicological information:         Normal handling of the undeployed product poses little or no health hazards, One should avely wearing appropriate respiratory protection when exposed to the chemical ingredients of above listed TLV's or when exposed to the post ignition by-products. This product is a car contains the various components completely sealed within. Therefore, under normal hap product, no exposure to any harmful materials will occur. When the product is used, par generated which may be irritating to the eyes and the respiratory tract.         Acute effects (acute toxicity, irritation and corrosivity): May be harmful if inhaled.         Repeated dose toxicity: Repeated exposures may result in skin and/or respiratory sensitivit         CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):  |   |  |  |
| Dermal       LD50       512 mg/kg (mouse)         Primary irritant effect:       Skin corrosion/irritation         Causes skin irritation.       Serious eye damage/irritation         Causes serious eye irritation.       Serious eye damage/irritation         Causes serious eye irritation.       Respiratory or skin sensitisation Based on available data, the classification criteria are not         Additional toxicological information:       Normal handling of the undeployed product poses little or no health hazards, One should ave by wearing appropriate respiratory protection when exposed to the chemical ingredients or above listed TLV's or when exposed to the post ignition by-products. This product is a car contains the various components completely sealed within. Therefore, under normal ha product, no exposure to any harmful materials will occur. When the product is used, par generated which may be irritating to the eyes and the respiratory tract.         Acute effects (acute toxicity, irritation and corrosivity): May be harmful if inhaled.         Repeated dose toxicity: Repeated exposures may result in skin and/or respiratory sensitivit         CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):  |   |  |  |
| <ul> <li>Primary irritant effect:</li> <li>Skin corrosion/irritation</li> <li>Causes skin irritation.</li> <li>Serious eye damage/irritation</li> <li>Causes serious eye irritation.</li> <li>Respiratory or skin sensitisation Based on available data, the classification criteria are not</li> <li>Additional toxicological information:</li> <li>Normal handling of the undeployed product poses little or no health hazards, One should ave by wearing appropriate respiratory protection when exposed to the chemical ingredients of above listed TLV's or when exposed to the post ignition by-products. This product is a car contains the various components completely sealed within. Therefore, under normal haproduct, no exposure to any harmful materials will occur. When the product is used, par generated which may be irritating to the eyes and the respiratory tract.</li> <li>Acute effects (acute toxicity, irritation and corrosivity): May be harmful if inhaled.</li> <li>Repeated dose toxicity: Repeated exposures may result in skin and/or respiratory sensitivit</li> <li>CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):</li> </ul>  |   |  |  |
| <ul> <li>Skin corrosion/irritation Causes skin irritation.</li> <li>Serious eye damage/irritation Causes serious eye irritation.</li> <li>Respiratory or skin sensitisation Based on available data, the classification criteria are not Additional toxicological information: Normal handling of the undeployed product poses little or no health hazards, One should av by wearing appropriate respiratory protection when exposed to the chemical ingredients of above listed TLV's or when exposed to the post ignition by-products. This product is a ca contains the various components completely sealed within. Therefore, under normal ha product, no exposure to any harmful materials will occur. When the product is used, par generated which may be irritating to the eyes and the respiratory tract.</li> <li>Acute effects (acute toxicity, irritation and corrosivity): May be harmful if inhaled.</li> <li>Repeated dose toxicity: Repeated exposures may result in skin and/or respiratory sensitivit</li> <li>CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):</li> </ul>   |   |  |  |
| <ul> <li>Serious eye damage/irritation         Causes serious eye irritation.     </li> <li>Respiratory or skin sensitisation Based on available data, the classification criteria are not</li> <li>Additional toxicological information:         Normal handling of the undeployed product poses little or no health hazards, One should ave by wearing appropriate respiratory protection when exposed to the chemical ingredients or above listed TLV's or when exposed to the post ignition by-products. This product is a car contains the various components completely sealed within. Therefore, under normal hap product, no exposure to any harmful materials will occur. When the product is used, par generated which may be irritating to the eyes and the respiratory tract.     </li> <li>Acute effects (acute toxicity, irritation and corrosivity): May be harmful if inhaled.</li> <li>Repeated dose toxicity: Repeated exposures may result in skin and/or respiratory sensitivit OMR effects (carcinogenity, mutagenicity and toxicity for reproduction):</li> </ul>   |   |  |  |
| <ul> <li>Serious eye damage/irritation         Causes serious eye irritation.     </li> <li>Respiratory or skin sensitisation Based on available data, the classification criteria are not</li> <li>Additional toxicological information:         Normal handling of the undeployed product poses little or no health hazards, One should ave by wearing appropriate respiratory protection when exposed to the chemical ingredients or above listed TLV's or when exposed to the post ignition by-products. This product is a car contains the various components completely sealed within. Therefore, under normal hap product, no exposure to any harmful materials will occur. When the product is used, par generated which may be irritating to the eyes and the respiratory tract.     </li> <li>Acute effects (acute toxicity, irritation and corrosivity): May be harmful if inhaled.</li> <li>Repeated dose toxicity: Repeated exposures may result in skin and/or respiratory sensitivit CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):</li> </ul>   |   |  |  |
| Causes serious eye irritation.<br>Respiratory or skin sensitisation Based on available data, the classification criteria are not<br>Additional toxicological information:<br>Normal handling of the undeployed product poses little or no health hazards, One should as<br>by wearing appropriate respiratory protection when exposed to the chemical ingredients of<br>above listed TLV's or when exposed to the post ignition by-products. This product is a car<br>contains the various components completely sealed within. Therefore, under normal has<br>product, no exposure to any harmful materials will occur. When the product is used, par<br>generated which may be irritating to the eyes and the respiratory tract.<br>Acute effects (acute toxicity, irritation and corrosivity): May be harmful if inhaled.<br>Repeated dose toxicity: Repeated exposures may result in skin and/or respiratory sensitivit<br>CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):<br>Germ cell mutagenicity   |   |  |  |
| <ul> <li>Respiratory or skin sensitisation Based on available data, the classification criteria are not</li> <li>Additional toxicological information:<br/>Normal handling of the undeployed product poses little or no health hazards, One should ave by wearing appropriate respiratory protection when exposed to the chemical ingredients or above listed TLV's or when exposed to the post ignition by-products. This product is a car contains the various components completely sealed within. Therefore, under normal hap product, no exposure to any harmful materials will occur. When the product is used, par generated which may be irritating to the eyes and the respiratory tract.</li> <li>Acute effects (acute toxicity, irritation and corrosivity): May be harmful if inhaled.</li> <li>Repeated dose toxicity: Repeated exposures may result in skin and/or respiratory sensitivit</li> <li>CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):</li> </ul>  |   |  |  |
| <ul> <li>Additional toxicological information:<br/>Normal handling of the undeployed product poses little or no health hazards, One should as by wearing appropriate respiratory protection when exposed to the chemical ingredients of above listed TLV's or when exposed to the post ignition by-products. This product is a car contains the various components completely sealed within. Therefore, under normal hap roduct, no exposure to any harmful materials will occur. When the product is used, par generated which may be irritating to the eyes and the respiratory tract.</li> <li>Acute effects (acute toxicity, irritation and corrosivity): May be harmful if inhaled.</li> <li>Repeated dose toxicity: Repeated exposures may result in skin and/or respiratory sensitivit</li> <li>CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):</li> </ul>  | t met   |  |  |
| Normal handling of the undeployed product poses little or no health hazards, One should as<br>by wearing appropriate respiratory protection when exposed to the chemical ingredients of<br>above listed TLV's or when exposed to the post ignition by-products. This product is a car<br>contains the various components completely sealed within. Therefore, under normal hap<br>product, no exposure to any harmful materials will occur. When the product is used, par<br>generated which may be irritating to the eyes and the respiratory tract.<br>• Acute effects (acute toxicity, irritation and corrosivity): May be harmful if inhaled.<br>• Repeated dose toxicity: Repeated exposures may result in skin and/or respiratory sensitivit<br>• CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):<br>• Germ cell mutagenicity  |   |  |  |
| Germ cell mutagenicity  | above listed TLV's or when exposed to the post ignition by-products. This product is a cansister which<br>contains the various components completely sealed within. Therefore, under normal handling of this<br>product, no exposure to any harmful materials will occur. When the product is used, particles may be<br>generated which may be irritating to the eyes and the respiratory tract.<br><b>Acute effects (acute toxicity, irritation and corrosivity):</b> May be harmful if inhaled.<br><b>Repeated dose toxicity:</b> Repeated exposures may result in skin and/or respiratory sensitivity. |  |  |
| Based on available data, the classification criteria are not met  |   |  |  |
| · Carcinogenicity   | Based on available data, the classification criteria are not met.   |  |  |
| Based on available data, the classification criteria are not met.   |   |  |  |
| <ul> <li>Reproductive toxicity</li> <li>Based on available data, the classification criteria are not met.</li> </ul>  |   |  |  |
| • STOT-single exposure  |   |  |  |
| Based on available data, the classification criteria are not met.   |   |  |  |
| STOT-repeated exposure  |   |  |  |
| Based on available data, the classification criteria are not met.   |   |  |  |
| <ul> <li>Aspiration hazard</li> <li>Based on available data, the classification criteria are not met.</li> </ul>  |   |  |  |
| Based on available data, the classification criteria are not met.   |   |  |  |

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Trade name: Defense Technology 40MM Ground Marker OC - 300 Meters

(Cont'd. from page 10)

Revision: July 21, 2015

## · Additional ecological information:

## · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

## 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

## · vPvB: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

## · 13.1 Waste treatment methods

## · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

## · Uncleaned packaging:

• Recommendation: Disposal must be made according to local official regulations.

| SECTION 14: Transport information |   |  |
|-----------------------------------|---|--|
| · 14.1 UN-Number                  |   |  |
| · DOT, ADR, IMDG                  | UN0301  |  |
|                                   | FORBIDDEN   |  |
| • 14.2 UN proper shipping name    |   |  |
| · DOT, IMDG                       | Ammunition Tear-producing with burster, expelling   |  |
| ADR                               | charge or propelling charge   |  |
| ADR                               | 0301, 1.4G, Ammunition Tear-producing with burster, expelling charge or propelling charge |  |
|                                   | FORBIDDEN   |  |
| 14.3 Transport hazard class(es)   |   |  |
| · DOT, ADR, IMDG                  |   |  |
| 1.4                               |   |  |
| · Class                           | 1.4   |  |
| · Label                           | 1.4G  |  |
| · IATA                            |   |  |
| · Class                           | FORBIDDEN   |  |
|                                   | (Cont'd. on page 12)  |  |

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date July 21, 2015

Revision: July 21, 2015

| Trade name: Defense Technology 40MM Ground Marker OC - 300 Meters  |                        |         |
|--|------------------------|---------|
|  | (Cont'd. from pa       |         |
| Label  | -                      | Jge II) |
| 14.4 Packing group   |                        |         |
| · DOT, ADR, IMDG   | II                     |         |
| ·IATA  | FORBIDDEN              |         |
| <ul> <li>14.5 Environmental hazards:</li> </ul>                    |                        |         |
| · Marine pollutant:  | No                     |         |
| 14.6 Special precautions for user                                  | Not applicable.        |         |
| · EMS Number:  | F-A,S-Q                |         |
| · Segregation groups   | Chlorates              |         |
| <ul> <li>14.7 Transport in bulk according to Annex II o</li> </ul> | f                      |         |
| Marpol and the IBC Code  | Not applicable.        |         |
| · UN "Model Regulation":   | UN0301, 0301, 1.4G, II |         |

## **SECTION 15: Regulatory information**

| <ul> <li>15.1 Safety, health and environmental regulations/legislation specific for the substance or mixt</li> <li>United States (USA)</li> <li>SARA</li> </ul> | ure    |
|---|--------|
| · Section 355 (extremely hazardous substances):   |        |
| None of the ingredients are listed.   |        |
| · Section 313 (Specific toxic chemical listings):   |        |
| None of the ingredients are listed.   |        |
| · TSCA (Toxic Substances Control Act):  |        |
| All ingredients are listed.   |        |
| · Proposition 65 (California):  |        |
| · Chemicals known to cause cancer:  |        |
| None of the ingredients is listed.  |        |
| · Chemicals known to cause reproductive toxicity for females:   |        |
| None of the ingredients are listed.   |        |
| · Chemicals known to cause reproductive toxicity for males:   |        |
| None of the ingredients are listed.   |        |
| Chemicals known to cause developmental toxicity:     Present in trace quantities.   |        |
| 12403-82-6 dihydroxy[styphnato(2-)]dilead / lead styphnate  |        |
| Carcinogenic Categories   |        |
| · EPA (Environmental Protection Agency)   |        |
| 598-62-9 manganese carbonate  | D      |
| · IARC (International Agency for Research on Cancer)  |        |
| None of the ingredients are listed.   |        |
| · TLV (Threshold Limit Value established by ACGIH)  |        |
| 57-50-1 sucrose, pure   | A4     |
| (Cont'd. on pag   | je 13) |

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date July 21, 2015

Trade name: Defense Technology 40MM Ground Marker OC - 300 Meters

Revision: July 21, 2015

(Cont'd. from page 12)

A4

7429-90-5 aluminium powder (pyrophoric)

## · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· Canada

## · Canadian Domestic Substances List (DSL)

All ingredients are listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

598-62-9 manganese carbonate

Canadian Ingredient Disclosure list (limit 1%)

100-21-0 terephthalic acid

## · Other regulations, limitations and prohibitive regulations

• Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients are listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## · Relevant phrases

H201 Explosive; mass explosion hazard.

H228 Flammable solid.

H250 Catches fire spontaneously if exposed to air.

H261 In contact with water releases flammable gases.

H271 May cause fire or explosion; strong oxidiser.

H272 May intensify fire; oxidiser.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.

## · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH)

(Cont'd. on page 14)

GHŚ

Printing date July 21, 2015

Revision: July 21, 2015

## Trade name: Defense Technology 40MM Ground Marker OC - 300 Meters

(Cont'd. from page 13) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Expl. 1.1: Explosives, Division 1.1 Expl. 1.4: Explosives, Division 1.4 Flam. Sol. 2: Flammable solids, Hazard Category 2 Pyr. Sol. 1: Pyorphoric Solids, Hazard Category 1 Water-react. 2: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 2 Ox. Sol. 1: Oxidising Solids, Hazard Category 1 Ox. Sol. 2: Oxidising Solids, Hazard Category 2 Acute Tox. 4: Acute toxicity, Hazard Category 4 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3 Sources SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com