



MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Fuel Air Distraction Device®		DATE: March 16, 2010	
PRODUCT NUMBER: 8001NR			
TRADE NAME: Fuel Air Distraction Device® GENERAL USE: Distraction Device CHEMICAL FAMILY: Incendiary/ Igniter/Powder Charge PRODUCT DESCRIPTION: Canister containing gray and silver powder mix. (Explosive Device)	 DEFENSE TECHNOLOGY		
MANUFACTURED FOR: Safariland L.L.C.		DATE PREPARED: March 16, 2010	
		SUPERSEDES: New Issue	
ADDRESS (NUMBER, STREET, P.O. BOX) 13386 International Parkway		TELEPHONE NUMBER FOR INFORMATION / Customer Service 904-741-5400	
(CITY, STATE AND ZIP CODE) Jacksonville, FL 32218		CHEMTEL 24-HOUR EMERGENCY TELEPHONE NUMBER	
COUNTRY USA		 1-800-255-3924 01-813-248-0585 North America Toll Free International	

SECTION 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

CAUTION! EXPLOSIVE/DEFLAGRATING (FAST BURN RATE) PRODUCT. KEEP AWAY FROM HEAT. DO NOT SUBJECT TO MECHANICAL OR ELECTRICAL SHOCK. EXPLODING CARTRIDGES MAY EJECT SHRAPNEL AT HIGH VELOCITIES. PARTICLES FROM FIRING MAY BE HARMFUL IF INHALED. DO NOT TAKE INTERNALLY.

Individual cartridges may ignite if the actuator is released or if the unit is exposed to excess heat. Oxides of Nitrogen, Carbon, and Sulfur may be formed. Small quantities of various metal fumes and oxides may be formed during use.

WARNING: This product contains Lead chromate and Barium chromate listed as 'Chromium (VI) compounds', chemicals known to the state of California to cause cancer. WARNING: This product contains Lead chromate, listed as 'Lead, inorganic compounds', a chemical known to the State of California to cause developmental reproductive toxicity and cancer. WARNING: This product contains Carbon Black, a chemical known to the state of California to cause cancer.

POTENTIAL HEALTH EFFECTS

INHALATION:

Both pre and post ignition ingredients are hazardous and capable of producing long term health effects due primarily to the presence of zirconium, lead, chromium, and barium in the product. While normal handling of the undetonated product poses little or no health hazards, one should avoid inhalation by wearing appropriate respiratory protection when exposed to the chemical ingredients of the product above listed TLV's or when exposed to the post ignition by-products. This product is a finished canister which contains the various components completely sealed within. Therefore, under normal handling of this product, no exposure to any harmful materials will occur. When the product is used, particles may be generated which may be irritating to the eyes and the respiratory tract.

SKIN:

No exposure to chemical hazards anticipated with normal handling procedures.

EYES:

No exposure to chemical hazards anticipated with normal handling procedures.

INGESTION:

No exposure to chemical hazards anticipated with normal handling procedures. Contents of this product are toxic by ingestion and in the unlikely event this should occur immediate medical attention is advised.

CARCINOGENICITY:

NTP? Yes - Hexavalent Chromium, Lead Compounds	IARC MONOGRAPHS? Hexavalent Chromium (Group 1), Lead Compounds (Group 2A), Carbon Black (Group 2B)	OSHA REGULATED? Yes- Hexavalent Chromium, Lead
CALIFORNIA, Prop.65? Yes - Carbon Black, Chromium compounds (Hexavalent), Lead compounds	ESIS NOTATION? Yes	

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Fuel Air Distraction Device®
PRODUCT NUMBER: 8001NR **DATE:** March 16, 2010

SECTION 3 - HAZARDOUS INGREDIENTS

Hazardous Components	% (by Weight)	CAS #	EINECS #	Hazard Symbol	RISK PHRASES (Full Text Section 15)
Potassium perchlorate	NR	7778-74-7	231-912-9	Xn, O	R9, R22
Potassium nitrate	NR	7757-79-1	231-818-8	Xn, O	R8, R36/37/38
Sulfur	NR	7704-34-9	231-722-6	F, Xi	R11, 36/37/38
Charcoal	NR	16291-96-6	240-383-3	None	None
Graphite	NR	7782-42-5	231-955-3	None	None
Barium Chromate	NR	10294-40-3	233-660-5	T	None
Manganese Powder	NR	7439-96-5	231-105-1	None	None
Lead Chromate	NR	7758-97-6	231-846-0	T,N	R33,R40,R50/53,R62
Nitrocellulose	NR	9004-70-0	NR	E	NR
Red Iron Oxide	NR	1309-37-1	215-168-2	None	None
Titanium Powder	NR	7440-32-6	231-142-3	None	None
Zirconium Powder	NR	7440-67-7	231-176-9	F	R15,R17
Aluminum Powder	NR	7429-90-5	231-072-3	F	R15, R17
Aluminum Oxide	NR	1344-28-1	215-691-6	None	None
Carbon Black	NR	1333-86-4	215-609-9	Xi	R36/37/38

NOTES: This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Directive 1907/2006 (REACH). Hazard symbols and risk phrases are based on maximum listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) or the European (GHS) directive 1907/2006 and are considered trade secrets under US Federal Law (29CFR and 40CFR), Canadian Law (Health Canada Legislation), and European Union Directive 67/548/EEC.

SECTION 4 - FIRST AID MEASURES

INHALATION:

For symptoms of lung irritation occur (coughing, wheezing or breathing difficulty), remove from exposure area to fresh air immediately. If breathing has stopped, perform artificial respiration. Keep affected person warm and at rest. Get medical attention.

EYES:

Remove contact lenses, then wash for 15 minutes with clean potable water lifting upper and lower lids occasionally. Seek medical attention if irritation persists.

SKIN:

Wash with plenty of soap and water. Seek medical attention if delayed dermatitis develops. For contact with burning (ignited) particles, medical treatment may be needed for thermal burns.

INGESTION:

Contact medical authorities immediately. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs naturally, have victim lean forward to avoid aspiration of regurgitant. Give 1-2 glasses of water to victim if victim is conscious and able to swallow and seek immediate medical assistance. Never give anything by mouth to an unconscious person.

SECTION 5 - FIRE FIGHTING MEASURES

GENERAL HAZARDS:

Flammability Classification: (defined by 29 CFR 1910.1200) Explosive. Can explode under fire conditions. Individual devices will randomly explode. Will not mass explode if multiple devices are involved. Burning material may produce toxic and irritating vapors. Shrapnel may be thrown from exploding devices under containment. See 2008 Emergency response Guidebook for further information.

EXTINGUISHING MEDIA:

Flood area with water. If no water is available, carbon dioxide, dry chemical or earth may be used. If the fire reaches the cargo, withdraw and let fire burn.

FIRE FIGHTING PROCEDURES:

In case of fire, use normal fire fighting equipment. Protection concerns must also address the potential of the physical characteristic of this product as explosive. Quarantine area for at least 1500 feet from fires involving product.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

If fire reaches cargo, do not fight; withdraw personnel to safe distance. Evacuate all persons, including emergency responders from the area for 1500 feet (1/3 mile) in all directions.

HAZARDOUS COMBUSTION PRODUCTS:

Metal Compounds, Carbon Monoxide, Carbon Dioxide, Nitrous Oxides, Various complex oxides of metals, Nitrogen.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Fuel Air Distraction Device®
PRODUCT NUMBER: 8001NR **DATE:** March 16, 2010

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

FOR ALL TRANSPORTATION ACCIDENTS, CALL CHEMTEL AT 1-800-255-3924. Spills of this material should be handled carefully. Do not subject materials to mechanical shock or extreme heat. A spill of this material will normally not require emergency response team capabilities.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

HANDLING: Canister may detonate or burn if case is punctured or severely damaged.

STORAGE: Avoid storage near extreme heat, ignition sources or open flame.

CONDITIONS TO AVOID: Mechanical impact or shock, electrical discharge, high energy EM fields (radar stations).

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous Components	CAS #	ACGIH Exposure Limits	OSHA Exposure Limits
Barium Chromate	10294-40-3	0.5 mg/m3	0.5 mg/m3
Manganese Powder	7439-96-5	0.2 mg/m3	5 mg/m3 (Ceiling)
Lead Chromate (a)(b)	7758-97-6	0.012 mg/m3 as Chromium / 0.05 mg/m3 as Lead	0.1 mg/m3 (Ceiling as CrO3)
Red Iron Oxide	1309-37-1	5 mg/m3 respirable	10 mg/m3
Zirconium Powder	7440-67-7	5 mg/m3 (NIOSH)	5 mg/m3
Aluminum Powder	7429-90-5	1.0 mg/m3 (respirable)	5 mg/m3 (respirable)
Aluminum Oxide	1344-28-1	1.0 mg/m3 (respirable)	15 mg/m3 total , 5 mg/m3 respirable
Carbon Black	1333-86-4	3.5 mg/m3	3.5 mg/m3
Graphite	7782-42-5	2 mg/m3	2.5 mg/m3 (respirable dust)
Sulfur	7704-34-9	15 mg/m3	15 mg/m3
NitroCellulose	9004-70-0	NE	NE
Potassium perchlorate	7778-74-7	NE	NE
Potassium nitrate	7757-79-1	NE	NE
Titanium Powder	7440-32-6	NE	NE
Charcoal	16291-96-6	NE	NE

(a) - OSHA 30 aeg/M3 Action Level as Lead. Poison-see (29CFR 1910.10-25) (listed under Lead, inorganic compounds).

(b) - NIOSH Recommended Exposure Limit (REL): As Pb: < 0.1 mg/m3 (TWA); As Cr: 0.001 mg/m3 (TWA).

PERSONAL PROTECTION

RESPIRATORY PROTECTION:

A half-face high efficiency particulate respirator (NIOSH type N100 filter) should be worn when cleaning post-discharge debris. A particulate or combined particulate/vapor respirator should be worn at time of use.

PROTECTIVE GLOVES:

None required for normal handling.

EYE PROTECTION:

Safety glasses with side shields required.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Local exhaust ventilation is recommended if significant dusting occurs or fumes are generated. Otherwise, use general exhaust ventilation. Use hearing protection with this product.

WORK / HYGIENIC PRACTICES:

Avoid breathing fumes from ignition. DO NOT EAT/DRINK/SMOKE WHILE HANDLING PRODUCT!!!

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Fuel Air Distraction Device®		DATE: March 16, 2010	
PRODUCT NUMBER: 8001NR			
SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES			
APPEARANCE AND ODOR Canister containing gray and silver powder mix. (Explosive Device)		VAPOR PRESSURE Not applicable.	
pH Not applicable.		SPECIFIC GRAVITY (WATER = 1) Not applicable	
MELTING POINT Not applicable.		SOLUBILITY IN WATER Insoluble - some components are soluble in water	
FLASH POINT Not applicable.		VISCOSITY Not applicable	
FLAMMABLE LIMITS EXPLOSIVE!! LEL: None UEL: None		VAPOR DENSITY (AIR = 1) Not applicable.	
AUTOIGNITION TEMPERATURE NR		EVAPORATION RATE (WATER = 1) Not applicable.	
VOLATILE ORGANIC COMPOUND (VOC) INFORMATION Not applicable.			
NOTES:			
SECTION 10 - STABILITY AND REACTIVITY			
STABILITY STABLE X		CONDITIONS TO AVOID:	
Stable under normal temperatures and pressure.		Cartridge may detonate if case is punctured or severely damaged.	
INCOMPATIBILITY (MATERIALS TO AVOID): Acids, Class A & B explosives, strong oxidizers, and caustics.			
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Nitrogen oxides, carbon monoxide, lead oxides, carbon dioxide, lead dust/fume.			
HAZARDOUS POLYMERIZATION: Will not occur.		CONDITIONS TO AVOID: None related to polymerization.	
SECTION 11 - TOXICOLOGICAL INFORMATION			
Complete Product			
Oral LD ₅₀	NA		
Dermal LD ₅₀	NA		
Inhalation LC ₅₀	Not applicable for product. Particles generated from use may be irritating or slightly toxic.		
Irritation	Not a skin or eye irritant as a loaded round. Particulate dusts and gases from spent round may be a mild respiratory / eye irritant.		
Product Components			
Hazardous Components	CAS #	LD50 of Ingredient (Oral, Rat - unless otherwise specified)	LC50 of Ingredient (Inhalation, Rat - unless otherwise specified)
Barium Chromate	10294-40-3	Not Established	Not Established
Lead Chromate	7758-97-6	> 12 g/kg (oral, mouse)	Not Established
Potassium Nitrate	7757-79-1	3450 mg/kg	Not Established
Potassium Perchlorate	7778-74-7	Not Established	Not Established
Manganese Powder	7439-96-5	9 gm/kg	Not Established
Nitrocellulose	9004-70-0	> 5 g/kg	Not Established
Graphite	7782-42-5	Not Established	Not Established
Red Iron Oxide	1309-37-1	Not Established	Not Established
Titanium Powder	7440-32-6	Not Established	Not Established
Zirconium Powder	7440-67-7	Not Established	Not Established
Carbon Black	1333-86-4	> 15.4 g/kg	Not Established
Charcoal	16291-96-6	Not Established	Not Established
Sulfur	7704-34-9	> 8437 mg/kg	Not Established
Aluminum Powder	7429-90-5	Not Established	Not Established
Aluminum Oxide	1344-28-1	>3600 mg/kg (Intraperitoneal, mouse)	Not Established

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Fuel Air Distraction Device®
PRODUCT NUMBER: 8001NR **DATE:** March 16, 2010



SECTION 12 - ECOLOGICAL INFORMATION

No data is available on this product, but leachates of metal components may be harmful or toxic to aquatic life and waterfowl. Collection and careful disposal of spent cartridges is highly advisable. Lead and chromium are especially problematic when introduced into many ecosystems.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD:
 The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous. Damaged materials pose a danger to anyone in the immediate area; consult experts for disposal of damaged products.

SECTION 14 - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Grenades, Practice, Hand or Rifle, UN0452	
DOT HAZARD CLASS / Pack Group: Explosives, 1.4G/ II REFERENCE: 49CFR UN / NA IDENTIFICATION NUMBER: UN0452 LABEL: Explosives 1.4G	IATA HAZARD CLASS / Pack Group: 1.4G / II, 75Kg Cargo Aircraft Only IMDG HAZARD CLASS: Explosives, 1.4G/ II RID/ADR Dangerous Goods Code: Explosives, 1.4G/ II UN TDG Class / Pack Group: Explosives, 1.4G/ II Hazard Identification Number (HIN): NA
HAZARD SYMBOLS:	
	

Note: Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, EU, United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

SECTION 15 - REGULATORY INFORMATION

TSCA (USA - Toxic Substance Control Act): Components are listed under Section 8b.

SARA TITLE III (USA - Superfund Amendments and Reauthorization Act):

Acute Health:	YES	Chronic Health:	YES
Fire:	YES	Sudden Release of Pressure:	YES
Reactive:	NO		

SARA 313 REPORTABLE INGREDIENTS: Copper, Zinc (fume or dust), Lead, Chromium

CERCLA (USA - Comprehensive Response Compensation and Liability Act): Aluminum, Aluminum Oxide, Manganese R.Q. = 1000 lbs. : Chromium, R.Q. = 5000 lbs. : Lead, R.Q. = 100 lbs. (No reporting is required if diameter of the pieces of metal is equal to or exceeds 100 micrometers (0.004 inches). Nitrates, Barium, Lead, and Chromium compounds are CERCLA reportable, although no RQ has been assigned.

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986: **WARNING:** This product contains Lead chromate and Barium chromate listed as 'Chromium (VI) compounds', chemicals known to the state of California to cause cancer. **WARNING:** This product contains Lead chromate, listed as 'Lead, inorganic compounds', a chemical known to the State of California to cause developmental reproductive toxicity and cancer. **WARNING:** This product contains Carbon Black, a chemical known to the state of California to cause cancer.

State Right To Know Laws: **This product contains chemicals listed on the Right-to-Know Laws of CA, FL, MA, MI, MN, NJ, PA, & RI.**

CPR (Canadian Controlled Products Regulations): **Exempt under WHMIS regulations as explosive.**

IDL (Canadian Ingredient Disclosure List): **Components are listed in Section 2.**

DSL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List): **Listed or exempt on both CDSL and NDSL.**

EINECS (European Inventory of Existing Commercial Chemical Substances): **Referenced.**

WGK Water Quality Index: **NA for product.**

MATERIAL SAFETY DATA SHEET

PRODUCT NAME:	Fuel Air Distraction Device®	DATE:	March 16, 2010
PRODUCT NUMBER:	8001NR		

SECTION 15 - REGULATORY INFORMATION Continued

EUROPEAN (GHS) HAZARD SYMBOLS




EU RISK PHRASES

R2: Risk of explosion by shock, friction, fire or other sources of ignition.

R20/22: Harmful by inhalation and if swallowed.

R33: Danger of cumulative effects.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R61: May cause harm to the unborn child.

R62: Possible risk of impaired fertility.

EU SAFETY PHRASES

S1/2: Keep locked up and out of the reach of children.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S53: Avoid exposure — obtain special instructions before use.

S60: This material and its container must be disposed of as hazardous waste.

SECTION 16 - OTHER INFORMATION

HMIS HAZARD RATINGS			
	HEALTH:	2	0 = INSIGNIFICANT
	FLAMMABILITY:	3	1 = SLIGHT
	PHYSICAL HAZARD:	2	2 = MODERATE
Personal Protective Equipment: E			3 = HIGH
			4 = EXTREME

Legend:

ACGIH - American Congress of Government Industrial Hygienists , CAS - Chemical Abstracts Service

EINECS- European Inventory of Existing Commercial Chemical Substances

HMIS - Hazardous Materials Identification System, IARC - International Agency for Research on Cancer

NA - Not Available , ND - Not Determined, NE - Not Established, NR - Not Reported

NIOSH - National Institute for Occupational Safety and Health, NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

Full R-Phrases:R1 Explosive when dry. R2 Risk of explosion by shock, friction, fire or other sources of ignition. R3 Extreme risk of explosion by shock, friction, fire or other sources of ignition. R5 Heating may cause an explosion. R8 Contact with combustible material may cause fire. R9 Explosive when mixed with combustible material. R11 Highly flammable. R15 Contact with water liberates extremely flammable gases. R17 Spontaneously flammable in air. R20 Harmful by inhalation. R20/22 Harmful by inhalation and if swallowed. R22 Harmful if swallowed. R23/24/25 Toxic by inhalation, in contact with skin and if swallowed. R23/25 Toxic by inhalation and if swallowed. R33 Danger of cumulative effects. R36 Irritating to eyes. R36/37/38 Irritating to eyes, respiratory system and skin. R40 Limited evidence of a carcinogenic effect. R43 May cause sensitization by skin contact. R45 May cause cancer. R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed. R50 Very toxic to aquatic organisms. R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53 Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment. R61 May cause harm to the unborn child. R62 Possible risk of impaired fertility. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapors may cause drowsiness and dizziness. R68 Possible risk of irreversible effects.

REVISION SUMMARY: New Edition 3/16/2010. LB

MSDS Prepared by:
 ChemTel Inc.
 1305 North Florida Avenue
 Tampa, Florida USA 33602-2902
 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
 Website: www.chemtelinc.com



The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.