

SAFETY DATA SHEET **BAYTRIL 100**

Version 1.1

Revision Date 12/09/2010

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product information	
Product Name:	BAY

BAYTRIL 100 122000007167

Use

: veterinary medicine

Company

MSDS Number:

BAYER HEALTHCARE LLC Animal Health Division 12707 Shawnee Mission Parkway (West 63rd) Shawnee, KS 66216-1846 UNITED STATES (800) 633-3796

In case of emergency: (800) 422-9874 Chemtrec: (800) 424-9300 BAYER INFORMATION PHONE:(800) 633-3796 INTERNATIONAL:(703) 527-3887

2. HAZARDS IDENTIFICATION

Emergency Overview

WARNING! Combustible Liquid Colour: yellow, brownish **Form:** liquid **Odour:** weak, Alcohol. May cause eye, skin, and respiratory tract irritation.

Hazard Communication (29CFR 1910.1200)

Inhalation Skin Contact Skin Absorption Eye Contact

Acute Inhalation Hazards	May cause respiratory tract irritation with symptoms of coughing, sore throat and runny nose. Overexposure to vapor may produce dizziness, drowsiness, or nausea.
Acute Skin Hazards	May cause irritation with symptoms of reddening and itching.
Acute Eye Hazards	May cause irritation with symptoms of reddening, tearing and stinging.
Acute Ingestion Hazards	Symptoms of ingestion may include abdominal pain, nausea, vomiting, and diarrhea.

SAFETY DATA SHEET BAYTRIL 100	122000007167
Version 1.1 R	evision Date 12/09/2010
Chronic Effects of Exposure	Chronic exposure to the solvent can cause defatting of the skin. Hearing loss has been associated with prolonged inhalation of butyl alcohol.
Medical Conditions Aggrevated by Exposure	Eye disorders, Skin disorders, Respiratory tract disorders
No Carcinogenic substances as defined by IARC	C, NTP and/or OSHA

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients:		
Weight percent	Components	CAS-No.
1 - 5%	Butan-1-ol	71-36-3
0.1 - 10%	Enrofloxacin	93106-60-6
1 - 5%	Alcohol derivative	

4. FIRST AID MEASURES

General advice: Take off all contaminated clothing immediately.

If inhaled: Remove to fresh air. Call a physician immediately.

In case of skin contact: After contact with skin, wash immediately with plenty of soap and water. If skin reactions occur, contact a physician.

In case of eye contact: In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

If swallowed: If swallowed, seek medical advice immediately and show this container or label.

Contact Number: Use the Bayer Emergency Number in Section 1

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media: High volume water jet

Revision Date 12/09/2010

Specific hazards during fire fighting: Fire may cause evolution of: Hydrogen cyanide (hydrocyanic acid) Hydrogen fluoride nitrogen oxides (NOx) Carbon oxides

Special protective equipment for fire-fighters: In the event of fire, wear self-contained breathing apparatus.

Further information: Prevent fire extinguishing water from contaminating surface water or the ground water system.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Use personal protective equipment. Use adequate ventilation.

Methods for cleaning up: Suppress (knock down) gases/vapours/mists with a water spray jet. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Place in closed containers. Label for proper disposal.

Additional advice: Keep away from/remove sources of ignition.

Further AccidentalKeep away from/remove sources of ignition.Release Notes

7. HANDLING AND STORAGE

Handling:

Avoid formation of aerosol. Only handle product with local exhaust ventilation. Avoid contact with skin, eyes and clothing. Do not refrigerate.

Take measures to prevent the build up of electrostatic charge. Keep away from open flames, hot surfaces and sources of ignition.

Storage:

Keep away from direct sunlight.

Storage temperature: < 104 °F (< 40 °C)

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Butan-1-ol (71-36-3)

- US. ACGIH Threshold Limit Values
 - Time Weighted Average (TWA): 20 ppm
- US. NIOSH: Pocket Guide to Chemical Hazards
 - Ceiling Limit Value and Time Period (if specified): 50 ppm, 150 mg/m3
- US. NIOSH: Pocket Guide to Chemical Hazards
- Skin designation: Can be absorbed through the skin.
- US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) PEL: 100 ppm, 300 mg/m3

SAFETY DATA SHEET **BAYTRIL 100**

Version 1.1

Alcohol derivative

US. Workplace Environmental Exposure Level (WEEL) Guides Time Weighted Average (TWA): 10 ppm, 44 mg/m3

Respiratory protection:

Recommended Filter type: Organic vapor with prefilter

Hand protection: Chemically resistant gloves.

Eye protection:

Safety glasses

Other protective measures:

Wear suitable protective equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Colour:	yellow, brownish	
Odour:	weak Alcohol	
Boiling point/boiling range:	no data available	
Density:	1.08 g/cm3 at 68 °F (20 °C)	DIN 51757
Vapour pressure:	no data available	
Viscosity, dynamic:	no data available	
Miscibility with water:	completely miscible	
pH:	8.9 - 10.9 at (68 °F (20 °C)) (undiluted)	
Partition coefficient (n-octanol/water):	no data available	
Flash point: Ignition temperature:	145 °F (62.78 °C) not determined	

10. STABILITY AND REACTIVITY

Conditions to avoid: Do not allow product to come in contact with: Exposure to light

Materials to avoid: Oxidizing agents

Hazardous reactions: None known.

Thermal decomposition:

no data available

Revision Date 12/09/2010

Hazardous decomposition products:

Hydrogen cyanide (hydrocyanic acid), Hydrogen fluoride, nitrogen oxides (NOx), Carbon oxides

11. TOXICOLOGICAL INFORMATION

Other information on toxicity: Alcohol derivative Dermal absorption possible

If inhaled: irritations, Shortness of breath, Cough

If swallowed: Vomiting, Nausea, Irrtiation of mucous membranes in the mouth, throat, gullet and gastro-intestinal tract following swallowing

Systemic toxicity: headaches, Nausea, CNS disorders, Convulsions, Unconsciousness, cessation of breathing

Acute oral toxicity:

Alcohol derivative LD50 rat: 1,230 mg/kg

Enrofloxacin LD50 rat: > 5,000 mg/kg

Acute inhalation toxicity:

Butan-1-ol LC50 rat: 8,000 mg/l

Skin irritation:

Alcohol derivative rabbit **Result: non-irritant**

Enrofloxacin rabbit Result: No skin irritation Method: OECD Test Guideline 404

Eye irritation:

Alcohol derivative rabbit Result: Mild eye irritation

Enrofloxacin rabbit Result: Mild eye irritation Method: OECD Test Guideline 405 Version 1.1

Sensitisation:

Enrofloxacin Skin sensitization guinea pig Result: Did not cause sensitization on laboratory animals. Method: Buehler Test

Genotoxicity in vitro:

Butan-1-ol Ames test Result: negative

Micronucleus test Result: negative

Alcohol derivative Ames test Result: negative

Pharmaceutic effects:

Enrofloxacin Antibiotic

12. ECOLOGICAL INFORMATION

General advice:

Do not allow to enter surface waters or groundwater.

Toxicity to fish:

Butan-1-ol Acute Fish toxicity: LC50 1,200 mg/l Test species: Leuciscus idus (Golden orfe) Duration of test: 48 h

Acute Fish toxicity: LC50 1,730 mg/l Test species: Pimephales promelas (fathead minnow) Duration of test: 96 h

Alcohol derivative Acute Fish toxicity: LC50 10 mg/l Test species: Lepomis macrochirus (Bluegill) Duration of test: 96 h

Enrofloxacin Acute Fish toxicity: LC0 > 10 mg/l Test species: Salmo gairdneri Duration of test: 96 h

Acute Fish toxicity: LC0 > 9.6 mg/l Test species: Lepomis macrochirus (Bluegill) Duration of test: 96 h

Toxicity to daphnia and other aquatic invertebrates:

Butan-1-ol EC50 1,983 mg/l Test species: Daphnia magna (Water flea) Duration of test: 48 h

SAFETY DATA SHEET **BAYTRIL 100**

Version 1.1

Alcohol derivative EC50 400 mg/l Test species: Daphnia magna (Water flea) Duration of test: 24 h

Enrofloxacin EC0 >= 10 mg/l Test species: Daphnia magna (Water flea) Duration of test: 48 h

Toxicity to bacteria:

Alcohol derivative EC50 71.4 mg/l tested on: Photobacterium phosphoreum Duration of test: 0.5 h

Enrofloxacin EC0 0.003 mg/l tested on: Pseudomonas putida

13. DISPOSAL CONSIDERATIONS

If discarded in its purchased form, this product would not be a hazardous waste either by listing or by characteristic. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. (40 CFR 261.20-24)

Waste disposal should be in accordance with existing federal, state and local environmental control laws.

14. TRANSPORT INFORMATION

Land transport (DOT) Non-Regulated

Inland waterway transport Non-Regulated

Railway transport Non-Regulated

Sea transport (IMDG) Non-Regulated

<u>Air transport (ICAO / IATA cargo aircraft only)</u> Non-Regulated

<u>Air transport (ICAO / IATA passenger and cargo aircraft)</u> Non-Regulated

15. REGULATORY INFORMATION

	SHEET	1220000716
YTRIL 100 sion 1.1	I	Revision Date 12/09/2010
US. Toxic Substa	ances Control Act	This product is exempt from TSCA under Section 3 (2)(B)(vi) when used for pharmaceutical application.
		Community Right-To-Know Act (EPCRA) SARA Title III Se e (40 CFR 355, Appendix A)
SARA Section 31 Categories	1/312 Hazard	Exempt from SARA Section 311/312
		Community Right-To-Know Act (EPCRA) SARA Title III Se 5) - Supplier Notification Required
US. EPA CERCLA Butan-1-ol	A Hazardous Subst	ances (40 CFR 302)Components Reportable quantity: 5000 lbs
Massachusetts, N Weight percent 1 - 5%		nsylvania Right to Know Substance Lists CAS-No. 71-36-3
1 - 5%	Alcohol derivative	
New Jersey Envir Substances Lists		us Substances List and/or New Jersey RTK Special Haza
Weight percent	Components	CAS-No.
1 - 5%	Butan-1-ol	71-36-3
California Prop. 6	65	
		product does not contain any of the listed chemicals, whic se cancer, birth defects or other reproductive harm.
OSHA Hazcom S	tandard Rating	Hazardous

NFPA 704M Rating

Health	2
Flammability	2
Reactivity	0
Other	

0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.