

MATERIAL SAFETY DATA SHEET

LAMBENT TECHNOLOGIES CORP.

3938 Porett Drive

Gurnee, IL 60031

Phone (800) 432-7187

FAX (847) 244-9753

CHEMTREC EMERGENCY RESPONSE

TOLL FREE NUMBER: (800) 424-9300

INTERNATIONAL NUMBER : (703) 527-3887

1. PRODUCT IDENTIFICATION

Product Name: **LUMULSE™ 1255**

Synonym: Proprietary Blend

2. COMPOSITION / INFORMATION ON INGREDIENTS

	CAS Number	Weight %	ACGIH TLV	OSHA PEL
Proprietary Blend	NA		Not est.	Not est.

3. HAZARDS IDENTIFICATION

Potential Health Effects

INHALATION: Negligible unless heated to produce vapors or as a mist. Vapors or finely misted materials may irritate the mucous membranes and cause irritation, dizziness, and nausea. Remove to fresh air.

EYE CONTACT: May cause irritation. Irrigate eye with water for at least 15 to 20 minutes. Seek medical attention if symptoms persist.

SKIN CONTACT: Prolonged or repeated contact may cause irritation of the hair follicles and block sebaceous glands, causing rash, acne or dermatitis. For hot molten material, cool burned skin area by immersing in cold water or apply cold water.

INGESTION: No hazards anticipated from ingestion incidental to industrial exposure.

4. FIRST AID MEASURES

EYES: Irrigate eyes with a heavy stream of water for at least 15 to 20 minutes.

SKIN: Wash exposed areas of the body with soap and water.

INHALATION: Remove from area of exposure, seek medical attention if symptoms persist.

INGESTION: Give one or two glasses of water to drink. If Gastro-intestinal symptoms develop, consult physician. (Never give anything by mouth to an unconscious person.)

5. FIRE FIGHTING MEASURES

FLASH POINT (Method Used): > 175°C (COC)

FLAMMABILITY LIMITS: None known

EXTINGUISHING MEDIA: Dry chemical, foam, halon, CO₂, water spray (fog). Water stream may splash burning liquid and spread fire.

SPECIAL FIRE FIGHTING PROCEDURES: Use water spray to cool drums exposed to fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Firefighters should use self-contained breathing apparatus to avoid exposure to smoke and vapor.

6. ACCIDENTAL RELEASE MEASURES

SPILL CLEAN-UP PROCEDURES: Remove sources of ignition, contain spill to smallest area possible. Stop leak if possible. Pick up small spills with absorbent materials such as paper towels, "Oil Dry", sand or dirt. Recover large spills for salvage or disposal. Wash hard surfaces with safety solvent or detergent to remove remaining oil film. Greasy nature will result in a slippery surface.

7. HANDLING AND STORAGE

Store in closed containers between 50°F and 120°F. Keep away from oxidizing agents, excessive heat, and ignition sources. Store and use in well ventilated areas. Do not store or use near heat, spark, or flame; store out of sun. Do not puncture, drag, or slide this container. Drum is not a pressure vessel; never use pressure to empty.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION: If vapors or mists are generated, wear a NIOSH approved organic vapor/mist respirator.

PROTECTIVE CLOTHING: Safety glasses, goggles, or face shield recommended to protect eyes from mists or splashing. PVC coated gloves recommended to prevent skin contact.

OTHER PROTECTIVE MEASURES: Employees must practice good personal hygiene, washing exposed areas of skin several times daily and laundering contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point, 760mm Hg:	> 200°C
Specific Gravity, (H ₂ O=1):	1.04
Vapor Pressure, mm Hg:	< 1
Vapor Density, (Air=1):	> 1
Volatiles, % by Volume:	< 1
Evaporation Rate, (Butyl Acetate=1):	< 1
Solubility in Water, % by Volume:	Dispersible
Appearance and Odor:	Pale Yellow liquid, mild fatty odor

10. STABILITY AND REACTIVITY

GENERAL: This product is stable and hazardous polymerization will not occur.

INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID: Strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion produces carbon monoxide, carbon dioxide along with thick smoke.

11. DISPOSAL CONSIDERATIONS

Waste may be disposed of by a licensed waste disposal company. Contaminated absorbent material may be disposed of in an approved land fill. Follow local, state and federal disposal regulations.

12. TRANSPORT INFORMATION

UN HAZARD CLASS: N/A

13. REGULATORY INFORMATION

OSHA STATUS: This product is not hazardous under the criteria of the Federal OSHA hazard Communication Standard 29 CFR 1910.1200. However, thermal processing and decomposition fumes from this product may be hazardous as noted in Sections 2 and 3.

TSCA STATUS: The components of this product are listed on TSCA.

14. OTHER INFORMATION:

NFPA Codes: Health: 1 Fire: 1 Reactivity: 0

Revision Notes: New 5/18/05

6/19/06 Change Gurnee phone number.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. Such information is to the best of the company's knowledge and believed accurate and reliable as of the date indicated. However, no representation, warranty or guarantee of any kind, express or implied, is made as to its accuracy, reliability or completeness and we assume no responsibility for any loss, damage or expense, direct or consequential, arising out of use. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.