

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date December 4, 2015

Revision: December 4, 2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Spede-Heat™ 40mm Short-Range Round, OC
- **Article number:** 6280 (1185342)
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture:** Crowd Control Device
- **Uses advised against** Contact manufacturer.
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Safariland, LLC
13386 International Parkway
Jacksonville, FL 32218
Customer Care (800) 347-1200
- **1.4 Emergency telephone number:**
ChemTel Inc.
+1 (800)255-3924, +1 (813)248-0585



SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



exploding bomb

Expl. 1.4 H204 Fire or projection hazard.



Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2 H319 Causes serious eye irritation.
 STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Additional information:** 0 % of the mixture consists of component(s) of unknown toxicity.

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.

- **Hazard pictograms**



GHS01 GHS07

(Cont'd. on page 2)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 40mm Short-Range Round, OC

(Cont'd. from page 1)

- **Signal word** Warning

- **Hazard-determining components of labelling:**

Oleoresin Capsicum

- **Hazard statements**

H204 Fire or projection hazard.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

- **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P250 Do not subject to grinding/shock/friction.

P261 Avoid breathing dust.

P264 Wash thoroughly after handling.

P280 Wear protective gloves / eye protection.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P373 DO NOT fight fire when fire reaches explosives.

P370+P380 In case of fire: Evacuate area.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P372 Explosion risk in case of fire.

P312 Call a POISON CENTER/doctor if you feel unwell.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P401 Store in accordance with local/regional/national/international regulations.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**

Contains lead. Should not be used on surfaces liable to be chewed or sucked by children.

Can become highly flammable in use.

- **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 0

Reactivity = 3

The substance demonstrates unusual reactivity with water.

- **HMIS-ratings (scale 0 - 4)**

HEALTH 2

Health = 2

FIRE 0

Fire = 0

REACTIVITY 3

Reactivity = 3

Warning: Contains lead salt(s). Long-term health hazard.

(Cont'd. on page 3)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 40mm Short-Range Round, OC

(Cont'd. from page 2)

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Explosive Product Notice**

PREVENTION OF ACCIDENTS IN THE USE OF EXPLOSIVES - The prevention of accidents in the use of explosives is a result of careful planning and observance of the best known practices. The explosives user must remember that he is dealing with a powerful force and that various devices and methods have been developed to assist him in directing this force. He should realize that this force, if misdirected, may either kill or injure both him and his fellow workers.

WARNING - All explosives are dangerous and must be carefully handled and used following approved safety procedures either by or under the direction of competent, experienced persons in accordance with all applicable federal, state, and local laws, regulations, or ordinances. If you have any questions or doubts as to how to use any explosive product, **DO NOT USE IT** before consulting with your supervisor, or the manufacturer, if you do not have a supervisor. If your supervisor has any questions or doubts, he should consult the manufacturer before use.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:**

Product will contain various combinations of the following substances. Not all substances will be in each product.

Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 3811-04-9 EINECS: 223-289-7 Index number: 017-004-00-3	potassium chlorate ----- ☠ Ox. Sol. 1, H271 ☠ Aquatic Chronic 2, H411 ☠ Acute Tox. 4, H302; Acute Tox. 4, H332	10-25%
CAS: 9004-70-0 EC number: 603-037-0	Nitrocellulose, colloided, granular ----- ☠ Expl. 1.1, H201	10-25%
CAS: 57-50-1 EINECS: 200-334-9	sucrose, pure substance with a Community workplace exposure limit	10-25%
CAS: 100-21-0 EINECS: 202-830-0	terephthalic acid substance with a Community workplace exposure limit	10-25%
CAS: 8023-77-6 EINECS: 288-920-0	Oleoresin Capsicum ----- ☠ Eye Dam. 1, H318 ☠ Acute Tox. 4, H302; Skin Irrit. 2, H315	2,5-10%
CAS: 598-62-9 EINECS: 209-942-9	manganese carbonate substance with a Community workplace exposure limit	2,5-10%
CAS: 7757-79-1 EINECS: 231-818-8	potassium nitrate ----- ☠ Ox. Sol. 2, H272	2,5-10%

(Cont'd. on page 4)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 40mm Short-Range Round, OC

(Cont'd. from page 3)

CAS: 557-04-0 EINECS: 209-150-3	magnesium distearate, pure substance with a Community workplace exposure limit	≤ 2,5%
CAS: 7440-21-3 EINECS: 231-130-8	silicon ⚠ Flam. Sol. 2, H228	≤ 2,5%
CAS: 7429-90-5 EINECS: 231-072-3 Index number: 013-001-00-6	aluminium powder (pyrophoric) ⚠ Pyr. Sol. 1, H250; Water-react. 2, H261	≤ 2,5%

· **Additional information:**

For the listed ingredient(s), the identity and exact percentages are being withheld as a trade secret.
For the wording of the listed Hazard Statements refer to section 16.

· **Notable Trace Components (≤ 0,1% w/w)**

CAS: 15245-44-0 EINECS: 239-290-0 Index number: 609-019-00-4	lead 2,4,6-trinitro-m-phenylene dioxide/ lead styphnate ⚠ Unst. Expl., H200 ⚠ Repr. 1A, H360Df; STOT RE 2, H373 ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410 ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332
--	---

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.
Take affected persons out into the fresh air.

· **After inhalation:**

Remove victim to fresh air.
Seek medical help for symptoms or if unconscious.

· **After skin contact:**

Brush off loose particles from skin.
If skin irritation continues, consult a doctor.

· **After eye contact:**

Remove contact lenses if worn.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.
Do not induce vomiting; call for medical help immediately.

· **4.2 Most important symptoms and effects, both acute and delayed**

Blast injury if mishandled.
May cause respiratory irritation.
Coughing
Nausea
Dizziness
Cramp
Breathing difficulty
Irritant to skin and mucous membranes.
Irritant to eyes.

(Cont'd. on page 5)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 40mm Short-Range Round, OC

(Cont'd. from page 4)

- **Hazards**
Danger of blast or crush-type injuries.
Danger of impaired breathing.
- **4.3 Indication of any immediate medical attention and special treatment needed**
If necessary oxygen respiration treatment.
Product may produce physical injury if mishandled. Treatment of these injuries should be based on the blast and compression effects.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
DO NOT fight fire when fire reaches explosives.
Flood area with water. If no water is available, carbon dioxide, dry chemical or earth may be used. If the fire reaches the cargo, withdraw and let fire burn.
- **For safety reasons unsuitable extinguishing agents:** None.
- **5.2 Special hazards arising from the substance or mixture**
Fire or projection hazard.
Formation of toxic gases is possible during heating or in case of fire.
Product may explode if burned in confined space. Individual cartridges may explode. Mass explosion of many cartridges at once is unlikely.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information**
Eliminate all ignition sources if safe to do so.
Cool endangered receptacles with water spray.
Evacuate area and fight fire from from the upwind side.
Flammability Classification: (defined by 29 CFR 1910.1200) Explosive. Can explode under fire conditions. Individual devices will randomly explode. Will not mass explode if multiple devices are involved. Burning material may produce toxic and irritating vapors. In unusual cases, shrapnel may be thrown from exploding devices under containment. See 2008 Emergency response Guidebook for further information.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
FOR ALL TRANSPORTATION ACCIDENTS, CALL CHEMTEL AT 1-800-255-3924. Spills of this material should be handled carefully. Do not subject materials to mechanical shock or extreme heat. A spill of this material will normally not require emergency response team capabilities.
Remove persons from danger area.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Protect from heat.
Keep away from ignition sources.
Isolate area and prevent access.

(Cont'd. on page 6)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 40mm Short-Range Round, OC

(Cont'd. from page 5)

- **6.2 Environmental precautions:**
Do not allow to enter sewers/ surface or ground water.
Inform respective authorities in case of seepage into water course or sewage system.
- **6.3 Methods and material for containment and cleaning up:**
Send for recovery or disposal in suitable receptacles.
Dispose contaminated material as waste according to section 13.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Use only outdoors or in a well-ventilated area.
Handle with care. Avoid jolting, friction and impact.
- **Information about fire - and explosion protection:**
Protect from heat.
Keep respiratory protective device available.
Emergency cooling must be available in case of nearby fire.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Avoid storage near extreme heat, ignition sources or open flame.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.
- **8.1 Control parameters**

Ingredients with limit values that require monitoring at the workplace:

57-50-1 sucrose, pure

PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	Long-term value: 10 mg/m ³
EL (Canada)	Long-term value: 10* 3** mg/m ³ *total dust; **respirable fraction
EV (Canada)	Long-term value: 10 mg/m ³ total dust

(Cont'd. on page 7)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 40mm Short-Range Round, OC

(Cont'd. from page 6)

100-21-0 terephthalic acid

TLV (USA)	Long-term value: 10 mg/m ³
EL (Canada)	Long-term value: 10* 3** mg/m ³ *total dust; **respirable fraction
EV (Canada)	Long-term value: 10 mg/m ³

598-62-9 manganese carbonate

PEL (USA)	Ceiling limit: 5 mg/m ³ as Mn
REL (USA)	Short-term value: 3 mg/m ³ Long-term value: 1 mg/m ³ as Mn
TLV (USA)	Long-term value: 0,02* 0,1* mg/m ³ as Mn; *respirable **inhalable fraction
EL (Canada)	Long-term value: 0,2 mg/m ³ as Mn; R

557-04-0 magnesium distearate, pure

TLV (USA)	Long-term value: 10 mg/m ³
-----------	---------------------------------------

7440-21-3 silicon

PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	TLV withdrawn
EL (Canada)	Long-term value: 10* 3** mg/m ³ *total dust; **respirable fraction
EV (Canada)	Long-term value: 10 mg/m ³ total dust

7429-90-5 aluminium powder (pyrophoric)

PEL (USA)	Long-term value: 15*; 5** mg/m ³ *Total dust; ** Respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ as Al* Total dust** Respirable/pyro powd./welding f.
TLV (USA)	Long-term value: 1* mg/m ³ as Al; *as respirable fraction
EL (Canada)	Long-term value: 1,0 mg/m ³ respirable, as Al
EV (Canada)	Long-term value: 5 mg/m ³ aluminium-containing (as aluminium)

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.

(Cont'd. on page 8)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 40mm Short-Range Round, OC

(Cont'd. from page 7)

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale dust / smoke / mist.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- **Respiratory protection:**

Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in large quantities.

- **Protection of hands:**



Protective gloves

Wear gloves when handling deployed rounds.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Safety glasses

- **Limitation and supervision of exposure into the environment**

No special requirements.

No further relevant information available.

- **Risk management measures**

See Section 7 for additional information.

Organizational measures should be in place for all activities involving this product.

No further relevant information available.

(Cont'd. on page 9)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 40mm Short-Range Round, OC

(Cont'd. from page 8)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:	Solid material
· Colour:	Dark grey
· Odour:	Characteristic
· Odour threshold:	Not determined.

· pH-value: Not applicable.

· Change in condition

· Melting point/Melting range:	Not determined.
· Boiling point/Boiling range:	Not determined.

· Flash point: Not applicable.

· Flammability (solid, gaseous): Highly flammable.
Contact with water liberates extremely flammable gases.

· Auto/Self-ignition temperature: Not determined.

· Decomposition temperature: Not determined.

· Self-igniting: Product is not self-igniting.

· Danger of explosion: Fire or projection hazard.

· Explosion limits:

· Lower:	Not determined.
· Upper:	Not determined.

· Vapour pressure: Not applicable.

· Density: Not determined.

· Relative density: Not determined.

· Vapour density: Not applicable.

· Evaporation rate: Not applicable.

· Solubility in / Miscibility with
water:

Insoluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

· Dynamic:	Not applicable.
· Kinematic:	Not applicable.

· 9.2 Other information: No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity: No further relevant information available.

(Cont'd. on page 10)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 40mm Short-Range Round, OC

(Cont'd. from page 9)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
Toxic fumes may be released if heated above the decomposition point.
Fire or projection hazard.
Reacts with strong acids and alkali.
Reacts violently with oxidising agents.
- **10.4 Conditions to avoid** Sources of ignition, open flame, incompatible materials.
- **10.5 Incompatible materials:** Oxidizers
- **10.6 Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Nitrogen oxides
Sulphur oxides (SO_x)

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

3811-04-9 potassium chlorate

Oral	LD50	1870 mg/kg (rat)
------	------	------------------

8023-77-6 Oleoresin Capsicum

Oral	LD50	3000 mg/kg (rat)
------	------	------------------

Dermal	LD50	>2500 mg/kg (mouse)
--------	------	---------------------

- **Primary irritant effect:**
Effects based on exposure to dusts/mists/spray/vapours released during deployment. Unused product does not possess these effects.
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Acute effects (acute toxicity, irritation and corrosivity):** Irritating to eyes, respiratory system and skin.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

(Cont'd. on page 11)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 40mm Short-Range Round, OC

(Cont'd. from page 10)

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** The product contains materials that are harmful to the environment.
- **12.2 Persistence and degradability** The product is partially biodegradable. Significant residuals remain.
- **12.3 Bioaccumulative potential** May be accumulated in organism
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
This statement was deduced from the properties of the single components.
The product contains heavy metals. Avoid transfer into the environment. Specific preliminary treatments are necessary
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Must be specially treated adhering to official regulations.
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|---|
| <ul style="list-style-type: none"> · 14.1 UN-Number · DOT, ADR, IMDG, IATA | UN0301 |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · DOT, IMDG, IATA · ADR | Ammunition Tear-producing with burster, expelling charge or propelling charge
0301 Ammunition Tear-producing with burster, expelling charge or propelling charge |

(Cont'd. on page 12)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 40mm Short-Range Round, OC

(Cont'd. from page 11)

· **14.3 Transport hazard class(es)**

· **DOT**



· **Class** 1.4
 · **Label** 1.4G, 6.1, 8

· **ADR**



· **Class** 1.4
 · **Label** 1.4G+6.1+8

· **IMDG**



· **Class** 1.4
 · **Label** 1.4/6.1/8

· **IATA**



· **Class** 1.4
 · **Label** 1.4 (6.1, 8)

· **14.4 Packing group**

· **DOT, ADR, IMDG, IATA** II

· **14.5 Environmental hazards:**

· **Marine pollutant:** No

· **14.6 Special precautions for user**

Not applicable.

· **EMS Number:**

F-A,S-Q

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Tunnel restriction code** D/E

(Cont'd. on page 13)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 40mm Short-Range Round, OC

(Cont'd. from page 12)

<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	0 Code: E2 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 500 g
<ul style="list-style-type: none"> · UN "Model Regulation": 	UN0301, Ammunition Tear-producing with burster, expelling charge or propelling charge, 1.4G (6.1+8), II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

- **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

- **Section 313 (Specific toxic chemical listings):**

598-62-9 manganese carbonate

7757-79-1 potassium nitrate

- **TSCA (Toxic Substances Control Act):**

3811-04-9 potassium chlorate

9004-70-0 Nitrocellulose, colloided, granular

57-50-1 sucrose, pure

100-21-0 terephthalic acid

7757-69-9 carbonic acid, magnesium salt

8023-77-6 Oleoresin Capsicum

598-62-9 manganese carbonate

7757-79-1 potassium nitrate

557-04-0 magnesium distearate, pure

7440-21-3 silicon

7440-44-0 carbon

1317-61-9 triiron tetraoxide

7704-34-9 sulfur

7429-90-5 aluminium powder (pyrophoric)

16291-96-6 charcoal

- **Proposition 65 (California):**

- **Chemicals known to cause cancer:**

Present in trace quantities.

15245-44-0 lead 2,4,6-trinitro-m-phenylene dioxide/ lead styphnate

(Cont'd. on page 14)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 40mm Short-Range Round, OC

(Cont'd. from page 13)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

Present in trace quantities.

15245-44-0 | lead 2,4,6-trinitro-m-phenylene dioxide/ lead styphnate

· Carcinogenic Categories
· EPA (Environmental Protection Agency)

598-62-9 | manganese carbonate

D

· IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· Canada
· Canadian Domestic Substances List (DSL)

3811-04-9 | potassium chlorate

9004-70-0 | Nitrocellulose, colloided, granular

57-50-1 | sucrose, pure

100-21-0 | terephthalic acid

7757-69-9 | carbonic acid, magnesium salt

8023-77-6 | Oleoresin Capsicum

598-62-9 | manganese carbonate

7757-79-1 | potassium nitrate

557-04-0 | magnesium distearate, pure

7440-21-3 | silicon

7440-44-0 | carbon

1317-61-9 | triiron tetraoxide

7704-34-9 | sulfur

7429-90-5 | aluminium powder (pyrophoric)

16291-96-6 | charcoal

· Canadian Ingredient Disclosure list (limit 0.1%)

598-62-9 | manganese carbonate

· Canadian Ingredient Disclosure list (limit 1%)

100-21-0 | terephthalic acid

· Other regulations, limitations and prohibitive regulations
· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients are listed.

(Cont'd. on page 15)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 40mm Short-Range Round, OC

(Cont'd. from page 14)

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H201 Explosive; mass explosion hazard.
 H228 Flammable solid.
 H250 Catches fire spontaneously if exposed to air.
 H261 In contact with water releases flammable gases.
 H271 May cause fire or explosion; strong oxidiser.
 H272 May intensify fire; oxidiser.
 H302 Harmful if swallowed.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H332 Harmful if inhaled.
 H411 Toxic to aquatic life with long lasting effects.

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 SVHC: Substances of Very High Concern
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 Expl. 1.1: Explosives, Division 1.1
 Expl. 1.4: Explosives, Division 1.4
 Flam. Sol. 2: Flammable solids, Hazard Category 2
 Pyr. Sol. 1: Pyrophoric Solids, Hazard Category 1
 Water-react. 2: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 2

 Ox. Sol. 1: Oxidising Solids, Hazard Category 1
 Ox. Sol. 2: Oxidising Solids, Hazard Category 2
 Acute Tox. 4: Acute toxicity, Hazard Category 4
 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2
 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

(Cont'd. on page 16)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date December 4, 2015

Revision: December 4, 2015

Trade name: Spede-Heat™ 40mm Short-Range Round, OC

(Cont'd. from page 15)

· **Sources**

SDS Prepared by:
ChemTel Inc.
1305 North Florida Avenue
Tampa, Florida USA 33602-2902
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
Website: www.chemtelinc.com