



SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Identicator Easy Print Ink Chemistry (Easy Print)		DATE: August 01, 2011	
PRODUCT NUMBER: EP 10 (1006609), EP 15 (1006610), EP 25 (1006612), EP 35 A,B (1006613, 1006614) EP 200 (1006611)			
TRADE NAME: Easy Print			
GENERAL USE: Fingerprint Pad			
CHEMICAL FAMILY:			
PRODUCT DESCRIPTION: Pad containing black liquid with negligible odor.			
MANUFACTURER: Safariland LLC	DATE PREPARED: August 01, 2011	SUPERSEDES: October 21, 2008	
ADDRESS (NUMBER, STREET, P.O. BOX): 13386 International Parkway	TELEPHONE NUMBER FOR INFORMATION / Customer Service: 800-347-1200		
(CITY, STATE AND ZIP CODE): Jacksonville, FL. 32218	COUNTRY: USA	CHEMTEL 24-HOUR EMERGENCY TELEPHONE NUMBER:  1-800-255-3924 01-813-248-0585 North America Toll Free International	

SECTION 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW
 Note: All components are in full compliance with the Toxic Substances Control Act (TSCA) Inventory Regulations. All SARA Title III requirements have been complied with.

POTENTIAL HEALTH EFFECTS

INHALATION:
Unlikely route of entry.

SKIN:
Possible slight to moderate redness may occur with extended daily exposure. Not classified as a primary skin irritant or corrosive.

EYES:
Possible transient irritation. Not classified as a primary irritant.

INGESTION:
May cause gastro-intestinal irritation.

CARCINOGENICITY:
 NTP? **No** IARC MONOGRAPHS? **No** OSHA REGULATED? **No**
 CALIFORNIA, Prop.65? **No**

SECTION 3 - HAZARDOUS INGREDIENTS

Hazardous Components	% (by Weight)	CAS #	EINECS #	Hazard Symbol	RISK PHRASES (Full Text Section 15)
Petroleum Hydrocarbons	55-65	64741-96-4	265-097-6	None	None

Notes: All SARA Title III materials have been reported. All ingredients contained in this formula are listed on the Toxic Substances Control Act (TSCA) Chemical Inventory.

SECTION 4 - FIRST AID MEASURES

INHALATION:
N/A

EYES:
Flush for at least 15 minutes with potable water, contact a physician if irritation persists.

SKIN:
Wash with plenty of soap and water after use.

INGESTION:
If swallowed, do not induce vomiting. Seek immediate medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

GENERAL HAZARDS:
Flash Point: 148°C (300°F)

EXTINGUISHING MEDIA:
Carbon Dioxide, Dry Chemical, Foam. Avoid the use of water.

FIRE FIGHTING PROCEDURES:
Firefighters should wear NIOSH approved, positive pressure, self-contained breathing apparatus to avoid exposure from decomposition products. Proper eye and skin protection should be used.

UNUSUAL FIRE AND EXPLOSION HAZARDS:
Ignition may produce dense black smoke.

HAZARDOUS COMBUSTION PRODUCTS:
Carbon Monoxide, Carbon Dioxide.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Identicator Easy Print Ink Chemistry (Easy Print)
PRODUCT NUMBER: EP 10 (1006609), EP 15 (1006610), EP 25 (1006612), EP 35 A,B (1006613, 1006614) EP 200 (1006611) **DATE:** August 01, 2011

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

DO NOT FLUSH TO SEWER. Always store the waste in closed containers.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep away from open flame or other ignition sources. Do not store above 120°F. Maintain adequate ventilation and keep from children. Note that some vapors are heavier than air and can displace air in low areas or confined spaces such as pits or tanks. Do not enter those areas where large quantities of vapors are suspected of collecting until exchanging the air or using special breathing apparatus with an observer present for possible assistance.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

HAZARDOUS COMPONENTS	NIOSH				ACGIH		OSHA	
	TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3	TLV/TWA ppm	TWA mg/m3	TWA ppm	PEL mg/m3
Petroleum Hydrocarbons	NA	5*	NA	NA	5*	NA	NA	NA

* - As mist

PERSONAL PROTECTION

RESPIRATORY PROTECTION:

Not required for normal work situations where adequate ventilation is provided. Use NIOSH European EN-149 approved self contained, positive pressure respirators for emergencies and in situations where air may be displaced by vapors. Follow OSHA Std. 29CFR 1910.134.

PROTECTIVE GLOVES:

Use gloves and full protective clothing if there is prolonged or repeated contact of liquid with skin. Solvex gloves recommended.

EYE PROTECTION:

For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash proof goggles. Contact lenses should not be worn under such conditions. If vapor exposure causes eye discomfort, use a full-face respirator.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Safety shower and eye-wash fountain in manufacturing areas. Personal protective clothing and use of equipment must be in accordance with 29CFR 1910.132 and 29CFR 1910.133.

WORK / HYGIENIC PRACTICES:

Do not smoke, eat or drink while using the product. Wash hands with soap and water before smoking, eating, drinking or using toilet facilities. Launder contaminated clothing before re-use.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR Pad containing black liquid with negligible odor.	VAPOR PRESSURE Approx. 90 psig at 70°F (~20°C)
pH NA	SPECIFIC GRAVITY (WATER = 1) NA
BOILING POINT / BOILING RANGE ND	SOLUBILITY IN WATER Insoluble
FLASH POINT 149°C (300°F)	VISCOSITY NA
FLAMMABLE LIMITS LEL: NE UEL: NE	VAPOR DENSITY (AIR = 1) NA
AUTO-IGNITION TEMPERATURE NE	EVAPORATION RATE < Butyl Acetate

SECTION 10 - STABILITY AND REACTIVITY

STABILITY STABLE X	CONDITIONS TO AVOID: Extreme heat.
------------------------------	--

INCOMPATIBILITY (MATERIALS TO AVOID):

Oxidizers.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Carbon Monoxide, Carbon Dioxide. Nitrogen oxides, Sulfur oxides.

HAZARDOUS POLYMERIZATION:

Will not occur.

CONDITIONS TO AVOID:

None related to polymerization.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Identicator Easy Print Ink Chemistry (Easy Print)
PRODUCT NUMBER: EP 10 (1006609), EP 15 (1006610), EP 25 (1006612), EP 35 A,B (1006613, 1006614) EP 200 (1006611) **DATE:** August 01, 2011

SECTION 16 - OTHER INFORMATION

Legend: NA = Not Available, NE = Not Established, ND = Not Determined, C = Carcinogen, NTP = National Toxicology Program

HMIS HAZARD RATINGS	HEALTH: FLAMMABILITY: PHYSICAL HAZARD: PERSONAL PROTECTIVE EQUIPMENT:	1 1 0 B	0 = INSIGNIFICANT 1 = SLIGHT 2 = MODERATE 3 = HIGH 4 = EXTREME
---------------------	--	------------------	---

REVISION SUMMARY:
 Revised to E.U. protocols 8/1/2011 supersedes 10/21/2008 issue.LB/JTV

MSDS Prepared by:
 ChemTel Inc.
 1305 North Florida Avenue
 Tampa, Florida USA 33602-2902
 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
 Website: www.chemtelinc.com



The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.